700-km intercity Yb/Sr optical clock comparison at 2.3×10^{-18}

xxxxx[1,2,3]

[1]Hefei National Laboratory, University of Science and Technology of China, Hefei, China
[2]Jinan Institute of Quantum Technology and CAS Center for Excellence in Quantum Information and Quantum Physics, University of Science and Technology of China, Jinan, China
[3]Innovation Academy for Precision Measurement Science and Technology, Chinese Academy of Sciences, Wuhan 430071, China

Abstract

Redefining the International System of Units (SI) second requires independent frequency-ratio measurements between clocks based on different atomic transitions in different laboratories, with an overall uncertainty below 5×10^{-18} and consistent results. However, the self-assessed uncertainties of these clocks have not yet been validated by such comparisons. We compared a ytterbium optical lattice clock in Wuhan with a strontium optical lattice clock in Shanghai—about 700 km apart—over a phase-stabilized fiber link spanning 1 350 km, and determine the Yb/Sr frequency ratio to be 1.207 507 039 343 337 720 1(28), with a Bayesian statistical uncertainty of 1.14×10^{-18} and a total uncertainty of 2.34×10^{-18}. The value differs from the NIST–JILA result 1.207 507 039 343 337 723 0(37) by -2.87×10^{-18}, consistent within the combined standard uncertainty. To our knowledge, this is the first intercity frequency-ratio measurement to meet the uncertainty requirement of the roadmap for the redefinition of the SI second, and together with the NIST–JILA result it provides the second, independent determination of the Yb/Sr ratio by a different institute, as required by criterion I.2.b for this pair of transitions. The measurement also demonstrates, at intercity scale, the capability that a wide-area optical-clock network requires.

Introduction

Optical lattice and single-ion clocks now reach fractional systematic uncertainties at or below 2×10^{-18} [1–8], two orders of magnitude better than current primary frequency standards[9;10]. Comparing independent clocks in different regions and laboratories verifies these self-assessed precision budgets more objectively: the environmental conditions and geodetic assumptions entering a self-evaluation are typically tied to a single location, and identical methods within one laboratory may share common systematic biases. Linking clocks of different types and locations into a collaborative network is therefore a key pathway toward establishing optical clocks as a verifiable metrological infrastructure[11;12]. The idea has moved from proposal to practice: fiber links with noise levels below those of the clocks themselves now span thousands of kilometers[13;14], and multi-clock campaigns have measured tens of ratios among clocks in six countries[15] and across a continental network[16]. Satellite-based advanced links with comparable performance[17–20] are also being developed and will interconnect with fiber networks to form a future global optical clock network.

The most immediate purpose of such a network is the redefinition of the SI second. One of the mandatory requirements (I.2.b) in the roadmap for this redefinition[21] is that at least five non-unit frequency ratios between standards of different clock transitions be measured, each ratio at least twice by different institutes, in agreement with an overall uncertainty of the comparison $\Delta\nu/\nu < 5 \times 10^{-18}$—a requirement reiterated in the 2025 CCTF progress report[22;23]. However,



Figure 1: The two-clock network. An IAPMST ytterbium clock in Wuhan and a USTC strontium clock in Shanghai are connected by a phase-stabilized 1 550 nm fiber link. Relay stations along the route carry erbium-doped fiber amplifiers and fiber-noise-cancellation loops.

comparisons across independent institutions and different locations have reached at best a precision of 7.7×10^{-18} [16]. So far, no frequency-ratio measurements between clocks in different cities have satisfied this uncertainty requirement [24].

Closing that gap matters beyond the definition itself. Chronometrically leveled clocks map the gravitational potential of the Earth at centimeter resolution [1;25;26], and clock networks have been proposed and used as sensors for dark matter [27–29]. All of these applications assume that remote clocks agree at a level that, until now, has been demonstrated only locally, in three experiments: a Sr/Yb/Al^+ triple-clock ratio measurement with an uncertainty of 3.2×10^{-18} by NIST–JILA in Boulder (US) [30], and two transportable-clock comparisons at the 10^{-18} level [26;31].

Here we report an intercity frequency-ratio measurement between an IAPMST ytterbium lattice clock in Wuhan and a USTC strontium lattice clock in Shanghai, about 700 km apart, connected by a 1 350 km fiber link. We determine the Yb/Sr ratio with a total uncertainty of 2.34×10^{-18}; gravitational redshift effects have been corrected, whereas measurement error and the time-varying gravitational redshift term associated with gravitational tides have been retained as uncertainty components. The result establishes the two sites as a prototype node pair for a distributed optical-clock network, and demonstrates, at intercity scale, the class of ratio measurement that the redefinition process depends on.

Results

0.1 Network and observation campaign

Figure 1 shows the two-clock network. A ytterbium (Yb) lattice clock at IAPMST [8] in Wuhan and a strontium (Sr) lattice clock at USTC [5] in Shanghai are separated by 700 km and compared through a 1 350 km phase-stabilized fiber link on a commercial telecom network used non-exclusively, with the carrier transmitted from Shanghai to Wuhan (Methods). Both combs are self-referenced and phase-locked to their local clock, so the two clocks are the system's only independent frequency sources; the recorded quantity is the out-of-loop beat between the received carrier and the local Yb-referenced comb, sampled every second and normalized to the carrier frequency f_{1550}, with the fiber loop-back monitored out of loop throughout; all optical




Figure 2: Frequency-ratio measurement results. (a) Fractional instability of a representative segment (Yb/Sr), together with the instability of the Yb and Sr clocks, the out-of-loop instabilities of the two frequency combs (SH, WH) and of the fiber link, and the white-frequency-noise fit. (b) Per-segment ratio deviations from the final reported value. (c) The same deviations colored by measurement campaign.

phase-locked loops in the chain are likewise monitored to evaluate the status of the experiment. The geopotential difference between the two clocks was measured by spirit leveling to be $\Delta W = 280.042 \pm 0.085\ \mathrm{m^2\,s^{-2}}$ (Methods).

0.2 Clock-ratio determination

Over two months (58 days) the two clocks and their transfer chains ran synchronously for a total of 274 effective hours, recorded as 16 jump-free segments in three measurement stages defined by the experiment team (late June to early July, early August, and late August); several of the segment boundaries correspond to deliberate clock shutdowns and restarts, so the reproducibility of the ratio rests on tested restart behavior rather than on continuous operation. The segment estimates show no systematic drift over the campaign. Figure 2a shows the instability budget within a representative segment: at short averaging times the fiber-link noise dominates, while at long averaging times the combined Yb/Sr instability follows the white-frequency-noise slope, below both clocks, confirming that the transfer chain is not the limiting element for the ratio. The per-segment ratio deviations (Figure 2b) are consistent with the final value, and colored by measurement campaign (Figure 2c) they show no drift between the three stages.

We determine the Yb/Sr frequency ratio from the 16 segments. Each segment yields a ratio estimate with its own statistical uncertainty, taken as the last computable point of the overlapping Allan deviation rather than an extrapolation of the white-frequency slope, because the beat record develops a low-frequency plateau beyond $\tau \approx 4096\,\mathrm{s}$ that an extrapolation would misrepresent (Methods). Following recent ratio comparisons[16;30], we combine the segments with a random-effect model that admits a common excess scatter[32;33], and evaluate three estimators (Table 1). The three agree at the 10^{-18} level; their center values spread by 3.7×10^{-21} in fractional units. We adopt the Bayesian random-effect estimate, which carries the largest standard uncertainty of the three, as the primary value,

$$\mathrm{Yb/Sr} = 1.207\,507\,039\,343\,337\,720\,1, \tag{1}$$

Table 1: Statistical combination of the 16 segment ratios. WLS denotes weighted least squares with inverse-variance weights $w_i = 1/u_i^2$; ξ is the inferred common excess scatter. χ^2_{red} is the reduced chi-square of the WLS combination (15 degrees of freedom, $p = 9.8 \times 10^{-1}$, Birge ratio 0.642).

Estimator	Yb/Sr	u (10^{-18})	ξ (10^{-18})	χ^2_{red}
WLS (inverse variance)	1.207 507 039 343 337 720 130	1.128	—	0.412
Mandel–Paule	1.207 507 039 343 337 720 130	1.128	0.00	1
Bayesian random effect	1.207 507 039 343 337 720 134	1.139	0.14	—

with statistical uncertainty 1.139×10^{-18}.

0.3 Uncertainty budget

Beyond the statistical uncertainty of the ratio combination, the comparison carries several systematic contributions: the published evaluations of the two clocks, the geodetic determination of the gravitational-potential difference between the sites, and the residuals of the transfer subsystems. We discuss each in turn and combine them into the total standard uncertainty (Table 2).

The Sr clock contributes 0.92×10^{-18} from its published systematic evaluation[5], and the Yb clock 1.3×10^{-18}[8]. The static gravitational-potential term is the leveling uncertainty 0.085 $\mathrm{m^2\,s^{-2}}$ converted to fractional frequency as $u(\Delta W)/c^2$, giving 0.946×10^{-18}; this is the same leveled geopotential difference already applied as the static correction (Section 0.1). The frequency conversion stages each contribute below 1×10^{-19} from the digitization error of the direct-digital-synthesis frequency-reference settings.

The time-varying gravitational redshift is more involved. Solid Earth and ocean tides, together with atmospheric, hydrological and non-tidal ocean loading, move the local potential by amounts reaching the 10^{-18} level over the campaign[34–36], and no prediction model reproduces the record at this precision. We therefore evaluated two independent tide templates: one from the public software ETideLoad4.5[37], implementing the IERS Conventions (2010)[38], and one built from the DE421 ephemerides[39] and the FES2022 ocean-tide model[40]. The beat record is significantly correlated with the templates, but with a response coefficient below the expected value of 1: the precision-weighted within-segment amplitudes are +0.58 and +0.87. The templates therefore overestimate the tidal impact. Correcting the record accordingly degrades rather than improves the fit, raising the reduced chi-square of the combination from 0.41 to 0.54 and 0.50, respectively, and the two templates shift the center in opposite directions, by -0.85×10^{-18} versus $+0.21 \times 10^{-18}$ (Methods). With the models disagreeing in sign, no correction can be applied reliably; we therefore carry the larger of the two model shifts, 0.85×10^{-18}, as an uncertainty term, which is a conservative estimate—the observed coupling suggests the actual tidal impact on the ratio is smaller.

Combining the statistical and systematic components in quadrature gives the total standard uncertainty 2.34×10^{-18}; the reported ratio is therefore

$$\mathrm{Yb/Sr} = 1.207\,507\,039\,343\,337\,720\,1(28), \tag{2}$$

where the parenthesized digits are the total standard uncertainty in the last two decimal places of the value.

Discussion and outlook

The value reported here agrees with the NIST–JILA measurement at the level set by the redefinition roadmap (Figure 3): relative to the NIST–JILA value 1.207 507 039 343 337 723 0(37)[30]

Table 2: Uncertainty budget of the Yb/Sr frequency-ratio measurement. Components are treated as independent; the fiber-link and frequency-comb entries are upper bounds (each below 1×10^{-19}, from the digitization error of the direct-digital-synthesis frequency-reference settings), carried at 0.1×10^{-18} in the quadrature.

Component	Contribution (10^{-18})
Statistical (Bayesian random effect)	1.139
Sr systematics	0.92
Yb systematics	1.3
Static gravitational potential	0.946
Fiber link	$<$0.1
Frequency comb	$<$0.1
Time-varying redshift	0.85
Total (quadrature)	2.34




Figure 3: Evolution of the Yb/Sr frequency-ratio measurements. Deviations from the final value are shown against the measurement year for the historical determinations and for this work.

our central value differs by -2.87×10^{-18}, well within the 5×10^{-18} agreement threshold of the roadmap's frequency-ratio criterion[21;23], and within the combined standard uncertainty of the two measurements. The European-network value 1.207 507 039 343 337 718(32)[16], which differs from ours by $+2.13 \times 10^{-18}$, provides a supporting cross-check at a larger uncertainty of 3.2×10^{-17}.

The evolution of the Yb/Sr ratio also shows how comparison measurements drive the field forward. Since 2015[41], independent ratios were measured with increasing precision, yet the determinations disagreed well beyond their quoted uncertainties—an early sign of common-mode errors in the absolute frequency chain on which the earlier values relied[29]. The successive comparisons exposed those errors and guided their elimination (Figure 3).

Changes in the Earth's gravitational potential enter the comparison directly. The static difference between the two clock transitions is fixed by a first-order spirit leveling campaign carried out specifically for this comparison: it is an equivalent measurement of the gravitational-potential difference, built on honest field data and national standards (Methods), and can be taken as credible. Such high-precision leveling is costly and its result is not permanent— the geopotential difference may change over time—so clock comparisons are the more natural route

to replace long-distance leveling calibration in the future, while an independent cross-check of the leveled value remains desirable.

The time-varying part is observed directly. In any single segment the 1200-s demeaned beat waveform and the tidal template are too noisy to resolve, but across the 16 segments entering the ratio combination the combined evidence is decisive: the sign of the within-segment correlation is positive in 12 out of 16 segments for both tide models, and the precision-weighted response amplitude differs from zero at 5.0σ for the ETideLoad4.5 template (+0.58) and at 5.7σ for the DE421+FES2022 template (+0.87) (Methods). A signal at the tidal period is therefore present in the record at the 10^{-18} level, yet no template captures it: the two amplitudes differ from each other and both fall short of the full expected response of +1. A tide model that correctly describes the data would convert this uncertainty term into a correction, but constructing one requires more comparison data and dedicated geodetic inputs, which is beyond the scope of this paper.

The effect grows with the scale of the comparison: on longer, continental- and intercontinental-scale baselines the time-varying redshift becomes one of the dominant systematic terms[36]. That same sensitivity turns the network into an instrument for the Earth: clock comparisons over large baselines directly sense the time-variable gravitational potential, providing an independent means of testing and calibrating tide and loading models at the 10^{-18} level—the model disagreement seen here can be refined, or removed, by more comparison data from an expanding optical-clock network. Conversely, tidal knowledge gained in this way feeds back into the comparisons themselves: with data-consistent models, the time-varying term can be corrected rather than carried, extending the accuracy reach of large-scale clock comparisons.

Looking ahead, the result is a milestone on the necessary path toward a wide-area optical-clock network: the building blocks are now in place—terrestrial fiber links of the kind used here[13;14] carry comparisons over thousands of kilometers within continents, while free-space and satellite-based links are closing the remaining gaps[17–19;42]. The natural next step is a hybrid architecture in which optical-clock nodes on continental fiber backbones are interconnected across oceans by satellite or free-space optical links, so that any pair of clocks on Earth can be compared at the level demonstrated here. Such a network and the geodetic infrastructure will develop together: precise geopotential referencing supports the comparisons, while the network's time-variable gravity observations in turn refine the geodetic models[1;25].

Conclusion

Together with the NIST–JILA measurement, this comparison provides, for the first time, two independent determinations of the Yb/Sr ratio in agreement at the precision required by the roadmap for the redefinition of the SI second, satisfying criterion I.2.b of the roadmap for this pair of transitions. The two sites now form a working node pair of a distributed optical-clock network: with more optical-clock nodes joined through terrestrial fiber backbones and interconnected across continents by satellite and free-space links, the comparison demonstrated here extends naturally into the global network on which the redefinition, chronometric leveling of the gravitational potential, and distributed searches for new physics will depend.

References

[1] W. F. McGrew, X. Zhang, R. J. Fasano, S. A. Schäffer, K. Beloy, D. Nicolodi, R. C. Brown, N. Hinkley, G. Milani, M. Schioppo, T. H. Yoon, and A. D. Ludlow. Atomic clock performance enabling geodesy below the centimetre level. *Nature*, 564:87–90, 2018. doi: 10.1038/s41586-018-0738-2.

[2] Alexander Aeppli, Kyungtae Kim, William Warfield, Marianna S. Safronova, and Jun Ye.

Clock with 8×10^{-19} systematic uncertainty. *Phys. Rev. Lett.*, 133:023401, 2024. doi: 10.1103/PhysRevLett.133.023401.

[3] Xiao-Tong Lu, F. Guo, Y.-Y. Liu, J. Cao, J.-A. Li, J.-J. Xia, Q.-F. Xu, B.-Q. Lu, Y.-B. Wang, and H. Chang. NTSC SrII optical lattice clock with uncertainty of 2×10^{-18}. *Metrologia*, 62(3):035007, 2025. doi: 10.1088/1681-7575/addc77.

[4] Mason C. Marshall, Daniel A. Rodriguez Castillo, Willa J. Arthur-Dworschack, Alexander Aeppli, Kyungtae Kim, Dahyeon Lee, William Warfield, Joost Hinrichs, Nicholas V. Nardelli, Tara M. Fortier, Jun Ye, David R. Leibrandt, and David B. Hume. High-stability single-ion clock with 5.5×10^{-19} systematic uncertainty. *Phys. Rev. Lett.*, 135:033201, 2025. doi: 10.1103/hb3c-dk28.

[5] Zhi-Peng Jia, Jie Li, De-Quan Kong, Xiang Zhang, Hai-Wei Yu, Xiao-Yong Liu, Yu-Chen Zhang, Yuan-Bo Wang, Xian-Qing Zhu, Jia-Hao Zhang, Ming-Yi Zhu, Pei-Jun Feng, Xing-Yang Cui, Ping Xu, Xiao Jiang, Xiang-Pei Liu, Peng Liu, Han-Ning Dai, Yu-Ao Chen, and Jian-Wei Pan. Improved systematic evaluation of a strontium optical clock with uncertainty below 1×10^{-18}. *Metrologia*, 63:025002, 2026. doi: 10.1088/1681-7575/ae449e.

[6] K. J. Arnold, M. D. K. Lee, Qi Zhao, Qichen Qin, Zhao Zhang, N. Jayjong, and M. D. Barrett. Lu^+ optical frequency references with accuracy verified at the 19th digit. *Nature*, 2026. doi: 10.1038/s41586-026-11072-8.

[7] Bao-lin Zhang, Zi-xiao Ma, Yao Huang, Hui-li Han, Ru-ming Hu, Yu-zhuo Wang, Hua-qing Zhang, Li-yan Tang, Ting-yun Shi, Hua Guan, and Ke-lin Gao. Liquid-nitrogen-cooled $^{40}ca^+$ ion optical clock with a systematic uncertainty of 4.4×10^{-19}. *Phys. Rev. Lett.*, 136: 053202, 2026. doi: 10.1103/vngc-c1xv.

[8] Qiang Zhu, Jingran Shi, Yuechen Zhang, Xiatian Xu, Bing Wang, Dezhi Xiong, Zhuanxian Xiong, Pengcheng Fang, Qunfeng Chen, Lingxiang He, and Baolong Lyu. Ytterbium lattice clock with systematic uncertainty of 1.3×10^{-18} and instability at the 10^{-19} level. *arXiv preprint*, 2026. arXiv:2606.10514; submitted to Metrologia.

[9] Thomas P. Heavner, Elizabeth A. Donley, Filippo Levi, Giovanni Costanzo, Thomas E. Parker, Jon H. Shirley, Neil Ashby, Stephan Barlow, and Steven R. Jefferts. First accuracy evaluation of NIST-F2. *Metrologia*, 51(3):174–182, 2014. doi: 10.1088/0026-1394/51/3/174.

[10] S. Weyers, V. Gerginov, M. Kazda, J. Rahm, B. Lipphardt, G. Dobrev, and K. Gibble. Advances in the accuracy, stability, and reliability of the PTB primary fountain clocks. *Metrologia*, 55(6):789–805, 2018. doi: 10.1088/1681-7575/aae008.

[11] P. Kómár, E. M. Kessler, M. Bishof, L. Jiang, A. S. Sørensen, J. Ye, and M. D. Lukin. A quantum network of clocks. *Nature Physics*, 10(8):582–587, 2014. doi: 10.1038/nphys3000.

[12] Fritz Riehle. Optical clock networks. *Nature Photonics*, 11(1):25–31, 2017. doi: 10.1038/nphoton.2016.235.

[13] Marco Schioppo, Jochen Kronjäger, Alissa Silva, Rada Ilieva, Chris W. Oates, Jacopo Tunesi, Charles F. A. Baynham, Helen S. Margolis, and Rachel M. Godun. Comparing ultrastable lasers at 7×10^{-17} fractional frequency instability through 2220 km of optical fiber. *Nature Communications*, 13:212, 2022. doi: 10.1038/s41467-021-27884-3.

[14] Fa-Xi Chen, Li-Bo Li, Jiu-Peng Chen, Kan Zhao, Jian-Yu Guan, Yang Xu, Lei Hou, Fei Zhou, Cheng-Zhi Peng, Qiang Zhang, Hai-Feng Jiang, and Jian-Wei Pan. 10^{-21}-level optical frequency dissemination over 2067 km of noise-loaded field-deployed fiber network. *Light: Science & Applications*, 15:276, 2026. doi: 10.1038/s41377-026-02299-1.

[15] T. Lindvall, M. Pizzocaro, R. M. Godun, M. Abgrall, others, and H. S. Margolis. Coordinated international comparisons between optical clocks connected via fiber and satellite links. *Optica*, 12(6):843, 2025. doi: 10.1364/optica.561754.

[16] Marco Pizzocaro, Clara Zyskind, Anne Amy-Klein, Erik Benkler, Sebastien Bize, Davide Calonico, Etienne Cantin, Christian Chardonnet, Cecilia Clivati, Stefano Condio, E. Anne Curtis, Simone Donadello, Sören Dörscher, Chen-Hao Feng, Melina Filzinger, Jacques-Olivier Gaudron, Rachel M. Godun, Irene Goti, Ian R. Hill, Wei Huang, Nils Huntemann, Matthew Johnson, Joshua Klose, Jochen Kronjäger, Alexander Kuhl, Rodolphe Le Targat, Filippo Levi, Burghard Lipphardt, Christian Lisdat, Jerome Lodewyck, Olivier Lopez, Helen S. Margolis, Maxime Mazouth-Laurol, Alberto Mura, Benjamin Pointard, Paul-Eric Pottie, Matias Risaro, Billy I. Robertson, Marco Schioppo, Kilian Stahl, Martin Steinel, Alexandra Tofful, Mads Tø nnes, and Jacob Tunes. International optical clock comparison using the european optical fiber network. *Phys. Rev. Research*, 8:033250, 2026. doi: 10.1103/l4bh-ryxs.

[17] Qi Shen, Jian-Yu Guan, Ting Zeng, Qi-Ming Lu, Liang Huang, Yuan Cao, Jiu-Peng Chen, Tian-Qi Tao, Jin-Cai Wu, Lei Hou, Sheng-Kai Liao, Ji-Gang Ren, Juan Yin, Jian-Jun Jia, Hai-Feng Jiang, Cheng-Zhi Peng, Qiang Zhang, and Jian-Wei Pan. Experimental simulation of time and frequency transfer via an optical satellite–ground link at 10^{-18} instability. *Optica*, 8(4):471–476, 2021. doi: 10.1364/OPTICA.413114.

[18] Qi Shen, Jian-Yu Guan, Ji-Gang Ren, Ting Zeng, Lei Hou, Meng Li, Yuan Cao, Jiu-Jiang Han, Meng-Yang Lian, Yin Chen, Xuan-Xuan Peng, Chao-Ze Wang, Deng-Ke Zou, Zhao Wang, Yu Wang, Gan-Sheng Pan, Juan Yin, Qiang Zhang, Cheng-Zhi Peng, and Jian-Wei Pan. Free-space dissemination of time and frequency with 10^{-19} instability over 113 km. *Nature*, 610:661–666, 2022. doi: 10.1038/s41586-022-05228-5.

[19] Emily D. Caldwell, Jean-Daniel Deschenes, Jennifer Ellis, William C. Swann, Benjamin K. Stuhl, Hugo Bergeron, Nathan R. Newbury, and Laura C. Sinclair. Quantum-limited optical time transfer for future geosynchronous links. *Nature*, 618:721–726, 2023. doi: 10.1038/s41586-023-06032-5.

[20] Andrei Derevianko, Kurt Gibble, Leo Hollberg, Nathan R. Newbury, Chris Oates, Marianna S. Safronova, Laura C. Sinclair, and Nan Yu. Fundamental physics with a state-of-the-art optical clock in space. *Quantum Sci. Technol.*, 7(4):044002, 2022. doi: 10.1088/2058-9565/ac7df9.

[21] N. Dimarcq, M. Gertsvolf, G. Mileti, S. Bize, C. W. Oates, E. Peik, D. Calonico, T. Ido, P. Tavella, et al. Roadmap towards the redefinition of the second. *Metrologia*, 61(1):012001, 2024. doi: 10.1088/1681-7575/ad17d2.

[22] Comité Consultatif du Temps et des Fréquences (CCTF). CCTF strategy 2025–2035. Bureau International des Poids et Mesures, 2025. URL `https://www.bipm.org/documents/20126/2071143/CCTF+Strategy.pdf`.

[23] Marina Gertsvolf. Task force on the redefinition of the second: Progress report. Comité Consultatif du Temps et des Fréquences (CCTF), BIPM, 2025. URL `https://www.bipm.org/documents/20126/273113451/1_CCTF_TE_28042025_Gertsvolf/667adba6-fd36-be37-5237-9be9ccc24d06`.

[24] Tara M. Fortier, Andre N. Luiten, and Helen S. Margolis. Optical atomic clocks: defining the future of time and frequency metrology. *Optica*, 13(1):143–163, 2026. doi: 10.1364/OPTICA.575770.

[25] Jacopo Grotti, Silvio Koller, Stefan Vogt, Sebastian Häfner, Uwe Sterr, Christian Lisdat, Heiner Denker, Christian Voigt, Ludger Timmen, Antoine Rolland, Fred N. Baynes, Helen S. Margolis, Michał Zawada, Ursula Kleinevoss, Nils Huntemann, Ekkehard Peik, Marco Pizzocaro, Simone Donadello, Guglielmo M. Tino, Filippo Levi, Davide Calonico, Alberto Iaco, Marco Tarallo, Elio Rocco, Thomas König, Ali Al-Masoudi, Tanja Mehlstäubler, Christian Lück, Britta Börchert, and Harald Schnatz. Geodesy and metrology with a transportable optical clock. *Nature Physics*, 14:437–441, 2018. doi: 10.1038/s41567-017-0042-3.

[26] Masao Takamoto, Ichiro Ushijima, Noriaki Ohmae, Toshihiro Yahagi, Kensuke Kokado, Hisa-aki Shinkai, and Hidetoshi Katori. Test of general relativity by a pair of transportable optical lattice clocks. *Nature Photonics*, 14:411–415, 2020. doi: 10.1038/s41566-020-0619-8.

[27] Andrei Derevianko and Maxim Pospelov. Hunting for topological dark matter with atomic clocks. *Nature Physics*, 10(12):933–936, 2014. doi: 10.1038/nphys3137.

[28] P. Wcisło, P. Ablewski, K. Beloy, S. Bilicki, M. Bober, R. Brown, R. Fasano, R. Ciurylo, H. Hachisu, K. Hosaka, et al. New bounds on dark matter coupling from a global network of optical atomic clocks. *Science Advances*, 4(12):eaau4869, 2018. doi: 10.1126/sciadv.aau4869.

[29] Kyle Beloy, Martha I. Bodine, Tobias Bothwell, Samuel M. Brewer, Sarah L. Bromley, Jwo-Sy Chen, Jean-Daniel Deschênes, Scott A. Diddams, Robert J. Fasano, Tara M. Fortier, Youssef S. Hassan, David B. Hume, Dhruv Kedar, Colin J. Kennedy, Isaac Khader, Amanda Koepke, David R. Leibrandt, Holly Leopardi, Andrew D. Ludlow, William F. McGrew, William R. Milner, Nathan R. Newbury, Daniele Nicolodi, Eric Oelker, Thomas E. Parker, John M. Robinson, Stefania Romisch, Stefan A. Schäffer, Jeffrey A. Sherman, Laura C. Sinclair, Lindsay Sonderhouse, William C. Swann, Jian Yao, Jun Ye, and Xiaogang Zhang. Frequency ratio measurements at 18-digit accuracy using an optical clock network. *Nature*, 591:564–569, 2021. doi: 10.1038/s41586-021-03253-4.

[30] Alexander Aeppli, Willa J. Arthur-Dworschack, Kyle Beloy, Caitlin M. Berry, Tobias Bothwell, Angela Folz, Tara M. Fortier, Tanner Grogan, Youssef S. Hassan, Zoey Z. Hu, David B. Hume, Benjamin D. Hunt, Kyungtae Kim, Amanda Koepke, Dahyeon Lee, David R. Leibrandt, Ben Lewis, Andrew D. Ludlow, Mason C. Marshall, Nicholas V. Nardelli, Harikesh Ranganath, Daniel A. Rodriguez Castillo, Jeffrey A. Sherman, Jacob L. Siegel, Suzanne Thornton, William Warfield, and Jun Ye. Atomic clock frequency ratios with fractional uncertainty $\leq 3.2 \times 10^{-18}$. *Phys. Rev. Lett.*, 137:033201, 2026. doi: 10.1103/g865-9mk1.

[31] Chetan Vishwakarma, Ingo Nosske, Tim Lücke, Martin Steinel, Melina Filzinger, Erik Benkler, Sören Dörscher, Nils Huntemann, and Christian Lisdat. Interspecies clock comparison below 5×10^{-18} uncertainty with a transportable clock, 2026. URL `https://arxiv.org/abs/2608.01916`.

[32] Raymond T. Birge. The calculation of errors by the method of least squares. *Phys. Rev.*, 40(2):207–227, 1932. doi: 10.1103/PhysRev.40.207.

[33] John Mandel and Robert C. Paule. Interlaboratory evaluation of a material with unequal numbers of replicates. *Anal. Chem.*, 42(11):1194–1197, 1970. doi: 10.1021/ac60293a019.

[34] Duncan Carr Agnew. Earth tides. In *Treatise on Geophysics, Volume 3: Geodesy*, pages 151–178. Elsevier, 2nd edition, 2015. doi: 10.1016/B978-0-444-53802-4.00058-0.

[35] Christian Voigt, Heiner Denker, and Ludger Timmen. Time-variable gravity potential components for optical clock comparisons and the definition of international time scales. *Metrologia*, 53(6):1365–1383, 2016. doi: 10.1088/0026-1394/53/6/1365.

[36] Heiner Denker, Ludger Timmen, Christian Voigt, Stefan Weyers, Ekkehard Peik, Helen S. Margolis, Pacôme Delva, Peter Wolf, and Gérard Petit. Geodetic methods to determine the relativistic redshift at the level of 10^{-18} in the context of international timescales: a review and practical results. *Journal of Geodesy*, 92:487–516, 2018. doi: 10.1007/s00190-017-1075-1.

[37] Chuanyin Zhang. ETideLoad4.5: Earth tide, load effect and deformation monitoring computation. Scientific Computing Platform for Geophysical Geodesy, 2026. URL `https://www.zcyphygeodesy.com/en/h-col-113.html`. Publicly available at `https://www.zcyphygeodesy.com/en/h-col-113.html`.

[38] Gérard Petit and Brian Luzum. IERS conventions (2010). Technical Report 36, International Earth Rotation and Reference Systems Service (IERS), 2010. IERS Technical Note No. 36, Verlag des Bundesamts für Kartographie und Geodäsie, Frankfurt am Main.

[39] William M. Folkner, James G. Williams, and Dale H. Boggs. The planetary and lunar ephemeris de421. Technical Report IPN Progress Report 42-178, Jet Propulsion Laboratory, California Institute of Technology, 2009. Interplanetary Network Progress Report 42-178.

[40] Florent H. Lyard, Damien J. Allain, Mathilde Cancet, Loren Carrère, and Nicolas Picot. Fes2014 global ocean tide atlas: design and performance. *Ocean Science*, 17:615–649, 2021. doi: 10.5194/os-17-615-2021.

[41] Nils Nemitz, Takuya Ohkubo, Masao Takamoto, Ichiro Ushijima, Manoj Das, Noriaki Ohmae, and Hidetoshi Katori. Frequency ratio of Yb and Sr clocks with 5×10^{-17} uncertainty at 150 seconds averaging time. *Nat. Photon.*, 10:258–261, 2016. doi: 10.1038/nphoton.2016.20.

[42] Marco Pizzocaro, Mamoru Sekido, Kazuhiro Takefuji, Hideki Ujihara, Hidekazu Hachisu, Nils Nemitz, Masanori Tsutsumi, Tetsuro Kondo, Eiji Kawai, Ryuichi Ichikawa, Kunitaka Namba, Yoshihiro Okamoto, Rumi Takahashi, Junichi Komuro, Cecilia Clivati, Filippo Bregolin, Piero Barbieri, Alberto Mura, Elena Cantoni, Giancarlo Cerretto, Filippo Levi, Giuseppe Maccaferri, Mauro Roma, Claudio Bortolotti, Monia Negusini, Roberto Ricci, Giampaolo Zacchiroli, Juri Roda, Julia Leute, Gérard Petit, Federico Perini, Davide Calonico, and Tetsuya Ido. Intercontinental comparison of optical atomic clocks through very long baseline interferometry. *Nature Physics*, 17:223–227, 2021. doi: 10.1038/s41567-020-01038-6.

[43] Federal Geodetic Control Committee (FGCC). Standards and specifications for geodetic control networks. Technical report, National Oceanic and Atmospheric Administration (NOAA), National Geodetic Survey, Rockville, MD, USA, September 1984.

[44] General Administration of Quality Supervision, Inspection and Quarantine of the People's Republic of China and Standardization Administration of China. Specifications for the first and second order leveling. Technical Report GB/T 12897–2006, Standards Press of China, Beijing, China, 2006. In Chinese.

[45] Český úřad zeměměřický a katastrální (ČÚZK). Návod pro správu geodetických základů České republiky. Technical report, ČÚZK, Praha, Czechia, 2015. In Czech.

[46] Arbeitsgemeinschaft der Vermessungsverwaltungen der Länder der Bundesrepublik Deutschland (AdV). Feldanweisung für präzisionsnivellements im deutschen haupthöhennetz (fa-pn). Technical report, AdV, Germany, June 2022. In German.

Methods

Leveling determination of the geopotential difference

The static gravitational-redshift correction is fixed by the geopotential difference between the atomic-transition positions of the two clocks, determined by a first-order spirit leveling campaign carried out specifically for this comparison: a 1 113 km line between the Wuhan benchmark WS-03 and the Shanghai benchmark WS-01, observed in both directions with digital levels and bar-code invar staffs, with gravity observed along the line. The geopotential difference is integrated section by section, $\Delta W_{AB} = -\sum_i g_i \, \Delta H_i$, and combined with the local benchmark-to-transition offsets, giving $\Delta W = 280.042 \pm 0.085$ m^2 s^{-2}, equivalent to an optical fractional shift of -3.116×10^{-15}. The per-kilometer accidental error $M_\Delta = 0.255\,\mathrm{mm\,km^{-1}}$ satisfies the most stringent first-order requirements of the Chinese, US, German and Czech national standards (Supplementary Section 3)[43–46]. An independent GNSS-plus-EGM2008 geoid-model calibration gives 280.60 ± 2.558 m^2 s^{-2}, consistent with the leveled value but about 30 times less precise, so it serves as a consistency check rather than a calibration at the reported accuracy.

Experimental setup, frequency transfer and data processing

The two sites are connected by a phase-stabilized fiber link of 1 350 km single-pass length (2 700 km loop-back), operated at 1 550 nm and carried on a commercial telecom network used non-exclusively. The route is divided into spans of tens of kilometers, each terminated by a relay station carrying a narrow-linewidth laser, an erbium-doped fiber amplifier and a fiber-noise-cancellation loop; the added instability of the link is kept below the clock noise for averaging times beyond 100 s.

Both ends use independent optical frequency combs, self-referenced and phase-locked to their local clock, to bridge the spectral gap between the clock transitions and the telecom carrier; all frequencies in the chain derive from the two clock transitions through fixed factor-of-two relations, $f^{1397}_{\mathrm{comb}} = \frac{1}{2}(1+a)\, f_{\mathrm{Sr}}$ and $f^{1156}_{\mathrm{comb}} = \frac{1}{2}(1+b)\, f_{\mathrm{Yb}}$, where a and b collect the Sr and Yb systematic corrections (density, lattice, second-order Zeeman and blackbody shifts). The observable is the out-of-loop beat between the received carrier and the local Yb-referenced comb, converted to fractional units with the transfer frequency $f_{1550} = 193.3992$ THz. The static gravitational-redshift correction enters the ratio inversion as a multiplicative factor, $(\mathrm{Yb/Sr})_{\mathrm{corr}} = (\mathrm{Yb/Sr})_{\mathrm{raw}} \times (1+\delta_g)$ with $\delta_g = -3.116 \times 10^{-15}$, derived from the leveled geopotential difference above.

The counters sample the beat every second in phase-averaging mode. Each accepted segment contributes its longest jump-free record; the per-segment retained counts, ratio deviations and statistical uncertainties are listed in Supplementary Table 1. Five segments whose stability slopes fall outside the white-frequency-noise band are flagged there as model-limited; they lie at the steep end of a continuous slope distribution with no common campaign, weather or laboratory condition that distinguishes them from the remaining segments.

Tidal analysis

Two analyses quantify the tidal impact on the ratio, each with its own quantity: the within-segment response of the beat waveform (Section 0.3 of the main text) and the spliced stability of the concatenated record (below). They are equivalent measures of the same effect—how strongly the beat follows the tidal template—and are expected to converge as the record grows; we report both.

Tidal templates and the correction test. The solid Earth tide and ocean tide loading displacement difference between the two sites is computed every 30 s with the public software ETideLoad4.5, converted to an equivalent geopotential difference and then to a beat-frequency template $h = f_{1550}\, \Delta W / c^2$ with the same f_{1550} normalization as the beat record. A second, independent template is built from the DE421 ephemerides and the FES2022 ocean-tide model on a 90 s grid.

The within-segment analysis windows the retained beat record and the 1-s template with the same 1200-s triangular window at 600-s stride, demeans both, and fits beat $= A \cdot$ tide through the origin, with the template sign corrected for the beat polarity so that a positive amplitude corresponds to the expected response $A = +1$; amplitudes, Pearson r and p values are inferred from non-overlapping 1200-s windows only, and the per-segment amplitudes are combined with precision weights $1/u_A^2$. The combined response amplitudes are +0.58 (ETideLoad4.5) and +0.87 (DE421+FES2022), as reported in the main text; because the two models share the same beat record, their significance values are not independent replications.

As a correction test, the ratio combination is repeated with the tide series applied before the inversion at two fixed amplitudes, the theoretical $A = +1$ and the historical $A = +0.54$ from the demeaned beat waveform of our earlier analysis of the same campaign. Both templates degrade rather than improve the fit: the reduced chi-square of the combination rises from 0.41 to 0.57 and 0.54 for the ETideLoad4.5 template (Bayesian center shift -0.85×10^{-18}), and to 0.50 for the DE421+FES2022 template, which moves the center in the opposite direction, by $+0.21 \times 10^{-18}$. Repeating the segment-mean correlation with the solid tide alone ($r = +0.36$ instead of +0.43) locates the dominant coupling in the ocean-tide loading term. Templates that degrade the segment agreement, and whose two independent realizations disagree in sign, are treated as inconsistent with the data: no tidal correction is applied to the reported central value, and the larger of the two center shifts is carried as the time-varying-redshift uncertainty item 0.85×10^{-18}.

Spliced stability. The 16 segments were spliced end-to-end on a continuous 1-s clock with the wall-clock gaps removed, giving a single 986 416 sample record whose overlapping Allan deviation $\sigma_y(\tau)$ can reach averaging times beyond a single segment (Figure 4). The spliced curve extends the per-segment stability points to τ up to about 4.6 days of pure data time, at which the raw record reaches $\sigma_y \approx 8.6 \times 10^{-19}$; applying the two theoretical tide corrections ($A = +1$) shifts the long-τ level by less than 10% in opposite senses, and the removed correction terms (h/f_{1550}) themselves lie below the corrected curves. Because the spliced axis removes the inter-segment gaps, points with τ exceeding one segment mix different campaigns; the pair count behind each point is reported with the data. This diagnostic is a data record, not a statistical uncertainty.

The components of the uncertainty budget (Table 2) are treated as independent and combined in quadrature, giving the total standard uncertainty 2.34×10^{-18}.

Data availability

The frozen, machine-readable result layer underlying this manuscript is archived in the repository (`https://github.com/hjiang555-a11y/gravitation-whsh`) under `results/audit-v1/verified/`: the manifest with SHA-256 `ac725aaba8ec744bf4e7a17cf37cee41af57461f0d3684584711b24a02b0962e`, the derived ledgers and statistics, and the generated audit report. The raw beat files and the leveled geopotential inputs are available from the corresponding author upon reasonable request.

Code availability

The analysis and manuscript pipelines are in the same repository under the Apache License 2.0. The manuscript numbers are generated by `paper/rev2/tools/build_numbers.py`, which reads only the frozen manifest and the curated constants listed in `generated/numbers_manifest.json`.




Figure 4: Spliced concatenated stability of the 16 segments. The segments are placed end-to-end on a continuous 1-s clock (gaps removed, 986 416 samples, 11.4 d of pure data time); one overlapping Allan deviation per series, from $\tau = 1\,000$ s to 4.6 d. Curves: the raw record ($A = 0$), the theoretical tide correction ($A = +1$) for the ETideLoad4.5 and DE421+FES2022 templates, and the removed correction terms h/f_{1550} themselves (dotted). Error bars are 1-σ equivalent degrees of freedom; the pair count at each τ is reported with the data. Points beyond one segment mix campaigns, so the curve is a data record rather than an uncertainty estimate.