

Part II - Registered Statistical Site Discovery and Kinetic-Network Architecture

Species-Dependent Evidence, Ensemble Certification, Sampling Confidence, Thermodynamics, Paths, and Deferred Kinetics

mdstats

2026-07-27 (architecture revision 57; Stage 11E-GR3 fixed-kernel scientific grid refinement implemented)

Contents

Purpose and current status	5
Authoritative architectural decisions	7
Structural identity remains species-independent	7
The atom-resolved ring boundary is authoritative	7
No universal canonical frame	7
Physical site identity is learned from data	8
Basin, pathway, and kinetic claims are separate	8
Position, force, and temporal evidence remain inspectable	8
Calculation controls, not user labels, define the ensemble	8
Canonical reduced landscapes are PMFs, not microscopic potential-energy surfaces	9
PMF interpretation is ensemble-specific	9
No scientific claim outside sampled support	9
Every MD-derived catalog is sampling-scoped and partial	9
Manual site models remain optional	9
Part I structural dependency contract	10
Stage C0 - Spatial frame registration and coordinate canonicalization	10
Affine registration contract	10
Periodic lattice-basis gauge and registered products	11
Reference-cell selection and initial periodic scope	11
Registration policies	11
physical	12
translation_registered	12
reference_material	12
Periodic reference-translation gauge	12
Temporally continuous translation-branch lift	13
Positions, displacements, forces, and velocities	13
Externally defined and structure-fitted maps	13
Analysis requirement profiles	14
Registration result and diagnostics	14
Multi-trajectory registration groups	15
Registered structural geometry view	15
Initial Stage C0 implementation boundary	15
Discovery coordinate policy and evidence catalog	16
Default site-discovery coordinates	16
Evidence masks and admissibility overlays	16
Topology-regime segmentation	17
Source trajectory bundle identity	17
Source-control reconstruction and ensemble certificate	17
Energy reconstruction, conservation, stationarity, and production regimes	18

Ionic-temperature reconstruction	18
Three-level trajectory-quality verdict	19
Ensemble-aware statistical-mechanical contract	21
Force provenance	21
Position-density evidence	22
Species number density and probability density	22
Kernel metric and reference-cell covariance	22
Analysis geometry metric and certified periodic distance	23
Periodized Gaussian on a triclinic torus	23
Physical and reference-material density measures	24
Sampled support and local evidence	24
Feature-level sampling adequacy and cross-fitting	24
Matched density and force smoothing	25
Density score covector and metric gradient	25
Bandwidth ladder and attractor lineage	26
Operational scale-consensus catalog	26
Isolated modes and extended attractors	26
State-local periodic charts	27
Deterministic attractor and basin construction	27
Continuous ridge criterion	27
Support-certified periodic cell complex and transition candidates	27
Field and topology certification	28
Provisional cores	28
Mechanical force evidence and thermodynamic mean-force reconstruction	29
Two force products with different admissibility	29
Canonical conditional mean force	29
Local mechanical force refinement	29
Raw mean-force field	30
Curl and periodic harmonic components	30
Optional support-limited force-PMF reconstruction	30
Joint site validation and structural classification	30
Orthogonal evidence and classification statuses	30
Provisional temporal evidence	31
Basin and transition-corridor sampling certificates	31
Partial-catalog and saturation certificate	32
Density-force consistency refers to the authoritative force contract	32
Major and minor sites	32
Ion-time probability and many-ion occupancy	32
Structural association and species-dependent coordination	33
Statistical-state instances and structural symmetry orbits	33
Exact coordination fingerprint	33
Forward-model check	33
Classification evidence	34
Occupancy-conditioned fingerprints	34
EvidenceCrossfitPartition, thermodynamic partitions, and final refit	34
Geometry-conditioned site refinement	35
Statistical states, structural complexes, and classes	36
Ensemble-specific basin, corridor, and catalog thermodynamics	37
Provenance-first thermodynamic reporting	37
Source energy catalog and thermodynamic channel selection	37
NVT and reweighted canonical basin thermodynamics	37
NpT basin thermodynamics	38

NVE basin thermodynamics	38
Biased, constrained, and reweighted thermodynamics	38
Effective occupancy Hamiltonian	38
Transition-region and activation thermodynamics	38
Optional pre-kinetic thermodynamic verification	38
Final temporal residence and transition segmentation	39
Raw evidence remains immutable	39
Core-basin hysteresis	39
Final segmented outputs	39
Observed transition-path ensembles	39
Observed event, path-resolved, and structural networks	40
Refactor design	41
Dependency direction	41
Coordinate-registration ownership	41
Incremental scientific-density extraction	41
E0a - analysis facade - implemented	41
Density extraction follow-ups D0b-D0d - decomposed into 11E-GR0-GR5	42
Statistical bandwidth, grid realization, and partial numerical refactor	42
Existing atomic-density machinery is the common numerical oracle	42
Plotting and scientific refinement remain separate policies	43
Scientific resolution and convergence certificates	43
Budget and sampling rules	43
Position-force sample catalog	44
Existing manual-model branch	44
Interactive analysis scene	44
Revision-47 authoritative typed dependency graph	44
Planned persistent data model	45
Revised implementation sequence	47
Part I structural prerequisites - Stages 11A-D implemented	47
Stage 11E-M1/11E-M2 - manual and transferred site models - implemented foundation	47
Stage C0A1 - source semantics and periodic lattice gauge - implemented	47
Stage C0A2 - affine registration and coordinate products - implemented	48
Stage 11C3 - atom-resolved structural ring boundary and harmonics - implemented	48
Stage C0A3 - registered structural-view integration - implemented	49
Stage C0B - consumer migration - implemented	50
Stage 11E0a - scientific density facade and ownership boundary - implemented	50
Stage 11E-ENS0 - source-control bundle and energy-channel reconstruction	51
Stage 11E-ENS1 - ensemble, control, and force-provenance certificate	51
Stage 11E-STAT0 - ionic temperature, integrity, conservation, and quality verdict	52
Stage 11E-STAT1 - source-observable production-regime catalog	52
Stage 11E0b - immutable registered raw sample catalog	53
Stage 11E-STAT2 - preliminary ensemble-specific admissibility	53
Stage 11E-SAMP0 - cross-fitted block and effective-sample foundation	53
Stage 11E-GR0 - common grid geometry and numerical diagnostics	54
Stage 11E-GR1 - common budgeted planner and deterministic grid ladder	54
Stage 11E-GR2 - plotting adaptation and visual-policy preservation	54
Stage 11E1 - discovery-block periodic species-density estimation	55
Stage 11E2 - per-realization numerical basin and density-boundary candidates	55
Stage 11E-GR3 - Stage 11 fixed-kernel scientific grid refinement	55
Stage 11E-GR4 - cross-fitted numerical-hypothesis selection and freeze	56
Stage 11E-STAT3 - held-out distribution-stability refinement	56
Stage 11E3A/11E3B - mechanical refinement and thermodynamic mean-force estimation	57

Stage 11E3A - local mechanical-force refinement	57
Stage 11E3B - thermodynamic mean-force estimation and certification	57
Stage 11E4 - provisional assignment and temporal-persistence diagnostics	57
Stage 11E-SAMP1 - held-out basin sampling certificates	58
Stage 11E5 - joint evidence validation and structural association	58
Stage 11E5a - species-dependent coordination fingerprints and classification	59
Stage 11E5b - optional geometry-conditioned site refinement	60
Stage 11E-SAMP2 - preliminary corridor and saddle-candidate sampling support	60
Stage 11E-SAMP3 - partial-catalog scope, novelty, and saturation	61
Stage 11E-THERMO0 - thermodynamic state and channel selection	61
Stage 11E-THERMO1 - ensemble-specific basin thermodynamics	61
Stage 11E-THERMO2 - conditional energies and identifiable effective Hamiltonians	61
Stage 11E-THERMO3A - static finite transition-region thermodynamics	61
Stage 11E6 - final hysteretic segmentation and residence statistics	62
Stage 11E6b - observed transition-path ensembles	62
Stage 11E-THERMO3B - event/path-conditioned transition-state validation	63
Stage 11E7 - observed event network with optional geometric annotations	63
Stage 11E-GR5 - density numerical-ownership closeout	64
Stage 11E-PMF-DENSITY - optional density-derived PMF	64
Stage 11E-PMF-FORCE - optional force-integrated PMF	64
Stage 11E-PMF-CROSSCHECK - optional independent PMF verification	65
Stage 11E8a - Na-LTA NVE continuation integration dossier	65
Stage 11E-THERMO4A - optional product-scoped thermodynamic verification	65
Stage 11E8b - cross-dataset comparison by product class	66
Stage 11E7A - rate-candidate edge universe and exposure support	66
Stage 11E-KSAMP0 - kinetic fit and validation partition	66
Stage 11E9A - pre-rate event-process and state-model adequacy	67
Stage 11G0 - gating diagnosis and state-model selection	67
Stage 11F0 - empirical rates and rate bounds	67
Stage 11E9B - post-fit kinetic-model validation	68
Stage 11F1 - barrier-derived and transition-state rate laws	68
Stage 11E-THERMO4B - kinetic-thermodynamic consistency	68
Stage 11G1 - gate-conditioned rate comparison and final model selection	68
Stage 11H - kinetic propagation and first-passage statistics	69
Stage 11I - integrated scientific ground gate	69
Validation strategy	69
Stage C0 algebra and transformation tests	69
Synthetic site landscapes	70
Statistical robustness	70
Coordinate and structural interpretation	70
Atom-resolved ring and coordination tests	70
Ensemble, energy, and production-regime validation	71
Sampling-confidence and cross-fitting validation	71
Shared grid-refinement and ownership validation	71
Thermodynamic validation	71
Kinetic cross-fitting and zero-event rate validation	71
Real trajectory audit	71
Deferred boundaries	71
Borrowed theories and original constructions	72
Borrowed or adapted foundations	72
Current mdstats architectural constructions	73
References	73

Purpose and current status

This manual is **Part II** of the Stage 11 architecture. The species-independent framework, primitive-ring, natural-tiling, tile/cage/window, serrated ring-boundary, and framework-semantic layers are owned by `framework_ring_architecture.{md,pdf}` (**Part I**). Part II begins at registered trajectory evidence. It consumes Part I identities but never recreates or mutates them.

Architecture revision 57 is the controlling normative contract. The ensemble and quality plan first consolidated in architecture revision 48 remains preserved and is now partially implemented. It preserves the revision-47 typed dependency and thermodynamic-provenance contract and marks Stage 11E-ENS0 source-control/named-energy reconstruction, 11E-ENS1 control/ensemble certification, 11E-STAT0 ionic-temperature/integrity/quality evaluation, 11E-STAT1 source-observable production-regime identification, 11E-STAT2 ensemble-specific admissibility, 11E-SAMP0 complete-system cross-fit sampling, 11E-GR0 common grid geometry and numerical diagnostics, 11E-GR1 common budgeted planning and deterministic grid ladders, 11E-GR2 plotting adaptation and visual-policy preservation, and 11E-GR3 fixed-kernel scientific grid refinement as implemented. GR4 and all later GR/SAMP/STAT/THERMO migration stages remain subject to their own specifications and acceptance tests. It preserves the event/path/saddle separation and additionally requires source-bound provenance on every thermodynamic result, treats independent cross-checking as optional verification rather than a prerequisite for a source-qualified estimate, splits density-derived and force-integrated PMFs, introduces an independent kinetic fit/validation partition and a predeclared rate-candidate edge universe, assigns final candidate freezing to GR4, and replaces the two-field DAG with typed dependency edges and source-identity constraints.

Release chronology, previous architecture revisions, and package-specific implementation history are maintained only in `stage11_site_kinetics_status_history.{md,pdf}`. They are descriptive and cannot override this manual, the machine-readable stage DAG, or a signed scientific acceptance certificate.

Stage 11 connects a certified periodic framework topology to observed mobile-ion states and, only after validation, to a kinetic model. The revised architecture adopts one controlling principle:

normalized source trajectory → analysis-specific frame registration → trajectory evidence
→ statistical sites → structural interpretation → kinetics

The framework geometry must not prescribe the physical site catalog. It supplies stable identities, ring and cage coordinates, periodic translations, and local geometric descriptors. A new cross-cutting spatial-frame-registration layer supplies the analysis coordinate system without altering the immutable physical source trajectory. The mobile-ion trajectory then determines where species-specific basins occur and whether they are spatially and temporally metastable.

The following completion list describes the **baseline compatibility behavior** at the time of this contract. It does not imply complete revision-52 compliance. ENS0, ENS1, STAT0, STAT1, STAT2, and SAMP0 are implemented; later SAMP certificates, GR migration, revised force products, event-network branching, typed provenance, kinetic cross-fitting, and downstream thermodynamic records remain migration work until their own implementation and acceptance tests pass.

The baseline compatibility state contains the structural stack through Stage 11D, the first three cross-cutting coordinate-registration foundations, and the atom-resolved structural ring-boundary layer:

- certified natural tiling;
- exact reference tile and window geometry;
- compatible-frame tile geometry;
- persistent T/O ring geometry;
- compatible-frame ring centers, normals, side frames, and breathing descriptors;
- generic tile and ring-interface semantics;
- an explicit LTA semantic profile;
- Stage C0A1 source-field semantics, periodic lattice-basis validation, optional explicit unimodular reconciliation, reference-cell definitions, and separate geometric/PMF force-admissibility contracts;
- Stage C0A2 immutable fit/analysis metrics, certified triclinic closest-image geometry, affine registration, matched periodic framework translation, temporal branch lifting, registered coordinate products, and covector-correct force transformation;
- Stage 11C3 persistent T/O atom chemistry, exact cyclic structural sequences, unweighted cyclic spectra, boundary-measure angular moments, rank-safe physical-angle fits, dihedral gauges, and fail-closed LTA oxygen aliases; and

- Stage C0A3 source-bound physical/registered structural views, certified transformed periodic atom images, reconstructed registered orthonormal ring frames, and optional registered tile, cage, face, and window embeddings.
- Stage C0B source-bound compatibility adapters for displacement, velocity, atomic density, framework density, trajectories, and framework plotting, with centralized scientific drift ownership and exact legacy regression semantics.
- Stage 11E0a analysis-owned scientific density protocols, zero-copy field adapters, canonical atomic/framework preparation facades, and disjoint scientific-versus-rendering resource policies, while retaining the current numerical fields as explicit compatibility-owned objects.
- Stage 11E0b compact registered species sample catalogs with raw availability and geometry masks, segment-aware represented-time weights, topology regimes, lazy structural annotations, and optional shared-domain multi-trajectory registration groups. Scientific force, ensemble, stationarity, and PMF admissibility are later overlay products under the revision-49 migration contract.
- Stage 11E-ENS0 immutable source-bundle identity, explicit/effective VASP control reconstruction, non-authoritative user-label diagnostics, exact named frame-energy channels, companion-file classification, numerical MD controls, per-step SCF traces, strict serialization, and VASP reader metadata integration. Ensemble interpretation is Stage 11E-ENS1.
- Stage 11E-ENS1 signed control-inferred dynamics, ensemble, propagator, thermostat, barostat, cell-control, bias, constraint, force-provider, initial-velocity, and continuation certificates, with missing companion evidence retained as unresolved.
- Stage 11E-STAT0 source-bound equipartition ionic temperature, autocorrelation-aware confidence and drift statistics, NVE energy-conservation diagnostics, explicit hard integrity versus soft quality checks, and the exact `strictly_qualified`, `degraded_quality`, and `unqualified` execution verdicts. Degraded sources continue with one warning; only catastrophic integrity failure rejects by default.
- Stage 11E1 source-bound periodic species-density estimation with explicit physical/reference-material measures, covariance and analysis-metric separation, normalized triclinic Gaussian lattice sums, bounded image truncation, density/score/metric-gradient/Hessian fields, local support, dense/block realizations, bandwidth ladders, and complete-system block uncertainty.
- Stage 11E2 deterministic isolated modes, derivative-supported extended ridges, unresolved flat components, support-restricted periodic basin ownership, numerically supported density-boundary and saddle candidates, local periodic charts, provisional cores, covariance-scale lineage, explicit scale ambiguity, and separate topology refinement certificates.
- legacy Stage 11E3 combined local mechanical fits and PMF-oriented force fields; the current contract maps mechanical center/stiffness/curvature quantities to E3A and requires thermodynamic mean-force, density-score residual, and PMF claims to be recomputed under E3B/PMF ensemble, partition, measure, kernel, and support contracts.
- Stage 11E4 immutable raw core/basin/transition/background/unknown memberships, segment-aware core visits and preliminary residences, explicit jump/excursion/unresolved/censored passages, local decorrelation estimates, stride sensitivity, recrossing diagnostics, and separate temporal-support and evidence-pattern statuses.
- Stage 11E5 frozen joint-evidence catalogs with orthogonal spatial, temporal, force, force-score, stationarity, geometry, curvature, and validation statuses; fail-closed registered structural associations; legacy block provenance mapped to `EvidenceCrossfitPartition`; conservative symmetry exchangeability; and an explicit frozen-versus-refit boundary.
- Stage 11E5a exact state-conditioned physical M–O/M–T sample matrices, persistent atom/image identities, direct local ion coordinates, centered- reference and geometry-forward diagnostics, exact cyclic and boundary-measure spectra, rank-safe actual-angle fits, phase-locking evidence, occupancy- conditioned mixtures, and conservative structural classes.
- Stage 11E5b optional one-pass framework-only affine center refinement, frozen discovery assignments, model-selection and held-out basin/corridor gates, translated nested cores/basins, joint static/dynamic membership, comoving and boundary displacement diagnostics, exclusive overlap conflicts, and occupancy bounds.
- Stage 11E6 final core-entry/basin-retention hysteresis, explicit residence, excursion, transition, recrossing, gap, conflict, and censoring intervals, represented-time residence and occupancy statistics, and threshold/stride stability certification.
- Stage 11E6b exact observed registered paths with periodic translations, cadence and first-hit resolution, optional structural/force evidence, compatible cross-run path ensembles, and diagnostic collective-event context.
- Stage 11E7 an observed periodic network on validated state instances, exact structural-versus-observed edge comparison, separate complex/orbit/class summaries, compact source-anchor transfer models, and fail-closed held-out or external transfer application records.

The explicit manual or transferred-model branch has permanent labels:

Legacy label in pre-revision documents	Current label	Ownership
former manual-model 11E1	11E-M1	explicit ring/site model construction
former manual-model 11E2	11E-M2	application and assignment of a supplied model

The legacy labels appear only in this migration table. Normative prose uses 11E-M1 and 11E-M2; 11E1 and 11E2 exclusively mean density estimation and numerical feature discovery.

Stage 11F rate-law work is postponed until the revised Stage 11E discovery, ensemble, stationarity, sampling-confidence, thermodynamic, and kinetic-adequacy gates are complete.

Detailed implementation history and release-by-release pilot status are maintained in `stage11_site_kinetics_status_history.{md,pdf}`. That appendix is descriptive, not normative. This manual and `stage11_dependency_graph.json` contain the authoritative current contracts and stage order.

Authoritative architectural decisions

Structural identity remains species-independent

The following identities are fixed by the certified framework and natural tiling:

- framework vertex and edge identities;
- primitive-ring keys and ring order;
- natural-tile keys and face signatures;
- the two oriented ring–tile incidences of each window;
- periodic translation labels;
- reference and compatible-frame ring geometry; and
- generic or profile-specific semantic labels.

Changing the mobile species, temperature, loading, force model, clustering method, or bandwidth must not change these structural identities.

The atom-resolved ring boundary is authoritative

A ring is not represented scientifically by a circle, ellipse, or smooth aperture alone. The authoritative object is the persistent ordered sequence of framework T atoms, bridging oxygen atoms, periodic images, chemical environments, and instantaneous coordinates. Area, ellipticity, aperture, and harmonic coefficients are derived summaries.

A geometrically centered ion need not see equivalent ring atoms. In LTA, the single 6-ring contains alternating O(2) and O(3) sites. Experimental refinements report three shorter and three longer M–O contacts for centered Na and Ag, and an analogous three-plus-three pattern for the principal K site [S11-32, S11-33]. The architecture therefore distinguishes geometric centering from coordination isotropy.

Conventional crystallographic aliases such as O(1), O(2), and O(3) are attached only by an explicit validated framework profile. Generic ring analysis uses persistent atom identities and local chemical/topological signatures. A profile must not force an alias when the input ordering, symmetry, chemistry, or origin convention is incompatible.

The species-independent structural boundary and species-dependent ion coordination are separate owners. Stage 11C3 records only framework geometry and chemistry. Stage 11E5a records M–O/M–T distances and coordination harmonics after a statistical state has been associated with structural objects.

No universal canonical frame

`AtomisticFrameCollection` remains the normalized physical source truth. It is never rewritten into one permanently drift-free or strain-free trajectory. A pair-distance analysis, a material-frame density, a laboratory-frame current, and a rotating-frame visualization do not require the same coordinates.

The package therefore defines **spatial frame registration** as an explicit, analysis-specific view. “Frame canonicalization” is the architectural role; the public API should emphasize registration because no single canonical frame is physically correct for all observables.

Every analysis declares its requirements. The registration layer resolves one policy, records the framewise transforms, and rejects incompatible requests.

Physical site identity is learned from data

For species M , a physical site is not created by ring order, cage type, ionic radius, or a manually selected offset. It is a trajectory-supported metastable region. Position and temporal evidence can establish a spatially reproducible, temporally metastable site. Admissible force evidence raises the certification to force-validated or fully validated status.

The full evidence channels are:

1. a reproducible local maximum of the species position density;
2. a mechanically restoring local force field with stable local curvature;
3. repeated temporal residence beyond the local vibration timescale; and
4. reproducibility across trajectory blocks, ions, and moderate estimator changes.

A low-population site may still be real. Population and temporal persistence are reported separately.

Basin, pathway, and kinetic claims are separate

One trajectory can support different levels of claim. Two reproducible residence regions may establish two candidate basins. One accepted core-to-core passage establishes one observed connection. A transition-path ensemble, directional rate, or Markov model requires substantially more repeated evidence.

The package therefore reports the following separately:

- existence and geometry of each basin;
- spatial and temporal evidence for metastability;
- each observed successful or failed passage;
- whether a transition-path ensemble is resolved;
- whether directional rates are identifiable; and
- whether a Markov, semi-Markov, or gated kinetic model is supported.

A single observed jump is never promoted automatically to a representative minimum-free-energy path or a rate estimate.

Position, force, and temporal evidence remain inspectable

The first implementation must not fuse all evidence into one opaque score. Position-only density, force-only reconstruction, and temporal segmentation are separate results with shared provenance. Their agreement is a validation result. Their disagreement is scientifically meaningful and must remain visible.

Calculation controls, not user labels, define the ensemble

Free-form source labels such as VASP SYSTEM, POSCAR comments, filenames, directory names, or user-provided run descriptions are retained as comments only. They never define the ensemble, thermostat, barostat, target temperature, bias, constraint, or production interval. `SimulationControlCertificate` reconstructs the **control-inferred dynamics mode** from explicit/effective controls and source-format semantics only. Observed time-series diagnostics never redefine that mode; they produce a separate `RealizedEnsembleConsistency` and contribute to trajectory quality and method-specific thermodynamic admissibility.

For VASP, the first implementation must distinguish the compact explicitly supplied `<incar>` section from the complete effective `<parameters>` section and resolve at least IBRION, MDALGO, SMASS, ISIF, ANDERSEN_PROB, LANGEVIN_GAMMA, LANGEVIN_GAMMA_L, PMASS, NHC_NCHAINS, NHC_PERIOD, CSVR controls, multiple-thermostat controls, bias mode, and constraint provenance. The decision table follows the official VASP ensemble and MD-control documentation [S11-38–S11-42]. Unknown or internally inconsistent controls fail closed only for claims that require a resolved dynamics mode. Descriptive structural analysis may continue when hard trajectory-integrity checks pass.

A user comment may disagree with the inferred controls without changing the certificate. Such a disagreement is recorded explicitly as `user_label_conflicts_with_controls`.

Canonical reduced landscapes are PMFs, not microscopic potential-energy surfaces

For a coarse coordinate $\mathbf{q}$, the equilibrium one-body probability density for species M defines the potential of mean force

$$A_M(\mathbf{q}) = -k_B T \ln p_M(\mathbf{q}) + C.$$

The remaining framework and mobile-ion coordinates have been integrated out. The result is therefore a free-energy landscape conditional on the selected ensemble, composition, loading, temperature, and coordinate definition. It must not be labeled the microscopic potential-energy surface.

PMF interpretation is ensemble-specific

The canonical identity

$$A_T(\mathbf{q}) = -k_B T \ln p_T(\mathbf{q}) + C$$

requires a stationary canonical distribution or a justified reweighted equivalent. A stationary microcanonical trajectory instead defines an energy-shell conditional distribution. It may support a microcanonical occupancy landscape directly and may approximate a canonical subsystem PMF only under an explicit finite-bath or ensemble- equivalence policy. NVE, NVT, NpT, biased, constrained, and mixed-thermostat data therefore have different admissibility contracts.

The package must keep these products distinct:

```
position_density
microcanonical_occupancy_distribution
canonical_probability_density
canonical_PMF
reweighted_PMF
force_integrated_PMF
```

No stage silently converts an NVE density into a canonical PMF by inserting a mean kinetic temperature.

No scientific claim outside sampled support

Density, force, PMF, and basin results are valid only where sampling support is adequate. Sparse interpolation may connect sampled values numerically, but it must not create a physical site or barrier in an unsampled region.

Every field result must retain a support mask, local sample count or effective sample size, and uncertainty diagnostic.

Every MD-derived catalog is sampling-scoped and partial

A finite trajectory can certify only features supported on its observed timescale, temperature, composition, loading, and sampling protocol. Even a long machine- learned-force-field trajectory cannot prove that all higher-barrier basins and saddles have been found. The default catalog-level claim is therefore `observed_partial_catalog`, never `complete_site_network`.

Numerical maxima, ridges, basin boundaries, and saddle cells are candidates. A physical feature is reported only after effective independent sample counts, independent blocks or replicas, bootstrap recurrence, uncertainty, and held-out support pass a declared policy. Transition frames from one crossing remain one independent event regardless of how many stored frames resolve that crossing.

Unsupported features are rejected or retained as ambiguous. Absence of an event is reported as raw event/exposure/censoring evidence. A rate bound is produced only under a signed Stage 11F0 `RateBoundModel`, never as an automatic SAMP result.

Manual site models remain optional

The existing manual profile branch is retained as an explicit alternative:

```
manual or transferred site model
-> explicit geometric basins
-> framewise assignment
-> observed statistics
```

Its output must state that site locations and basin definitions were supplied, not discovered. Manual and learned catalogs may be compared or matched, but must never be silently merged.

Part I structural dependency contract

Part II requires a certified Part I structural product set. The minimum contract contains:

- immutable framework vertex/edge identities and periodic translations;
- source-bound primitive-ring keys and ordered atom-resolved T/O boundaries;
- certified natural-tile, face, window, cage, and adjacency identities when available;
- reference and compatible-frame ring geometry with centers, normals, side frames, planarity, breathing, and serrated-boundary descriptors;
- framework semantic labels and explicit profile provenance; and
- digests that prove every registered structural view derives from the same framework/topology catalog.

Part II may use these products to interpret a statistical state. It must not:

- replace an ordered oxygen polygon by a circle or ellipse;
- convert a ring side, cage, or window directly into a physical site;
- infer a transition from structural adjacency alone;
- merge states solely because they share a structural label; or
- modify Part I identity in response to species, temperature, loading, bandwidth, or clustering choices.

Detailed structural mathematics, implementation stages 11A-D, and the remaining general-topology roadmap are normative only in Part I.

Stage C0 - Spatial frame registration and coordinate canonicalization

Stage C0 is a cross-cutting prerequisite placed after source normalization and before analysis-specific coordinate preparation:

raw I/O

- > unit, atom-order, box-origin, and periodic-unwrapping normalization
- > immutable AtomisticFrameCollection
- > Stage C0 spatial frame registration
- > analysis-specific registered view
- > scientific analysis or plotting

Source normalization and frame registration are distinct. Normalization records what the source trajectory physically contains. Registration chooses how one analysis observes that trajectory.

Affine registration contract

Use the package row-vector convention. Let

$$\mathbf{x}_{i,t} = \mathbf{f}_{i,t} H_t$$

be an origin-relative Cartesian coordinate in the normalized source collection. A framewise affine registration is

$$\mathbf{q}_{i,t} = \mathbf{x}_{i,t} M_t + \mathbf{b}_t$$

with registered cell

$$G_t = H_t M_t.$$

Positions and cells must always be transformed together. A periodic analysis may use a fixed periodic domain only when the resolved G_t is constant within the declared tolerance.

For a reference group with continuously gauged center $\mathbf{c}_t$, choose

$$\mathbf{b}_t = \mathbf{c}_{\text{ref}} - \mathbf{c}_t M_t,$$

so that

$$\mathbf{q}_{i,t} = (\mathbf{x}_{i,t} - \mathbf{c}_t)M_t + \mathbf{c}_{\text{ref}}.$$

Reference centers may be centers of geometry, centers of mass, persistent anchors, or explicitly supplied trajectories. Their atom identities and periodic gauges are part of the registration signature. The framewise center $\mathbf{c}_t$ is always represented as a continuously unwrapped, origin-relative Cartesian row vector in the source frame before application of M_t . The target $\mathbf{c}_{\text{ref}}$ is a Cartesian row vector in the registered domain. A fractional reference-center input is converted through its declared source or reference cell before the affine map is assembled; the coordinate convention is never inferred implicitly.

Periodic lattice-basis gauge and registered products

The reference-material map assumes that the reported lattice basis has a continuous identity. Cells related by

$$H'_t = U_t H_t, \quad U_t \in GL(3, \mathbb{Z}),$$

describe the same lattice under a different integer basis. Stage C0 therefore checks cell handedness, determinant sign, periodic-axis consistency, and basis continuity before constructing M_t .

The first implementation may reject a basis change instead of solving the full lattice-matching problem, but it must never interpret a silent basis relabeling as physical strain or rotation. Later implementations may reconcile admissible unimodular changes and retain the integer gauge U_t in provenance.

Every registration result exposes four distinct products:

```
registered_unwrapped_cartesian
registered_wrapped_fractional
registered_image_shifts
registered_cell
```

Unwrapped coordinates preserve continuous framework centers and ion paths. Wrapped fractional coordinates define periodic density samples. Image shifts preserve lattice translations of observed hopping events. Wrapping is performed only after registration and never discards the unwrapped path or image labels.

The source collection also records, where known:

```
position_frame
velocity_frame
force_frame
box_origin_frame
```

Unknown source-frame semantics prevent exact transformed-velocity or PMF claims.

Reference-cell selection and initial periodic scope

Every reference-material registration owns an immutable `ReferenceCellDefinition`. The first implementation supports only:

```
explicit_matrix
    a caller-supplied full-rank reference cell

selected_source_frame
    the gauge-validated cell of one declared source frame
```

The result records the source kind, selected frame when applicable, basis gauge, periodic axes, handedness, cell digest, and tolerances. A reference structure or a gauge-reconciled weighted mean cell may be added later, but a mean is not formed until basis continuity, common handedness, and compatible periodic axes have been proved.

The first `reference_material` implementation supports fully periodic, full-rank three-dimensional cells only. Partial periodicity, singular embedding cells, and changes in periodic-axis identity fail closed until a dedicated mixed periodic/nonperiodic specification exists. Identity and translation-only registration may still be used by analyses whose own contracts support partial periodicity.

Registration policies

The first implementation supports three authoritative policies.

physical

$$M_t = I, \quad \mathbf{b}_t = \mathbf{0}, \quad G_t = H_t.$$

This is the normalized physical trajectory. It is the default for pair distances, coordination, bond geometry, topology reconstruction, and laboratory-frame transport.

translation_registered

$$M_t = I, \quad \mathbf{b}_t = \mathbf{c}_{\text{ref}} - \mathbf{c}_t.$$

This removes uniform drift while retaining the instantaneous physical cell, shape, orientation, and metric. It is appropriate for fixed-cell density and framework-relative trajectories when only translational drift is artificial.

reference_material

For an invertible, fully periodic cell,

$$M_t = H_t^{-1} H_{\text{ref}}, \quad G_t = H_{\text{ref}}.$$

Cell mapping and translation registration are orthogonal policy components. With a continuously gauged framework center, the composed map is

$$\mathbf{q}_{i,t} = (\mathbf{x}_{i,t} - \mathbf{c}_t) H_t^{-1} H_{\text{ref}} + \mathbf{c}_{\text{ref}}.$$

Equivalently, if $\mathbf{c}_t^{(\text{frac})} = \mathbf{c}_t H_t^{-1}$,

$$\mathbf{q}_{i,t} = (\mathbf{f}_{i,t} - \mathbf{c}_t^{(\text{frac})}) H_{\text{ref}} + \mathbf{c}_{\text{ref}}.$$

When `translation_mode="none"`, $\mathbf{c}_t = \mathbf{0}$ and $\mathbf{c}_{\text{ref}} = \mathbf{0}$, recovering $\mathbf{q}_{i,t} = \mathbf{f}_{i,t} H_{\text{ref}}$. The default variable-cell site-discovery policy uses reference-material cell mapping together with a framework translation gauge, not the translation-free shorthand.

This maps every frame to one fixed periodic reference torus and removes affine cell rotation, isotropic breathing, anisotropic stretch, and shear while also removing only the explicitly selected uniform reference-group translation. It preserves fractional/material internal motion. It is not used for physical RDFs or bond-length distributions.

Periodic reference-translation gauge

A framework center is not formed by averaging arbitrarily wrapped atom positions. After the declared cell map has placed frame t in the registered domain, let $\tilde{\mathbf{q}}_{j,t}$ denote the pre-translation coordinates of the persistent reference atoms and let $\mathbf{q}_{j,\text{ref}}$ denote their reference coordinates. The translation gauge is the torus displacement

$$\boldsymbol{\tau}_t = \underset{\boldsymbol{\tau} \in \mathbb{T}_G^3}{\text{argmin}} \sum_{j \in \mathcal{R}} w_j \left\| \text{MIC}_{G,R}(\tilde{\mathbf{q}}_{j,t} - \mathbf{q}_{j,\text{ref}} - \boldsymbol{\tau}) \right\|_R^2,$$

where $\mathcal{R}$ is a constant persistent reference set, w_j gives the COG, COM, or caller-declared weighting, and R is a positive-definite `RegistrationFitMetric`. The affine translation is $\mathbf{b}_t = -\boldsymbol{\tau}_t$ up to the declared reference-origin convention. The solver retains the selected torus branch, residual RMS and maximum, branch separation, and ambiguity status. A branch is rejected when competing translations are indistinguishable within tolerance or the residuals show that one uniform translation is inadequate.

The registration metric has its own coordinate frame, units, transformation law, and digest. Under $\mathbf{q}' = \mathbf{q}A$, the same fitting geometry transforms as

$$R' = A^{-1} R A^{-T}.$$

Its default is ordinary Euclidean distance in the registered Cartesian domain. It is not inherited from the downstream `AnalysisGeometryMetric`; an anisotropic transport or basin metric must not change the fitted framework origin. A caller may deliberately equate the two metrics only through an explicit policy.

This `ReferenceTranslationGauge` is invariant to a common relabeling of periodic images. It also prevents a deforming cell from converting arbitrary per-atom image offsets into fictitious Cartesian drift. COG and COM are weighting policies for the matched-displacement problem, not independent wrapped-coordinate averages.

Temporally continuous translation-branch lift

The torus solution is defined only modulo the registered lattice:

$$\boldsymbol{\tau}_t^{(\text{lift})} = \boldsymbol{\tau}_t + \mathbf{n}_t G, \quad \mathbf{n}_t \in \mathbb{Z}^3.$$

For every continuous trajectory segment, Stage C0 chooses the integer sequence $\mathbf{n}_t$ jointly or sequentially using temporal continuity, matched-framework residuals, and a declared branch-separation tolerance. The result retains:

torus translation per frame
temporally lifted translation per frame
integer lattice-branch sequence
continuity residual and competing-branch separation
branch ambiguity and segment reset points

A branch jump is never selected only because wrapped positions are unchanged. An ambiguous lift fails closed for registered unwrapped trajectories, finite-difference velocities, and transition lattice translations. Independent ensemble frames have no invented temporal lift; each receives only its torus representative and ambiguity status. Restart, missing-frame, topology-regime, and declared discontinuity boundaries reset the lift.

Later policies may remove only the rotational part of cell motion, only isotropic breathing, or perform a nonperiodic rigid-body Procrustes fit. They require separate specifications and are not part of the first Stage C0 implementation.

Positions, displacements, forces, and velocities

Different physical fields transform differently.

For a same-frame geometric displacement,

$$\Delta \mathbf{q} = \Delta \mathbf{x} M_t.$$

Work invariance requires the force covector transformation

$$\boxed{\mathbf{F}_q = \mathbf{F}_x M_t^{-T}}$$

for an externally defined affine map. Treating force as an ordinary displacement vector is incorrect for a nonorthogonal transformation.

For a time-dependent transform,

$$\mathbf{q} = \mathbf{x} M + \mathbf{b},$$

the exact registered velocity is

$$\boxed{\dot{\mathbf{q}} = \dot{\mathbf{x}} M + \mathbf{x} \dot{M} + \dot{\mathbf{b}}.}$$

Translation-only drift subtraction is exact when $M_t = I$. A rotating or deforming frame requires $\dot{M}_t$ and its convective term. VACF and current analyses must not inherit a position-registration policy silently.

Externally defined and structure-fitted maps

The result distinguishes externally defined affine maps from transforms fitted to instantaneous structure.

Examples of externally defined maps are the instantaneous-cell to reference-cell map and a user-supplied rigid transform. Their position and force rules are explicit.

Examples of structure-fitted maps are framework Procrustes rotation, dynamic ring frames, and cage-local frames. They are valid geometric coordinates. However, a naively rotated mobile-ion force is not automatically the exact generalized mean force after the fitted framework degrees of freedom are marginalized.

Every transformed force carries a geometric transformation status:

exact_external_affine_covector
exact_translation_relative_to_disjoint_reference_group

diagnostic_structure_fitted_projection
generalized_force_unavailable

This status answers only whether the vector or covector transformation is geometrically valid. A separate PMF-force status records whether the transformed force is admissible as a thermodynamic conditional mean force:

pmf_force_admissible
pmf_force_inadmissible_variable_cell_measure
pmf_force_inadmissible_structure_fitted_map
pmf_force_inadmissible_untracked_bias_or_constraint
pmf_force_provenance_unknown

exact_translation_relative_to_disjoint_reference_group additionally requires that translation is the sole fitted transform, the mobile atom is excluded from a constant reference group, and no untracked constraint, bias, thermostat, or stochastic force contributes. Geometric exactness never upgrades PMF admissibility automatically.

The first force-supported site-discovery implementation permits LocalMechanicalForceRefinement for fixed-cell physical or translation-registered coordinates when geometric transformation and conservative-force provenance pass. ThermodynamicMeanForceCertificate additionally requires a canonical/reweighted measure or separately implemented microcanonical/subsystem theory. Reference-material positions under a variable cell remain valid for density discovery, but their transformed forces are thermodynamically inadmissible until the ensemble measure, Jacobian, and cell-fluctuation terms are derived. Dynamic ring-frame forces remain diagnostic until their generalized-force measure is derived.

Analysis requirement profiles

The registration service provides one implementation but no universal default.

Analysis	Default spatial policy
RDF, coordination, physical pair distances	physical
Bond angles and neighbor topology	physical plus topology gauge
Laboratory MSD	physical, optional translation drift
Material-frame MSD under variable cell	reference_material
VACF	native velocity frame; optional exact translation subtraction
Charge current and conductivity	native laboratory frame unless explicitly redefined
Atomic density, fixed cell	translation_registered
Atomic density, variable cell	reference_material
Data-driven site discovery	translation_registered for fixed cell; reference_material for variable cell
Tile and ring geometry	physical topology gauge plus local structural frames
Interactive plotting	consume the registration chosen by the scientific field

The service rejects physically inconsistent requests, including a reference-affine RDF without an explicit strain-normalized-distance contract, a rotating-frame VACF without transform derivatives, or periodic KDE after an arbitrary rotation that does not yield one fixed registered cell.

Registration result and diagnostics

A provisional public interface is

```
registration = prepare_frame_registration(  
    collection,  
    policy=FrameRegistrationPolicy(  
        cell_mode="reference_affine",  
        translation_mode="center_of_geometry",  
        reference_atom_indices=framework_indices,
```

```

        reference_frame=0,
        periodic_domain="fixed_reference_cell",
    ),
)

```

The immutable result retains:

```

source normalization and source digest
reference frame and reference atoms
translation, cell, and rotation modes
framewise  $M_t$  and  $b_t$ 
source and registered cells
centers and periodic gauges
reference-translation branch, residual, and ambiguity diagnostics
analysis geometry metric and certified MIC semantics
determinant and condition number
cell deformation diagnostics
fit RMS and maximum residual when fitted
geometric force-transform and PMF-force admissibility semantics
velocity transformation semantics
reference-cell definition and periodic-scope compatibility
per-frame status and failure reason

```

It fails closed for singular cells, empty references, unresolved periodic gauges, rank-deficient rigid fits, incompatible fixed-domain requests, and unavailable transform derivatives for exact velocity output.

Multi-trajectory registration groups

Pooling independent trajectories requires one explicit `FrameRegistrationGroup`. It verifies common framework topology and atom correspondence, periodic axes, lattice-basis gauge, chemistry and loading, reference cell, origin convention, and registration semantics. Each member retains its own transform series and signature, but all registered samples inhabit one declared periodic domain. Independent runs are never pooled by matching filenames or approximate cell lengths alone.

Registered structural geometry view

Site discovery and ring interpretation may use different coordinate measures. The Stage C0 service therefore provides a source-bound `RegisteredStructuralGeometryView` for persistent T/O atoms, tile and cage centers, ring centers, and their periodic images.

The same framewise affine map used for mobile-ion positions is applied to the structural atom coordinates. Under a non-rigid affine map, the registered ring center, normal, and local basis are reconstructed from the transformed T/O coordinates. The implementation must not obtain a registered orthonormal frame by merely multiplying the physical frame axes by M_t .

Both representations remain available:

```

physical_structural_geometry
    actual Cartesian bond lengths, apertures, and M-O/M-T coordination

registered_structural_embedding
    site association, density-space displacement, and registered classification

```

A discovered density attractor and its candidate ring or cage are compared only inside one declared registered view. Physical distances and chemical coordination are then evaluated in the physical structural geometry with the same persistent atom and frame identities.

The registered view records the registration signature, source structural digest, transformed atom images, reconstructed local frames, and any failure of periodic or orientation continuity.

Initial Stage C0 implementation boundary

The first Stage C0 implementation provides:

1. identity/physical registration;
2. center-of-geometry and center-of-mass translation registration;

3. full reference-cell affine registration composed with an optional explicit translation gauge;
4. explicit-matrix or selected-frame reference-cell definitions;
5. registered positions, cells, displacements, geometric force covectors, and structural views;
6. separate geometric-force and PMF-force admissibility statuses;
7. immutable signatures, diagnostics, and round-trip checks;
8. compatibility adapters for current MSD and atomic-density behavior.

Reference-material registration is initially restricted to fully periodic, full-rank three-dimensional cells.

It does not initially implement arbitrary framework Procrustes rotation, rotation-only cell correction, isotropic-breathing-only correction, or exact rotating/deforming-frame velocities.

Discovery coordinate policy and evidence catalog

Default site-discovery coordinates

The initial site-discovery coordinate must inhabit one fixed periodic domain. For a fixed cell, use framework translation registration without an arbitrary global Procrustes rotation. For a variable cell, use the composed `reference_material` cell map and framework-translation gauge in H_{ref} for position-density discovery. Variable-cell force PMF certification remains disabled until the ensemble measure, Jacobian, and cell-fluctuation weighting are specified in a dedicated force-coordinate contract.

An arbitrary frame-dependent rigid rotation changes the periodic lattice to $Q_t^T H_t$ and cannot be combined into one periodic KDE unless the cell is transformed consistently and the resulting domain is explicitly reconciled. The previous global rigid-alignment proposal is therefore not the default periodic discovery coordinate.

After global sites are discovered, Stage 11C ring and cage frames provide local coordinates for interpretation. Full orthonormal (u, v, z) coordinates preserve the mobile-ion volume measure for a fixed structural identity. Reduced polar coordinates such as (z, ρ, θ) require the corresponding Jacobian and are not the initial discovery measure.

Evidence masks and admissibility overlays

The immutable E0b catalog owns raw availability and geometry masks only:

```
raw_position_available_mask
raw_force_available_mask
raw_time_available_mask
registration_valid_mask
structural_geometry_mask
topology_compatible_mask
connectivity_flicker_mask
```

Scientific admissibility is attached later through an immutable `EvidenceAdmissibilityOverlay` that references the E0b signature and the exact `SimulationControlCertificate`, `ProductionRegimeCatalog`, and `PmfAdmissibilityCertificate` used to construct it:

```
position_analysis_mask
force_analysis_mask
joint_position_force_mask
temporal_analysis_mask
canonical_pmf_mask
microcanonical_analysis_mask
reweighted_analysis_mask
```

E0b does not infer equilibrium, stationarity, production windows, PMF temperature, or thermostat/constraint admissibility. An unresolved certificate produces an unresolved overlay; it never causes an assumption to be embedded in the raw catalog. Density-force consistency uses the exact joint admissible subset, kernel metric, covariance scale, weights, and coordinate transformation recorded by the overlay.

Topology-regime segmentation

The sample catalog separates changes in framework connectivity from ordinary ring breathing and cutoff flicker. Every frame carries:

```
topology_regime_id
topology_compatible_mask
connectivity_flicker_mask
structural_phase_status
```

The initial data-driven site catalog requires one compatible framework-topology regime. Frames with unresolved transient connectivity may remain available for position-only analyses only when the selected topology regime and registration remain unambiguous; genuinely distinct structural phases are never pooled into one density or PMF. Later workflows may build separate site catalogs per regime.

Source trajectory bundle identity

Every source-derived record is bound to one immutable `SourceTrajectoryBundleIdentity`. The identity covers the normalized primary trajectory bytes, coordinate payload, atom identity/order, frame/time axis, companion-control manifest, source-program/version, and any restart lineage that is included in the analysis. `SOURCE_BYTES` and `SOURCE_COORDINATES` are views of this one bundle, not independent roots.

ENS0 and C0 each retain the same bundle signature. Combining controls from one run with coordinates from another is a hard source-integrity failure even when atom counts and cell dimensions happen to match. Derived records carry both their immediate parent signatures and the shared bundle identity so that source mixing is machine-detectable.

Source-control reconstruction and ensemble certificate

The source-general architecture is owned by:

```
SimulationControlBundleManifest
SimulationRunControls
SimulationControlCertificate
RealizedEnsembleConsistency
EnsembleInferencePolicy
```

A source adapter, such as `VaspRunControls`, implements `SimulationRunControls` and records a versioned control-semantics identifier. Inference is therefore reproducible against the source program and version rather than against an unversioned decision table.

`SimulationControlBundleManifest` records every relevant primary or companion input with one of:

```
present_and_bound
known_absent
not_applicable
not_provided
required_missing
```

Absence proves nonuse only when source semantics make the file or tag optional and the bound primary controls explicitly disable the corresponding feature. Otherwise the result remains `not_provided` or `required_missing`; missing `ICONST`, `REPORT`, `hills`, or `bias` metadata is never silently interpreted as proof that constraints or `bias` were absent.

For VASP the reconstruction owns:

```
explicit_incar_controls
effective_parameter_controls
user_comment
program_and_version
control_semantics_version
control_source_precedence
ensemble_decision_trace
thermostat_certificate
barostat_certificate
bias_and_constraint_certificate
```

```

initial_velocity_provenance
continuation_provenance
numerical_md_quality_controls
per_step_electronic_convergence_trace

```

The VASP adapter must parse both the explicitly supplied <incar> values and the complete effective <parameters> values from vasprun.xml, preserving source precedence and original tag names. It must also parse per-ionic-step electronic-step counts and convergence outcomes wherever the XML contains them. The initial numerical MD quality-control record includes at least:

```

POTIM
NSW_and_present_ionic_step_count
output_cadence
EDIFF
NELM
NELMIN
ALGO_or_IALGO
PREC
LREAL
ROPT
ENCUT
ISYM
per_step_SCF_iteration_count
per_step_SCF_convergence_status
position_cell_force_energy_completeness
restart_and_initial_velocity_provenance

```

These controls do not redefine the ensemble. They explain expected numerical quality and provide evidence for later conservation and integrity verdicts. The parser retains unknown or source-version-specific values rather than forcing them into an unsupported category. The official VASP output and control documentation establishes that vasprun.xml contains effective calculation parameters and that timestep, SCF convergence, and force-evaluation settings are relevant to MD stability and NVE energy conservation [S11-39, S11-40, S11-50–S11-54].

The initial resolver covers at least MDALGO, SMASS, ISIF, ANDERSEN_PROB, LANGEVIN_GAMMA, LANGEVIN_GAMMA_L, PMASS, NHC_NCHAINS, NHC_PERIOD, CSVR controls, multiple-thermostat controls, and source-bound bias/constraint controls. The VASP rules are taken from the official control documentation [S11-38–S11-42].

The source-level decision uses canonical diagnostic status plus a domain outcome:

```

diagnostic_status = resolved | unresolved | insufficient | rejected |
                    unavailable | not_applicable
ensemble_outcome  = NVE | NVT | NpT | NpH | driven | mixed_or_partial |
                    unsupported_variant | inconsistent_controls

```

SYSTEM, filenames, directory names, and user descriptions are retained only as comments and conflict diagnostics.

Energy reconstruction, conservation, stationarity, and production regimes

Exact source-level energy reconstruction precedes conservation analysis. A FrameEnergyCatalog records every named electronic, ionic kinetic, thermostat, barostat, lattice, bias, constraint, and reported-total channel with source name, units, completeness, and the source-specific conserved-quantity identity. A generic energy field is never sufficient.

Ionic-temperature reconstruction

Ionic temperature is reconstructed from the source-bound ionic kinetic energy using the equipartition theorem:

$$T_t = \frac{2K_{\text{ion}}(t)}{f_{\text{ion}}k_B},$$

where f_{ion} is the active quadratic ionic velocity degree-of-freedom count for that source. The definition remains simple and explicit: fixed coordinates, affirmatively known holonomic constraints, and an affirmatively removed center-of-mass mode reduce f_{ion} ; no degree of freedom is removed merely because the trajectory happens to have small momentum. Variable-cell kinetic terms remain separate from ionic kinetic temperature. VASP’s documented periodic-system example uses $f_{\text{ion}} =$

$3N - 3$ when center-of-mass translation is excluded; the adapter must reconstruct rather than assume that convention [S11-55].

A signed `IonicTemperatureDefinition` records the kinetic-energy channel, masses, active-coordinate mask, constraint evidence, center-of-mass convention, and resulting f_{ion} . A signed `IonicTemperatureStatistics` records at least:

```
frame_temperature_series
represented_time_weighted_mean
represented_time_weighted_standard_deviation
minimum_and_maximum
integrated_autocorrelation_time
effective_sample_count
block_means
mean_standard_error_and_confidence_interval
drift_slope_and_confidence_interval
stationarity_outcome
target_temperature_comparison_if_applicable
```

The standard deviation describes physical temperature fluctuation; confidence in the mean is computed from complete-system block or autocorrelation-aware uncertainty and is never obtained by treating adjacent frames as independent. For NVT/NpT the statistics may be compared with an authoritative target temperature. For NVE/NpH there is no active temperature target; the code evaluates temporal stability of the reconstructed temperature instead of demanding equality to a historical label.

Three-level trajectory-quality verdict

Trajectory quality is aggregated from two disjoint classes of checks:

```
hard_integrity_checks
soft_numerical_quality_checks
```

The signed `TrajectoryQualityVerdict` has exactly three top-level outcomes:

```
strictly_qualified
degraded_quality
unqualified
```

`strictly_qualified` means every required integrity check passes, the source controls meet the active policy, the relevant conserved or controlled quantities pass, and no material numerical-quality issue is detected.

`degraded_quality` means the trajectory remains finite, structurally valid, and quantitatively usable, but one or more noncatastrophic quality checks fail or remain marginal. Examples include measurable but bounded NVE energy drift, a manageable temperature trend, looser-than-preferred SCF convergence, real-space projection or a timestep that produces detectable integration error, or absence of a channel that is verdict-critical or required by the requested method. A genuinely optional, method-irrelevant channel is recorded as unavailable and does not degrade the trajectory. A degraded trajectory proceeds through downstream analysis. The public API emits one `TrajectoryDegradedQualityWarning`, and every result carries the exact verdict, failed checks, effect estimates, and uncertainty/provenance flags.

`unqualified` is reserved for catastrophic trajectory-integrity failure, including nonfinite or divergent energies/forces/positions, singular or inverted cells, broken atom identity, unexpected internal frame loss or nonmonotonic time, missing mandatory coordinates/cells, physically impossible atomic overlap under a species-aware hard integrity policy, or runaway displacement/velocity/force behavior. Production scientific APIs raise `TrajectoryIntegrityError` for this outcome. A diagnostic-only parse mode may return the failure certificate for inspection, but it cannot silently continue into scientific analysis.

The aggregation rule is deterministic:

```
any hard integrity failure -> unqualified
else any soft failure or material warning -> degraded_quality
else -> strictly_qualified
```

The quality verdict controls execution rejection only. It does not replace ensemble-specific scientific admissibility. For example, a degraded NVE trajectory may still yield descriptive density and occupancy statistics, while a canonical-PMF method may independently remain unavailable because the source is not canonical.

The diagnostic stage is governed by persistent TrajectoryQualityPolicy and ProductionWindowPolicy records. Their first implementation must contain at least:

```
primary_observables
physical_time_units
autocorrelation_estimator
minimum_independent_blocks
block_length_rule
drift_normalization
trend_significance_threshold
change_point_method_and_penalty
cell_and_stress_tolerances
energy_conservation_tolerance
ionic_temperature_confidence_level
ionic_temperature_mean_tolerance_if_targeted
ionic_temperature_drift_tolerance
hard_integrity_thresholds
soft_quality_thresholds
warning_emission_policy
unqualified_error_policy
selection_validation_partition
short_trajectory_behavior
```

The default block length is the maximum declared minimum duration and twice the largest accepted integrated autocorrelation time among the primary source observables. Acceptance requires at least the policy’s minimum number of independent complete-system blocks; fewer blocks yield insufficient, never relaxed thresholds. Correlated uncertainty and block resampling follow stationary-sequence methods [S11-36, S11-37, S11-46]. A configured change-point method, initially PELT with a persisted cost and penalty, records all selected boundaries and uncertainty rather than presenting a silent visual choice [S11-47].

For observable $x(t)$, drift diagnostics include both the uncertainty-normalized slope and the observation-span change normalized by the block-scale fluctuation:

$$Z_{\hat{x}} = \frac{|\hat{x}|}{\text{SE}(\hat{x})}, \quad D_x = \frac{|\hat{x}|T_{\text{obs}}}{\max(\hat{\sigma}_{x,\text{block}}, \sigma_{x,\text{floor}})}.$$

Thresholds are policy values, not hidden constants. NVT, NVE, NpT, NpH, driven, and biased runs select different primary conserved or controlled quantities. A smooth but statistically significant NVE drift is not hidden by small detrended residuals.

11E-STAT1 uses only source-level or predeclared low-complexity observables: energy, temperature, cell, stress, momentum, framework RMS descriptors, and other diagnostics whose definitions are fixed before site discovery. It does not use the adaptive E1 site density to select a production interval.

TrajectoryQualityVerdict is trajectory-wide or source-segment-wide and records whether analysis may execute. ProductionRegimeCatalog is finer-grained and records which contiguous portions support particular interpretations. A degraded trajectory may contain one or more usable production regimes. An unqualified trajectory has no scientific production regime.

The result is a ProductionRegimeCatalog, not one Boolean stationarity label. Each contiguous regime records:

```
thermalization_status
stationarity_status
energy_conservation_status
ensemble_consistency_status
production_interval_status
selection_conditioning_status
thermodynamic_admissibility_status
```

Externally proven continuation boundaries are tested preferentially. When the same trajectory must be used to select and analyze a regime, discovery and validation blocks or nested resampling are mandatory, and downstream uncertainty is labeled selection_conditioned. Multiple stationary regimes remain separate datasets.

After E1 candidate density exists, optional 11E-STAT3 evaluates held-out blockwise distribution stability. It may reject or condition a thermodynamic interpretation, but it cannot retroactively tune the production window using the same blocks that support the reported occupancy.

Ensemble-aware statistical-mechanical contract

Every landscape declares a `ThermodynamicPotentialDefinition` and a `ThermodynamicStateDefinition`. No equation is ensemble-general by default.

For stationary canonical NVT data or a certified reweighted canonical equivalent, restricted-state probabilities determine Helmholtz free-energy differences:

$$\Delta A_{ij} = -k_B T \ln \frac{P_i/g_i}{P_j/g_j}.$$

For stationary isothermal-isobaric NpT data, the analogous probability ratio defines Gibbs free-energy differences ΔG_{ij} ; energetic decomposition uses conditional enthalpy and explicit pV treatment rather than silently reusing an NVT potential-energy formula.

For stationary microcanonical NVE data at energy shell E ,

$$P_i(E) = \frac{\Omega_i(E)}{\sum_j \Omega_j(E)}, \quad \Delta S_{ij}(E) = k_B \ln \frac{P_i(E)/g_i}{P_j(E)/g_j}.$$

A canonical subsystem approximation is a separate conditional result requiring a persisted finite-bath/ensemble-equivalence policy and diagnostics [S11-48]. It is not obtained by inserting the mean kinetic temperature into the canonical formula.

Biased or constrained ensembles require exact bias/constraint provenance and an explicit reweighting measure. Raw, corrected, and reweighted energies and weights are retained separately.

The admissibility result separates diagnostic status from permitted products:

```
position_density
microcanonical_occupancy_distribution
canonical_probability_density
canonical_Helmholtz_landscape
isothermal_isobaric_Gibbs_landscape
reweighted_landscape
force_integrated_landscape
```

Each product records the selected production regime, ensemble, temperature or energy shell, standard measure, state definition, multiplicity convention, effective sample size, and approximation status.

Force provenance

The label `exact_translation_relative_to_disjoint_reference_group` is valid only when translation is the sole fitted transformation, the mobile ion is excluded from the fixed reference group, the reference membership is constant, and the force source contains no untracked constraint or thermostat contribution. A structure-fitted rotation, changing reference group, or self-referential center forces the result to `diagnostic_structure_fitted_projection` or `generalized_force_unavailable`.

A force-aware sample is admissible only when its provenance is explicit. The catalog records source format, force unit, model or electronic-structure source, frame completeness, bias and constraint contributions, thermostat or stochastic contributions, and the spatial transformation semantics.

Conservative physical forces with a geometrically exact transformation may support mechanical refinement. Only forces in a thermodynamically admissible coordinate and ensemble measure may certify a PMF gradient. Unknown, mixed, variable-cell-measure-incomplete, or diagnostic projected forces remain available as vectors but cannot elevate a site to thermodynamic-force-validated status. Biased simulations additionally retain:

```
unbiased_physical_force
known_bias_force_subtracted
density_reweighted_force_unusable
bias_force_unknown
```

Position reweighting alone does not convert the biased force into the unbiased PMF gradient. A reweighted density may be admissible while its force channel remains unusable. Bias-force subtraction requires explicit framewise bias-gradient provenance in the same coordinate measure. The geometric transform status, PMF-force status, and bias-force status are retained independently in every sample and derived force field.

Position-density evidence

Species number density and probability density

Let ω_t be the represented time interval of frame t . For all selected species atoms present in a position-admissible frame, define

$$\hat{\rho}_M(\mathbf{q}; \Sigma_h) = \frac{1}{\sum_t \omega_t} \sum_t \omega_t \sum_{a \in M_t} K_{G, \Sigma_h}^{\text{per}}(\mathbf{q} - \mathbf{q}_{a,t}).$$

Then

$$\int_{\Omega} \hat{\rho}_M(\mathbf{q}; \Sigma_h) d\mathbf{q} = \frac{\sum_t \omega_t N_{M,t}}{\sum_t \omega_t} = \bar{N}_M.$$

The one-particle probability density is

$$\hat{p}_M(\mathbf{q}; \Sigma_h) = \frac{\hat{\rho}_M(\mathbf{q}; \Sigma_h)}{\bar{N}_M}, \quad \int_{\Omega} \hat{p}_M(\mathbf{q}; \Sigma_h) d\mathbf{q} = 1.$$

Frame weights are not assumed equal when timesteps are nonuniform, trajectories are concatenated, or frames are subsampled. Weight construction is segment aware. Each sample retains:

```
trajectory_segment_id
segment_local_frame_weight
represented_interval_left
represented_interval_right
discontinuity_status
```

The default quadrature uses midpoint intervals only inside one continuous trajectory segment and half intervals at segment endpoints. A frame never represents time across a restart gap, rejected interval, ensemble change, thermostat change, topology-regime boundary, or independent-trajectory boundary. A position-admissible frame normally contains the complete selected species population; atom-specific missingness must not silently alter frame weight.

Kernel density estimation follows Rosenblatt and Parzen [S11-18, S11-19]. The bandwidth is a statistical model parameter, not a numerical grid interval or a rendering tolerance.

Kernel metric and reference-cell covariance

A Gaussian KDE owns a symmetric positive-definite covariance Σ_h in its declared coordinate measure:

$$K_{\Sigma_h}(\boldsymbol{\delta}) = \frac{\exp[\frac{1}{2} \boldsymbol{\delta} \Sigma_h^{-1} \boldsymbol{\delta}^T]}{(2\pi)^{3/2} \sqrt{\det \Sigma_h}}.$$

The initial policies are:

```
registered_cartesian_isotropic
    Sigma_h = h^2 I in the registered Cartesian domain
```

```
fractional_coordinate_isotropic
    isotropic width h_f in fractional coordinates, equivalent to
    Sigma_h = h_f^2 G^T G in a fixed registered cell G
```

```
explicit_covariance
    caller-supplied positive-definite covariance with declared units and frame
```

Under a fixed row-vector coordinate change $\mathbf{q}' = \mathbf{q}A$, the same physical smoothing operator transforms as

$$\Sigma'_h = A^T \Sigma_h A.$$

The kernel metric, covariance, coordinate measure, units, and transformation provenance are part of the field signature. Selecting a different valid H_{ref} must not silently redefine the estimator. The Na-LTA pilot includes a modest reference-cell sensitivity comparison, such as frame 0 versus a representative production frame, with the covariance transformed consistently when the same physical smoothing is intended.

Analysis geometry metric and certified periodic distance

The smoothing covariance does not by itself define the geometry used for minimum-image lifting, gradient flow, ridges, basins, path comparison, or catalog correspondence. Every registered analysis owns a separate immutable positive-definite metric P :

$$\| \delta \|_P^2 = \delta P \delta^T.$$

Under a fixed row-vector coordinate change $\mathbf{q}' = \mathbf{q}A$, the same geometry transforms as

$$P' = A^{-1} P A^{-T}.$$

The initial policy registered_cartesian_euclidean uses $P = I$ in the declared registered Cartesian domain. An explicit metric is permitted when its units, coordinate frame, and transformation provenance are supplied. The same P governs:

periodic closest-image distance and local-chart lifting
density metric-gradient or mean-shift flow
Hessian orthogonality and ridge normal spaces
basin and saddle construction
attractor correspondence and path-shape distance
periodic comparison clustering

Three metric-bearing objects remain distinct:

RegistrationFitMetric
fits framework alignment and translation residuals

AnalysisGeometryMetric
defines MIC, local charts, gradient flow, ridges, basins, and path geometry

KernelMetricDefinition
defines statistical smoothing covariance

They may be derived from one declared physical convention, but none is silently substituted for another.

All differential topology is evaluated in a metric-orthonormal chart. Choose a fixed factor L with $P = LL^T$ and local row coordinate $\mathbf{y} = \mathbf{q}L$. Gradients, Hessian eigenvalues, ridge normal spaces, and steepest-ascent flow appearing below refer to this $\mathbf{y}$ chart, or to an algebraically equivalent metric-aware operator. This prevents a nonorthogonal change of registered coordinates from changing the scientific basin topology.

For a triclinic cell, $\text{MIC}_{G,P}\{\mathbf{G}, \mathbf{P}\}$ means the closest lattice-vector solution

$$\text{MIC}_{G,P}(\delta) = \delta - \mathbf{n}_* G, \quad \mathbf{n}_* = \underset{\mathbf{n} \in \mathbb{Z}^3}{\text{argmin}} \ \| \delta - \mathbf{n} G \|_P.$$

Componentwise fractional rounding is not assumed to solve this problem for a skewed cell. The backend uses a certified reduced-lattice or bounded integer search and records ties or near ties. Ambiguous closest images fail closed for local moments, force centers, and event translations.

The kernel covariance Σ_h controls statistical smoothing; P controls geometric notions of distance and topology. They may be chosen consistently from one physical length scale, but one is never silently substituted for the other.

Periodized Gaussian on a triclinic torus

For fixed registered cell G , the normalized periodic kernel is

$$K_{G,\Sigma}^{\text{per}}(\boldsymbol{\delta}) = \sum_{\mathbf{n} \in \mathbb{Z}^3} K_{\Sigma}(\boldsymbol{\delta} + \mathbf{n}G),$$

where $\mathbf{n}$ is an integer row vector. It integrates to one over one periodic cell. The direct image sum is the numerical oracle. Image enumeration is performed in lattice coordinates and is truncated by a declared Mahalanobis-radius or equivalent tail bound; the omitted-mass bound is retained. A minimum-image Gaussian is not generally identical to the periodized Gaussian and is permitted only when a conservative small-bandwidth certificate bounds the neglected images.

For a uniform fractional grid with dimensions (N_1, N_2, N_3) , each node or voxel uses the declared quadrature convention with volume weight

$$\Delta V = \frac{|\det G|}{N_1 N_2 N_3}.$$

Normalization, gradient, and Hessian evaluations use one kernel contract. Dense, adaptive, and block-sparse backends must agree with the same triclinic image sum within their stated field-error bounds. The kernel contract records behavior when the covariance scale is not small compared with the torus injectivity radius; no minimum-image shortcut is inferred.

Physical and reference-material density measures

A density in the physical policy is measured with respect to the instantaneous physical Cartesian volume element. Under `reference_material`, the field is measured with respect to the declared reference-material coordinate $d\mathbf{q}$ and fixed cell H_{ref} .

These are different scientific objects:

`physical_cartesian_density`
`reference_material_density`

The reference-material field is appropriate for locating material-coordinate sites under cell breathing or strain. It must not be described as an instantaneous physical Cartesian density or PMF without the corresponding Jacobian and ensemble treatment. The real Na-LTA pilot compares physical or translation-registered and reference-material results where both are feasible.

A pooled `physical_cartesian_density` initially requires a constant registered cell. Variable-cell trajectories use `reference_material_density` or produce separate per-frame physical fields. No single pooled physical Cartesian torus is implied when the periodic domain changes with time.

Sampled support and local evidence

For a kernel value $K_n(\mathbf{q})$ and sample weight w_n , retain the raw local kernel effective sample size

$$N_{\text{eff}}^{\text{kernel}}(\mathbf{q}) = \frac{[\sum_n w_n K_n(\mathbf{q})]^2}{\sum_n [w_n K_n(\mathbf{q})]^2}.$$

This quantity is correlation-blind and is not an uncertainty estimate by itself. Scientific support requires both a minimum local kernel support and reproducibility across complete-system contiguous time blocks or independent trajectories. Highly correlated adjacent frames cannot manufacture support.

Feature-level sampling adequacy and cross-fitting

Local KDE support determines whether a numerical field value can be evaluated; it does not certify a physical basin or transition state. The architecture tracks:

$$N_{\text{raw}} \rightarrow N_{\text{eff}} \rightarrow N_{\text{independent visits/events}} \rightarrow N_{\text{independent blocks/replicas}}.$$

The primary resampling unit is the complete-system time block or an independent trajectory. Multiple mobile ions in one frame increase spatial coverage but do not multiply independent energetic or thermodynamic observations.

`SamplingAdequacyPolicy` and `FeatureCorrespondencePolicy` define this candidate-validation sequence:

1. construct `EvidenceCrossfitPartition` before feature discovery;
2. discover per-realization basin and density-boundary candidates on discovery data;
3. select bandwidth, grid, correspondence, and candidate-complexity policies using only discovery/model-selection data;

4. let GR4 freeze one FrozenCandidateCatalog and its exact numerical hypothesis;
5. assign held-out basin-validation blocks without refitting;
6. count independent basin residences and basin-to-basin passages without requiring a saddle;
7. certify basins;
8. validate density-boundary/corridor candidates using independent corridor-validation evidence not used for discovery or selection; and
9. perform any final refit only after validation and retain the pre-refit certificates.

Candidate confidence is represented by orthogonal fields, not one hierarchy:

```
numerical_support_status
spatial_recurrence_status
temporal_recurrence_status
cross_block_validation_status
cross_replica_status
uncertainty_status
promotion_decision
```

E2 owns per-realization numerical candidates. GR4 alone owns the source-bound FrozenCandidateCatalog evaluated by held-out stages. A later all-data FinalRefitCatalog has a new signature and cannot inherit the frozen catalog's parameter-validation certificate.

Matched density and force smoothing

Density-force consistency requires the same periodized kernel definition, covariance scale, sample weights, and joint frame subset. Define

$$\hat{p}_{\Sigma_h}(\mathbf{q}) = \frac{1}{W} \sum_n w_n K_{G, \Sigma_h}^{\text{per}}(\mathbf{q} - \mathbf{q}_n),$$

and

$$\hat{\mathbf{f}}_{\Sigma_h}(\mathbf{q}) = \frac{\sum_n w_n K_{G, \Sigma_h}^{\text{per}}(\mathbf{q} - \mathbf{q}_n) \mathbf{f}_n}{\sum_n w_n K_{G, \Sigma_h}^{\text{per}}(\mathbf{q} - \mathbf{q}_n)}.$$

The finite-sample consistency test compares this matched pair. A density estimated on all admissible positions remains available for site discovery, but it is not compared directly with a force field from a smaller subset.

Density score covector and metric gradient

The coordinate derivative of the log density is the score covector

$$\mathbf{s}_q(\mathbf{q}) = d_q \ln p(\mathbf{q}).$$

Under a fixed row-vector coordinate change $\mathbf{q}' = \mathbf{q}A$,

$$\mathbf{s}_{q'} = \mathbf{s}_q A^{-T}.$$

It therefore transforms like the force covector. The equilibrium density-force consistency relation is

$$\boxed{\bar{\mathbf{F}}_q(\mathbf{q}) = k_B T \mathbf{s}_q(\mathbf{q})}$$

in one declared coordinate measure. The vector that generates steepest-ascent flow under analysis metric P is a different object:

$$\boxed{\text{grad}_P \ln p = \mathbf{s}_q P^{-1}}.$$

DensityScoreCovector is used for force comparison, thermodynamic integration, and covector-valued diagnostics. MetricGradientVector is used for gradient flow, mean shift, ridge normals, and basin construction. A consumer must never compare force directly with the metric-raised vector unless it first lowers that vector with the declared metric. Score, metric gradient, derivative realization error, and coordinate-transform provenance are stored separately. Their shared field signature

records P , Σ_h , registered domain, coordinate measure, and sample subset so a consumer cannot combine incompatible derivatives.

Bandwidth ladder and attractor lineage

No single smoothing scale is authoritative. For one fixed positive-definite metric shape B , the default ladder uses

$$\Sigma_\ell = h_\ell^2 B, \quad h_1 < h_2 < \dots < h_L.$$

An explicit covariance ladder is also permitted when every matrix and correspondence is declared. Each covariance scale produces a deterministic attractor and basin catalog. A `DensityAttractorLineage` records:

- attractor type and periodic support at every covariance scale;
- parent and child merge or split events;
- basin-overlap score;
- periodic displacement of isolated modes;
- overlap and intrinsic-dimension changes for extended attractors;
- basin probability change;
- split or merge ambiguity; and
- the smoothing-scale survival interval.

A grid index or local-maximum number is never a persistent site identity. Attractors that exist only over one narrow smoothing interval remain method-dependent unless independently supported.

Operational scale-consensus catalog

Downstream force fitting, temporal persistence, and segmentation require one concrete, versioned catalog. A `ScaleConsensusCatalog` is therefore produced from the full lineage; no plotting default or visually convenient bandwidth may become authoritative implicitly. Its `OperationalScaleDecision` retains:

candidate topology-stable scale intervals
selected covariance or consensus construction
selection criterion and independent selection evidence
competing split/merge hypotheses
support and numerical certificates
selection uncertainty and `scale_ambiguous` status

The decision first identifies covariance intervals with stable supported topology, then rejects intervals without field and topology certification. When several nested split/merge hypotheses remain plausible, independent `model_selection` temporal persistence and admissible force evidence may distinguish physical substates from smoothing artifacts. If they do not, the catalog retains the competing hypotheses and is `scale_ambiguous`; later rate or PMF claims that depend on one unresolved choice are prohibited. An optional consensus construction may retain only attractors with stable correspondence over a declared interval, but its basin construction and uncertainty must be explicit.

When the spatial evidence alone cannot choose, Stage 11E2 emits a `ScaleHypothesisSet` rather than pretending that one catalog is resolved. Stage 11E3 and Stage 11E4 then evaluate each retained hypothesis under identical force and temporal contracts; Stage 11E5 may select one hypothesis only when `model_selection` evidence distinguishes it, otherwise `scale_ambiguous` persists. The exact catalog or hypothesis set used by each downstream stage records the lineage digest and operational decision. Re-selecting a scale creates a new catalog identity rather than mutating the previous one.

Isolated modes and extended attractors

A statistical site need not be an isolated point maximum. The authoritative object is a `DensityAttractor` with one of the forms:

`isolated_mode`
`ridge_or_manifold`
`flat_unresolved_component`

An annular site is a connected one-dimensional ridge with restoring confinement normal to the ridge and weak tangential variation. It must not be reduced to an arbitrary point by plateau tie breaking. Discrete off-center sites remain separate isolated modes.

For an extended attractor, retain its connected ridge support, intrinsic dimension, normal confinement, tangential variation, compact geometric representation, basin probability, and bootstrap stability.

State-local periodic charts

Wrapped coordinates are suitable for a periodic density field but not directly for Euclidean moments, local force fits, or compact transfer models. Every attractor therefore owns an `AttractorLocalChart` bound to the registered-cell signature. For an isolated mode with periodic anchor μ_i , samples are lifted by minimum-image displacement,

$$\delta_n = \text{MIC}_{G,P}(\mathbf{q}_n - \mu_i),$$

and covariance, local Hessians, and harmonic fits use δ_n , not globally wrapped coordinates. The chart records the anchor, image convention, lifted samples, validity radius, and any chart-boundary ambiguity.

An extended attractor may require an intrinsic periodic parameterization or several overlapping charts. The first implementation supports isolated-mode charts and an explicitly parameterized annular chart; a general manifold whose chart cannot be certified remains `manifold_chart_unresolved` and is excluded from Euclidean force fitting.

Deterministic attractor and basin construction

The initial authoritative backend is:

```
periodic KDE field
-> deterministic periodic-grid extrema and ridge components
-> canonical plateau-component ownership
-> discrete steepest-ascent or ridge-attraction labels
-> support-restricted periodic basin ownership
-> supported inter-basin saddle densities
-> attractor lineage across bandwidths
-> operational scale-consensus catalog
```

Continuous ridge criterion

In the metric-orthonormal coordinate $\mathbf{y} = \mathbf{q}L$, let the smooth periodized KDE have Hessian eigendecomposition

$$\nabla_{\mathbf{y}}^2 \hat{p} = V \Lambda V^T, \quad \lambda_1 \geq \lambda_2 \geq \lambda_3.$$

For a one-dimensional ridge in three dimensions, let $V_{\perp} = [\mathbf{v}_2, \mathbf{v}_3]$. A supported point is a ridge candidate when

$$V_{\perp}^T \nabla_{\mathbf{y}} \hat{p} = \mathbf{0}, \quad \lambda_2(\mathbf{q}) \leq -\kappa_{\perp} < 0,$$

with a declared eigengap, support, and derivative-uncertainty requirement. This adapts density-ridge definitions from the nonparametric ridge literature [S11-34]. If the normal eigenspace, eigengap, or intrinsic dimension is unresolved, the component remains `ridge_dimension_unresolved`. A point mode instead satisfies $\nabla_{\mathbf{y}} \hat{p} = \mathbf{0}$ with all three curvatures negative within uncertainty.

A corrugated annulus remains one extended attractor only when its connected ridge survives bandwidth and grid refinement and the tangential modulation does not meet the declared persistent-saddle criterion for splitting into separate point states. The exact persistence and curvature thresholds belong to the Stage 11E2 specification.

Support-certified periodic cell complex and transition candidates

The production topology is built on one complete periodic cell complex in fractional- grid coordinates with explicit wrap adjacency. Density, gradient, Hessian, critical-cell, plateau, ridge, numerical transition-candidate, and basin labels share that complex. `SupportedPeriodicCellComplex` classifies every cell as:

```
supported_basin
supported_transition_region
supported_background
unsupported_unknown
numerically_unresolved
```

A face-adjacent merge cell or density bottleneck is a `density_boundary_candidate`. When field and derivative support also pass, it may be called a `numerically_supported_saddle_candidate`. Neither name implies an observed transition event, an equilibrium transition state, a barrier, or an authoritative kinetic edge.

Unsupported or unevaluated cells are never assigned to a basin and are never treated as zero-density background. A basin cannot connect through unsupported space. Disconnected supported components acquire no inferred adjacency or relative thermodynamic offset. Rendering sparsification is downstream and cannot create scientific connectivity.

The discrete critical-cell and attachment logic may adapt Forman cell-complex Morse theory [S11-35]. Mean-shift ascent remains the theoretical mode-seeking reference [S11-20]. HDBSCAN remains an independent cluster-stability validator using the same certified periodic metric [S11-21]. None of these numerical backends bypasses SAMP2 event and held-out-corridor validation.

Field and topology certification

Numerical realization owns two independent certificates:

`FieldErrorCertificate`

density, gradient, and Hessian error bounds against the declared operator

`TopologyStabilityCertificate`

critical points, ridges, saddles, basin adjacency, and periodic connectivity
stable under declared refinement and backend comparison

A small pointwise field error does not by itself certify topology. Sparse or adaptive blocks that have not been evaluated are treated as unknown, not as zero. A block may be excluded from topology only when a conservative upper/derivative bound proves it cannot contain a supported critical feature or create a basin connection. Refinement concentrates around extrema, ridges, saddles, basin boundaries, and periodic seams until identities are stable or explicitly unresolved. Small synthetic fixtures use a dense oracle; production fields retain the refinement history and both certificates.

Provisional cores

Each attractor owns a nonparametric basin B_i and a type-specific core construction. For an isolated mode, let $p_i^{\max}$ be its maximum and p_i^{saddle} the highest resolved density connecting it to a neighboring basin. Define

$$\chi_i(\mathbf{q}) = \frac{\log \hat{p}(\mathbf{q}) - \log p_i^{\text{saddle}}}{\log p_i^{\max} - \log p_i^{\text{saddle}}},$$

and, for declared $0 < \tau_c < 1$,

$$C_i(\tau_c) = \{\mathbf{q} \in B_i : \chi_i(\mathbf{q}) \geq \tau_c\}.$$

For an extended attractor, one global maximum is not used. Let $\pi_i(\mathbf{q})$ project a supported point to the certified ridge or manifold, and let $p_i^{\text{ridge}}(\pi_i(\mathbf{q}))$ be the local ridge density. The normal-depth coordinate is

$$\chi_i^\perp(\mathbf{q}) = \frac{\log \hat{p}(\mathbf{q}) - \log p_i^{\text{saddle}}}{\log p_i^{\text{ridge}}(\pi_i(\mathbf{q})) - \log p_i^{\text{saddle}}}.$$

An annular core uses $\chi_i^\perp$ together with the certified annular chart so that weak tangential density modulation does not break one continuous state into arbitrary core sectors. General manifold cores remain unresolved until a projection and local ridge-density model are certified.

A core owns one explicit depth source:

`interbasin_saddle_depth`
`supported_boundary_depth`
`probability_content_core`
`core_unresolved`

`interbasin_saddle_depth` is preferred when a neighboring supported basin and resolved saddle exist. A single attractor or an attractor isolated in its supported component has no interbasin saddle; it may use a declared supported-boundary depth or a probability-content core with retained mass fraction and uncertainty. A fallback never invents a neighboring state or

barrier. If the connecting saddle, supported boundary, local chart, projection, or ridge density is unresolved and no declared fallback passes, the core remains unresolved. The canonical nonparametric basin and core remain authoritative even when an ellipsoid, Gaussian, annulus, or other compact transfer model is fitted.

Mechanical force evidence and thermodynamic mean-force reconstruction

Two force products with different admissibility

Stage 11 keeps two force-derived products separate.

`LocalMechanicalForceRefinement` uses geometrically admissible conservative physical forces to test local restoring behavior, center offsets, stiffness, and manifold-normal confinement. It does not require a canonical PMF and may be available for NVE data.

`ThermodynamicMeanForceCertificate` tests whether a conditional force is the gradient of a declared canonical or validly reweighted reduced free-energy landscape. It requires the matching ensemble measure, coordinate Jacobian, temperature/reweighting provenance, and joint position-force support. Mechanical validity never promotes thermodynamic validity.

Canonical conditional mean force

For a canonical or validly reweighted-canonical coarse coordinate in the declared coordinate measure,

$$\bar{\mathbf{F}}_{M,q}(\mathbf{q}) = \mathbb{E}[\mathbf{F}_M^{(q)} \mid \mathbf{q}] = -d_q A_M(\mathbf{q}) = k_B T d_q \ln p_M(\mathbf{q}).$$

This identity is not applied generically to NVE, NpH, unknown, or mixed-thermostat data. A stationary NVE trajectory may use a separately implemented microcanonical mean-force formalism or an explicitly certified subsystem-canonical approximation; otherwise density-force comparison is diagnostic-only. The metric gradient used for basin flow is obtained only after raising the score with P^{-1} and is not the covector compared directly with force. Average-force free-energy methods and force matching provide the theoretical basis [S11-22, S11-23].

Local mechanical force refinement

For a position-derived point candidate, fit inside its certified local periodic chart using only SAMP0 discovery/model-selection evidence,

$$\mathbf{f}_n = \mathbf{b}_i - \delta_n \mathbf{K}_i + \epsilon_n, \quad \mathbf{K}_i = \mathbf{K}_i^T.$$

When $\mathbf{K}_i$ is nonsingular under the row-vector convention, the force-defined center offset is

$$\delta_i^{(F)} = \mathbf{b}_i \mathbf{K}_i^{-1}.$$

The result retains the density anchor, intercept, force-defined center, joint center/stiffness uncertainty, chart containment, and positive-definiteness probability. The force center is not reported when $\mathbf{K}_i$ is singular, poorly conditioned, or places the center outside the supported chart. A point basin requires locally restoring curvature within uncertainty; an annular manifold is fitted in certified ridge-normal coordinates without imposing one global point center.

A held-out mechanical-force evaluation may measure residuals and center agreement but may not refit parameters. An optional all-data post-validation refit receives a new signature and does not inherit the original held-out certificate.

The residence covariance diagnostic

$$\Sigma_i^{(\text{res})} = \text{Cov} [\delta \mid \text{provisional residence in } B_i]$$

is always reported descriptively. The harmonic equipartition relation

$$\Sigma_i^{(\text{res})} \approx k_B T \mathbf{K}_i^{-1}$$

is evaluated only for canonical/reweighted-canonical data or under an explicitly accepted subsystem-canonical approximation. Basin truncation, anharmonicity, correlated many-ion conditioning, and unresolved ensemble measure may invalidate this thermodynamic comparison without invalidating the mechanical fit or spatial attractor.

Raw mean-force field

The matched-kernel conditional force field retains local force variance, effective sample size, support, and time-block uncertainty. Force-assisted density estimators may reduce variance but cannot create claims in unsampled regions [S11-28].

Curl and periodic harmonic components

For an exact equilibrium PMF,

$$\nabla \times \bar{\mathbf{f}} = \mathbf{0}.$$

On a periodic three-torus, a vector field decomposes schematically as

$$\mathbf{f} = -\nabla A + \nabla \times \mathbf{B} + \mathbf{h},$$

where $\mathbf{h}$ is a harmonic component. Nonzero curl, nonzero circulation, or a nonzero harmonic component is a diagnostic of sampling error, nonequilibrium, coordinate or force mis-specification, or unresolved conditioning.

Helmholtz-Hodge decomposition supplies the mathematical language [S11-26]. Poisson or least-squares integration may expose the closest conservative field [S11-27], but projection is never automatic.

The full periodic torus and a sampled support subdomain are different mathematical domains. The full torus has its periodic harmonic directions and circulation cycles. A support-limited component may also have boundaries, disconnected pieces, or holes, so its harmonic space and admissible boundary terms depend on the topology of that subdomain. Curl-free behavior on sampled cells alone does not establish a single-valued potential when nontrivial circulation remains. Every PMF attempt therefore records:

```
full_torus_hodge or supported_domain_integrability
domain cell-complex topology and connected component
boundary conditions and excluded unsupported boundary
independent circulation generators and measured circulation
harmonic-space dimension or unresolved status
```

No full-torus conclusion is inferred from a partial support component, and no supported-domain relative offset is invented across disconnected components.

Optional support-limited force-PMF reconstruction

This subsection describes the force-integrated estimator only. A density-derived PMF is a separate estimator and does not require force evidence. Global force-PMF reconstruction is optional and does not block local site discovery. It is attempted only when:

- the declared numerical domain and boundary conditions are explicit;
- the sampled support component is connected;
- the field is adequately supported across the integration domain;
- periodic circulation and harmonic diagnostics are reported; and
- disconnected support components are not assigned relative free-energy offsets.

The preferred reconstruction fits a scalar potential directly:

$$\mathcal{L}_F(\theta) = \sum_n w_n \left\| \mathbf{f}_n^{(q)} + \nabla A_\theta(\mathbf{q}_n) \right\|^2 + \mathcal{R}(\theta).$$

Conservativity is guaranteed by construction. Periodic splines or radial basis functions are initial candidates. Variational reconstruction follows single-sweep free-energy methods [S11-24]. Gaussian-process gradient reconstruction is a later uncertainty-aware option [S11-25, S11-31]. Raw and projected fields, support, boundary conditions, residuals, and additive-constant conventions remain available together.

Joint site validation and structural classification

Orthogonal evidence and classification statuses

Every evidence channel uses the canonical diagnostic registry:

resolved | unresolved | insufficient | rejected | unavailable | not_applicable

Each channel also carries a domain outcome rather than embedding that outcome in a new incompatible status enum:

```
spatial_diagnostic_status
spatial_outcome          # candidate | recurrent | method_dependent | absent

temporal_diagnostic_status
temporal_outcome         # persistent | nonpersistent | censored | unavailable

force_diagnostic_status
force_outcome            # diagnostic_only | correlated | consistent | inconsistent

stationarity_diagnostic_status
stationarity_outcome     # stationary | nonstationary | selection_conditioned

geometry_diagnostic_status
attractor_geometry      # isolated_point | annular_manifold |
                        # general_manifold | flat_unresolved

curvature_diagnostic_status
curvature_outcome       # stable | saddle | unstable | unresolved

overall_promotion_decision # accepted | conditional | blocked | rejected
```

Mappings from ENS/STAT/SAMP results to E5 fields are explicit and immutable. Force availability may strengthen certification but never deletes accepted position/time evidence. Position and force from one trajectory are not independent; uncertainty uses matched complete-system block resamples. A state with accepted spatial and temporal evidence but unavailable admissible force evidence may receive a conditional metastable interpretation, not a force-validated one.

Provisional temporal evidence

Frozen numerical basin candidates may be assigned provisionally before final basin or saddle certification. Held-out assignments use only the frozen basin regions and do not require a saddle definition. Core entry and basin retention produce raw dwell intervals, local decorrelation estimates, censoring, and basin-to-basin passages. This stage does not publish the final cleaned event catalog.

A passage is recognized when one atom leaves a frozen basin and subsequently enters a different frozen basin under the declared gap/censoring policy. A validated saddle is not an input to passage recognition; the resulting independent passages are later used to validate or reject candidate transition corridors.

The local vibration/decorrelation timescale is explicit. Acceptable estimators include a site-conditioned coordinate autocorrelation time, site-conditioned VACF decay, Hessian-derived harmonic timescale, or declared physical minimum. The estimator, block provenance, and uncertainty are retained, and short trajectories may return insufficient.

Basin and transition-corridor sampling certificates

Every candidate basin receives a `BasinSamplingCertificate` with raw and effective sample counts, represented time, independent residences, complete-system blocks, trajectory/replica coverage, ion-time probability, occupancy, bootstrap recurrence, held-out support, anchor/shape uncertainty, and grid/bandwidth survival.

Its evidence fields are orthogonal:

```
numerical_support_status
spatial_recurrence_status
temporal_recurrence_status
cross_block_validation_status
cross_replica_status
uncertainty_status
promotion_decision
rejection_reasons
```

A long single residence can support spatial localization while remaining insufficient for recurrent metastability.

Every candidate basin pair or corridor receives a `TransitionCorridorSamplingCertificate` containing independent passage count, forward/reverse counts, complete-system block and replica support, path-progress coverage, local field support, candidate recurrence, corridor-location uncertainty, density-level uncertainty, and event-path agreement.

Terminology is fixed:

`density_boundary_candidate`
`numerically_supported_saddle_candidate`
`observed_one_off_passage`
`sampling_supported_transition_corridor`
`sampling_supported_saddle_candidate`

`density_level_uncertainty`, `free_energy_barrier_uncertainty`, and `conditional_energy_uncertainty` are distinct fields. One passage may be retained as an observation but never validates an equilibrium saddle or rate.

Partial-catalog and saturation certificate

Every dataset produces a `DiscoveryScopeCertificate` with species, composition, loading, ensemble, temperature or energy-shell scope, trajectory/replica counts, physical and effective observation time, cumulative basin/corridor/event discovery, holdout novelty, and saturation diagnostics. Allowed public claims include:

`strongly_undersaturated`
`still_discovering`
`apparently_plateauing_at_this_timescale`
`replicated_partial_catalog`
`structurally_enumerated_but_dynamically_partial`
`observed_partial_catalog`

A plateau means only that no new supported feature appeared over the observed extension. SAMP3 reports raw event count, at-risk exposure, occupancy exposure, censoring, and model eligibility. A formal zero-event or low-count rate interval is owned by Stage 11F0 and requires a signed `RateBoundModel` specifying Poisson or other event assumptions, stationarity, exposure, censoring, and confidence method [S11-49].

Density-force consistency refers to the authoritative force contract

Density-force comparison is governed exclusively by **Canonical conditional mean force** and Stage 11E3B. It is available only under the exact ensemble, reweighting, coordinate-measure, Jacobian, transformed-covector, matched-kernel, and joint-support requirements stated there. Generic NVE data are not upgraded by this cross-reference.

A failed or unavailable thermodynamic mean-force comparison remains explicit and never deletes a valid E3A mechanical refinement or descriptive density result.

Major and minor sites

The catalog reports separate rankings by basin probability and temporal persistence. A low-population, long-lived basin may be a minor metastable site. A high-density bridge with short visits may be transition support. No fixed majority-occupancy threshold defines a site.

Ion-time probability and many-ion occupancy

For a normalized species probability density, the integral over basin B_i ,

$$P_i^{\text{ion}} = \int_{B_i} \hat{p}_M(\mathbf{q}) d\mathbf{q},$$

is the fraction of ion-time samples in that basin. It is not, by itself, the probability that the structural site is occupied. The mean occupancy is

$$\langle n_i \rangle = \int_{B_i} \hat{p}_M(\mathbf{q}) d\mathbf{q}.$$

Final site statistics separately report ion-time fraction, mean occupancy, occupancy distribution, vacancy fraction, and multiple-occupancy fraction. Many-ion correlations are retained at the complete-frame level.

Structural association and species-dependent coordination

Only after statistical discovery and provisional temporal validation is one state associated with Stage 11C/11D structural objects. Association is not restricted to one ring. A cage-interior, interstitial, or transition state may be influenced by several windows or tiles.

StructuralAssociationSet

- primary association, when identifiable
- secondary ring/cage/tile associations
- geometric and chemical scores
- ambiguity and support
- registered and physical geometry references

The registered structural view is used to compare density-space positions. The physical geometry is used for exact bond distances, apertures, and coordination. An association remains ambiguous rather than being forced to the nearest ring.

Statistical-state instances and structural symmetry orbits

Every learned basin is first a distinct ValidatedStatisticalState instance. Optional structural grouping records

StructuralSymmetryOrbit

- orbit identity and member state instances
- ideal multiplicity and observed multiplicity
- stabilizer or site-symmetry provenance
- missing, unresolved, or split members
- Si/Al-order, occupancy, and geometry symmetry-breaking evidence

The observed kinetic network always retains state instances as nodes. An orbit-level summary is created only after framework chemistry, oxygen classes, local occupancy, density, force, and transition statistics pass an exchangeability test. No symmetry augmentation of trajectory samples occurs by default; it would hide genuine symmetry breaking and overstate uncertainty support.

Exact coordination fingerprint

For one state and one associated structural object, the authoritative species-dependent record is

$$\mathbf{d}_M = (d_{MO_1}, \dots, d_{MO_k}, d_{MT_1}, \dots),$$

with persistent atom identities, oxygen classes, local ion coordinates, and the complete conditioning context. Stage 11E5a owns this record; Stage 11C3 does not.

Coordination descriptors use the same separation as structural ring analysis:

- an exact unweighted cyclic-index spectrum for ordered discrete M–O sequences;
- boundary-measure angular moments when a continuous angular measure is intended; and
- a rank-safe actual-angle fit for physical angular modulation.

For a hypothetical point with the same normal coordinate and zero in-plane displacement, compute the exact centered-reference distances $d_j^{(0)}$ and

$$\Delta d_j = d_j - d_j^{(0)}.$$

The residual spectra ΔD_m are diagnostic summaries. They are not an orthogonal or exact separation of ring corrugation and cation displacement. Irregular spacing, puckering, large off-centering, and nonlinear distance geometry can mix harmonics. The authoritative off-center measures remain the direct local coordinates

$$(u_M, v_M, z_M), \quad r_\perp = \sqrt{u_M^2 + v_M^2},$$

and the exact ordered distance vector.

Forward-model check

For one learned registered center or instantaneous geometry-conditioned center, first map the center back to the physical frame of each sample:

$$\mathbf{x}_{\text{site},t} = (\mathbf{q}_{\text{site},t} - \mathbf{b}_t)M_t^{-1}.$$

Using the persistent matched image of oxygen j , calculate the framewise physical distance

$$d_{j,t}^{\text{geom}} = \|\mathbf{x}_{\text{site},t} - \mathbf{x}_{\text{O}_j,t}^{(\text{matched image})}\|.$$

Compare the conditional distribution or conditional mean of these framewise distances with the observed state-conditioned M-O sequence. Distances are never computed between a registered site coordinate and a physical oxygen coordinate, and distance from averaged structures is not substituted for the average of framewise distances. The result separates:

geometrically_explained_off_centering
chemical_or_environment_residual
occupancy_conditioned_residual
unresolved_mixture

A large $m = 1$ coordination amplitude alone is insufficient to declare an off-centered site.

Classification evidence

For each association retain at least:

normal and in-plane site displacement
ordered M-O and M-T distances
structural cyclic and physical-angle spectra
coordination cyclic and physical-angle spectra
off-center residual diagnostics
chemical phase-locking scores
opposite-side partner score
angular multiplicity and annularity scores
ring/cage distance and association confidence
forward-model residual

For an S6R, a centered serrated site may satisfy

$$r_{\perp} \simeq 0, \quad |\Delta D_1| \simeq 0, \quad |D_3| > 0,$$

whereas an off-centered serrated site has nonzero direct $r_{\perp}$, a long-wavelength modulation compatible with the exact geometry, and a retained short-wavelength chemical component. An $m = 2$ structural component can indicate elliptical or twofold ring deformation and must not be relabeled as cation off-centering.

Phase locking is evaluated only when the amplitude and phase are resolved under the formal structural gauge. Persistent locking may support labels such as oxygen-directed, gap-directed, or sector-locked. Several persistent angular modes are separate statistical microstates. Angular circulation with normal and radial confinement may define `smooth_annular`, `corrugated_annular`, or `discreteAngularMinima` according to density, force, and temporal evidence.

Occupancy-conditioned fingerprints

Before pooling all samples from one nominal state, compare the coordination fingerprint under local occupancy context η :

$$p(\mathbf{d}_M \mid \eta).$$

When supported by the data, report center shifts, phase changes, covariance changes, or split subpopulations conditioned on neighboring occupancy. The first implementation need not build a many-body PMF, but it must detect when one pooled fingerprint is an unresolved occupancy-conditioned mixture.

Nominally equivalent rings are pooled only after exchangeability tests. Local Si/Al ordering, oxygen-class splitting, neighboring occupancy, distortion, and site history may require separate subclasses even when the natural-tiling interface family is the same. Borderline cases remain general or `classification_ambiguous`.

EvidenceCrossfitPartition, thermodynamic partitions, and final refit

One signed EvidenceCrossfitPartition assigns complete-system blocks or independent trajectories to structural/statistical roles:

discovery
model_selection
basin_validation
corridor_validation
thermodynamic_estimation
thermodynamic_validation
optional_final_refit

thermodynamic_estimation owns source-qualified occupancy, conditional-energy, PMF, or effective-Hamiltonian estimation. thermodynamic_validation is reserved for an optional independent cross-check. If the latter is unavailable, the estimate may still be reported when its own ensemble, state, sampling, and uncertainty gates pass; it is labeled source_qualified_unverified, not rejected.

Partition	Permitted ownership
discovery	E1/E2 per-realization candidate construction and exploratory E3A fitting
model_selection	bandwidth, grid, candidate complexity, correspondence policy, and E3A hyperparameter selection
basin_validation	SAMP1 recurrence, occupancy, residence, and E5 basin evidence without refitting
corridor_validation	SAMP2 preliminary passage/corridor evidence without changing basin or corridor definitions
thermodynamic_estimation	THERMO1/2/3A, PMF_DENSITY, PMF_FORCE, and source-qualified thermodynamic estimators
thermodynamic_validation	optional THERMO4A or PMF_CROSSCHECK evidence that does not build the estimator it verifies
optional_final_refit	post-validation parameter refit with a new signature and no inherited parameter-validation certificate

Discovery and model-selection evidence may share a signed nested-selection policy only when the nesting is explicit and uncertainty is propagated. Reuse between thermodynamic estimation and verification must be labeled selection_conditioned_verification; it is never described as independent.

Candidate identities are frozen by GR4 before held-out assignment. FrozenCandidateCatalog retains the exact numerical hypothesis and candidate set evaluated on validation data. FinalRefitCatalog is a new product and cannot inherit validation evidence for moved centers, changed boundaries, changed force parameters, or changed state identity.

The protocol reports independence separately for each product:

independent_selection_supported
independent_basin_validation_supported
independent_corridor_validation_supported
independent_thermodynamic_verification_supported
selection_conditioned_verification
independent_verification_unavailable

Attractors, basins, ridges, and corridors are matched across bandwidths, grids, bootstrap replicas, blocks, and independent trajectories through the signed FeatureCorrespondencePolicy. Numeric mode order is never a persistent identity.

Geometry-conditioned site refinement

After a site has been associated independently with a persistent ring or cage, its complete assignment region may follow framework geometry. A first model is

$$\mathbf{q}_i(t) = \mathbf{q}_{i,0} + B_i [\boldsymbol{\xi}_R(t) - \bar{\boldsymbol{\xi}}_R] + \epsilon_t,$$

where ξ_R may contain aperture, area, puckering, oxygen-class radii, rank-safe structural spectra, gauge-defined phase features, and cage volume from the registered and physical structural views. The fitted object is not only a moving point. It defines instantaneous nested regions

$$C_i(t) \subset B_i(t).$$

The first implementation translates or rigidly transports a fixed basin shape in the associated local frame. Shape- or covariance-conditioned models are later extensions. The static nonparametric discovery basin and the optional dynamic assignment basin remain separately available.

A dynamic boundary can pass over an ion even when the ion barely moves in the local comoving frame. Every candidate crossing therefore retains

ion displacement in the local comoving frame
center and boundary displacement
static-basin and static-core membership
dynamic-basin and dynamic-core membership
boundary_induced_crossing flag and uncertainty

A transition is never interpreted as purely ion-driven when the dynamic and frozen memberships disagree. The final catalog may use the validated dynamic basin, but it reports the frozen-basin counterfactual so ring breathing or cage deformation cannot masquerade silently as hopping.

The fitting protocol is noncircular by default:

1. fit candidate geometry-conditioned models on discovery evidence using assignments from the frozen static catalog;
2. choose among candidate models on model_selection evidence while keeping frozen state identity unchanged;
3. freeze the selected dynamic model;
4. evaluate state geometry, occupancy, and assignment stability on basin_validation evidence and passage/crossing effects on corridor_validation evidence;
5. use thermodynamic_validation only for separately requested thermodynamic products;
6. report all static/dynamic disagreements, assignment conflicts, and boundary-induced crossings; and
7. treat any optional_final_refit as a new signed product.

Static and geometry-conditioned models are selected on complete-system model_selection evidence and confirmed independently for each requested held-out product. The dynamic model is retained only when it reproducibly reduces residual variance without changing persistent state identity. Mobile-ion coordinates never redefine the ring frame or chemical boundary used as the predictor. Any iterative reassignment/refit method is a separately named, versioned algorithm with declared initialization and convergence criteria; it is never an implicit refinement step.

Independently transported dynamic regions can overlap even when the static nonparametric basins are disjoint. Every frame therefore receives one exclusive AssignmentConflictStatus:

unique_core
unique_basin
multiple_core_overlap
multiple_basin_overlap
static_dynamic_conflict
outside_supported_regions
assignment_unresolved

One ion is never double-counted in occupancy. Simultaneous membership in multiple cores is not an exact first hit, and a transition target remains ambiguous until one unique core is resolved. The result reports overlap volume or sample fraction, site-specific lower and upper occupancy bounds, and all static/dynamic conflicts. A dynamic model that produces persistent core overlap or an excessive unresolved fraction fails the relevant basin- or corridor-validation gate.

Statistical states, structural complexes, and classes

The kinetic node is a ValidatedStatisticalState. Structural reporting may group several microstates into a StructuralSiteComplex, and several complexes may share one SiteClass.

Examples include two opposite wells grouped as one bilateral complex, several angular minima grouped as one off-center family, or one extended annular state. Grouping never erases the individual statistical states or their transitions.

Structural classification retains continuous evidence such as normal and radial displacement, opposite-side partner score, angular multiplicity, annularity, ring/cage distance, and classification confidence. Borderline cases remain general or `classification_ambiguous`.

Ensemble-specific basin, corridor, and catalog thermodynamics

Thermodynamic analysis begins only after ensemble, production-regime, sampling, and state-identity gates are explicit. `ThermodynamicStateDefinition` distinguishes:

```
tagged_ion_basin_marginal
pooled_symmetry_orbit
site_class_probability
many_ion_occupation_vector
joint_metastable_state
```

It records the state scope, tagged/pooled/joint semantics, multiplicity convention, standard measure, ensemble, and coordinate Jacobian. Multiplicity correction is used only when the probability is pooled over equivalent members; applying it to an already per-state probability is prohibited.

Provenance-first thermodynamic reporting

Every thermodynamic estimate carries a required `ThermodynamicResultProvenance` record:

```
estimator_kind
source_trajectory_bundle_signature
source_record_signatures
ensemble_and_target_measure
state_definition_signature
energy_or_force_channel_signature
coordinate_measure_and_Jacobian
estimation_partition_signature
sampling_and_effective_counts
assumptions_and_approximations
uncertainty_method
verification_status
verification_record_signatures
```

A result may be reported as `source_qualified_unverified` when its own estimator-specific assumptions, sampling, and uncertainty gates pass but no independent channel is available. Cross-checking is an additional verification step with statuses:

```
not_requested
unavailable
insufficient
agreed
partially_agreed
disagreed
```

Unavailable verification never erases a valid source-qualified estimate. Disagreement is retained and prevents promotion to a combined or cross-validated consensus, but both source estimates remain inspectable with their own provenance. A cross-check may be mandatory only for a specifically requested `cross_validated` product, never for basic source-qualified thermodynamic reporting.

Source energy catalog and thermodynamic channel selection

The source-level `FrameEnergyCatalog` is constructed before `STAT0`. `THERMO0` consumes that immutable catalog and creates a `ThermodynamicEnergySelection` for the requested estimand. Raw source energies, bias-corrected energies, reweighting reduced potentials, conditional potential energies, enthalpies, and extended-system conserved quantities remain separate.

NVT and reweighted canonical basin thermodynamics

For validated canonical basin regions Ω_i ,

$$\Delta A_{ij} = -k_B T \ln \frac{P_i/g_i}{P_j/g_j}.$$

A `BasinThermodynamicCertificate` records occupancy and uncertainty, relative Helmholtz free energy, state/multiplicity definition, complete-system effective block count, and selection/reweighting provenance. The conditional potential energy

$$U_i = \langle U_{\text{pot}} \mid X \in \Omega_i \rangle$$

is a whole-system conditional mean, not a unique atomic site energy. When both ΔA and ΔU are independently supported,

$$\Delta S_{ij} = \frac{\Delta U_{ij} - \Delta A_{ij}}{T}$$

may be reported with propagated uncertainty.

NpT basin thermodynamics

For a stationary isothermal-isobaric ensemble, probability ratios define relative Gibbs free energies ΔG_{ij} . Energetic decomposition uses conditional enthalpy, including the declared pressure-volume term and any required extended- system convention. NVT notation and potential-energy-only decomposition are not reused silently.

NVE basin thermodynamics

For a stationary energy shell, occupancy produces microcanonical state probabilities and restricted density-of-states or entropy differences, not canonical Helmholtz free energies. A subsystem-canonical result is separately labeled `canonical_subsystem_approximation_conditional` and requires a tested ensemble-equivalence policy [S11-48]. Energy-drifting NVE data may retain descriptive occupancies and conditional energies while rejecting shell thermodynamics.

Biased, constrained, and reweighted thermodynamics

A biased result requires bound bias/constraint provenance, an exact target measure, and configuration weights or cross-evaluated reduced potentials. Raw and corrected results are both retained. Unavailable companion evidence cannot be interpreted as zero bias.

Effective occupancy Hamiltonian

For many-ion systems an optional predictive model may use

$$E(t) = E_0 + \sum_i \epsilon_i n_i(t) + \frac{1}{2} \sum_{ij} J_{ij} n_i(t) n_j(t) + f(\xi_{\text{framework}}(t)) + \varepsilon_t.$$

`EffectiveHamiltonianPolicy` defines a nested basis hierarchy, symmetry constraints, regularization, rank/condition thresholds, feature selection using training blocks, held-out scoring, parameter uncertainty, and sensitivity to framework descriptors. The framework term may not be chosen using validation blocks. Parameters are predictive effective coefficients, never a causal or unique DFT atomic-energy decomposition.

Transition-region and activation thermodynamics

A mathematical point saddle has zero integrated probability. Thermodynamic analysis uses a declared finite transition tube, dividing surface, or reaction-coordinate bin. `SaddleThermodynamicCertificate` records the region measure, independent event support, probability-density or reweighted support, ensemble-specific activation potential, conditional energy or enthalpy, uncertainties, recrossing, and committor or enhanced-sampling provenance.

A `numerically_supported_saddle_candidate` is not a thermodynamic saddle. One-off passages, unstable density candidates, and unsupported regions cannot produce a promoted barrier.

Optional pre-kinetic thermodynamic verification

`ThermodynamicCrossValidationCertificate` is optional and compares noncircular channels that do not require a fitted kinetic model:

- density/occupancy thermodynamics versus an independently constructed admissible force-integrated landscape;
- conditional-energy derivatives across temperature;

- held-out temperature or independent-replica population predictions; and
- WHAM/MBAR estimates when a common target measure and cross-evaluated reduced potentials are available.

The certificate records exactly which result was estimated, which independent source was used for verification, and whether the verification was unavailable, insufficient, agreed, partially agreed, or disagreed. Absence of a second channel leaves the original result `source_qualified_unverified`; it does not block reporting.

WHAM or MBAR requires the cross-evaluated matrix $u_k(x_n)$, or an equivalent certified alchemical/reweighting map, together with overlap diagnostics [S11-43, S11-44]. Native energies from different species, compositions, or Hamiltonians are insufficient.

Detailed balance, empirical rate bounds, and barrier-rate consistency are not part of this pre-kinetic certificate. They are owned by Stage 11F0/11F1 and THERMO4B.

Final temporal residence and transition segmentation

Raw evidence remains immutable

Every accepted sample retains unsmoothed labels:

```
site_core_i
site_basin_i
basin_overlap
assignment_conflict_status
transition_support
background
geometry_unresolved
force_unavailable
```

Raw labels are never overwritten by a cleaned event sequence.

Core-basin hysteresis

For an accepted site i , use $C_i \subset B_i$. An ion enters state i only on reaching C_i , remains associated while inside B_i , and enters an explicit transition segment after leaving B_i until another core is reached. This prevents boundary chatter without nearest-center filling. Core-set and metastability ideas motivate the separation [S11-29, S11-30].

Final segmented outputs

The final result contains residence intervals, transition intervals, unresolved gaps, recrossings, left- and right-censoring, frame-stride sensitivity, static-versus- dynamic membership, boundary-induced crossing diagnostics, and raw-to-segmented provenance. The existing `compute_state_transition_statistics()` backend is reused after segmentation.

Bootstrap and robustness tests use independent trajectories when available, or contiguous time blocks containing the complete many-ion system. Per-ion resampling is only a secondary hierarchical diagnostic because ions within one frame are correlated.

Observed transition-path ensembles

For a resolved passage, the ion must most recently have occupied source core C_A . The event begins at its final exit from residence basin B_A . Its target is the first subsequently resolved core reached, not a target selected in advance. If C_C is reached before C_B , the event is $A \rightarrow C$.

$$C_A \rightarrow B_A \setminus C_A \rightarrow T_A \rightarrow B_J \setminus C_J \rightarrow C_J,$$

where J is the first resolved target. A return to C_A before another core is reached is a failed excursion or recrossing. Unresolved gaps remain unresolved and are not bridged automatically.

Finite output cadence may prevent an exact first-hit decision. Every event records one of

```
resolved_first_hit
temporally_bracketed_first_hit
multiple_targets_between_frames
```

target_ambiguous
gap_interrupted

No interpolation is allowed to fabricate a core crossing that is not resolved by the stored trajectory and declared dynamic-boundary model. Frame-stride sensitivity and the minimum resolvable event duration are part of the event provenance.

Each `ObservedTransitionEvent` retains:

ion identity
source and target statistical states
start and end frames and times
residence-exit and core-entry boundaries
registered path coordinates
periodic image displacement
ring and cage geometry along the path
available force samples
minimum-density or highest-PMF region encountered
first-hit resolution status and temporal bracket
recrossing, censoring, boundary-induced, and unresolved flags

The periodic image displacement

$$\lambda_{AB} \in \mathbb{Z}^3$$

is part of the event identity. It is derived from the continuous registered unwrapped path together with registration image bookkeeping, never from wrapped endpoint subtraction alone. Two events between the same state keys but with different lattice translations are different periodic-network events.

A `TransitionPathEnsemble` groups comparable successful paths without erasing physical time. Comparable events must share source and target statistical states, periodic translation, structural association, compatible unresolved-gap status, and one validated `RegistrationCompatibilityClass`. The compatibility class proves that member trajectories share a common registered domain, reference-cell and lattice gauge, analysis metric, unit convention, and state correspondence while retaining their distinct source and transform signatures. Identical per-trajectory registration signatures are not required and would incorrectly prevent independent runs from contributing to one path ensemble. Any progress-coordinate alignment retains the original physical time. It reports `single_observed_path`, `path_ensemble_undersampled`, or `path_ensemble_resolved`. One observed jump establishes one connection, not a representative pathway, minimum-free-energy path, directional rate, or detailed balance. Transition-path and core-set ideas motivate these definitions [S11-8, S11-29, S11-30].

Each path also retains the atom-resolved ring environment along the passage: ordered M–O distances, oxygen-class contacts, O–O sector crossed, ring/coordination harmonics, aperture, and puckering. This permits distinct pathways through chemically inequivalent sectors of the same nominal ring.

Nominally single-ion events are checked for temporal overlap with other mobile-ion transitions. The event record retains concurrent event identifiers, local occupancy before/during/after, exchange or swap candidates, and one of `isolated_single_ion`, `temporally_overlapping`, `candidate_exchange`, `candidate_concerted`, or `collective_unresolved`. Detection does not yet imply a many-body kinetic model.

A density shoulder between *A* and *B* becomes a third metastable state only if it has its own reproducible attractor, restoring curvature or equivalent stable normal confinement, and independent temporal residence. Otherwise it remains transition support.

Observed event, path-resolved, and structural networks

Three edge claims remain distinct:

`observed_event_edge`
`path_resolved_edge`
`transition_state_annotated_edge`

An `observed_event_edge` is created from a final E6 state-to-state event certificate and at-risk exposure. It does not require the intermediate geometric path to be resolved. E6b may enrich that edge with a `path_resolved_edge`; THERMO3B may

further attach a validated transition-state or saddle annotation. Failure of either enrichment never deletes a valid observed event edge.

The structural/manual candidate network remains separate. Its comparison reports observed and unobserved structural edges, off-network events, periodic displacement labels, geometry and occupancy conditioning, unresolved intermediate mechanisms, and path-resolution status. The structural network never forces observed topology.

Refactor design

Dependency direction

The revised dependency graph is:

```
raw I/O
-> source normalization and periodic unwrapping
-> immutable physical AtomisticFrameCollection
-> Stage C0 spatial frame registration
-> analysis-specific registered views
    -> pair geometry and topology
    -> displacement and velocity dynamics
    -> scientific density and force fields
    -> site discovery and temporal segmentation
    -> plotting adapters and interactive scenes
```

No scientific analysis module imports Plotly, browser budgets, mesh simplifiers, or HTML serialization.

Coordinate-registration ownership

Create a root numerical package, initially compact and later split as needed:

```
mdstats/coordinates/
  contracts.py
  periodic_gauge.py
  frame_registration.py
  transforms.py
  kinematics.py
  provenance.py
```

The shared owner consolidates the tested translation and reference-cell logic now spread across `_displacement_common.py`, `_velocity_common.py`, `framework_dynamics.py`, Stage 11B gauges, and Stage 11C local frames. The local ring and tile modules retain topology-specific gauge construction; they consume or extend the common transform contracts rather than being replaced by a generic fit. The registration layer additionally exposes a `RegisteredStructuralGeometryView` so density-space sites and structural atoms are never compared in different coordinate systems.

Migration is staged:

1. specify row-vector affine contracts, field transformations, and signatures;
2. implement identity, translation, and reference-cell registration;
3. migrate displacement preparation while preserving numerical regressions;
4. migrate translation-only velocity preparation without adding rotating-frame VACF;
5. move density coordinate preparation out of plotting;
6. integrate site-discovery sample catalogs;
7. add advanced rotation/stretch decomposition only after the base contracts are validated.

Incremental scientific-density extraction

The current plotting density code already contains backend-neutral contracts alongside rendering-specific machinery. Avoid a big-bang move.

E0a - analysis facade - implemented

Canonical analysis imports and field protocols now wrap the existing scientific density objects without changing numerical ownership. `mdstats.analysis.density` provides zero-copy adapters, atomic/framework field bundles, and a scientific-only

resource policy. `mdstats.plotting.density_resource_policy` owns the separate rendering policy. No rendering class appears in the analysis protocol.

Density extraction follow-ups D0b-D0d - decomposed into 11E-GR0-GR5

These older density-ownership items are not Stage 11E0b. Stage labels are unique: Stage 11E0b is the immutable registered raw sample catalog. Revision 44 decomposes the remaining density move into explicit grid-resolution stages rather than one big-bang migration:

- 11E-GR0 extracts common cell-metric grid geometry, periodic spread, reciprocal resolution, and artificial-broadening diagnostics into analysis ownership;
- 11E-GR1 extracts target-shape, finest-feasible-shape, deterministic nested-grid, field-signature reuse, and physical-resolution-first/backend-second planning;
- 11E-GR2 adapts atomic and framework plotting to the common layer while preserving plotting's visual smearing and browser/mesh policies;
- 11E-GR3 integrates a fixed-kernel scientific refinement ladder into E1/E2 and emits separate field, basin, and corridor convergence certificates;
- 11E-GR4 executes that ladder only on discovery/model-selection blocks and freezes the numerical hypothesis before held-out basin or corridor validation; and
- 11E-GR5 completes D0b-D0d by moving the remaining numerical owners, making plotting consume analysis-owned producers, and removing compatibility ownership only after dense, sparse, scientific, and visual regressions pass.

Scientific memory/work limits and rendering/mesh/browser budgets remain disjoint. Compatibility imports remain until 11E-GR5; no stage may force a coordinated rewrite of scientific numerics, sparse execution, meshing, browser admission, and public APIs in one release.

The intended package layout is:

```
mdstats/analysis/density/  
    contracts.py  
    kernel.py  
    sparse_reference.py  
    block_sparse.py  
    planning.py  
    diagnostics.py  
    hdr.py  
  
mdstats/analysis/site_samples.py  
mdstats/analysis/site_density.py  
mdstats/analysis/site_modes.py  
mdstats/analysis/site_force.py  
mdstats/analysis/site_validation.py  
mdstats/analysis/site_segmentation.py  
mdstats/analysis/observed_site_network.py
```

Statistical bandwidth, grid realization, and partial numerical refactor

The KDE covariance Σ_h - or scalar scale h on one fixed metric shape - the analysis grid interval Δ , and the rendering mesh tolerance are distinct:

$$\Sigma_h \neq \Delta \neq \text{mesh tolerance} .$$

A direct normalized triclinic image sum is the numerical oracle. `KernelMetricDefinition` and `PeriodicKernelDefinition` fix the coordinate measure, covariance, image truncation, and quadrature. Dense and block-sparse realizations must preserve that operator. The same certified scientific field drives attractor discovery, basin integration, uncertainty diagnostics, and optional rendering.

Existing atomic-density machinery is the common numerical oracle

The tested atomic-density implementation already owns mature backend-neutral algorithms for:

- grid-shape construction from target Cartesian interval in an oblique periodic cell;

- realized Cartesian grid intervals and logical node/voxel counts;
- periodic Frechet means and periodic item-spread diagnostics;
- reciprocal-resolution diagnostics;
- cloud-in-cell assignment covariance;
- discrete Gaussian-stencil and combined artificial broadening;
- target-shape and finest-feasible-shape search under scientific voxel/work budgets;
- physical-grid selection before dense or local-sparse backend selection; and
- immutable serializable resolution records and deterministic field reuse metadata.

Those algorithms are not intrinsically rendering operations. Their current `mdstats.plotting` ownership is a compatibility state. Revision 44 therefore chooses a **partial refactor**: move the common mathematics into `mdstats.analysis.density`, retain old plotting imports through adapters, and keep plotting-specific and Stage-11-specific policies separate.

Plotting and scientific refinement remain separate policies

Atomic-density plotting may retain its visual default

$$\sigma = c \max_i \Delta_i,$$

and may refine grid spacing and visual Gaussian width together when artificial smearing would dominate the rendered cloud. It selects one production grid and may display the finest feasible budget-limited result with a warning.

Stage 11 scientific convergence must instead hold the kernel hypothesis fixed:

$$\Sigma_h = \text{constant}, \quad \Delta^{(0)} > \Delta^{(1)} > \Delta^{(2)} > \dots$$

Changing Σ_h and Δ together would confound physical smoothing-scale uncertainty with numerical discretization error. Stage 11 therefore uses plotting's common geometry, broadening, resource, and backend machinery. Stage 11 never uses plotting's adaptive bandwidth selection or one-grid acceptance policy.

Scientific resolution and convergence certificates

One combined topology verdict is insufficient. The scientific refinement result owns three orthogonal certificates:

```
DensityFieldResolutionCertificate
BasinGridConvergenceCertificate
CorridorGridConvergenceCertificate
```

`DensityFieldResolutionCertificate` records exact grid shapes, realized intervals, fixed kernel covariance and signature, Δ/σ or reciprocal metrics, CIC and stencil broadening, normalization residuals, backend, scientific resource limits, and budget limitation.

`BasinGridConvergenceCertificate` records candidate correspondence, attractor-count stability, anchor displacement, basin overlap, integrated probability changes, split/merge and unmatched candidates, and acceptance or unresolved reasons.

`CorridorGridConvergenceCertificate` records density-boundary adjacency, corridor location and width, bottleneck-density changes, split/merge and correspondence ambiguity, and whether a stable refinement regime was reached. A valid scientific outcome may be:

```
field numerics: converged
basins: converged
transition corridors: unresolved
```

Basin convergence never implies corridor convergence. This distinction is mandatory for the current Na-LTA pilot, whose basin identities are more stable than its numerical saddle adjacency.

Budget and sampling rules

The common planner resolves physical grid requirements before selecting dense versus local-sparse storage. A scientific caller may receive a budget-limited ladder, but if the requested convergence criterion is not reached the status is `unresolved_due_to_resolution_budget`; the finest affordable field is not promoted as authoritative merely because it can be rendered.

The grid ladder is selected and executed only within SAMP0 discovery/model-selection evidence. Candidates are frozen before held-out assignment. An optional all-data final refit is a new signed product and does not inherit held-out parameter-certification evidence. Grid convergence concerns discretization of one fixed statistical hypothesis; SAMP1/SAMP2 independently determine whether basins and corridors have adequate trajectory support.

Position-force sample catalog

The global sample catalog remains compact and does not eagerly materialize every ion-frame-ring descriptor. It retains species, atom and frame identities, registered positions, force evidence, evidence masks, weights, source and registration signatures, and stationarity provenance.

Structural annotations are lazy views created after a statistical candidate is associated with a fixed ring or tile identity. This preserves global discovery before semantic interpretation and avoids an $N_{\text{ion}}N_{\text{frame}}N_{\text{ring}}$ materialization.

Existing manual-model branch

ring_site.py, site_kinetic_network.py, and site_assignment.py remain an explicit manual or transferred-model branch. Current public names may remain through the pre-release series, but documentation must state that their site locations and basin widths are supplied rather than discovered.

Interactive analysis scene

The interactive scene consumes registered scientific fields and validated site results. It may overlay the framework, tiles, rings, density, attractor lineages, basin/core surfaces, mean-force vectors, residence segments, and semantic labels. The scene is diagnostic; every scientific result remains usable without rendering.

Revision-47 authoritative typed dependency graph

The machine-readable companion stage11_dependency_graph.json is normative. Revision 47 introduced the typed-edge graph retained by architecture revision 51 rather than treating execution order, promotion gates, optional enrichment, and verification as one relationship. Required acyclicity is evaluated over source_identity_requires, execution_requires, and unconditional promotion_requires edges. The edge vocabulary is:

```
source_identity_requires
execution_requires
promotion_requires
conditional_requires
optional_enrichment
optional_verification
supersedes
replay_triggers
```

A condition-bearing edge records its predicate and product scope. A bounded gating replay creates a new signed StateModelGeneration; it is not a cycle within one generation.

```
SourceTrajectoryBundleIdentity
-> SOURCE_BYTES and SOURCE_COORDINATES views of the same source
-> ENS0 controls/energies and C0 coordinates retain the same bundle signature
```

```
ENS0 -> ENS1 -> STAT0 -> STAT1 -> STAT2
C0 + Part I -> E0b-RAW
STAT1 + E0b-RAW -> SAMP0 EvidenceCrossfitPartition
```

```
E0a -> GR0 -> GR1 -> GR2
SAMP0 + GR1 -> E1 -> E2 per-realization candidates
E2 + GR1 -> GR3 convergence evidence
GR3 + SAMP0 -> GR4 FrozenCandidateCatalog
GR4 -> STAT3, E3A, E4
STAT2 + STAT3 + E3A -> E3B where canonical/reweighted force thermodynamics are admissible
E4 + GR4 -> SAMP1 -> E5 -> E5a -> optional E5b
E4 + E5 + GR3 -> SAMP2
SAMP1 + SAMP2 -> SAMP3
```

THERM00 -> THERM01 -> optional THERM02
THERM01/2 results carry mandatory ThermodynamicResultProvenance.
THERM04A is optional verification, not a prerequisite for source-qualified reporting.

STAT2 + STAT3 + GR3 + SAMP1 -> PMF_DENSITY
STAT2 + STAT3 + E3B + GR3 + SAMP1 -> PMF_FORCE
PMF_DENSITY + PMF_FORCE -> optional PMF_CROSSCHECK
No force record is required for PMF_DENSITY.

SAMP2 + GR3 + THERM00 -> THERM03A
E6 -> optional E6b
E6b + THERM03A -> optional THERM03B

E5 + a signed RateCandidateEdgePolicy -> RATE_EDGE_UNIVERSE
SAMP2 and M2 may optionally enrich that universe.
E6 -> E7 observed-event network
E6 + E7 -> KSAMP0 KineticCrossfitPartition
KSAMP0 + E7 -> E9A -> G0
KSAMP0 + RATE_EDGE_UNIVERSE + E6 + E7 + G0 -> F0
F0 + held-out kinetic-model-validation episodes -> E9B
Zero-event bounds attach to RateCandidateEdge records, not only observed edges.

THERM03B + G0 -> F1
F0 + E9B + optional independent populations -> optional THERM04B
F0 + E9B + G0 -> G1 -> H -> I

E8b product nodes are independent:
E8B_BASIN_GEOMETRY from E5/SAMP1/GR3
E8B_BASIN_THERMO from THERM01 and optional THERM02/THERM04A verification
E8B_CORRIDOR from SAMP2/GR3
E8B_TRANSITION_REGION from THERM03A
E8B_PATH from E6b
E8B_TRANSITION_STATE from THERM03B
E8B_EVENT_NETWORK from E7
E8B_KINETIC from F0/E9B and optional G1/F1/THERM04B

E8a remains a cross-cutting milestone dossier. PMF, thermodynamic verification, paths, and rates are optional sub-dossiers and do not gate earlier ENS/STAT/GR/SAMP milestones.

QualityDiagnosticBlockPartition, EvidenceCrossfitPartition, and KineticCrossfitPartition are distinct signed objects. Control-inferred dynamics, realized ensemble consistency, trajectory quality, source-qualified thermodynamic results, optional verification, and method-specific admissibility remain separate records.

Planned persistent data model

The new stages introduce source-general immutable records:

SourceTrajectoryBundleIdentity
SimulationControlBundleManifest
SimulationRunControls
SimulationControlCertificate
RealizedEnsembleConsistency
EnsembleInferencePolicy
VaspRunControls
NumericalMDQualityControls
FrameEnergyCatalog
IonicTemperatureDefinition
IonicTemperatureStatistics
TrajectoryQualityPolicy
TrajectoryQualityVerdict
ProductionWindowPolicy

QualityDiagnosticBlockPartition
ProductionRegimeCatalog
EvidenceCrossfitPartition
KineticCrossfitPartition
PmfAdmissibilityCertificate
EvidenceAdmissibilityOverlay
SamplingAdequacyPolicy
FeatureCorrespondencePolicy
GridConvergenceStoppingPolicy
CommonDensityGridPolicy
ScientificGridRefinementPolicy
DensityFieldResolutionCertificate
BasinGridConvergenceCertificate
CorridorGridConvergenceCertificate
PerRealizationCandidateCatalog
FrozenCandidateCatalog
FinalRefitCatalog
LocalMechanicalForceRefinement
ThermodynamicMeanForceCertificate
BasinSamplingCertificate
TransitionCorridorSamplingCertificate
PreliminaryCorridorSupport
FinalTransitionEventCertificate
RateCandidateEdgePolicy
RateCandidateEdge
RateCandidateEdgeUniverse
ObservedEventEdge
PathResolvedEdge
TransitionStateAnnotatedEdge
ObservedEventNetwork
DiagnosticKineticModel
PreRateKineticAdequacyCertificate
StateModelGeneration
GenerationReplayPlan
GenerationTerminationCertificate
GatingModelSelectionCertificate
EmpiricalRateCertificate
PostFitKineticAdequacyCertificate
BarrierDerivedRateCertificate
FinalGateModelSelectionCertificate
KineticPropagationResult
IntegratedGroundGateDossier
CrossDatasetComparisonCertificate
DiscoveryScopeCertificate
ThermodynamicStateDefinition
ThermodynamicPotentialDefinition
ThermodynamicEnergySelection
ThermodynamicResultProvenance
EffectiveHamiltonianPolicy
BasinThermodynamicCertificate
StaticTransitionRegionThermodynamics
TransitionStateValidationCertificate
SaddleThermodynamicCertificate
DensityPmfCertificate
ForcePmfCertificate
PmfCrossCheckCertificate
ThermodynamicCrossValidationCertificate
KineticThermodynamicConsistencyCertificate
RateBoundModel

Every thermodynamic certificate contains `ThermodynamicResultProvenance`. Verification is an optional linked record; its absence is metadata, not automatic rejection. Every source- derived record carries `SourceTrajectoryBundleIdentity`. Every model-generation replay carries parent/child signatures and a bounded termination certificate.

The canonical diagnostic status registry is:

`resolved` | `unresolved` | `insufficient` | `rejected` | `unavailable` | `not_applicable`

Promotion decisions are:

`accepted` | `conditional` | `blocked` | `rejected`

Thermodynamic verification statuses are:

`not_requested` | `unavailable` | `insufficient` | `agreed` | `partially_agreed` | `disagreed`

Domain outcomes such as `NVE`, `nonstationary`, `spatial_density_only`, `source_qualified_unverified`, `cross_validated`, or `observed_partial_catalog` are separate values, not replacements for diagnostic status.

Revised implementation sequence

This section follows the revision-47 typed dependency graph and its machine-readable companion. Status and historical release chronology are descriptive metadata; they do not override the acceptance gates or the authoritative dependency map.

Part I structural prerequisites - Stages 11A-D implemented

Stages 11A, 11B, 11C1, 11C2, 11C3, and 11D are implemented and owned by `framework_ring_architecture.{md,pdf}`. Part II records their completion only as a prerequisite; detailed deliverables and remaining general-topology work are not duplicated here.

Stage 11E-M1/11E-M2 - manual and transferred site models - implemented foundation

The existing site-topology/structural-network implementation is documented as legacy/manual Stage 11E-M1, and the explicit trajectory assignment implementation as Stage 11E-M2. Their modules and public APIs remain unchanged. Their specification headers use the E-M names so that historical statements such as “Stage 11E2 complete” cannot be confused with the new deterministic-attractor Stage 11E2. Site locations and basins in this branch are supplied explicitly.

Stage C0A1 - source semantics and periodic lattice gauge - implemented

Deliverables:

- source position, velocity, force, and box-origin frame semantics;
- cell handedness and determinant checks;
- periodic-axis continuity;
- lattice-basis continuity and optional unimodular gauge reconciliation;
- explicit rejection of unsupported basis changes;
- explicit-matrix and selected-source-frame reference-cell definitions;
- full-periodicity/full-rank scope for initial reference-material registration;
- separate geometric-force and PMF-force admissibility contracts.

Acceptance gate:

- a basis relabeling is never interpreted silently as physical strain;
- unknown field semantics block only claims that require them.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.coordinates.contracts` owns normalized source-field semantics, force-source provenance, geometric/PMF admissibility, reference-cell definitions, deterministic schemas, and immutable digests;
- `mdstats.coordinates.periodic_gauge` owns determinant, condition, handedness, periodic-axis, and basis-continuity validation;
- nontrivial unimodular relabelings are rejected by default and reconciled only under an explicit option with the integer matrix retained;

- normalized collections now persist source-field semantics, while legacy collections remain readable through conservative inference; and
- focused tests cover rejection, reconciliation, partial-claim availability, reference-cell scope, and deterministic signatures.

C0A1 itself does not construct M_t , b_t , registered coordinates, translation gauges, or transformed forces; those products are supplied by the following C0A2 layer.

Stage C0A2 - affine registration and coordinate products - implemented

Deliverables:

- affine row-vector contracts with explicit source and registered center semantics;
- physical, periodic matched-displacement translation, and composed reference-material-plus-translation policies;
- dedicated `RegistrationFitMetric`, separate immutable `AnalysisGeometryMetric`, and certified triclinic closest-image solvers under their declared metrics;
- torus reference-translation solution, segment-continuous `TranslationBranchLift`, residual, competing-branch separation, reset, and ambiguity diagnostics;
- registered cells and fixed-domain checks;
- unwrapped Cartesian, wrapped fractional, and image-shift products;
- position, displacement, and force transformations;
- immutable signatures, diagnostics, and round-trip validation.

Acceptance gate:

- $G_t = H_t M_t$ for every valid frame;
- coordinate round trips and force-work invariance pass;
- singular, basis-inconsistent, and incompatible transforms fail closed.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.coordinates.metric_geometry` owns immutable `RegistrationFitMetric` and `AnalysisGeometryMetric` contracts and a finite, singular-value-certified triclinic closest-image enumeration with explicit tie diagnostics;
- `mdstats.coordinates.registration` owns physical, translation-registered, and reference-material affine policies, persistent reference sets and weights, matched periodic translation fitting, trajectory-segment branch lifting, fixed-domain validation, and registered coordinate products;
- force fields are transformed as affine covectors and validated by work invariance, while structure-fitted translation retains conservative geometric and PMF admissibility statuses;
- independent ensembles receive no invented temporal branch continuity; and
- focused tests cover skew-cell closest images, exact ties, periodic drift across boundaries, variable-cell reference-material maps, segment resets, ensembles, unimodular source-basis reconciliation, serialization, and public exports.

Stages 11C3, C0A3, C0B, and 11E0a exist in the baseline runtime. Current normative progression is defined only by the revision-47 typed dependency graph.

Stage 11C3 - atom-resolved structural ring boundary and harmonics - implemented

Deliverables:

- persistent per-atom T/O boundary records and generic chemical environments;
- optional validated O(1)/O(2)/O(3) aliases for LTA;
- exact ordered structural sequences;
- exact unweighted cyclic-index spectra with correct even-ring Nyquist handling;
- rank-safe actual-angle spectra with explicit weights, rank, condition, regularization, and unresolved status;
- separate boundary-measure angular moments and weighted actual-angle fits;
- raw and normalized amplitudes;
- canonical dihedral phase gauges and phase-defined uncertainty;
- per-frame symmetry-breaking and oxygen-class splitting diagnostics;
- explicit radial-center convention and uncertainty;
- angular-coordinate validity and fail-closed singularity diagnostics.

Acceptance gate:

- an alternating S6R recovers the cyclic $m = 3$ component exactly;
- an irregularly spaced ring does not force the same sequence into a pure physical-angle $m = 3$ component;
- underdetermined mode sets fail closed;
- cyclic permutation, reversal, rigid motion, and periodic wrapping follow the declared dihedral and geometric transforms;
- phase becomes undefined when amplitude support is insufficient;
- crystallographic aliases fail closed when the framework profile is incompatible.

This stage owns no M–O/M–T fingerprint and no species-dependent site label.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.ring_boundary` owns immutable per-atom T/O boundary records, ordered neighboring-T chemistry, generic oxygen-environment signatures, and exact-source optional LTA O(1)/O(2)/O(3) alias profiles;
- exact equal-atom DFT descriptors retain the complete real-sequence mode set with signed even-ring Nyquist coordinates and explicit dihedral transforms;
- arc-length Voronoi boundary moments and equal-atom/arc-length physical-angle fits remain distinct, with rank, condition, regularization, residual, phase support, and uncertainty provenance;
- singular projected atoms and non-identifiable mode sets fail closed without arbitrary angles or pseudoinverse coefficients;
- framewise outputs retain class splitting, radial symmetry breaking, and reference phase/amplitude continuity while exact Cartesian coordinates remain authoritative; and
- focused tests cover synthetic serrated rings, dihedral transforms, rank and singularity failures, source-bound aliases, serialization, resource preflight, rigid rotation, and all 58 LTA reference rings.

Stage C0A3 is implemented below.

Stage C0A3 - registered structural-view integration - implemented

Deliverables:

- apply the resolved Stage C0 transform to persistent T/O, ring, tile, and cage atoms;
- reconstruct registered orthonormal ring frames from transformed atoms using the standard least-squares closest-plane and polygon constructions [S11-15, S11-16];
- retain linked physical and registered structural embeddings;
- integration tests coupling Stage 11C3 boundary identities to registered views;
- immutable structural-view signatures and unresolved-frame diagnostics.

Acceptance gate:

- site-space association never mixes registered positions with physical structural coordinates;
- physical bond lengths and apertures remain available unchanged;
- non-rigid affine maps reconstruct, rather than affinely distort, local orthonormal frames.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.registered_structural_view` owns one immutable, source-bound integration product joining the collection, C0A2 registration, compatible C2 ring geometry, C3 atom-resolved boundaries, and optional compatible tiling geometry;
- every ring view exposes separately named physical and registered children, so physical distances, apertures, areas, perimeters, planarity, and T–O metrics remain unchanged and cannot be confused with registered projected descriptors;
- persistent T/O atom images are transformed by the exact resolved affine map, then their registered fractional images are independently certified against the registered cell;
- registered ring centers and orthonormal frames are reconstructed from the transformed oxygen polygon and persistent cyclic-origin atom; transformed physical axes are retained only as a distortion diagnostic;
- optional tile/cage centers, tile-face vertices and reconstructed normals, and window centers share the same registration while retaining physical tiling measures unchanged;
- trajectory orientation continuity is diagnostic, respects explicit registration segment resets, and is not inferred for independent ensembles;

- unresolved geometry, identity mismatch, source mismatch, resource excess, serialization tampering, and degenerate transformed polygons fail closed; and
- focused tests cover all 58 LTA ring identities, identity and non-rigid maps, periodic registered images, tiling integration, reset semantics, ensembles, serialization, resource preflight, and public exports.

Stage C0A3 is complete.

Stage C0B - consumer migration - implemented

Deliverables:

- displacement preparation migrated with exact regression compatibility;
- translation-only velocity preparation migrated without changing VACF semantics;
- atomic density and framework plotting consume shared registration;
- compatibility adapters for current public options.

Acceptance gate:

- current MSD and density reference results remain unchanged within declared tolerance;
- pair geometry remains on the physical policy;
- plotting does not own scientific drift removal.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.coordinates.consumer_adapters` owns immutable, source-bound compatibility products for displacement, velocity, and plotting consumers;
- laboratory and reference-material displacement preparation delegates its affine map to C0A2 and retains the exact historical optional COG/COM zero-centering translation;
- translation-only velocity preparation retains the exact instantaneous COG/COM drift used by VACF, spectra, and velocity-derived transport while recording its registration-policy provenance separately;
- `framework_dynamics.py` prepares one coordinate view before framework averaging, trajectories, atomic density, framework vertex density, or framework edge density, and no longer computes a scientific drift vector;
- material, framework-registered, and laboratory plotting modes retain their historical numerical coordinates and public options;
- pair geometry is declared physical and is not replaced by display or reference-material geometry;
- larger smooth variable-cell changes admitted historically are handled by an explicit compatibility continuity envelope, while certifiable unimodular basis relabelings remain fail-closed;
- very large historical unwrapped absolute coordinates use an explicit floating-point-ULP floor for round-trip certification without changing the returned consumer coordinates;
- partial-periodic material plotting remains available so the owning density preflight can issue its more specific validation; and
- focused regression tests compare the migrated products against the legacy coordinate, velocity, plotting, and atomic-density oracles and verify public API compatibility, immutability, and provenance.

Stage 11E0a is complete.

Stage 11E0a - scientific density facade and ownership boundary - implemented

Deliverables:

- analysis-owned `ScientificDensityField3D` and periodic-node protocols;
- zero-copy adapters and deterministic scientific field bundles;
- canonical atomic and framework density preparation entry points;
- lazy compatibility imports for current numerical option and field classes;
- `ScientificDensityResourcePolicy` containing only field-construction limits;
- plotting-owned `DensityRenderingResourcePolicy` containing only browser/mesh limits;
- explicit temporary numerical-owner and permanent scientific-owner metadata.

Acceptance gate:

- atomic and framework fields match the current numerical oracle exactly;

- adapters retain the exact current field object and storage;
- scientific preparation invokes no mesh extraction or browser admission;
- Plotly and scikit-image remain unnecessary for field construction;
- rendering options are absent from the analysis facade; and
- existing plotting APIs remain compatible.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.protocols` defines the canonical structural field protocols, zero-copy compatibility adapter, bundle, immutable ownership metadata, and contract signatures;
- `mdstats.analysis.density.resources` defines runtime-resolvable scientific limits without mesh faces, Plotly traces, browser payloads, or HTML budgets;
- `mdstats.analysis.density.facade` delegates to the unchanged atomic and framework numerical producers and wraps their exact result objects;
- `mdstats.plotting.density_resource_policy` owns the explicitly separate rendering policy;
- canonical analysis imports expose current numerical contracts lazily but omit all 3-D render-option classes; and
- focused tests compare dense atomic and framework vertex/edge fields against the current oracle and guard against optional rendering imports or browser admission.

Stage 11E0a is complete. Stage 11E0b is implemented below.

Stage 11E-ENS0 - source-control bundle and energy-channel reconstruction

Deliverables:

- `SimulationControlBundleManifest`;
- source-general `SimulationRunControls` protocol and versioned VASP adapter;
- explicit-versus-effective control precedence;
- companion-file state classification;
- source-level `FrameEnergyCatalog` with exact channel names and units;
- `NumericalMDQualityControls` reconstructed from explicit and effective `vasprun.xml` parameters, including timestep, electronic convergence, precision, projection, cutoff, symmetry, and per-step SCF traces;
- user-label conflict diagnostics.

Acceptance gate:

- the Na-LTA fixture resolves the misleading comment as non-authoritative;
- `MDALGO=2`, `SMASS=-3`, and `ISIF=2` enter the decision trace;
- missing companion evidence is classified, not silently treated as absent;
- every conservation input channel is available to `STAT0` before `STAT0` executes;
- the Na-LTA fixture exposes `POTIM`, `EDIFF`, `PREC`, `LREAL`, `ROPT`, `NELM`, present ionic-step count, and per-step electronic-step counts from the XML without consulting the `SYSTEM` comment.

Implementation status: complete in 0.20.17a0. The runtime owners are `mdstats.io.source_controls`, `mdstats.io.vasp_controls`, and the metadata integration in `mdstats.io.vasp`. Stages 11E-ENS1 through 11E-STAT2 are now implemented.

Stage 11E-ENS1 - ensemble, control, and force-provenance certificate

Deliverables:

- `SimulationControlCertificate` with ensemble, propagator, thermostat, barostat, driven/bias/constraint, cell, and force-provenance outcomes;
- versioned `EnsembleInferencePolicy` and complete decision trace;
- initial-velocity and continuation provenance;
- explicit unresolved outcomes for unsupported or incomplete source bundles.

Acceptance gate:

- source controls, not comments, determine the outcome;
- thermostat friction is not_applicable when the thermostat is disabled;

- bias/constraint nonuse is asserted only from affirmative source evidence;
- inconsistent controls block only ensemble-dependent methods; descriptive analysis may continue when STAT0 hard-integrity checks pass.

Implementation status: complete in 0.20.18a0. Runtime owners are `mdstats.io.control_certificates`, `mdstats.io.vasp_ensemble`, and ENS1 metadata integration in `mdstats.io.vasp`. The permanent specification is `docs/specs/io/vasp_ensemble_certificate_spec.md`.

Stage 11E-STAT0 - ionic temperature, integrity, conservation, and quality verdict

Deliverables:

- source-bound `IonicTemperatureDefinition` and equipartition-derived per-frame ionic temperature;
- weighted mean, standard deviation, autocorrelation-aware confidence interval, block stability, and drift statistics in `IonicTemperatureStatistics`;
- ensemble-specific conserved or controlled quantity reconstructed from the ENS0 `FrameEnergyCatalog`;
- dimensionless drift, slope significance, residual fluctuation, cell, stress, momentum, equipartition, SCF quality, frame completeness, collision, and runaway diagnostics;
- signed `TrajectoryQualityPolicy` and three-level `TrajectoryQualityVerdict`;
- `TrajectoryDegradedQualityWarning` and `TrajectoryIntegrityError` execution contracts;
- `RealizedEnsembleConsistency`, separate from the control-inferred dynamics mode;
- a required/optional diagnostic matrix classifying each channel as `hard_integrity_required`, `verdict_critical`, `method_specific`, or `optional`.

Acceptance gate:

- ionic temperature is computed as $2K_{\text{ion}}/(f_{\text{ion}}k_B)$ from a signed active-DOF definition;
- the time mean, standard deviation, and correlated confidence interval are all reported rather than replacing one another;
- NVE, NVT, NpT/NpH, biased, and driven cases use distinct conserved or controlled quantities;
- no generic total-energy convention is guessed and smooth drift remains visible after detrending;
- `strictly_qualified` proceeds without a quality warning;
- `degraded_quality` proceeds with one warning and immutable downstream flags;
- only unqualified blocks scientific execution by default;
- fewer than the required independent blocks may degrade confidence or return an insufficient diagnostic, but it does not become unqualified unless an independent hard integrity failure is present.

Implementation status: complete in 0.20.19a0, with the default NVE drift policy revised in 0.20.20a0 to strict/degraded/hard thresholds of 1 and 26 meV/(atom ps). Runtime owners are `mdstats.io.trajectory_quality`, `mdstats.io.vasp_quality`, and full-source metadata integration in `mdstats.io.vasp`. The permanent specification is `docs/specs/io/trajectory_quality_spec.md`.

Stage 11E-STAT1 - source-observable production-regime catalog

Deliverables:

- complete-system block construction and uncertainty;
- predeclared energy, temperature, cell, stress, momentum, and framework-observable stability tests;
- configured change-point detection and contiguous `ProductionRegimeCatalog`;
- selection-conditioning and external-continuation provenance.

Acceptance gate:

- adaptive E1 site density is not used to select the production window;
- user-declared continuation boundaries are tested rather than trusted;
- insufficient blocks yield insufficient and do not by themselves make the source catastrophic;
- strictly qualified and degraded-quality trajectories may both contain usable regimes;
- unqualified trajectories cannot create a scientific production regime;
- multiple regimes remain separate.

Implementation status: implemented in 0.20.20a0. Runtime owners are `mdstats.io.production_regimes`, `mdstats.io.vasp_stationarity`, and full-source metadata integration in `mdstats.io.vasp`. The permanent specification is `docs/specs/io/production_regime_catalog_spec.md`. Stage 11E-STAT2 is implemented in 0.20.21a0.

Stage 11E0b - immutable registered raw sample catalog

Current implementation provides compact frame-major registered species samples, represented-time weights, topology segments, source and registration signatures, raw position/force availability, and lazy structural annotations.

Revision-47 contract:

- E0b owns raw availability and geometry masks only;
- it references but does not infer `SimulationControlCertificate`, `ProductionRegimeCatalog`, or `PmfAdmissibilityCertificate`;
- later `EvidenceAdmissibilityOverlay` objects select position, force, temporal, canonical, microcanonical, or reweighted subsets without mutating E0b;
- no field may encode an untested stationarity assertion as scientific evidence;
- unresolved prerequisite certificates retain descriptive raw evidence but block the corresponding scientific interpretation.

Acceptance gate:

- raw-source, registration, atom, frame, topology, and represented-time identities replay exactly;
- scientific masks cannot be produced without exact prerequisite signatures;
- user labels cannot alter a mask.

Stage 11E-STAT2 - preliminary ensemble-specific admissibility

Deliverables:

- `PmfAdmissibilityCertificate` and initial `EvidenceAdmissibilityOverlay`;
- explicit permissions for descriptive density, microcanonical occupancy, canonical/NpT/reweighted landscapes, conditional force, and diagnostic-only use;
- temperature, energy-shell, bias/reweighting, and approximation provenance.

Acceptance gate:

- NVE data are not silently converted to a canonical PMF;
- NpT uses Gibbs/enthalpy semantics;
- unresolved stationarity blocks thermodynamic promotion while retaining descriptive spatial evidence;
- every permission is policy- and source-bound.

Implementation status: implemented in 0.20.21a0. Runtime owners are `mdstats.io.admissibility`, `mdstats.io.vasp_admissibility`, and full-source metadata integration in `mdstats.io.vasp`. The permanent specification is `docs/specs/io/ensemble_admissibility_spec.md`. The following runtime stage is Stage 11E-SAMP0.

Stage 11E-SAMP0 - cross-fitted block and effective-sample foundation

Deliverables:

- `QualityDiagnosticBlockPartition` remains owned by STAT1;
- one `EvidenceCrossfitPartition` contained within an accepted production regime;
- explicit discovery, model_selection, basin_validation, corridor_validation, thermodynamic_estimation, thermodynamic_validation, and optional final_refit domains;
- a signed nested-selection alternative confined to discovery/model-selection data;
- local decorrelation times, complete-system effective sample counts, represented time, and block/replica support;
- `SamplingAdequacyPolicy` and an implementation-complete `FeatureCorrespondencePolicy`.

The initial correspondence preset `stage11_feature_correspondence_v1` uses the normalized cost

$$C_{ab} = w_d(d_{ab}/\sigma_{\min})^2 + w_o(1 - O_{ab}) + w_p|P_a - P_b|/P_{\text{scale}},$$

with versioned weights, admissible point/ridge type pairs, maximum cost, ambiguity margin, deterministic tie breaking, and explicit split/merge/unmatched outcomes. Exact preset values are serialized and never inferred from feature order.

Acceptance gate:

- all mobile ions from one frame remain in one complete-system block;
- model selection cannot inspect held-out validation domains;
- held-out blocks never change bandwidth, grid, candidate count, or correspondence;
- thermodynamic estimation and optional verification are distinguished;
- final all-data refits receive new signatures and do not inherit parameter-validation certificates.

Implementation status: implemented in 0.20.22a0. Runtime owner is `mdstats.io.sampling_crossfit`; the permanent specification is `docs/specs/io/sampling_crossfit_spec.md`. The following completed runtime stage is Stage 11E-GR0.

Stage 11E-GR0 - common grid geometry and numerical diagnostics

Deliverables:

- analysis-owned cell-metric grid-shape and realized-interval functions;
- periodic spread and Frechet-mean diagnostics;
- reciprocal-resolution diagnostics;
- CIC, Gaussian-stencil, and effective artificial-broadening diagnostics;
- analysis-domain density numerical exceptions;
- compatibility aliases preserving the current plotting imports and serialized values.

Acceptance gate:

- exact numerical and serialization parity with the tested atomic-density oracle;
- oblique-cell Euclidean geometry is preserved;
- no Plotly, mesh, browser, or graph-specific policy is imported by the common layer;
- graph-facing exceptions remain adapter behavior rather than common numerical types.

Implementation status: implemented in 0.20.23a0. Runtime owners are `mdstats.analysis.density.grid_geometry`, `mdstats.analysis.density.diagnostics`, `mdstats.analysis.density.stencil_diagnostics`, and `mdstats.analysis.density.broadening`; the permanent specification is `common_grid_diagnostics_spec.md` under `docs/specs/analysis/density/`. The following completed runtime stage is Stage 11E-GR1.

Stage 11E-GR1 - common budgeted planner and deterministic grid ladder

Deliverables:

- target Cartesian interval to grid-shape planning;
- finest-feasible shape search under scientific limits;
- deterministic nested-grid ladder generation;
- physical-resolution-first and backend-second planning;
- identical-field signature reuse and cache keys;
- explicit budget-limited status without scientific promotion.

Acceptance gate:

- dense and local-sparse plans represent the same logical grid and fixed kernel;
- requested and realized intervals are both retained;
- a ladder that cannot reach its requested finest level remains signed as budget-limited;
- browser and mesh budgets cannot change the scientific grid plan.

Implementation status: implemented in 0.20.24a0. Runtime owner is `mdstats.analysis.density.planning`; the permanent specification is `common_grid_planning_spec.md` under `docs/specs/analysis/density/`. The plotting-private finest-budgeted shape name is a compatibility adapter only. The following completed runtime stage is Stage 11E-GR2.

Stage 11E-GR2 - plotting adaptation and visual-policy preservation

Deliverables:

- atomic and framework plotting adapters over the common GR0/GR1 layer;

- preservation of plotting’s automatic visual bandwidth/grid coupling;
- graph-facing error translation and rendering metadata;
- unchanged browser, mesh, and scene-admission behavior.

Acceptance gate:

- atomic/framework density values, default selected grids, warnings, sparse routing, meshes, scenes, and public option serialization remain regression-compatible;
- plotting may accept a finest-feasible grid with a visual warning, but that outcome is not a scientific convergence certificate;
- the common analysis layer remains independently usable without rendering libraries.

Implementation status: implemented in 0.20.25a0. Runtime owner is `mdstats.plotting.density_visual_policy`; the permanent specification is `plotting_grid_adaptation_spec.md` under `docs/specs/analysis/density/`. Atomic and framework field producers consume the adapter while retaining their established visual and rendering contracts. The following completed runtime stage is Stage 11E-GR3.

Stage 11E1 - discovery-block periodic species-density estimation

Deliverables remain the existing source-bound physical/reference-material density, periodized triclinic kernel, support, score, Hessian, dense/sparse realization, bandwidth ladder, and uncertainty products.

Revision-47 requirements:

- density discovery uses only the SAMP0 discovery blocks and an admissibility overlay;
- descriptive position density may run when thermodynamic interpretation is blocked;
- discovery-block identities and policy signatures are mandatory;
- validation blocks are never used to choose bandwidth, grid, or candidate count.

Acceptance gate:

- held-out mass and feature recurrence can be evaluated without refitting;
- canonical, microcanonical, or descriptive labels come from STAT2 rather than E1;
- numerical support is not represented as feature-level sampling confidence;
- the kernel covariance is explicit and remains fixed within each GR3 grid ladder;
- E1 does not call plotting’s adaptive Gaussian-to-grid policy.

Stage 11E2 - per-realization numerical basin and density-boundary candidates

Deliverables remain deterministic point/ridge/flat candidates, support-restricted basin ownership, local periodic charts, provisional cores, lineage, scale ambiguity, and one `PerRealizationCandidateCatalog` for each bandwidth/grid realization.

Revision-47 terminology and ownership:

- E2 emits `density_boundary_candidate` and, with derivative support, `numerically_supported_saddle_candidate`;
- it does not emit a validated transition saddle, kinetic edge, or final frozen catalog;
- candidates are constructed only from discovery data;
- `FeatureCorrespondencePolicy` defines matching among E2 realizations.

Acceptance gate:

- unsupported space remains unknown;
- each realization is deterministic and serializable;
- no event or barrier claim follows from face adjacency alone;
- final selection and freezing are owned exclusively by GR4.

Stage 11E-GR3 - Stage 11 fixed-kernel scientific grid refinement

Deliverables:

- `ScientificGridRefinementPolicy` and `GridConvergenceStoppingPolicy`;
- deterministic nested cell-metric grids with fixed kernel covariance;
- `DensityFieldResolutionCertificate`;
- `BasinGridConvergenceCertificate`;

- CorridorGridConvergenceCertificate; and
- explicit budget-limited unresolved outcomes.

The stopping policy records the refinement factor or interval ladder, target $\max_i \Delta_i / \sigma_{\min}$, maximum ladder depth, and the number of consecutive level pairs required to pass. Basin convergence records tolerances for count, correspondence ambiguity, anchor displacement relative to kernel scale, basin overlap, and integrated probability change. Corridor convergence records adjacency equality, corridor/ridge overlap, bottleneck-location displacement, width/density changes, and split/merge ambiguity. Defaults may be policy presets, but every resolved certificate retains their numerical values. The initial `stage11_grid_stopping_v1` preset uses factor-two interval refinement, $\Delta_{\max} / \sigma_{\min} \leq 0.5$, and two consecutive passing level pairs. Its basin and corridor thresholds and the matching weights of `stage11_feature_correspondence_v1` are defined exactly in `scientific_grid_refinement_spec.md`; any change requires a new preset identifier.

At least two consecutive refinement comparisons must pass after the minimum physical resolution is reached. A single matching level pair is diagnostic only. Basin convergence does not imply corridor convergence. Hitting the resource or maximum-depth limit before passing returns `unresolved_due_to_resolution_budget` or `unresolved_due_to_refinement_limit`.

Acceptance gate:

- plotting's adaptive bandwidth selection does not enter the scientific ladder;
- all levels use one fixed density hypothesis and exact common metric;
- field, basin, and corridor outcomes remain orthogonal;
- unresolved corridor topology cannot block a separately converged basin catalog, but it blocks saddle/barrier promotion.

Implementation status: implemented in 0.20.26a0. Runtime owner is `mdstats.analysis.density.refinement`; the permanent specification is `fixed_kernel_grid_refinement_spec.md` under `docs/specs/analysis/density/`. The implementation records exact `stage11_grid_stopping_v1` policy values, requests the additional post-gate level required for two consecutive comparisons, and retains budget-, depth-, metric-, and missing-evidence outcomes as signed unresolved certificates. Stage 11E-GR4 is the next implementation stage.

Stage 11E-GR4 - cross-fitted numerical-hypothesis selection and freeze

Deliverables:

- grid, bandwidth, candidate-complexity, and correspondence selection restricted to discovery/model-selection evidence;
- one source-bound `FrozenCandidateCatalog` containing the accepted numerical hypothesis, exact E2 realization lineage, correspondence policy, and convergence certificates;
- optional all-data `FinalRefitCatalog` with a new signature;
- selection-conditioned uncertainty when nested selection is unavoidable.

Acceptance gate:

- held-out blocks cannot change kernel covariance, grid level, candidate count, candidate identities, or feature correspondence;
- all-data refinement does not inherit held-out parameter-certification evidence;
- GR4 numerical convergence and SAMP1/SAMP2 trajectory support remain orthogonal;
- no other stage may claim ownership of the final frozen numerical catalog.

Stage 11E-STAT3 - held-out distribution-stability refinement

Deliverables:

- distribution and occupancy stability measured on the dedicated `thermodynamic_validation` partition or an explicitly signed nested equivalent; this verification is optional for source-qualified descriptive/thermodynamic estimators but required for a `cross_validated` claim;
- selection-conditioned uncertainty and regime-sensitivity diagnostics;
- a refined `PmfAdmissibilityCertificate` without retuning E1/E2 candidates.

Acceptance gate:

- held-out instability may block occupancy thermodynamics or PMF interpretation while preserving descriptive density and basin geometry;

- STAT3 never consumes basin-validation or corridor-validation evidence unless a prespecified nested policy proves independence;
- validation results do not alter bandwidth, grid level, candidate identity, or local mechanical-force parameters.

Stage 11E3A/11E3B - mechanical refinement and thermodynamic mean-force estimation

Stage 11E3A - local mechanical-force refinement

- consumes only discovery/model-selection blocks and geometrically admissible conservative physical forces;
- fits LocalMechanicalForceRefinement for center offsets, restoring stiffness, manifold-normal confinement, and uncertainty;
- remains available for NVE and other noncanonical runs when force provenance is geometrically valid;
- makes no PMF, free-energy, or Boltzmann claim.

Stage 11E3B - thermodynamic mean-force estimation and certification

- evaluates a frozen E3A model and constructs matched-kernel conditional force on the thermodynamic_estimation partition;
- emits a source-qualified ThermodynamicMeanForceCertificate only for canonical, validly reweighted, microcanonical-theory, or explicitly accepted subsystem-canonical contracts; the result carries mandatory ThermodynamicResultProvenance;
- retains curl, circulation, residual, and support diagnostics without projecting them away;
- rejects thermodynamic interpretation without deleting the E3A mechanical result.

Acceptance gate:

- no thermodynamic-estimation or verification block refits E3A parameters;
- an optional final all-data refit is separately signed;
- mechanical and thermodynamic statuses remain orthogonal in E5 and downstream records.

Legacy E3 migration is explicit:

Legacy E3 field	Revision-47 owner	Migration rule
local center offset, symmetric stiffness, mechanical curvature	E3A	may be replayed only on discovery/model-selection evidence
conditional force average on a matched support subset	E3B candidate input	recompute on the signed thermodynamic-validation subset
density-score/force residual	E3B	recompute when ensemble, measure, kernel, or subset changes
PMF-admissible or equilibrium label	E3B/PMF-DENSITY/PMF-FORCE certificate	never inherited from the legacy record

A legacy E3 result therefore proves neither E3A nor E3B compliance without the corresponding replay and certificate.

Stage 11E4 - provisional assignment and temporal-persistence diagnostics

Deliverables:

- raw core, basin, transition, background, unknown, unresolved, and overlap memberships;
- segment-aware core visits and preliminary core-entry/basin-retention intervals;
- explicit jump, return-excursion, unresolved-gap, and right-censored passages;
- local decorrelation-timescale estimates in the E1 analysis metric;
- dwell, censoring, stride, excursion, and recrossing diagnostics;
- independent temporal-support and global evidence-pattern statuses.

Acceptance gate:

- transition/background/unknown samples are not nearest-center filled;
- one jump, repeated hopping, short excursions, and unresolved gaps receive distinct evidence statuses;
- source segment boundaries and independent ensembles never acquire invented temporal continuity;

- temporal evidence is reported before final site certification.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.temporal_assignment` owns the Stage-11E4 result;
- E0b, E1, E2, and optional E3 signatures are validated before temporal work;
- raw memberships preserve the exact E2 cell classification and provisional-core sets, including explicit core overlap and unsupported space;
- only core and basin samples carry an attractor identity; no transition, background, unknown, unresolved, overlap, or excluded sample is filled by nearest anchor;
- trajectory continuity is restricted to one atom and one E0b segment, while independent ensembles retain spatial memberships but no intervals or passages;
- preliminary passages distinguish resolved jumps, same-state return excursions, unsupported/unresolved gaps, and right-censored exits;
- local periodic-coordinate autocorrelation uses a Geyer initial-positive-sequence truncation and downgrades irregular physical-time stride to a frame-only claim;
- stride sensitivity is evaluated separately from the authoritative full-resolution membership table;
- short-excursion and recrossing diagnostics use declared frame and local decorrelation thresholds without creating final events; and
- focused tests cover single jumps, repeated hopping, short excursions, unsupported gaps, ensembles, stride sensitivity, serialization, resources, source binding, and public API contracts.

Stage 11E-SAMP1 - held-out basin sampling certificates

Deliverables:

- one `BasinSamplingCertificate` per frozen E2 basin candidate;
- held-out recurrence, residence, anchor/shape uncertainty, block/replica coverage, and grid/bandwidth survival;
- orthogonal evidence fields and final basin-promotion decision.

Acceptance gate:

- validation blocks are assigned with frozen candidate regions;
- one long correlated residence may support localization but not recurrence;
- accepted basins reproduce on held-out blocks within policy uncertainty.

Stage 11E5 - joint evidence validation and structural association

Deliverables:

- orthogonal spatial, temporal, force, stationarity, geometry, curvature, and overall-certification statuses;
- matched force-to-score-covector consistency, never force-to-unqualified-gradient comparison;
- the exact `EvidenceCrossfitPartition` with separate discovery, model-selection, basin-validation, corridor-validation, thermodynamic-validation, and optional-final-refit independence statuses;
- `StructuralAssociationSet` records using registered structural views;
- statistical-state instances, preliminary structural complexes, and optional symmetry-orbit candidates;
- exchangeability checks before any orbit grouping of nominally equivalent rings;
- no default symmetry augmentation of trajectory samples;
- explicit `ValidatedFrozenCatalog` and optional `FinalRefitCatalog`.

Acceptance gate:

- force-free trajectories can produce spatial/temporal sites but not force-validated sites;
- disagreement among evidence channels remains explicit;
- association ambiguity is retained rather than resolved by nearest-ring fallback;
- held-out basin validation never rejects a one-transition trajectory merely because early and late blocks occupy different basins; limited data instead produce an explicit selection-conditioned or independent-validation-unavailable status.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.evidence_validation` owns the Stage-11E5 result;

- E0b, E1, E2, E4, optional E3, and C0A3 registration/source identities are reconciled transactionally before block or association work;
- ValidatedFrozenCatalog retains one record per E2 state with orthogonal evidence statuses and explicit disagreement diagnostics;
- force evidence is compared only with the E3 density-score covector in the same registered measure, never with an unqualified Euclidean gradient;
- structural associations use the E1 analysis metric and certified triclinic periodic-image geometry under a declared radius, retain all plausible candidates, and prohibit nearest-object fallback;
- discovery, model-selection, basin-validation, corridor-validation, thermodynamic-validation, and optional-final-refit partitions retain independent, selection-conditioned, unavailable, and insufficient-transfer statuses rather than forcing rejection;
- nominal structural-symmetry candidates remain opt-in, require exchangeability evidence before orbit acceptance, and never augment observations by default;
- FinalRefitCatalog is separately signed and cannot inherit parameter-validation evidence for refitted positions, boundaries, or force parameters; and
- focused tests cover force-free and force-validated states, force-score disagreement, ambiguous/unresolved association, limited transitions, block independence, symmetry exchangeability, refit provenance, serialization, resources, source binding, and public API contracts.

Stage 11E5a - species-dependent coordination fingerprints and classification

Deliverables:

- exact state-conditioned M–O/M–T distance vectors;
- cyclic-index and rank-safe actual-angle coordination spectra;
- direct local off-center coordinates and diagnostic residual spectra;
- gauge-defined oxygen-, gap-, and sector-locking scores;
- exact unweighted cyclic spectra, boundary-measure angular moments, and raw/normalized amplitudes;
- geometry-predicted coordination and unexplained residual;
- occupancy-conditioned fingerprint diagnostics;
- point, bilateral, discrete off-center, smooth/corrugated annular, cage, general, and ambiguous structural classes with continuous evidence.

Acceptance gate:

- a centered serrated S6R is not classified as off-center;
- direct off-centering and geometry-predicted distance modulation agree within uncertainty for a coherent point state;
- residual spectra are not interpreted as exact component separation;
- phase-dependent labels require resolved amplitude and stable circular phase;
- occupancy-conditioned mixtures remain explicit;
- one state may retain several plausible structural associations.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.coordination_fingerprints` owns the Stage-11E5a result;
- exact physical M–O/M–T sample matrices and persistent atom/image identities are authoritative, while mean sequences and all spectra are derived views;
- the centered-reference construction preserves each sample’s normal coordinate and removes only in-plane displacement;
- equal-index DFTs, boundary-measure angular moments, and rank-safe actual-angle fits are stored as three distinct measures;
- direct local coordinates gate off-center labels, so a centered serrated S6R remains centered despite a strong short-wavelength harmonic;
- phase-dependent locking and discrete-angular labels require a resolved radial amplitude and a stable circular resultant;
- geometry-forward residuals compare average framewise physical distances rather than distances to an averaged structure;
- occupancy-conditioned mixtures and multiple plausible structural associations remain explicit; and
- focused tests use real ASE 3.29.0 for VASP I/O and triclinic minimum-image behavior, and cover classification, harmonics, serialization, resources, and public API contracts.

Stage 11E5b - optional geometry-conditioned site refinement

Deliverables:

- static and framework-descriptor-conditioned center models;
- atom-resolved structural predictors and rank-safe harmonic features;
- separate `model_selection` comparison, `basin_validation` confirmation, and `corridor_validation` crossing checks;
- instantaneous predicted centers and nested cores/basins with persistent global state identity;
- static/dynamic memberships, comoving ion displacement, boundary displacement, and boundary-induced crossing diagnostics;
- residual covariance before and after conditioning;
- exclusive `AssignmentConflictStatus`, overlap fractions, and occupancy bounds.

Acceptance gate:

- the dynamic model is retained only when model-selection residuals improve and the relevant held-out basin/corridor evidence does not contradict the gain;
- a moving center never uses a frozen basin implicitly;
- dynamic and frozen memberships remain jointly reportable;
- a boundary-swept crossing is not silently labeled ion-driven;
- mobile-ion positions never redefine the structural predictor frame.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.geometry_conditioning` owns the Stage-11E5b result;
- `FrameworkPredictorTable` accepts only framework-derived predictors and rejects mobile-ion-dependent tables;
- `FrozenRegionDefinition` binds one persistent state/association to a static center and strictly nested core/basin radii;
- discovery assignments remain frozen while a represented-time weighted affine center model is fit with rank, condition, residual RMS, and covariance records;
- model-selection and untouched basin/corridor-validation evidence decide whether the dynamic model is retained, contradicted, or unsupported;
- moving cores and basins rigidly translate the frozen shape and never reuse a frozen basin around a moving center;
- static, candidate-dynamic, and selected memberships are all persistent;
- atom/segment-local crossings retain ion, center, boundary, and comoving displacement, including explicit boundary-induced status;
- global assignment conflicts are exclusive and state occupancy is reported as lower/upper bounds under overlap; and
- deterministic signatures, strict replay serialization, resource preflight, real-ASE regression, permanent specifications, and public exports are tested.

Stage 11E-SAMP2 - preliminary corridor and saddle-candidate sampling support

Deliverables:

- `PreliminaryCorridorSupport` built from E4 provisional passages not used for candidate discovery;
- `TransitionCorridorSamplingCertificate` with independent passage count, forward/reverse directions, block/replica support, path-progress coverage, local field support, candidate recurrence, and corridor uncertainty;
- explicit `observed_one_off_passage`, `sampling_supported_transition_corridor`, and `sampling_supported_saddle_candidate` outcomes.

SAMP2 does not create a validated thermodynamic saddle or final transition event. E6 may alter event boundaries, censoring, recrossing, and event count. Final evidence therefore supersedes rather than silently inherits preliminary counts.

Acceptance gate:

- raw transition-frame count never substitutes for independent event count;
- candidate correspondence uses the frozen GR4 policy;
- one event remains one-off evidence;
- promotion to a physical transition saddle is reserved for THERMO3B or an equivalent independently specified transition-state test.

Stage 11E-SAMP3 - partial-catalog scope, novelty, and saturation

Deliverables:

- cumulative basin, corridor, and event discovery curves;
- holdout novelty and unsupported-assignment rates;
- `DiscoveryScopeCertificate` with `observed_partial_catalog` semantics;
- raw event/exposure/censoring outputs and `RateBoundModel` eligibility only.

Acceptance gate:

- no finite trajectory claims complete discovery;
- formal rate intervals remain deferred to Stage 11F0 unless a complete signed model certificate exists;
- longer trajectories increase supported evidence rather than only fitted features.

Stage 11E-THERMO0 - thermodynamic state and channel selection

Deliverables:

- `ThermodynamicStateDefinition` and `ThermodynamicPotentialDefinition`;
- `ThermodynamicEnergySelection` referencing the preexisting `FrameEnergyCatalog`;
- tagged-ion, pooled-orbit, occupation-vector, and joint-state semantics;
- multiplicity and standard-measure convention.

Acceptance gate:

- THERMO0 does not reconstruct source energy channels after STAT0;
- no generic energy or ambiguous state probability is accepted;
- multiplicity correction cannot be applied twice.

Stage 11E-THERMO1 - ensemble-specific basin thermodynamics

Deliverables:

- NVT/reweighted Helmholtz, NpT Gibbs, or NVE microcanonical occupancy/entropy products as permitted by the selected potential definition;
- correlated-data uncertainty and selection-conditioning status;
- descriptive occupancy retained when thermodynamic promotion is blocked.

Acceptance gate:

- canonical formulas are used only for canonical target measures;
- NpT includes pressure-volume/enthalpy semantics;
- NVE canonical approximation requires a separate accepted policy;
- population-derived thermodynamics are never validated against the same population.

Stage 11E-THERMO2 - conditional energies and identifiable effective Hamiltonians

Deliverables:

- ensemble-appropriate conditional potential energy or enthalpy;
- complete-system block uncertainty and background-control sensitivity;
- optional nested effective occupancy models under `EffectiveHamiltonianPolicy`;
- energy/entropy decomposition where independently identifiable.

Acceptance gate:

- frame energies are not duplicated across ions as independent samples;
- rank, condition, occupancy-variation, symmetry, regularization, and held-out-score gates are explicit;
- predictive coefficients are not represented as unique atomic energies.

Stage 11E-THERMO3A - static finite transition-region thermodynamics

Deliverables:

- a declared finite transition tube, dividing-surface neighborhood, or reaction-coordinate bin for each SAMP2-supported candidate;
- static probability density or reweighted support, conditional whole-system energy or enthalpy, region measure, and uncertainty;
- `StaticTransitionRegionThermodynamics` with no event-conditioned or committor claim.

Acceptance gate:

- point saddles are never assigned integrated probability;
- unsupported or grid-unstable regions remain unresolved;
- static transition-region evidence cannot promote a transition state or rate.

Stage 11E6 - final hysteretic segmentation and residence statistics

Deliverables:

- immutable raw labels;
- frozen-catalog core-basin hysteresis;
- residence and transition intervals;
- unresolved-gap, recrossing, excursion, censoring, and moving-boundary policies;
- static-versus-dynamic membership, assignment-conflict, overlap, and boundary-induced crossing records;
- reuse of generic temporal statistics;
- ion-time, mean-occupancy, vacancy, and multiple-occupancy statistics.

Acceptance gate:

- final event statistics are stable over a documented range of thresholds and frame strides;
- `FinalTransitionEventCertificate` records final independent event count, censoring, recrossing, at-risk exposure, and the exact relationship to superseded E4/SAMP2 preliminary evidence.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.final_segmentation` owns the Stage-11E6 result;
- immutable E4 raw labels remain authoritative and nearest-center filling is prohibited;
- frozen E4, selected E5b, and static/dynamic-agreement membership policies are explicit;
- qualified core entry and basin-retention hysteresis preserve short excursions and require confirmed exits;
- unsupported gaps, assignment conflicts, boundary-induced passages, recrossings, return excursions, and censoring remain explicit;
- residence records retain exact atom, segment, state, and compact sample identities with represented-time components;
- state summaries report ion-time, uncensored residence durations, occupancy bounds, vacancy bounds, and multiple-occupancy bounds without a rate-law assumption;
- declared threshold/stride perturbations produce an independent stability certificate; and
- deterministic signatures, strict replay serialization, resource preflight, permanent specifications, public exports, and real-ASE validation are tested.

Stage 11E6b - observed transition-path ensembles

Deliverables:

- first-subsequently-resolved-core passages;
- resolved, bracketed, multiple-target, ambiguous, and gap-interrupted first-hit statuses;
- failed excursions and recrossings;
- full registered paths and periodic translations;
- `RegistrationCompatibilityClass` for pooling paths from independent registered trajectories;
- geometry, exact ring-sector coordination, harmonics, and force evidence along paths;
- single-path, undersampled-ensemble, and resolved-ensemble statuses;
- optional path clustering only when event support is adequate;
- concurrent-event and local occupancy context without forcing a many-body model.

Acceptance gate:

- one jump produces one observed connection but no inferred rate or representative pathway;
- repeated paths retain physical time, unwrapped image bookkeeping, and periodic identity;
- output cadence limitations remain explicit rather than interpolated away;
- an intermediate density shoulder is not promoted to a site without independent spatial and temporal evidence.

Baseline compatibility requirements (implemented; release chronology is in the status appendix):

- `mdstats.analysis.density.transition_paths` owns the Stage-11E6b result;
- every event is reconstructed from exact E6 compact sample brackets and retains registered Cartesian positions, wrapped fractional positions, integer image shifts, physical times where available, represented-time weights, and force availability without interpolation;
- resolved, cadence-bracketed, target-ambiguous, gap-interrupted, failed, recrossing, and censored first-hit outcomes remain explicit;
- periodic translation is validated as the endpoint image-shift difference and is part of the path-ensemble identity;
- optional sample-bound ring, sector, ordered coordination, harmonic, aperture, puckering, occupancy, density, PMF, and transformed-force evidence is retained without changing the E6 state catalog;
- `RegistrationCompatibilityClass` permits pooling distinct independent registrations only under a common registration group or identical registration, unit convention, and explicit state correspondence;
- path ensembles distinguish single observations, undersampled collections, and resolved support; optional diagnostic clustering is admitted only above a declared event count and preserves original time;
- overlapping events retain local occupancy context and isolated, overlapping, candidate-exchange, candidate-concerted, or unresolved collective status without creating a many-body model; and
- deterministic signatures, strict replay serialization, resource preflight, permanent specifications, public exports, and real-ASE validation are tested.

The optional PMF-DENSITY, PMF-FORCE, and PMF-CROSSCHECK branches may proceed only under their own ensemble, support, and integrability gates. Current implementation priority is defined only by the revision-47 typed dependency graph.

Stage 11E-THERMO3B - event/path-conditioned transition-state validation

Deliverables:

- transition-region statistics recomputed from final E6 events and E6b path ensembles;
- recrossing, directional support, path-conditioned energy/enthalpy, dividing-surface behavior, and committor or enhanced-sampling provenance where available;
- `TransitionStateValidationCertificate`;
- promoted `SaddleThermodynamicCertificate` is a composition of the exact `StaticTransitionRegionThermodynamics` from THERMO3A and the THERMO3B validation certificate, and exists only when all required gates pass.

Acceptance gate:

- preliminary SAMP2 counts are not treated as final events;
- repeated passages alone do not prove a thermodynamic saddle;
- one-off or undersampled paths remain observations without barrier/rate promotion;
- `validated_transition_saddle` is a THERMO3B outcome, never an E2 or SAMP2 outcome.

Stage 11E7 - observed event network with optional geometric annotations

Deliverables:

- `ObservedEventNetwork` whose nodes are validated state instances;
- `ObservedEventEdge` from final E6 directional events, at-risk exposure, censoring, and periodic endpoint translation where identifiable;
- optional `PathResolvedEdge` enrichment from E6b;
- optional `TransitionStateAnnotatedEdge` enrichment from THERMO3B;
- structural-versus-observed edge comparison without graph completion;
- separate state-instance, structural-complex, symmetry-orbit, and semantic-class summaries;
- compact source-anchor transfer models and fail-closed held-out/external assignment.

Acceptance gate:

- an event-supported edge does not require a resolved intermediate path or saddle;
- cadence-limited or geometry-unresolved paths remain event edges with explicit missing annotations;
- structural candidates never create observed edges;
- off-network events and failed transfer remain explicit; and
- rates, state merging, symmetry augmentation, and model refitting remain absent.

Baseline compatibility mapping:

- the existing observed-network implementation currently creates edges from successful E6b path ensembles;
- revision-47 migration must add E6-event-supported edges without changing legacy path-resolved edge serialization;
- existing path edges map to `PathResolvedEdge`; they do not define the complete event network after migration.

Stage 11E-GR5 - density numerical-ownership closeout

Deliverables:

- remaining field contracts, source provenance, periodized kernels, normalization, support masks, HDR integration, dense/local-sparse producers, and scientific planning moved to `mdstats.analysis.density` where not already migrated;
- plotting consumes only analysis-owned field protocols and producers;
- compatibility imports and adapters retained for one deprecation interval, then removed only after public-API approval;
- D0b-D0d marked complete.

Acceptance gate:

- dense, local-sparse, scientific-field, atomic/framework plotting, mesh, scene, and package-wide regression boundaries pass;
- numerical fields and signatures remain equal across compatibility and new import paths;
- no analysis module imports graph, browser, mesh, or HTML policy;
- removal of old numerical ownership is an engineering cleanup and cannot alter existing scientific certificates.

Stage 11E-PMF-DENSITY - optional density-derived PMF

Entry dependencies:

- STAT2 canonical/reweighted density-PMF admissibility;
- STAT3 distribution stability;
- converged field numerics and SAMP1-supported basins;
- explicit coordinate measure, Jacobian, support topology, temperature, and reweighting provenance.

Deliverables:

- `DensityPmfCertificate` with $A(q) = -k_B T \ln p(q) + C$ on declared supported components;
- component offsets, uncertainty, minima, and candidate bottlenecks only where supported;
- mandatory `ThermodynamicResultProvenance`.

Force data are not required. The result may be `source_qualified_unverified`.

Stage 11E-PMF-FORCE - optional force-integrated PMF

Entry dependencies:

- STAT2/STAT3 force-PMF admissibility;
- E3B matched-kernel thermodynamic mean-force evidence;
- converged field numerics and SAMP1-supported basins;
- coordinate-measure, Jacobian, curl, circulation, harmonic-component, topology, and boundary-condition policy.

Deliverables:

- `ForcePmfCertificate` with raw mean-force, curl, circulation, harmonic diagnostics, integrability status, scalar reconstruction, and provenance.

Stage 11E-PMF-CROSSCHECK - optional independent PMF verification

When both PMF estimators exist on compatible coordinates and support, `PmfCrossCheckCertificate` compares them without rebuilding either estimator. Agreement raises confidence; unavailability leaves either source-qualified PMF reportable; disagreement preserves both estimates and blocks only a combined cross-validated PMF.

None of the PMF stages blocks local site discovery, temporal segmentation, or observed transition paths.

Stage 11E8a - Na-LTA NVE continuation integration dossier

E8a is a cross-cutting source-bound acceptance dossier. It is updated at each migration milestone and is not ordered after GR5 or the optional PMF branches.

Milestone products:

E8a-ENS source controls, user-label conflict, ensemble and force provenance
E8a-STAT ionic temperature, integrity, energy conservation, quality, production regimes
E8a-GR fixed-kernel field/basin/corridor numerical convergence
E8a-SAMP held-out basin sampling confidence and preliminary corridor support
E8a-SCOPE novelty, saturation, and observed-partial-catalog scope
E8a-PMF-DENSITY optional density-derived PMF sub-dossier
E8a-PMF-FORCE optional force-integrated PMF sub-dossier
E8a-PMF-CROSSCHECK optional verification when both estimators exist
E8a-THERMO optional and present only when thermodynamic gates pass
E8a-PATH optional and present only when final events/path gates pass
E8a-RATE optional and present only when kinetic gates pass

The current real-source fixture is a fixed-cell Na-LTA continuation trajectory. Its historical user comment contains “300 K NVT”, but that label is non-authoritative. ENS0/ENS1 must reconstruct the controls and numerical MD settings. STAT0–3 must determine equipartition temperature, the three-level trajectory-quality verdict, production regimes, and permitted thermodynamic interpretations. The observed smooth NVE energy drift is expected to produce `degraded_quality`, not catastrophic rejection, provided all hard integrity checks pass.

The existing S0–S4 software path remains an engineering-complete exploratory baseline: 24 numerical basin identities are persistent across the tested pilot bandwidth/grid realizations, but they are not yet SAMP1-certified on held-out blocks. Saddle adjacency, PMF-force admissibility, and inter-basin transition evidence remain unresolved or unsupported. The dossier remains `scientifically_partial`.

Milestone acceptance requirements:

- E8a-ENS: resolve `MDALGO=2`, `SMASS=-3`, and `ISIF=2`; record the misleading comment only as `user_label_conflicts_with_controls`; reconstruct exact energy and numerical-control channels;
- E8a-STAT: classify integrity, NVE conservation, production regimes, and quality without untested stationarity assertions;
- E8a-GR: replace pilot-only hard-coded grid pairs with the GR3 fixed-kernel ladder, report field/basin/corridor convergence separately, and leave budget-limited unconverged corridors unresolved;
- E8a-SAMP: apply the signed crossfit partition and held-out basin/corridor confidence;
- E8a-SCOPE: label every result as a condition- and timescale-scoped partial catalog;
- no milestone requires optional PMF, GR5 ownership closeout, a validated saddle, or a rate unless that specific sub-dossier is requested.

Detailed S0–S4 release history and package-test evidence remain in the non-normative status appendix.

Stage 11E-THERMO4A - optional product-scoped thermodynamic verification

Deliverables:

- one optional `ThermodynamicCrossValidationCertificate` per requested product class;
- exact estimator provenance and independent verification-source provenance;
- optional occupancy/PMF, temperature-derivative, replica/held-out-temperature, or WHAM/MBAR checks when admissible.

Acceptance gate:

- THERMO1/2 source-qualified results do not require THERMO4A to be reported;
- every result states whether verification was not requested, unavailable, insufficient, agreed, partially agreed, or disagreed;
- a `cross_validated` claim requires genuinely independent or explicitly nested evidence;
- native energies from different Hamiltonians are never pooled as MBAR input;
- detailed balance and barrier-rate agreement are absent from this stage.

Stage 11E8b - cross-dataset comparison by product class

Every product retains its observation timescale, `observed_partial_catalog` scope, source bundle identity, and estimator provenance. Equal ring semantics do not imply equal statistical-state identity.

Product-specific nodes and gates:

- `E8B_BASIN_GEOMETRY`: E5/E5a, SAMP1, SAMP3, and converged basin numerics;
- `E8B_BASIN_THERMO`: THERMO1 and compatible state/ensemble definitions; THERMO2 and THERMO4A are optional energy-decomposition and verification annotations;
- `E8B_CORRIDOR`: SAMP2 plus converged corridor numerics;
- `E8B_TRANSITION_REGION`: THERMO3A;
- `E8B_PATH`: E6b only;
- `E8B_TRANSITION_STATE`: THERMO3B;
- `E8B_EVENT_NETWORK`: E7 with compatible state semantics;
- `E8B_KINETIC`: F0/E9B, with optional G1/F1/THERMO4B annotations.

Direct WHAM/MBAR pooling additionally requires a common target measure and cross-evaluated reduced potentials. Failure of a later product gate never blocks an earlier comparison class.

Stage 11E7A - rate-candidate edge universe and exposure support

Deliverables:

- one signed `RateCandidateEdgePolicy` defining the edge universe before event counting;
- `RateCandidateEdgeUniverse` containing source-bound `RateCandidateEdge` records;
- candidate sources may include structurally admissible all-pairs rules, M2 supplied edges, or SAMP2-supported corridors, each labeled separately;
- state-at-risk exposure and censoring eligibility even when zero events occur;
- multiplicity, symmetry pooling, and multiple-testing policy.

Acceptance gate:

- an observed event creates or annotates an `ObservedEventEdge`, but zero-event candidates remain representable;
- no candidate edge is interpreted as an observed transition or saddle;
- rate bounds are calculated only for policy-declared candidates with valid exposure.

Stage 11E-KSAMP0 - kinetic fit and validation partition

Deliverables:

- one `KineticCrossfitPartition` created after final E6 event episodes are frozen;
- explicit `kinetic_model_selection`, `kinetic_model_fit`, and `kinetic_model_validation` episodes;
- split boundaries respect complete residence/event episodes where possible;
- intervals crossing a split are censored according to a signed boundary policy;
- trajectory- or replica-level splitting is preferred when sufficient data exist.

Acceptance gate:

- E9A and G0 consume selection evidence only;
- F0 consumes kinetic-model-fit events and exposure only;
- E9B consumes untouched kinetic-model-validation events/exposure only;
- when independent kinetic validation is impossible, the outcome is `independent_kinetic_validation_unavailable`, not in-sample promotion.

Stage 11E9A - pre-rate event-process and state-model adequacy

Deliverables:

- dwell-time survival, censoring, recrossing, threshold, and stride diagnostics;
- event-count and at-risk-exposure sufficiency;
- diagnostic waiting-time, discrete-lag, and continuous-time models that are explicitly non-promoted and used only for adequacy testing;
- lag-time and Chapman–Kolmogorov diagnostics where data permit;
- one pre-rate state-model outcome:

```
current_state_model_supported
discrete_lag_model_required
semi_markov_required
gate_state_augmentation_required
sampling_insufficient
```

Acceptance gate:

- E9A uses only `kinetic_model_selection` episodes and may fit diagnostic models but does not publish production rates or rate bounds;
- a gating-required outcome routes to G0 before F0;
- sampling insufficiency remains explicit and cannot be repaired by regularization.

Stage 11G0 - gating diagnosis and state-model selection

Deliverables:

- identify no-gate, fast-gate, slow-gate, comparable-timescale, or unsupported regimes;
- define candidate gate observables from validated framework breathing, aperture, occupancy, or other descriptors;
- determine whether averaging, explicit augmented states, semi-Markov memory, or a nonstationary model is required;
- `GatingModelSelectionCertificate` for the accepted state-model generation.

Acceptance gate:

- if no augmentation is required, issue an explicit no-op accepted certificate;
- if augmentation is required, it must improve selection-stage adequacy without inspecting `kinetic_model_validation` episodes;
- augmentation creates a signed `StateModelGeneration`, `GenerationReplayPlan`, and `GenerationTerminationCertificate`, and repeats bounded assignment, segmentation, E7 construction, and E9A validation with new signatures;
- the iteration count is policy-bounded; failure to converge blocks promoted rates rather than creating a cycle or silently retaining ungated rates.

Stage 11F0 - empirical rates and rate bounds

Deliverables:

- directional final-event counts, at-risk state exposure, censoring, and uncertainty on `kinetic_model_fit` episodes;
- the owning `RateBoundModel` with event-process, stationarity, exposure, multiplicity, candidate-edge, and confidence assumptions;
- empirical directional rates where identifiable;
- zero- or low-event upper bounds on declared `RateCandidateEdge` records;
- conditional detailed-balance residuals only when an independent equilibrium population certificate and compatible thermodynamic measure exist.

Acceptance gate:

- requires E6 final events, E7 observed-event records, E7A candidate-edge universe, E9A support, KSAMP0, and an accepted G0 state model;
- E6b paths and THERMO3B saddles are not required;
- zero-event bounds require valid at-risk exposure and the signed candidate-edge policy;

- absent equilibrium admissibility suppresses detailed-balance output but does not delete otherwise valid empirical rates;
- insufficient fit events produce `sampling_insufficient`, not regularized certainty.

Stage 11E9B - post-fit kinetic-model validation

Deliverables:

- held-out likelihood or survival prediction on untouched `kinetic_model_validation` episodes;
- lag-time, implied-timescale, Chapman–Kolmogorov, residual, and censoring checks where identifiable;
- model-selection uncertainty and one outcome:

```
promoted_model_supported
semi_markov_revision_required
gating_revision_required
independent_kinetic_validation_unavailable
sampling_insufficient
rejected
```

Acceptance gate:

- E9B cannot reuse F0 fit episodes as independent validation;
- only `promoted_model_supported` permits Stage 11H propagation as a validated model;
- unavailable independent validation may permit a clearly labeled exploratory rate result, but not a held-out-validated kinetic claim;
- a revision-required outcome starts a new signed model generation under the bounded replay policy.

Stage 11F1 - barrier-derived and transition-state rate laws

Deliverables:

- ensemble-appropriate activation potentials from THERMO3B or dedicated enhanced sampling;
- prefactor and transmission provenance;
- descriptor-, temperature-, and gate-conditioned barrier-derived rate laws with uncertainty;
- no barrier inferred from a numerical density boundary alone.

Acceptance gate:

- requires THERMO3B and the accepted G0 state model, but not F0;
- every rate term is bound to state, path, thermodynamic, and provenance certificates;
- empirical F0 and barrier-derived F1 rates remain separate until THERMO4B.

Stage 11E-THERMO4B - kinetic-thermodynamic consistency

Deliverables:

- product-scoped `KineticThermodynamicConsistencyCertificate`;
- detailed-balance consistency when F0 and independent equilibrium populations exist;
- barrier-versus-empirical-rate comparison only when both F0 and F1 exist;
- temperature dependence and transmission-factor diagnostics where identifiable.

Acceptance gate:

- requires E9B support for any promoted F0 kinetic claim;
- missing F1 suppresses only the barrier-comparison subproduct;
- disagreement is retained and blocks promotion to a unified model;
- no circular comparison reuses the same fitted quantity as its own validation target.

Stage 11G1 - gate-conditioned rate comparison and final model selection

Deliverables:

- compare ungated, averaged-gate, augmented-state, semi-Markov, and nonstationary models that survived G0/E9B;
- gate-conditioned empirical and optional barrier-derived rates with uncertainty;
- final model-selection certificate for propagation.

Acceptance gate:

- unsupported gating remains absent rather than being imposed by framework semantics;
- the selected model improves held-out prediction and preserves state/provenance identity;
- G1 never retroactively changes the F0/E9B source generation.

Stage 11H - kinetic propagation and first-passage statistics

Deliverables:

- propagators or kinetic Monte Carlo only for an E9B-supported and G1-finalized model;
- mean first-passage times, survival probabilities, fluxes, and uncertainty;
- optional transition-path-theory observables where the model and sampling support them.

Acceptance gate:

- numerical propagation reproduces source-model invariants and held-out observables;
- uncertainty includes state, event, rate, gating, and model-selection components.

Stage 11I - integrated scientific ground gate

Deliverables:

- one source-bound dossier linking structural identities, registered coordinates, sampling certificates, thermodynamics, final events, kinetic adequacy, rates, gating, and propagated observables;
- explicit supported, conditional, unresolved, and rejected claims;
- no complete-site or complete-pathway claim from finite MD sampling.

Acceptance gate:

- every promoted result is traceable to its exact source, policy, partition, and upstream certificate;
- failure of any high-level gate preserves all valid lower-level products.

Validation strategy

Stage C0 algebra and transformation tests

Required synthetic trajectories include uniform translation, integer periodic wrapping, moving box origin, rigid cell rotation, isotropic breathing, anisotropic stretch, shear, combined affine deformation, and residual nonaffine motion.

For every valid frame,

$$G_t = H_t M_t,$$

coordinate round trips must close, and force work must satisfy

$$\mathbf{F}_x \cdot d\mathbf{x} = \mathbf{F}_q \cdot d\mathbf{q}.$$

Consumer regressions cover laboratory/reference MSD, COG/COM drift, translation-only VACF preparation, framework-registered density, and plotting. Additional C0 tests require:

- core affine registration followed by separate registered-structural-view integration;
- composed reference-material plus framework-translation registration;
- explicit-matrix and selected-frame reference-cell provenance;
- rejection of partial-periodic reference-material requests;
- independent geometric-force and PMF-force statuses;
- variable-cell transformed forces remaining PMF-inadmissible despite geometric work invariance;
- translation-fit invariance under changes to the downstream analysis metric;
- segment-continuous translation branch lifting across periodic crossings; and
- fail-closed branch ambiguity at restart or undersampled discontinuities.

Synthetic site landscapes

Controlled cases include isolated harmonic wells, anisotropic wells, double wells, saddles, annular manifolds, unequal populations, periodic-boundary modes, background transition support, and disconnected sampled components. Temporal fixtures include repeated $A \leftrightarrow B$ hopping, one irreversible-looking $A \rightarrow B$ event, short failed excursions, rapid recrossings, a true metastable intermediate, and a nonmetastable transition shoulder.

Tests require kernel-metric covariance, triclinic image-sum normalization, affine covariance of both the density score covector and metric gradient, density-ridge criteria, periodic cell-complex topology, field/topology certificates, attractor lineage, saddle densities, type-specific provisional cores, local periodic charts, local force curvature, temporal persistence, transition-path extraction, and evidence statuses to recover the declared structure without forcing every point into a site. Boundary-crossing wells must have compact lifted covariance, and a weakly corrugated annulus must retain one continuous core rather than only its highest angular sectors. Model selection must use `model_selection` evidence and leave basin-, corridor-, and thermodynamic-validation evidence untouched. Overlapping dynamic regions must produce exclusive conflict statuses and occupancy bounds. One observed jump must never produce a rate or a resolved path ensemble. Compatible paths from independent runs may pool despite distinct member registration signatures. Coarse output cadence must produce bracketed or ambiguous first-hit status rather than a fabricated exact path.

Statistical robustness

Primary uncertainty units are independent trajectories or contiguous time blocks containing the complete many-ion system. Tests include bandwidth ladders, separate the full discovery/model-selection/basin-validation/corridor-validation/thermodynamic-validation partition where sampling permits, leave-one-residence-episode-out checks, nested block resampling when independent validation is unavailable, frame-stride changes, segment-aware quadrature, topology-regime splitting, reference-cell/covariance sensitivity, density-backend field and topology certification, force-subset matching, and HDBSCAN comparison. Per-ion resampling is a secondary hierarchical diagnostic. A single-transition trajectory may return `selection_conditioned_validation` or `independent_validation_unavailable` rather than a false rejection.

Coordinate and structural interpretation

Rigid translation, periodic wrapping, and declared cell deformation corrections must not broaden a registered site artificially. Physical pair-distance analyses must retain real cell breathing. Ring/cage annotations must remain downstream of global statistical discovery.

Atom-resolved ring and coordination tests

Required structural cases include:

- a regular ring and an alternating-radius S6R;
- a puckered and chemically split S6R;
- exact even-ring Nyquist handling in cyclic-index spectra;
- an irregular-angle ring whose alternating sequence is not forced into a pure physical-angle Nyquist component;
- rank, condition, and unresolved checks for actual-angle fits;
- exact unweighted cyclic spectra versus boundary-measure angular moments;
- raw versus normalized amplitudes;
- dihedral shift/reversal transforms and undefined-phase behavior;
- rigid rotation, periodic wrapping, and compatible-frame deformation; and
- registered structural views under rigid and non-rigid affine maps.

Required species-conditioned cases include:

- centered three-short/three-long coordination;
- superposed direct $m = 1$ off-centering and short-wavelength serration;
- elliptic structural deformation without false off-center classification;
- exact geometry forward prediction of M–O distances;
- a residual coordination pattern not explained by geometry alone;
- phase locking to oxygen atoms, O–O gaps, or T–O–T sectors;
- weakly corrugated annuli and discrete angular states;
- multi-ring/cage and ambiguous structural associations;

- symmetry-equivalent state instances with true, broken, and occupancy-conditioned exchangeability;
- occupancy-conditioned center or phase splitting; and
- transition paths through inequivalent ring sectors.

Persistent identities must survive cyclic permutation, orientation reversal, registration, and source replay. A phase-dependent label is rejected when its amplitude or phase is unresolved.

Ensemble, energy, and production-regime validation

Tests cover comment/control conflicts, versioned VASP control semantics, companion-file states, thermostat-disabled NVE, NVT/NpT/driven variants, exact energy-channel mapping, controlled/conserved quantities, correlated block lengths, insufficient block outcomes, dimensionless drift, PELT boundary replay, multiple regimes, selection-conditioned uncertainty, and NVE/NVT/NpT/biased thermodynamic permissions. The Na-LTA continuation fixture must resolve fixed-cell NVE without using SYSTEM.

Sampling-confidence and cross-fitting validation

Tests freeze candidates on discovery blocks and validate them on disjoint complete- system blocks. They cover correlated long residences, multiple ions sharing one frame, one-off passages, forward/reverse events, corridor validation independent of saddle-required assignment, bootstrap feature correspondence, grid/bandwidth survival, holdout novelty, unsaturated accumulation curves, and partial-catalog reporting.

Shared grid-refinement and ownership validation

Tests replay the present atomic-density oracle and the extracted common layer over orthogonal and strongly triclinic cells, fixed and interval-derived grids, dense and local-sparse backends, periodic spread edge cases, reciprocal-resolution thresholds, CIC/stencil broadening, budgeted finest-shape search, serialization, and graph-facing compatibility errors. Stage 11 tests hold kernel covariance fixed while refining the grid, cover basin convergence with unresolved corridor topology, split/merge correspondence, budget-limited ladders, identical-field reuse, and discovery/model-selection versus held-out partition isolation. Existing atomic/framework plotting outputs must remain unchanged.

Thermodynamic validation

Tests require every thermodynamic product to retain ThermodynamicResultProvenance, cover source-qualified estimates with unavailable verification, compatible and incompatible PMF density/force cross-checks, disagreement retention, and prohibition of silent source or energy-channel mixing. Tests also cover tagged-ion versus pooled versus joint-state definitions, multiplicity, NVT Helmholtz, NpT Gibbs/enthalpy, NVE entropy and conditional canonical approximation, bias/reweighting separation, complete-system energy resampling, effective-Hamiltonian rank and held-out prediction, finite transition-region measures, noncircular checks, reduced-potential-matrix requirements, MBAR overlap failure, and rate-model deferral.

Kinetic cross-fitting and zero-event rate validation

Tests freeze complete residence/event episodes before constructing KineticCrossfitPartition, keep model-selection, fit, and validation episodes disjoint, apply signed censoring at split boundaries, and reject in-sample E9B promotion. Synthetic fixtures include observed edges, declared zero-event RateCandidateEdge records with positive exposure, multiplicity-aware candidate universes, and multiple-testing policy. Model-generation replay tests require parent/child signatures, bounded termination, and no in-generation cycle.

Real trajectory audit

The Na-LTA pilot reports accepted-frame fractions for every evidence mask, registration diagnostics, topology and ring mapping, stationarity, attractor lineage, basin/core probabilities, dwell support, force provenance, density-force consistency, declared PMF temperature where admissible, moving-boundary diagnostics, first-hit resolution, symmetry-orbit evidence, orthogonal site-evidence statuses, unresolved fractions, and computational cost. No universal LTA site model is released from synthetic fixtures alone.

Deferred boundaries

The first data-driven implementation does not claim:

- arbitrary structure-fitted global rotation for periodic KDE;
- exact rotating/deforming-frame VACF or current;

- exact generalized forces for dynamic ring coordinates;
- reference-material registration for partial-periodic systems;
- general-manifold local charts or cores without a certified intrinsic model;
- a minimum-image Gaussian substituted for the periodized kernel without a bound;
- scientific grid convergence inferred from plotting’s bandwidth-to-grid coupling;
- scientific promotion of the finest affordable grid when convergence was not reached;
- basin convergence treated as proof of transition-corridor convergence;
- grid convergence substituted for independent sampling-confidence certification;
- topology inferred from rendering meshes or uncertified sparse omissions;
- default symmetry augmentation or orbit pooling without exchangeability evidence;
- a universal site model transferable across species or temperatures;
- exact many-ion free energies at finite loading;
- automatic discovery of unsampled basins;
- a complete site or saddle catalog from any finite MD trajectory;
- ensemble inference from SYSTEM, filenames, directory labels, or user comments;
- canonical PMF interpretation of NVE data without an explicit approximation policy;
- equilibrium certification from thermostat settings alone;
- independent sample support inferred from raw frame count alone;
- a validated saddle from one crossing or from density adjacency alone;
- unique atomic site energies from framewise total energies;
- Boltzmann self-validation using the same occupancy data used to infer free energy;
- rejection of a source-qualified thermodynamic estimate solely because an independent cross-check is unavailable;
- thermodynamic results without exact estimator/source/channel/ensemble/partition provenance;
- unbiased PMFs from biased trajectories without reweighting;
- variable-cell force PMFs before the coordinate measure is specified;
- automatic treatment of thermostat or stochastic force contributions;
- exact cooperative multi-ion transition states;
- forced crystallographic O(1)/O(2)/O(3) labels without a validated profile;
- replacement of exact ring geometry by a circle, ellipse, or truncated harmonic model;
- a representative transition pathway from one observed jump;
- a minimum-free-energy path without supported PMF coverage;
- promoted Markovian kinetics before E9A pre-rate diagnostics, G0 state-model selection, and E9B post-fit validation pass;
- automatic rate-law selection; or
- barriers outside sampled or independently computed regions.

Conditional landscapes

$$A_M(\mathbf{q} \mid \eta, \xi_R)$$

for local occupancy η and framework descriptors ξ_R remain a later extension after the one-body marginal architecture is validated.

Borrowed theories and original constructions

Borrowed or adapted foundations

The following methods are borrowed or adapted and must be cited in specifications and source comments when implemented:

- natural tilings and zeolite natural-tile semantics [S11-13, S11-14];
- least-squares planes and orthogonal Procrustes alignment [S11-15, S11-17];
- kernel density estimation and mode estimation [S11-18, S11-19];
- mean-shift density-gradient mode seeking [S11-20];
- nonparametric density-ridge definitions [S11-34];
- discrete Morse theory on cell complexes as a basis for critical-cell bookkeeping [S11-35];
- hierarchical density clustering as an independent validator [S11-21];

- conditional mean force and average-force free-energy reconstruction [S11-22];
- force matching as a conditional mean-force estimator [S11-23];
- variational PMF reconstruction and Gaussian-process reconstruction from umbrella or gradient/force evidence [S11-24, S11-25, S11-31];
- Helmholtz-Hodge decomposition and Poisson integration [S11-26, S11-27];
- force-assisted reduced-variance density estimation [S11-28];
- metastable/core-set and Markov-state validation [S11-29, S11-30, S11-10];
- VASP source-control and ensemble semantics [S11-38–S11-42];
- correlated-data blocking, moving-block bootstrap, and effective-sample analysis [S11-36, S11-37, S11-46];
- persisted change-point detection for production-regime candidates [S11-47];
- explicit canonical/microcanonical ensemble-equivalence conditions [S11-48];
- exact low-count Poisson confidence intervals when a RateBoundModel is accepted [S11-49];
- WHAM and MBAR multistate free-energy estimation [S11-43, S11-44];
- restricted-ensemble/free-energy relations and thermodynamic derivatives [S11-45];
- transition-path ensemble and reactive-network concepts [S11-8]; and
- experimental LTA oxygen-class, centered S6R coordination, split-site, and off-center structural evidence [S11-32, S11-33].

Later kinetic work retains the existing citations for Eyring, Vineyard, Kramers, Gillespie, TPT, milestoning, NEB, and umbrella sampling [S11-1–S11-12].

Current mdstats architectural constructions

The following are project-specific design choices:

- the immutable source collection is separated from analysis-specific spatial registration;
- no universal drift-, rotation-, or strain-corrected trajectory is created;
- positions, cells, displacements, forces, and velocities follow distinct transform contracts;
- natural tiling and ring geometry interpret learned sites but do not create them;
- exact ordered chemical ring boundaries remain authoritative over circle, ellipse, or harmonic summaries;
- cyclic-index and rank-safe physical-angle spectra provide complementary structural and coordination descriptors;
- exact local displacement and ordered distances remain authoritative, while off-center residual harmonics remain diagnostic;
- position, force, temporal, stationarity, geometry, and curvature statuses remain orthogonal immutable results;
- manual site profiles are an optional branch rather than the default discovery path;
- statistical kernel covariance, analysis grid, and rendering resolution are distinct;
- field accuracy and topology stability are independently certified;
- one shared frame-registration signature and nested evidence catalog bind all discovery channels;
- raw and conservative force fields are retained together;
- curl, circulation, and periodic harmonic components are explicit diagnostics;
- nonparametric basins remain canonical even when compact models are fitted;
- site classes are conclusions from learned landscapes;
- source controls, not user labels, own ensemble inference;
- thermalization, stationarity, conservation, and PMF admissibility are separate certificates;
- numerical field support, basin support, event support, and catalog scope are distinct claims;
- every finite-trajectory catalog is partial and condition-scoped;
- occupancy free energy, conditional potential energy, entropy, and barrier free energy are separate quantities;
- population-derived thermodynamics require independent, noncircular validation;
- raw frame labels, segmented residences, and full transition paths are separate products;
- one observed connection, a resolved path ensemble, and an identifiable rate are separate claims;
- statistical-state instances, optional symmetry orbits, structural site complexes, and semantic classes are distinct identities;
- moving-boundary and first-hit resolution diagnostics remain explicit; and
- structural and observed transition networks remain distinct.

References

[S11-1] Eyring, H. (1935). *The Activated Complex in Chemical Reactions*. Journal of Chemical Physics, 3, 107-115. DOI: 10.1063/1.1749604.

- [S11-2] Vineyard, G. H. (1957). *Frequency Factors and Isotope Effects in Solid State Rate Processes*. Journal of Physics and Chemistry of Solids, 3, 121-127. DOI: 10.1016/0022-3697(57)90059-8.
- [S11-3] Kramers, H. A. (1940). *Brownian Motion in a Field of Force and the Diffusion Model of Chemical Reactions*. Physica, 7, 284-304. DOI: 10.1016/S0031-8914(40)90098-2.
- [S11-4] Haenggi, P., Talkner, P., and Borkovec, M. (1990). *Reaction-Rate Theory: Fifty Years after Kramers*. Reviews of Modern Physics, 62, 251-341. DOI: 10.1103/RevModPhys.62.251.
- [S11-5] Zwanzig, R. (1992). *Dynamical Disorder: Passage through a Fluctuating Bottleneck*. Journal of Chemical Physics, 97, 3587-3589. DOI: 10.1063/1.462993.
- [S11-6] Gillespie, D. T. (1977). *Exact Stochastic Simulation of Coupled Chemical Reactions*. Journal of Physical Chemistry, 81, 2340-2361. DOI: 10.1021/j100540a008.
- [S11-7] Fichthorn, K. A., and Weinberg, W. H. (1991). *Theoretical Foundations of Dynamical Monte Carlo Simulations*. Journal of Chemical Physics, 95, 1090-1096. DOI: 10.1063/1.461138.
- [S11-8] Metzner, P., Schuette, C., and Vanden-Eijnden, E. (2009). *Transition Path Theory for Markov Jump Processes*. Multiscale Modeling and Simulation, 7, 1192-1219. DOI: 10.1137/070699500.
- [S11-9] Faradjian, A. K., and Elber, R. (2004). *Computing Time Scales from Reaction Coordinates by Milestoning*. Journal of Chemical Physics, 120, 10880-10889. DOI: 10.1063/1.1738640.
- [S11-10] Prinz, J.-H., Wu, H., Sarich, M., Keller, B., Senne, M., Held, M., Chodera, J. D., Schuette, C., and Noe, F. (2011). *Markov Models of Molecular Kinetics: Generation and Validation*. Journal of Chemical Physics, 134, 174105. DOI: 10.1063/1.3565032.
- [S11-11] Henkelman, G., Uberuaga, B. P., and Jonsson, H. (2000). *A Climbing Image Nudged Elastic Band Method for Finding Saddle Points and Minimum Energy Paths*. Journal of Chemical Physics, 113, 9901-9904. DOI: 10.1063/1.1329672.
- [S11-12] Torrie, G. M., and Valleau, J. P. (1977). *Nonphysical Sampling Distributions in Monte Carlo Free-Energy Estimation: Umbrella Sampling*. Journal of Computational Physics, 23, 187-199. DOI: 10.1016/0021-9991(77)90121-8.
- [S11-13] Blatov, V. A., Delgado-Friedrichs, O., O’Keeffe, M., and Proserpio, D. M. (2007). *Three-Periodic Nets and Tilings: Natural Tilings for Nets*. Acta Crystallographica Section A, 63, 418-425. DOI: 10.1107/S0108767307038287.
- [S11-14] Anurova, N. A., Blatov, V. A., Ilyushin, G. D., and Proserpio, D. M. (2010). *Natural Tilings for Zeolite-Type Frameworks*. Journal of Physical Chemistry C, 114, 10160-10170. DOI: 10.1021/jp1030027.
- [S11-15] Pearson, K. (1901). *On Lines and Planes of Closest Fit to Systems of Points in Space*. Philosophical Magazine, Series 6, 2(11), 559-572. DOI: 10.1080/14786440109462720.
- [S11-16] O’Rourke, J. (1998). *Computational Geometry in C*, 2nd edition. Cambridge University Press.
- [S11-17] Schoenemann, P. H. (1966). *A Generalized Solution of the Orthogonal Procrustes Problem*. Psychometrika, 31, 1-10. DOI: 10.1007/BF02289451.
- [S11-18] Rosenblatt, M. (1956). *Remarks on Some Nonparametric Estimates of a Density Function*. Annals of Mathematical Statistics, 27, 832-837. DOI: 10.1214/aoms/1177728190.
- [S11-19] Parzen, E. (1962). *On Estimation of a Probability Density Function and Mode*. Annals of Mathematical Statistics, 33, 1065-1076. DOI: 10.1214/aoms/1177704472.
- [S11-20] Fukunaga, K., and Hostetler, L. D. (1975). *The Estimation of the Gradient of a Density Function, with Applications in Pattern Recognition*. IEEE Transactions on Information Theory, 21, 32-40. DOI: 10.1109/TIT.1975.1055330.
- [S11-21] Campello, R. J. G. B., Moulavi, D., and Sander, J. (2013). *Density-Based Clustering Based on Hierarchical Density Estimates*. In PAKDD 2013, Lecture Notes in Computer Science 7819, 160-172. DOI: 10.1007/978-3-642-37456-2_14.
- [S11-22] Darve, E., and Pohorille, A. (2001). *Calculating Free Energies Using Average Force*. Journal of Chemical Physics, 115, 9169-9183. DOI: 10.1063/1.1410978.

- [S11-23] Noid, W. G., Chu, J.-W., Ayton, G. S., Krishna, V., Izvekov, S., Voth, G. A., Das, A., and Andersen, H. C. (2008). *The Multiscale Coarse-Graining Method. I. A Rigorous Bridge between Atomistic and Coarse-Grained Models*. Journal of Chemical Physics, 128, 244114. DOI: 10.1063/1.2938860.
- [S11-24] Maragliano, L., and Vanden-Eijnden, E. (2008). *Single-Sweep Methods for Free Energy Calculations*. Journal of Chemical Physics, 128, 184110. DOI: 10.1063/1.2907241.
- [S11-25] Stecher, T., Bernstein, N., and Csanyi, G. (2014). *Free Energy Surface Reconstruction from Umbrella Samples Using Gaussian Process Regression*. Journal of Chemical Theory and Computation, 10, 4079-4097. DOI: 10.1021/ct500438v.
- [S11-26] Bhatia, H., Norgard, G., Pascucci, V., and Bremer, P.-T. (2013). *The Helmholtz-Hodge Decomposition - A Survey*. IEEE Transactions on Visualization and Computer Graphics, 19, 1386-1404. DOI: 10.1109/TVCG.2012.316.
- [S11-27] Henin, J. (2021). *Fast and Accurate Multidimensional Free Energy Integration*. Journal of Chemical Theory and Computation, 17, 6789-6798. DOI: 10.1021/acs.jctc.1c00593.
- [S11-28] Rotenberg, B. (2020). *Use the Force! Reduced Variance Estimators for Densities, Radial Distribution Functions, and Local Mobilities in Molecular Simulations*. Journal of Chemical Physics, 153, 150902. DOI: 10.1063/5.0029113.
- [S11-29] Sarich, M., Noe, F., and Schuette, C. (2010). *On the Approximation Quality of Markov State Models*. Multiscale Modeling and Simulation, 8, 1154-1177. DOI: 10.1137/090764049.
- [S11-30] Guarnera, E., and Vanden-Eijnden, E. (2016). *Optimized Markov State Models for Metastable Systems*. Journal of Chemical Physics, 145, 024102. DOI: 10.1063/1.4954769.
- [S11-31] Stecher, T., and Bernstein, N. (2016). *Exploration, Sampling, and Reconstruction of Free Energy Surfaces with Gaussian Process Regression*. Journal of Chemical Theory and Computation, 12, 4796-4807. DOI: 10.1021/acs.jctc.6b00553.
- [S11-32] Carey, T., Tang, C. C., Hriljac, J. A., and Anderson, P. A. (2014). *Chemical Control of Thermal Expansion in Cation-Exchanged Zeolite A*. Chemistry of Materials, 26, 1561-1566. DOI: 10.1021/cm403312q.
- [S11-33] Pluth, J. J., and Smith, J. V. (1979). *Crystal Structure of Dehydrated Potassium-Exchanged Zeolite A. Absence of Supposed Zero-Coordinated Potassium. Refinement of Si,Al-Ordered Superstructure*. Journal of Physical Chemistry, 83, 741-749.
- [S11-34] Genovese, C. R., Perone-Pacifico, M., Verdinelli, I., and Wasserman, L. (2014). *Nonparametric Ridge Estimation*. Annals of Statistics, 42, 1511-1545. DOI: 10.1214/14-AOS1218.
- [S11-35] Forman, R. (1998). *Morse Theory for Cell Complexes*. Advances in Mathematics, 134, 90-145. DOI: 10.1006/aima.1997.1650.
- [S11-36] Flyvbjerg, H., and Petersen, H. G. (1989). *Error Estimates on Averages of Correlated Data*. Journal of Chemical Physics, 91, 461-466. DOI: 10.1063/1.457480.
- [S11-37] Geyer, C. J. (1992). *Practical Markov Chain Monte Carlo*. Statistical Science, 7, 473-483. DOI: 10.1214/ss/1177011137.
- [S11-38] VASP Wiki. *MDALGO*. Official VASP documentation. <https://vasp.at/wiki/MDALGO>.
- [S11-39] VASP Wiki. *Molecular-dynamics calculations*. Official VASP documentation. https://vasp.at/wiki/Molecular-dynamics_calculations.
- [S11-40] VASP Wiki. *NVE ensemble*. Official VASP documentation. https://vasp.at/wiki/NVE_ensemble.
- [S11-41] VASP Wiki. *SMASS*. Official VASP documentation. <https://vasp.at/wiki/SMASS>.
- [S11-42] VASP Wiki. *OSZICAR*. Official VASP documentation. <https://vasp.at/wiki/OSZICAR>.
- [S11-43] Kumar, S., Rosenberg, J. M., Bouzida, D., Swendsen, R. H., and Kollman, P. A. (1992). *The Weighted Histogram Analysis Method for Free-Energy Calculations on Biomolecules. I. The Method*. Journal of Computational Chemistry, 13, 1011-1021. DOI: 10.1002/jcc.540130812.
- [S11-44] Shirts, M. R., and Chodera, J. D. (2008). *Statistically Optimal Analysis of Samples from Multiple Equilibrium States*. Journal of Chemical Physics, 129, 124105. DOI: 10.1063/1.2978177.
- [S11-45] Kirkwood, J. G. (1935). *Statistical Mechanics of Fluid Mixtures*. Journal of Chemical Physics, 3, 300-313. DOI: 10.1063/1.1749657.

- [S11-46] Kunsch, H. R. (1989). *The Jackknife and the Bootstrap for General Stationary Observations*. Annals of Statistics, 17, 1217-1241. DOI: 10.1214/aos/1176347265.
- [S11-47] Killick, R., Fearnhead, P., and Eckley, I. A. (2012). *Optimal Detection of Changepoints with a Linear Computational Cost*. Journal of the American Statistical Association, 107, 1590-1598. DOI: 10.1080/01621459.2012.737745.
- [S11-48] Touchette, H. (2015). *Equivalence and Nonequivalence of Ensembles: Thermodynamic, Macrostate, and Measure Levels*. Journal of Statistical Physics, 159, 987-1016. DOI: 10.1007/s10955-015-1212-2.
- [S11-49] Garwood, F. (1936). *Fiducial Limits for the Poisson Distribution*. Biometrika, 28, 437-442.
- [S11-50] VASP Wiki. *vasprun.xml*. Official VASP output-format documentation. <https://vasp.at/wiki/Vasprun.xml>.
- [S11-51] VASP Wiki. *POTIM*. Official VASP timestep documentation. <https://vasp.at/wiki/POTIM>.
- [S11-52] VASP Wiki. *EDIFF*. Official VASP electronic-convergence documentation. <https://vasp.at/wiki/EDIFF>.
- [S11-53] VASP Wiki. *PREC*. Official VASP precision-control documentation. <https://vasp.at/wiki/PREC>.
- [S11-54] VASP Wiki. *LREAL*. Official VASP real-space projection documentation. <https://vasp.at/wiki/LREAL>.
- [S11-55] VASP Wiki. *CSVR thermostat*. Official VASP kinetic-energy and degree-of-freedom documentation. https://vasp.at/wiki/CSVR_thermostat.