

Deterministic Density Attractors and Supported Periodic Basins

Stage 11E2: modes, ridges, unknown-space-safe basin ownership, bandwidth lineage, and provisional cores

mdstats

2026-07-25

Contents

1 Purpose and stage boundary	2
2 Scientific ownership and borrowed methods	2
3 Inputs and source binding	3
3.1 Required Stage-11E1 estimate	3
3.2 Canonical scalar field	3
3.3 Derivative fields	3
4 Supported periodic cell complex	3
4.1 Complete logical-node complex	3
4.2 Support and background	4
5 Deterministic attractors	4
5.1 Canonical plateau components	4
5.2 Isolated modes	4
5.3 One-dimensional ridges	4
5.4 Flat unresolved components	5
6 Deterministic basin ownership	5
6.1 Steepest-ascent graph	5
6.2 No forced assignment	5
6.3 Transition boundaries	5
7 Numerical density-boundary candidates and adjacency	6
8 Attractor-local periodic charts	6
8.1 Isolated-mode chart	6
8.2 Annular chart	6
9 Provisional cores	6
9.1 Point core from a numerical inter-basin boundary level	6
9.2 Annular normal-depth core	7
9.3 Fallback hierarchy	7
10 Bandwidth lineage	7
10.1 Pairwise correspondence	7
10.2 Survival and split/merge ambiguity	7
11 Scale consensus and selection provenance	7

12 Field error versus topology stability	8
13 Independent comparison adapters	8
13.1 Periodic k-means	8
13.2 Periodic HDBSCAN	8
14 Resource and determinism contract	8
15 Acceptance tests	9
16 References	9

1 Purpose and stage boundary

Stage 11E2 converts one immutable Stage-11E1 periodic species-density estimate, or an ordered covariance ladder of such estimates, into a source-bound catalog of statistical density attractors and support-restricted periodic basins. The canonical implementation is:

```
mdstats.analysis.density.attractors
```

The scientific path is:

```
PeriodicSpeciesDensityEstimate
```

- > complete supported periodic logical-node complex
- > isolated modes, extended ridges, or unresolved flat components
- > deterministic support-restricted steepest-ascent ownership
- > supported transition regions and numerical inter-basin boundary candidates
- > attractor-local periodic charts
- > point-specific or manifold-specific provisional cores

```
PeriodicSpeciesDensityLadder
```

- > adjacent-scale attractor correspondence
- > split/merge lineage
- > topology-stable scale interval or explicit competing hypotheses

This stage does **not** fit conditional mean forces, harmonic stiffness, temporal dwell persistence, final structural labels, transition events, barriers, rates, or kinetic networks. Those remain Stage 11E3 and later responsibilities.

2 Scientific ownership and borrowed methods

The following are established external methods or mathematical background:

- density-gradient and mean-shift mode seeking [1];
- nonparametric density-ridge conditions [2];
- discrete Morse theory on cell complexes as a conceptual basis for critical-cell bookkeeping [3];
- hierarchical density clustering as an independent comparison method [4]; and
- k-means as a deliberately limited partitioning baseline [5].

The following are package-specific constructions and are not claimed as direct implementations of those publications:

- deterministic ordering of periodic logical nodes and plateau components;
- propagation of Stage-11E1 support and unknown-space semantics into topology;
- the canonical support-restricted torus ascent graph;
- the rule that unsupported or omitted sparse blocks cannot create background, candidate adjacency, transition-saddle promotion, or free-energy connections;
- source-bound attractor and basin signatures;
- local annular-chart construction from a certified periodic ridge component;
- the provisional-core fallback hierarchy; and

- the exact bandwidth-lineage and scale-consensus record contracts.

3 Inputs and source binding

3.1 Required Stage-11E1 estimate

`prepare_density_attractor_catalog` consumes one `PeriodicSpeciesDensityEstimate`. Its domain, covariance, analysis metric, logical-grid shape, field-error certificate, support mask, and source catalog signature are immutable inputs.

The topology catalog records:

```
density_estimate_signature
domain_signature
covariance_signature
source_catalog_signature
options_signature
```

A shape-compatible field with a different source or registration identity is a different scientific object.

3.2 Canonical scalar field

Topology is constructed from the Stage-11E1 probability density

$$\hat{p}(\mathbf{q}), \quad \int_{\mathcal{T}^3} \hat{p}(\mathbf{q}) dV = 1,$$

on the complete logical periodic grid. Number density is not used to change attractor identity because it differs only by a constant mean-occupancy factor for one species catalog.

3.3 Derivative fields

Stage 11E2 consumes the separately stored:

- density score covector $d \log \hat{p}$;
- metric-raised gradient vector;
- covariant density Hessian; and
- support mask and Stage-11E1 error certificate.

The Hessian and score are transformed into the orthonormal chart of the declared analysis metric before curvature and ridge tests. The KDE covariance is never silently reused as a topology metric.

4 Supported periodic cell complex

4.1 Complete logical-node complex

For grid shape (N_1, N_2, N_3) , logical nodes are

$$\mathbf{q}_{ijk} = \left(\frac{i}{N_1}, \frac{j}{N_2}, \frac{k}{N_3} \right),$$

with explicit periodic wrap adjacency. Neighbor connectivity is one declared choice among 6, 18, or 26 neighbors. The default ascent complex uses 26-neighbor comparison, while numerically supported density-boundary edges and topological cycle checks use the face-adjacent 6-neighbor graph.

Every logical node has exactly one scientific classification:

`unsupported_unknown`
`supported_basin`
`supported_transition_region`
`supported_background`
`numerically_unresolved`

`unsupported_unknown` is not numerical zero and is not background.

4.2 Support and background

Let S be the Stage-11E1 derivative-support mask. Only nodes in S may participate in attractor, basin, ridge, or numerical boundary-candidate claims.

A supported node may be declared `supported_background` only when

$$\hat{p}(\mathbf{q}) \leq \epsilon_{\text{bg}} \max_{\mathbf{r} \in S} \hat{p}(\mathbf{r}),$$

for the explicit option `background_density_fraction`. An unsupported node may never satisfy this rule by implication.

A block omitted by a block-sparse Stage-11E1 realization remains unknown unless its support mask explicitly certifies the corresponding nodes.

5 Deterministic attractors

5.1 Canonical plateau components

A supported active node is a local-maximum candidate when no declared neighbor has density larger than its value by more than the plateau tolerance. Equal candidates are grouped into periodic connected components. Canonical ordering is by:

1. decreasing component maximum density;
2. attractor-geometry token; and
3. smallest flattened logical-node index.

Tie breaking creates a deterministic identity only inside one already unresolved plateau. It may not turn a stable extended ridge into a point.

5.2 Isolated modes

At representative node $\mathbf{q}_i$, transform the density Hessian to the metric-orthonormal coordinate $\mathbf{y}$. An isolated point mode requires

$$\lambda_1 < -\kappa_p, \quad \lambda_2 < -\kappa_p, \quad \lambda_3 < -\kappa_p,$$

where the eigenvalues are ordered from largest to smallest and κ_p is the explicit minimum point curvature. The first implementation is grid-local: it retains the representative node, plateau support, eigenvalues, and the numerical certificate rather than claiming a continuously optimized critical point.

5.3 One-dimensional ridges

For a one-dimensional ridge in three dimensions, let $V_{\perp} = [\mathbf{v}_2, \mathbf{v}_3]$ span the two normal Hessian eigendirections. A supported node is a ridge candidate when

$$\|V_{\perp}^T \nabla_{\mathbf{y}} \log \hat{p}\| \leq \epsilon_{\perp},$$

$$\lambda_2 < -\kappa_\perp, \quad \lambda_3 < -\kappa_\perp,$$

and

$$\frac{|\lambda_1|}{\max(|\lambda_2|, |\lambda_3|)} \leq r_{\parallel/\perp}.$$

This criterion adapts the nonparametric ridge definition of Genovese et al. [2] to the package’s declared metric and support contract.

Logical sampling may leave one-node gaps along an otherwise certified ridge. The implementation may join derivative-certified candidates through at most two face-adjacent layers of the same supported high-density band. This bounded joining cannot cross unsupported cells or a density value below the declared ridge-density floor.

A production extended attractor requires:

- at least `minimum_ridge_nodes` derivative-certified nodes;
- one connected periodic face-adjacent component after bounded joining; and
- a graph cycle in that component.

This preserves an annular state as one extended attractor rather than selecting an arbitrary maximum sector.

5.4 Flat unresolved components

A local maximum component that fails both the negative-definite point test and the supported ridge test is retained as `flat_unresolved_component`. It is not deleted and is not force-fit in later stages until its intrinsic dimension is resolved.

6 Deterministic basin ownership

6.1 Steepest-ascent graph

Every supported active non-seed node selects the neighboring node with greatest probability density. Exact density ties use the smallest canonical logical-node index. Repeated ascent terminates at an attractor seed or at an explicit `numerically_unresolved` cycle/step-limit failure.

This discrete ascent is the canonical Stage-11E2 basin definition. Mean shift is the theoretical mode-seeking reference [1], but it is not a second authoritative backend in this release.

6.2 No forced assignment

A node receives no basin owner when it is:

- outside Stage-11E1 support;
- below the explicit supported-background threshold;
- part of an unresolved ascent cycle; or
- excluded by numerical-resource failure.

Nearest-center filling and Voronoi completion are prohibited.

6.3 Transition boundaries

A supported owned node adjacent through a face to another supported basin is classified as `supported_transition_region` for the declared number of boundary layers. Its underlying ascent owner remains inspectable, but provisional core construction excludes transition nodes.

7 Numerical density-boundary candidates and adjacency

For two basins B_i and B_j , consider only face-adjacent edges whose two endpoints are supported and owned by different basins. The discrete density-boundary candidate level is

$$p_{ij}^{\text{boundary}} = \max_{(u,v) \in E_{ij}} \min\{\hat{p}(u), \hat{p}(v)\}.$$

The numerical candidate record retains the basin pair, density level, and canonical logical edge. No adjacency is created when the connecting neighborhood contains unsupported space. Disconnected supported components therefore receive no invented relative free-energy offset.

The retained public class name `SupportedSaddle` is a legacy compatibility name. Within Stage 11E2 it means only a numerically supported `density_boundary_candidate`; it is not an observed transition event, a sampling-supported corridor, a validated transition saddle, or an activation free-energy estimate. Later SAMP2/E5/E6b stages own those promotions.

8 Attractor-local periodic charts

8.1 Isolated-mode chart

An isolated mode stores a periodic anchor μ_i and logical support nodes. Local displacements use the declared periodic metric and minimum-image lift around the anchor. The chart validity radius is the maximum retained support node distance.

8.2 Annular chart

A one-dimensional cyclic ridge stores:

- its periodic support node sequence;
- a circular-mean anchor;
- a best-fit local plane from the periodic lifted support;
- an explicit $[0, 2\pi)$ intrinsic parameter; and
- a validity radius.

The intrinsic parameter is a chart coordinate, not a physical sector label. Weak tangential corrugation does not split the state unless a persistent numerical density-boundary candidate and bandwidth lineage support the split; later sampling stages must still validate the transition interpretation.

A general extended component that cannot be given a certified annular chart is retained as `manifold_chart_unresolved`.

9 Provisional cores

9.1 Point core from a numerical inter-basin boundary level

For an isolated mode with maximum p_i^{max} and highest supported neighboring boundary candidate p_i^{boundary} , define

$$\chi_i(\mathbf{q}) = \frac{\log \hat{p}(\mathbf{q}) - \log p_i^{\text{boundary}}}{\log p_i^{\text{max}} - \log p_i^{\text{boundary}}}.$$

For $0 < \tau_c < 1$, the provisional core is

$$C_i = \{\mathbf{q} \in B_i : \chi_i(\mathbf{q}) \geq \tau_c\}.$$

9.2 Annular normal-depth core

For an annular attractor, each basin node is matched to the closest certified ridge node under the analysis metric. Its local ridge density p_i^{ridge} replaces one global maximum:

$$\chi_i^\perp(\mathbf{q}) = \frac{\log \hat{p}(\mathbf{q}) - \log p_i^{\text{boundary}}}{\log p_i^{\text{ridge}}(\pi_i(\mathbf{q})) - \log p_i^{\text{boundary}}}.$$

The authoritative core stores its selected logical nodes and the range of local density thresholds. Tangential density modulation therefore does not create arbitrary core sectors.

9.3 Fallback hierarchy

Each core records exactly one depth source:

```
interbasin_saddle_depth # legacy compatibility field name
supported_boundary_depth
probability_content_core
core_unresolved
```

The order is:

1. numerically supported inter-basin boundary candidate;
2. supported basin boundary against explicit background or unknown space;
3. declared highest-density probability content; or
4. unresolved.

A fallback never invents a neighbor or barrier.

10 Bandwidth lineage

10.1 Pairwise correspondence

Adjacent covariance scales are matched by a deterministic minimum-cost assignment using:

- periodic anchor distance;
- basin Jaccard overlap on a common logical sampling; and
- an explicit attractor-geometry mismatch penalty.

Different grid shapes are compared by periodic nearest-node resampling into the source grid. The correspondence retains matched links, births, deaths, overlap, and periodic distance.

The same generic correspondence function is used for bootstrap replicas, complete-system time blocks, and independent compatible trajectories. The caller must retain the provenance of those replicas; Stage 11E2 does not pretend that they are independent when they are not.

10.2 Survival and split/merge ambiguity

A `DensityAttractorLineage` records a track survival interval over the ordered covariance ladder. An unmatched source or target marks the lineage ambiguous. Attractor grid indices are never persistent identities.

11 Scale consensus and selection provenance

`SelectionValidationProtocol` records disjoint or overlapping discovery, selection, and validation block identities. If independent selection or validation is required, overlap fails closed.

The first operational decision identifies consecutive scales with identical:

- attractor count;
- attractor-geometry multiset; and

- numerical density-boundary adjacency.

A unique interval spanning at least two covariance scales and having complete adjacent-scale correspondence may select its middle catalog. Otherwise the result is `scale_ambiguous` and retains all competing catalog signatures.

Temporal or force evidence is not consumed in Stage 11E2. Later stages may select among the retained hypotheses only under the recorded selection protocol.

12 Field error versus topology stability

A Stage-11E1 `DensityFieldErrorCertificate` and a Stage-11E2 `TopologyStabilityCertificate` are separate records.

A topology certificate compares at least two catalogs and reports:

```
attractor_count_stable
geometry_multiset_stable
saddle_adjacency_stable # legacy field: numerical boundary adjacency only
minimum matched-basin overlap
stable | unstable | unresolved
```

A small pointwise field error does not imply topological stability. The `DensityAttractorRefinementSeries` retains ordered grid shapes, catalog signatures, and the certificate. A single realization is explicitly `unassessed`.

13 Independent comparison adapters

13.1 Periodic k-means

The k-means adapter uses the declared torus metric for assignment and circular means for center updates. Deterministic farthest-point seeding is used. This is only a baseline because K is supplied and every sample is forced into a cluster.

13.2 Periodic HDBSCAN

The HDBSCAN adapter constructs the complete pairwise torus-distance matrix and calls the optional scikit-learn HDBSCAN implementation when available. Because that optional backend does not consume arbitrary represented-time weights, a nonuniform-weight request returns `unsupported_weights` rather than silently dropping the weights.

Neither adapter may overwrite the canonical periodic-cell basin catalog.

14 Resource and determinism contract

`DensityAttractorResourcePolicy` preflights:

```
max_grid_nodes
max_neighbor_edges
max_attractors
max_lineage_pairs
max_serialized_nodes
```

Failure is transactional. The module performs no rendering, marching cubes, Plotly construction, browser admission, or HTML serialization.

All authoritative arrays are immutable. Signatures use deterministic SHA-256 over schema-tagged metadata and array digests. Deserialization recomputes every record signature and rejects tampering.

15 Acceptance tests

The focused Stage-11E2 suite must include:

- one point mode crossing a periodic boundary;
- a numerically supported double well with one density-boundary candidate;
- two wells separated by unsupported space with no invented adjacency;
- an annulus retained as one one-dimensional attractor;
- stable and split/merge bandwidth ladders;
- stable and unstable topology-refinement certificates;
- periodic k-means boundary behavior;
- optional HDBSCAN status and weight rejection;
- provisional core depth-source checks;
- strict serialization replay and tamper rejection;
- transactional resource preflight; and
- public API and no-rendering ownership checks.

16 References

- [1] Fukunaga, K., and Hostetler, L. D. (1975). *The Estimation of the Gradient of a Density Function, with Applications in Pattern Recognition*. IEEE Transactions on Information Theory, 21, 32-40. DOI: [10.1109/TIT.1975.1055330](https://doi.org/10.1109/TIT.1975.1055330).
- [2] Genovese, C. R., Perone-Pacifico, M., Verdinelli, I., and Wasserman, L. (2014). *Nonparametric Ridge Estimation*. Annals of Statistics, 42, 1511-1545. DOI: [10.1214/14-AOS1218](https://doi.org/10.1214/14-AOS1218).
- [3] Forman, R. (1998). *Morse Theory for Cell Complexes*. Advances in Mathematics, 134, 90-145. DOI: [10.1006/aima.1997.1650](https://doi.org/10.1006/aima.1997.1650).
- [4] Campello, R. J. G. B., Moulavi, D., and Sander, J. (2013). *Density-Based Clustering Based on Hierarchical Density Estimates*. In PAKDD 2013, Lecture Notes in Computer Science 7819, 160-172. DOI: [10.1007/978-3-642-37456-2_14](https://doi.org/10.1007/978-3-642-37456-2_14).
- [5] Lloyd, S. P. (1982). *Least Squares Quantization in PCM*. IEEE Transactions on Information Theory, 28, 129-137. DOI: [10.1109/TIT.1982.1056489](https://doi.org/10.1109/TIT.1982.1056489).