

Trajectory Ionic Temperature and Quality Verdict Specification

2026-07-27

Purpose

This planning-parent specification owns the revision-43 contracts. The implemented runtime contract is `../../io/trajectory_quality_spec.md`.

This specification owns the revision-43 contracts for source-derived ionic temperature, deep numerical-MD control extraction, and execution behavior for strictly qualified, degraded-quality, and unqualified trajectories.

Ionic temperature

For every frame with a valid ionic kinetic energy,

$$T_t = \frac{2K_{\text{ion}}(t)}{f_{\text{ion}}k_{\text{B}}}.$$

`IonicTemperatureDefinition` records the exact kinetic channel and active ionic degree-of-freedom count. `IonicTemperatureStatistics` records the represented-time mean, standard deviation, autocorrelation time, effective sample count, confidence interval, block means, and drift. Adjacent frames are not treated as independent.

Numerical control extraction

The VASP adapter reads explicit `<incar>` and effective `<parameters>` values from `vasprun.xml` and preserves their source precedence. At minimum it extracts POTIM, EDIFF, PREC, LREAL, ROPT, NELM, NELMIN, ALGO/IALGO, ENCUT, ISYM, requested and present ionic-step counts, and per-step electronic iteration counts and convergence outcomes. User SYSTEM text has no scientific authority.

Verdicts

The only top-level quality outcomes are:

`strictly_qualified`
`degraded_quality`
`unqualified`

- **strictly_qualified**: all hard integrity and active soft quality checks pass.
- **degraded_quality**: the trajectory is finite and quantitatively usable but has one or more manageable numerical-quality violations. Analysis proceeds, one warning is emitted, and every result retains the verdict and failed checks.
- **unqualified**: catastrophic integrity failure. Production scientific APIs raise `TrajectoryIntegrityError`; diagnostic-only parsing may return the failure record.

The deterministic aggregation rule is hard failure -> unqualified; otherwise any soft failure -> degraded quality; otherwise strictly qualified.

Separation from scientific admissibility

The quality verdict decides whether the trajectory can be analyzed. It does not decide whether a particular thermodynamic estimator is mathematically applicable. Ensemble, stationarity, reweighting, PMF, and kinetic gates remain separate signed certificates.

Acceptance

The real Na-LTA NVE continuation fixture must expose the source controls and complete 1,500-step trace without consulting its misleading **SYSTEM** label. Its measurable NVE energy drift may produce **degraded_quality**; it must not be rejected unless an independent hard integrity check fails.