

mdstats source-coordinate contract specification

Stage C0A1: normalized field semantics, force provenance, and reference-cell definitions

mdstats

2026-07-24

Contents

1	Scope	1
2	Source-field semantics	1
3	Source metadata and backward compatibility	2
4	Force provenance and admissibility	2
4.1	Geometric status	2
4.2	PMF-force status	3
5	Reference-cell definition	3
6	Deterministic persistence	3
7	Validation	3

1 Scope

`mdstats.coordinates.contracts` owns the source meanings that must be known before an analysis-specific spatial registration is constructed. It does not transform positions, velocities, forces, cells, rings, tiles, or cages. Those operations begin in Stage C0A2.

The module makes four distinctions explicit:

1. normalized positions are cell-origin-relative Cartesian coordinates obtained from the stored unwrapped fractional coordinates and the reported row-vector cell;
2. velocities may be native Cartesian values, finite-difference values, absent, or semantically unknown;
3. forces are Cartesian covector components only when the normalized source frame is known; and
4. geometric force transformation and PMF-force admissibility are independent claims.

Unknown semantics fail only the claims that require them. A collection with unknown velocity semantics may still support position density, pair geometry, and other position-only analyses.

2 Source-field semantics

`SourceFieldSemantics` stores:

```
position_frame
velocity_frame
force_frame
box_origin_frame
```

The initial normalized position contract is

`cell_origin_relative_cartesian`

because source Cartesian coordinates are converted through

$$\mathbf{f} = (\mathbf{x} - \mathbf{o})H^{-1}, \quad \mathbf{x}_{\text{normalized}} = \mathbf{f}H,$$

where $\mathbf{o}$ is the source box origin and H is the row-vector cell. The source origin remains separately available in `AtomisticFrameCollection.origins`.

Velocity semantics distinguish native normalized Cartesian values from velocities reconstructed by finite differences. Both are geometrically transformable in a later exact policy only when that policy supplies the required time derivatives. They are not statistically equivalent for high-frequency dynamics.

Force semantics are

`normalized_cartesian_covector`
`unavailable`
`unknown`

The covector label is mandatory because under a row-vector affine position map

$$\mathbf{q} = \mathbf{x}M + \mathbf{b},$$

work invariance requires

$$\mathbf{F}_q = \mathbf{F}_x M^{-\top}.$$

3 Source metadata and backward compatibility

Newly normalized collections record a canonical `metadata["source_field_semantics"]` mapping. Older collections without this mapping are resolved from the normalized collection and its `FrameCollectionProvenance`.

Converting a trajectory subset to an independent ensemble sets the stored velocity-frame status to `unavailable`, matching the existing rule that ensemble outputs discard velocities.

4 Force provenance and admissibility

`ForceSourceProvenance` records three independent source facts:

`physical_force_complete`
`bias_or_constraint_force`
`stochastic_or_thermostat_force`

Each fact is `present`, `absent`, or `unknown`. `Unknown` is not interpreted as `absent`.

`ForceAdmissibilityContract` then reports two independent statuses.

4.1 Geometric status

For the C0A1 source identity map, a complete force field with known Cartesian covector semantics is

`exact_external_affine_covector`

An absent or semantically unknown force is

`generalized_force_unavailable`

The translation-relative and structure-fitted statuses are reserved for later registration policies.

4.2 PMF-force status

A source force is `pmf_force_admissible` only when all of the following are explicitly established:

- the physical force is complete;
- no untracked bias or constraint force is present; and
- no stochastic or thermostat-force contribution contaminates the stored force.

If contamination is present, the result is `pmf_force_inadmissible_untracked_bias_or_constraint`. If any required provenance is unknown, the result is `pmf_force_provenance_unknown`.

Geometric exactness never upgrades PMF admissibility.

5 Reference-cell definition

`ReferenceCellDefinition` supports only the two Stage-C0 initial sources:

`explicit_matrix`
`selected_source_frame`

An explicit matrix is caller supplied. A selected-source-frame definition uses one cell after the periodic lattice gauge has been validated and, where enabled, reconciled.

The initial reference-material scope requires:

- a finite full-rank 3×3 row-vector cell;
- full periodicity on all three axes;
- source/reference handedness agreement; and
- an immutable digest containing the matrix, source kind, selected frame, periodic axes, tolerance, and lattice-gauge signature.

Partial periodicity is rejected only when a reference-material cell is requested. Position-only physical or translation-only analyses may continue to use collections whose own analysis contract supports partial periodicity.

6 Deterministic persistence

The following schemas are authoritative:

`mdstats.source-field-semantics.v1`
`mdstats.force-admissibility.v1`
`mdstats.reference-cell-definition.v1`
`mdstats.source-coordinate-contract.v1`

Digests use canonical JSON with sorted keys, compact separators, finite numeric values, and SHA-256. Arrays are serialized as row-major nested lists.

7 Validation

Focused validation must cover:

- normalized semantic inference;
- explicit metadata replay;
- velocity-only claim rejection without blocking position claims;
- geometric-force availability with PMF provenance unknown;
- clean, biased, and missing force provenance;
- explicit and selected-frame reference cells;
- full-rank/full-periodic enforcement;
- handedness mismatch rejection; and
- deterministic contract signatures.