

# mdstats periodic lattice-gauge specification

Stage C0A1: cell identity, basis continuity, and explicit unimodular reconciliation

mdstats

2026-07-24

## Contents

|          |                                                    |          |
|----------|----------------------------------------------------|----------|
| <b>1</b> | <b>Scope</b>                                       | <b>1</b> |
| <b>2</b> | <b>Row-vector lattice convention</b>               | <b>1</b> |
| <b>3</b> | <b>Validation order</b>                            | <b>2</b> |
| <b>4</b> | <b>Trajectory and ensemble comparison policies</b> | <b>2</b> |
| <b>5</b> | <b>Candidate unimodular reconciliation</b>         | <b>2</b> |
| <b>6</b> | <b>Unresolved changes</b>                          | <b>3</b> |
| <b>7</b> | <b>Persistent records</b>                          | <b>3</b> |
| <b>8</b> | <b>Initial limitations</b>                         | <b>3</b> |
| <b>9</b> | <b>Validation</b>                                  | <b>3</b> |

## 1 Scope

`mdstats.coordinates.periodic_gauge` validates the identity of the reported periodic lattice basis before Stage C0A2 interprets frame-to-frame cell changes as physical affine deformation. It does not construct the affine registration map.

The controlling failure rule is:

a basis relabeling is never silently interpreted as strain

## 2 Row-vector lattice convention

Cells follow the package convention

$$\mathbf{x} = \mathbf{f}H.$$

Two reported cells can describe the same lattice under an integer basis change

$$H' = UH, \quad U \in GL(3, \mathbb{Z}), \quad |\det U| = 1.$$

For each frame, the gauge stores an integer matrix  $Q_t$  such that

$$\tilde{H}_t = Q_t H_t$$

is the gauged cell used by downstream registration. Without reconciliation,  $Q_t = I$  for every accepted frame.

### 3 Validation order

For every source cell, the implementation checks:

1. finite  $3 \times 3$  shape;
2. determinant magnitude above the configured singularity tolerance;
3. condition number below the configured limit;
4. handedness and periodic-axis compatibility; and
5. basis/deformation continuity.

`AtomisticFrameCollection` already stores one immutable three-axis PBC vector, so periodic-axis continuity is guaranteed by normalized collection construction and is recorded in the gauge signature. A future source model with frame-dependent PBC must pass an explicit continuity audit before entering this module.

### 4 Trajectory and ensemble comparison policies

Time-ordered trajectories compare frame  $t$  with the gauged frame  $t - 1$ . Independent ensembles compare every frame with gauged frame zero. The ensemble policy avoids inventing a temporal order.

The direct reported-basis change is

$$r_{\text{direct}} = \frac{\|H_t - \tilde{H}_{\text{cmp}}\|_F}{\max(\|\tilde{H}_{\text{cmp}}\|_F, \epsilon)}.$$

If this value is below the continuity tolerance, the reported basis is retained.

### 5 Candidate unimodular reconciliation

When the direct change is too large, form

$$A_t = \tilde{H}_{\text{cmp}} H_t^{-1}$$

and round it to the nearest integer matrix  $Q_t$ . The candidate is accepted only when:

- $|\det Q_t| = 1$ ;
- the normalized distance from  $A_t$  to  $Q_t$  is below `integer_matrix_tolerance`;
- the gauged cell  $Q_t H_t$  is continuous with the comparison cell; and
- the gauged residual is below the stricter reconciliation residual tolerance.

The integer tolerance is intentionally larger than floating-point roundoff because small physical strain can accompany a discrete basis relabeling. The independent gauged-cell residual prevents an arbitrary affine change from being accepted only because its inverse happens to lie near an integer matrix.

If a valid nontrivial candidate is found while reconciliation is disabled, the module raises `UnsupportedBasisChangeError`. When reconciliation is enabled, the matrix is applied explicitly and retained in provenance.

A determinant-sign change may be reconciled only through a certified orientation-reversing unimodular matrix. Otherwise it raises `CellHandednessError`.

## 6 Unresolved changes

If neither the reported basis nor a certified unimodular gauge provides a continuous cell identity, the module raises `LatticeBasisContinuityError`. The first implementation does not guess whether the discontinuity is a restart, large physical deformation, malformed cell, or unsupported basis operation. Callers must segment the trajectory or provide a later explicit policy.

## 7 Persistent records

`PeriodicLatticeGauge` retains:

```
source digest
frame semantics
periodic axes
common gauged handedness
per-frame comparison frame
reported and gauged cells
integer gauge matrix
reported determinant and condition number
direct and gauged relative changes
integer-candidate residual
frame status
options and immutable signature
```

Per-frame statuses are:

```
reference
continuous_reported_basis
reconciled_unimodular_basis
```

The source digest binds frame IDs, PBC, cells, origins, and frame semantics. A selected-source-frame reference cell must carry the lattice-gauge signature.

## 8 Initial limitations

Stage C0A1 deliberately does not:

- optimize over a broad family of integer matrices;
- reconcile non-unimodular supercell changes;
- infer atom remapping after a supercell transformation;
- accept abrupt unresolved deformation as physical by default;
- segment restarts automatically; or
- construct registered coordinates.

These boundaries keep the first gauge deterministic and fail closed.

## 9 Validation

Focused tests must include:

- smooth physical cell changes;
- exact and strained unimodular shear relabelings;
- orientation-reversing unimodular relabeling;
- default rejection when reconciliation is disabled;
- explicit reconciliation with the expected inverse matrix;
- unresolved noninteger cell jumps;
- handedness changes without lattice equivalence;
- trajectory versus ensemble comparison anchors; and

- deterministic gauge signatures.