

TARGET-DATA2C-RESCUE1 bounded upper-ladder coverage rescue

Release: mdstats 0.20.197a0

Architecture revision: 64

Authority: mdstats.target-data2c.ladder.2026-08.v4

Trigger

Build and score the frozen base target-size ladder first. Activate rescue only when the number of globally hard-coverage-qualified base rungs is below TARGET-DATA2D `min_coverage_qualifiers` (default 3).

Rescue sequence

Let P be the smallest authorized TARGET-DATA2A development-pool size across label domains and A the smallest base target size. For each numerator k in $\{3, 4, 5, 6, 7\}$, compute $\text{floor}((k \cdot P / 8) / A) \cdot A$. Retain unique values strictly greater than the largest base rung and strictly less than P . Sort them with the base ladder and materialize every globally available candidate as an exact prefix of the same TARGET-DATA2C deterministic ordering.

The 7/8 ceiling guarantees at least a 1/8 common development complement for leakage-safe EVAL2. No full-pool rescue rung is legal.

Scientific invariants

- Default TARGET-DATA2B hard coverage remains 0.95; no coverage tolerance is relaxed.
- Extent, required-stratum, mandatory-reservation, exact-FPS, and nested-monotonicity predicates are unchanged.
- Coverage is an admissibility gate only. It does not rank or truncate the materializable rescue candidates before Stage B0.
- Rescue activation, rescue sizes, and the minimum qualifier count are serialized and content-addressed.
- A changed minimum qualifier count invalidates stored TARGET-DATA2C authority.
- Pre-v4 TARGET-DATA2C authority is stale for generated campaigns and rebuilds from frozen upstream records.
- Acceleration is unchanged: source inference/DATA6/evaluation remain e3nn and TRAIN2 remains CuEq under CUEQ-DEFAULT1.

Failure

If fewer than the required qualifiers remain after the bounded rescue, TARGET-DATA2D fails closed and reports rescue state plus largest-rung family mass/threshold, extent failures, failed strata, and unsatisfied mandatory obligations.