

VASP Source Controls and Energy Catalog Specification

2026-08-04

Purpose

This specification owns the first executable Stage 11E-ENS0 boundary. It reconstructs source controls and exact named energy channels from `vasprun.xml` without inferring the ensemble, stationarity, trajectory quality, or PMF admissibility.

The implementation is split between:

<code>mdstats.io.source_controls</code>	source-general immutable records
<code>mdstats.io.vasp_controls</code>	versioned VASP XML adapter
<code>mdstats.io.vasp</code>	normalized trajectory integration

Non-authoritative user labels

SYSTEM, filenames, directory names, and user descriptions are comments. They are retained as `UserLabelDiagnostic` records with

`authority = comment_only`

and are excluded from ensemble or method inference. A string such as `Na-LTA 300K NVT AIMD` must not override MDALGO, SMASS, ISIF, or any later source-control certificate.

Source trajectory bundle identity

`SourceTrajectoryBundleIdentity` binds one primary source to:

- exact primary-file SHA-256 and size;
- source program and version;
- atom order and atom count;
- ionic-step count and frame axis;
- streamed coordinate/cell payload digest;
- companion-control manifest signature.

Absolute filesystem paths do not enter the scientific signature. A later C0 adapter must retain this same bundle signature when it consumes coordinates from the source.

Companion manifest

`SimulationControlBundleManifest` records the primary source and every recognized companion role using only:

`present_and_bound`
`known_absent`
`not_applicable`
`not_provided`
`required_missing`

A companion file is `present_and_bound` only when the caller explicitly supplies it. Merely finding a same-named file in the source directory is insufficient because it may belong to another run. Missing `ICONST`, `REPORT`, `PENALTYPOT`, or metadynamics evidence is therefore `not_provided`, not proof of nonuse.

Exact controls and precedence

VaspRunControls retains every <incar> and <parameters> i or v record with:

- original tag name;
- typed value;
- original text;
- source value type;
- section path;
- duplicate occurrence index;
- authority (explicit_input or effective_parameter).

The precedence contract is:

```
effective_parameters_for_realized_values
explicit_incar_for_input_provenance
```

Unknown and source-version-specific controls are retained rather than coerced into a known category. VaspRunControls implements the source-general SimulationRunControls protocol. ENS1, not ENS0, interprets the controls.

Frame energy catalog

FrameEnergyCatalog preserves every exact name under each ionic calculation/energy block. No generic field replaces these source channels.

The VASP adapter assigns initial semantic roles to well-known names:

Source name	Initial semantic role
e_fr_energy	electronic free energy
e_0_energy	zero-smearing extrapolated electronic energy
e_wo_entrp	electronic energy without entropy
kinetic	ionic kinetic energy
nosepot	Nose thermostat potential energy
nosekinetic	Nose thermostat kinetic energy
lattice kinetic	lattice kinetic energy
total	source-reported total energy

Unknown names remain `source_specific_energy`. Every channel records eV units, source path, frame count, present count, completeness fraction, exact values including missing entries, and a value digest. The catalog does not decide which combination is conserved; STAT0 consumes the named channels after ENS1 resolves the dynamics.

Numerical MD quality controls

NumericalMDQualityControls reconstructs evidence needed by later quality analysis:

POTIM

NSW and present ionic-step count

inferred full-output stride when justified by exact count equality

EDIFF

NELM and NELMIN

ALGO and IALGO
explicit and effective PREC
explicit and effective LREAL
ROPT
ENCUT
ISYM
per-step SCF iteration counts
whether the configured electronic iteration limit was reached
position/cell/force/stress completeness
native-velocity frame count
per-energy-channel completeness
source XML parse completeness and interruption diagnostic
whether a complete unclosed final ionic record was recovered
whether an ambiguous incomplete final ionic tail was discarded

A step count below NELM is recorded only as not reaching the configured limit. ENS0 does not claim electronic convergence from that fact alone.

Public API

```
from mdstats import read_vasp_run_controls

bundle = read_vasp_run_controls(
    "vasprun.xml",
    companion_files={"constraint_definition": "ICONST"},
)
```

The result is `VaspSourceControlBundle`, containing:

```
source_identity
manifest
run_controls
energy_catalog
numerical_quality_controls
```

All records are immutable, canonical-JSON signed, and support strict `to_dict` / `from_dict` round trips. Tampered signatures are rejected.

`read_vasp_frames()` reuses the same parser and attaches the source identity, control record, exact energy catalog, and numerical-quality record to collection metadata. The legacy normalized potential/kinetic/total arrays remain unchanged for compatibility.

Interrupted-stream recovery and fail-closed behavior

A `vasprun.xml` may end while VASP is still writing. ENS0 accepts only parser failures that are both interruption-like and located at the physical end of the file. Completed `<calculation>` records are retained. If the final `<calculation>` lacks only its closing tag, it is retained only when its positions, cell, forces, and energy payload are all complete and finite. An ambiguous partial final calculation is discarded while prior complete records remain usable.

Recovery is explicit evidence, not silent repair. `NumericalMDQualityControls` records `source_parse_complete`, `source_parse_warning`, `recovered_unclosed_ionic_step`, and `discarded_incomplete_ionic_tail`. The trajectory-quality layer reports an interrupted source as a soft-quality warning and separately checks requested-step completion.

ENS0 raises `SourceControlError` for:

- a missing primary XML source;
- malformed XML away from EOF or a non-interruption parser failure;
- an interrupted source lacking control blocks, atom identities, or any complete usable ionic calculation;
- non-finite signed energy/control values;
- inconsistent channel lengths;
- invalid manifest binding;
- invalid immutable record construction.

SourceControlSerializationError is raised for schema or signature mismatches. Missing optional controls, companion files, and energy channels are represented explicitly and do not by themselves reject coordinate parsing or descriptive analysis.

Acceptance tests

The permanent synthetic tests require:

- explicit/effective tag preservation and precedence;
- SYSTEM retained only as comment_only;
- exact named energy channels and partial-channel completeness;
- SCF iteration and quality-control traces;
- explicit-only companion binding;
- deterministic signatures and strict round trips;
- metadata integration through read_vasp_frames;
- trailing root-tag interruption recovery;
- complete unclosed final-calculation recovery;
- ambiguous partial-tail discard;
- hard rejection of mid-file structural corruption and critically ambiguous streams;
- public root exports.

The real Na-LTA source replay must reconstruct, without consulting SYSTEM:

```
program/version = VASP 6.4.2
atom count = 168
ionic steps = 1500
MDALGO = 2
SMASS = -3
ISIF = 2
POTIM = 1 fs
EDIFF = 1e-5 eV
NELM = 100
PREC explicit/effective = Accurate/accura
LREAL explicit/effective = Auto/true
ROPT = four values of -2.5e-4
SCF iterations = 3 through 24
native velocity frames = 0
```

It must expose complete e_fr_energy, e_0_energy, e_wo_entrp, kinetic, nosepot, nosekinetic, lattice kinetic, and total channels for all 1500 steps. Ensemble resolution remains the next ENS1 stage.