

Scientific Density Analysis Facade

Stage 11E0a: canonical imports, compatibility production, and ownership boundary

mdstats

2026-07-25

Contents

Purpose and stage boundary	1
Canonical public functions	1
Atomic density	1
Framework density	2
Ownership metadata	2
Canonical compatibility imports	2
Numerical equivalence	3
Rendering independence	3
Failure behavior	3
Acceptance requirements	4
Deferred density-extraction ownership move	4
Method provenance	4

Purpose and stage boundary

Stage 11E0a creates the canonical analysis entry point:

```
mdstats.analysis.density
```

The stage establishes **scientific ownership** without performing the larger a deferred density-extraction ownership move. The current numerical implementations remain in:

```
mdstats.plotting.atomic_density
mdstats.plotting.framework_density
```

and are recorded as temporary numerical owners. The facade wraps their exact fields in analysis-owned adapters.

The boundary is:

```
analysis request + scientific resource policy
-> current numerical producer
-> exact current field object
-> zero-copy scientific adapter
-> scientific field bundle
```

No renderer participates in this path.

Canonical public functions

Atomic density

```
prepare_atomic_density_fields(
    collection,
    *,
    frame_indices,
    frame_weights,
    display_cell,
    registration_mode,
    framework_drift,
    selections,
```

```

options,
registration_view=None,
resources=None,
planning_metadata_by_field=None,
progress=None,
progress_callback=None,
) -> ScientificDensityFieldBundle

```

selections and options remain the existing AtomicDensitySelection and AtomicDensityOptions compatibility objects. The facade forwards only scientific limits.

Framework density

```

prepare_framework_density_fields(
    *,
    vertex_fractional_by_frame,
    vertex_atom_indices,
    edge_segments_fractional_by_frame,
    edge_atom_indices,
    frame_weights,
    display_cell,
    registration_mode,
    options,
    consumer_registration_signature=None,
    scientific_drift_owner=None,
    resources=None,
    planning_metadata_by_field=None,
    vertex_source_keys=None,
    edge_source_keys=None,
    progress=None,
    progress_callback=None,
) -> ScientificDensityFieldBundle

```

Vertex occupancy and edge arc-length channels retain distinct units and source provenance. The wrapper preserves the current framework container metadata in the bundle without changing either field.

Ownership metadata

Every bundle records:

```

facade_stage = 11E0a
scientific_owner = mdstats.analysis.density
numerical_owner = current compatibility module
rendering_policy_consumed = false
mesh_constructed = false
browser_budget_consumed = false

```

Atomic and framework registration provenance remain on the underlying fields. The facade does not reinterpret the spatial registration.

Canonical compatibility imports

The following current numerical option/field classes are available lazily from `mdstats.analysis.density`:

```

AtomicDensityOptions
AtomicDensitySelection
PeriodicScalarField3D
FrameworkDensityOptions
FrameworkDensityFields
DensityResolutionOptions
DensityKernelOptions
DensityStorageOptions
DensityOptimizationOptions
DensitySourceProvenance

```

DensityStorageSummary
PeriodicWeightedSamples3D

Rendering option classes are intentionally absent. In particular the facade does not export atomic/framework 3-D render options.

Root aliases use explicit scientific names:

prepare_scientific_atomic_density_fields
prepare_scientific_framework_density_fields

This avoids collision with historical plotting-local helpers.

Numerical equivalence

For identical inputs and scientific limits, let F_{legacy} be the field produced by the current module and F_{facade} the unwrapped field in the Stage-11E0a bundle. The acceptance contract is:

$$F_{\text{facade}} \equiv F_{\text{legacy}},$$

including:

- field concrete type;
- dense or sparse storage;
- scalar values;
- logical grid;
- normalization;
- total measure;
- HDR thresholds;
- source provenance; and
- metadata.

The adapter may add ownership metadata only outside the field.

Rendering independence

Scientific preparation must succeed without:

- importing Plotly at call time;
- importing scikit-image at call time;
- extracting a mesh;
- simplifying a mesh;
- evaluating a browser mesh budget; or
- creating HTML.

The facade has no render-option or render-policy argument. A later plotting adapter may consume the returned field protocol.

Failure behavior

The facade fails closed for:

- an invalid collection;
- empty atomic selection sequence;
- a wrong compatibility option/selection type;
- a non-scientific resource policy;
- failures raised by the owning numerical producer;
- a resulting object that does not satisfy the scientific field protocol; or
- invalid bundle construction.

It does not catch and relabel numerical errors whose ownership remains in the current producer.

Acceptance requirements

- Atomic facade fields are exactly equal to the current numerical oracle.
- Framework vertex and edge fields are exactly equal to the current oracle.
- Dense field adapters are zero-copy.
- Scientific resource signatures are retained in bundles.
- Rendering/browser admission is not invoked.
- Optional rendering libraries are not required for field construction.
- Canonical analysis and root exports are present.
- Render option classes are absent from the analysis facade.
- Existing plotting APIs and numerical classes remain regression-compatible.

Deferred density-extraction ownership move

Stage 11E0a does not move:

- field concrete classes;
- weighted-sample contracts;
- kernel contracts or implementation;
- direct/sparse realization;
- normalization and HDR logic;
- scientific planning implementation; or
- source-provenance concrete classes.

Revision 44 decomposes those moves into GR0-GR5. GR0/GR1 extract the common grid, spread, broadening, and budgeted-planning layer; GR2 adapts plotting; GR3/GR4 add fixed-kernel scientific convergence and cross-fitting; GR5 completes the remaining numerical ownership move. Compatibility imports and dense/sparse numerical regression remain mandatory throughout. Stage 11E0b is reserved for the registered raw sample catalog.

Method provenance

No new scientific estimator is introduced. Existing cloud-in-cell, periodized Gaussian, and highest-density-region methods retain their original source citations in the current numerical specifications. The canonical facade, zero-copy result boundary, lazy compatibility imports, and resource ownership split are project-specific constructions.