# An Overview of AFL

*(american fuzzy lop)*

Claire Shin

# Introduction

# What is Fuzzing?

What is Fuzzing?

- Automated software crash-testing
- Done by feeding in fuzz to a program
  - Random, unexpected, or invalid data
- Goal: cause the program to crash, freeze, etc.




*Image Credit: Kealan Parr*

# The (Historical) Problem

**1. Blind Random Mutation**

- Fuzzer takes a valid file, randomly mutates it and feeds it to the program
- Input validation checks/other guardrails in the code make it less effective
- Fast but not very smart

**2. Symbolic Execution**

- Uses mathematics to analyze code, calculating inputs to reach inner logic of program
- Very slow and computationally intensive
- Smart but very expensive (especially on real software)

So… how to solve this?

# The Solution: AFL




*Image Credit: André Bermudes Viana (with edits from me)*

# AFL’s Design Goals

**Speed**

**Reliability**

**Simplicity**

**Chainability**

# The Secret Sauce

# 1. Edge Coverage

- Block vs. Edge
  - A -> B is different from B -> A
- 64KB (shared) memory map tracks every unique edge (edge coverage)
  - Set byte is a hit for a branch in (src, dst) form
- XOR & bit shifting
  - Used to calculate paths quickly
  - ID of A + ID of B = unique path ID



# 2a. The Evolutionary Algorithm

- The non-greedy approach
  - Multiple “interesting” files
- Smart mutations
  - Deterministic bit flips, math, file splicing
- Fitness test (survival of the fittest)
  - Only mutations that trigger new edges or loop behaviors “survive”
- Final corpus: interesting test cases
- Execution is policed via memory and execution time limits




*Image Credit: educba.com*

# AFL-FUZZ, GZIP BINARY

2,000 execs/sec, 1 core, 5 hours



# 2b. The Evolutionary Algorithm

Culling the Corpus:

- Algorithm saves every file that triggers a new path
- Over time:
  - Old file: [A, B]
  - Newer file: [A, B, C, D]
  - Overlap - wastes CPU time
- Solution: Periodically re-evaluate the entire queue to pick “favorites” (fastest/smallest)




*Image Credit: educba.com*

# 3. Mutation Strategies

# 4. Crash Exploration

# 5. Trimming & the Fork Server

- Fork Server: execution speed
  - Clone process (rather than reboot)
  - Bypasses OS overhead
- File Trimming: input speed
  - Trim dead weight from files
  - Smaller files = faster processing

# 6. Scaling & Black-Box Testing

```
                    american fuzzy lop 1.86b (test)

┌─ process timing ─────────────────────────────────────┬─ overall results ─────┐
│        run time : 0 days, 0 hrs, 0 min, 2 sec        │  cycles done : 0      │
│   last new path : none seen yet                      │  total paths : 1      │
│ last uniq crash : 0 days, 0 hrs, 0 min, 2 sec        │ uniq crashes : 1      │
│  last uniq hang : none seen yet                      │   uniq hangs : 0      │
├─ cycle progress ────────────────────┬─ map coverage ─┴───────────────────────┤
│  now processing : 0 (0.00%)         │    map density : 2 (0.00%)             │
│ paths timed out : 0 (0.00%)         │ count coverage : 1.00 bits/tuple       │
├─ stage progress ────────────────────┼─ findings in depth ────────────────────┤
│  now trying : havoc                 │ favored paths : 1 (100.00%)            │
│ stage execs : 1464/5000 (29.28%)    │  new edges on : 1 (100.00%)            │
│ total execs : 1697                  │ total crashes : 39 (1 unique)          │
│  exec speed : 626.5/sec             │   total hangs : 0 (0 unique)           │
├─ fuzzing strategy yields ───────────┴───────────────┬─ path geometry ────────┤
│   bit flips : 0/16, 1/15, 0/13                      │    levels : 1          │
│  byte flips : 0/2, 0/1, 0/0                         │   pending : 1          │
│ arithmetics : 0/112, 0/25, 0/0                      │  pend fav : 1          │
│  known ints : 0/10, 0/28, 0/0                       │ own finds : 0          │
│  dictionary : 0/0, 0/0, 0/0                         │  imported : n/a        │
│       havoc : 0/0, 0/0                              │  variable : 0          │
│        trim : n/a, 0.00%                            ├────────────────────────┘
└─────────────────────────────────────────────────────┘          [cpu: 92%]
```

# Limitations

# Where AFL Struggles

- if (input == “SECRET_KEY”)
  - The odds of AFL randomly mutating a file to spell that string are basically 0
- 64KB map collision
  - Every path is tracked in a memory map -> eventually, overlaps
- Structured file formats (JSON, JS, etc.)
  - Wasted cycles generating syntax errors
- Power scheduling
  - Treats all interesting files “fairly” -> time wasted on regular errors

# Improved Versions (Modern Fuzzers)

AFL++

- Hybrid fuzzing
- Collision-free tracking
- Grammar-aware fuzzing
- Smart power scheduling

# Conclusions

# Actionable Takeaways

1. Go beyond unit tests: integrate fuzzing into CI/CD pipelines
2. Fuzzer -> Target: match the right kind of fuzzer to a target
3. Speed > Perfection: practicality beats elegance (most of the time)