

Solutions

HE Jiayou

July 3, 2022

Contents

| | | |
|----------|---|----------|
| 1 | Codeforce | 2 |
| 1.1 | Global Round 21: D. Permutation Graph | 2 |

Chapter 1

Codeforce

1.1 Global Round 21: D. Permutation Graph

Brief

There is a permutation of n long, and the indices are viewed as vertices on an imaginary graph. Two vertices are said to be bi-connected if and only if the corresponding value of each index are the respective maximum and minimum of their underlying interval on the permutation array. Literally, for $i < j$,

$$\begin{aligned} i \leftrightarrow j &\iff \\ a_i &= \min\{a_i, a_{i+1}, \dots, a_j\}, a_j = \max\{a_i, a_{i+1}, \dots, a_j\} \\ \text{or } a_i &= \max\{a_i, a_{i+1}, \dots, a_j\}, a_j = \min\{a_i, a_{i+1}, \dots, a_j\} \end{aligned}$$

Find the shortest path from 1 to n .

Solution

After working on the last sample, it appears that traveling toward the right as far as possible at each step will work. Backward to the left seems uneconomical since the distance to n increases, adding constraints. This approach can be proved correct, and the implementation is $O(n \log n)$ interval minimum/maximum. Nevertheless, establishing the greedy will lead to a $O(n)$ algorithm.

Let us make it simple, consider shortest between an ordered pair (i, j) .