# Attention

HE Jiayou

July 7, 2022

HE Jiayou July 7, 2022 1 / 29

### Table of Contents


- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- 6 Conclusion



- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- 6 Conclusion



## **RNN**



$$H_t = \phi \left( X_t W_{xh} + H_{t-1} W_{hh} + b_h \right)$$
$$O_t = H_t W_{ha} + b_a$$


$$X_t \in \mathbb{R}^{n \times d}$$
  $H_t \in \mathbb{R}^{n \times h}$   
 $O_t \in \mathbb{R}^{n \times q}$   $b_h \in \mathbb{R}^{1 \times h}$ 

1

HE Jiayou July 7, 2022 4 / 29

<sup>&</sup>lt;sup>1</sup>Aston Zhang et al. "Dive into Deep Learning". In: CoRR abs/2106.11342 (2021). arXiv: 2106.11342. URL: https://arxiv.org/abs/2106.11342.

### GRU Gated Recurrent Unit





HE Jiayou July 7, 2022

### GRU Gated Recurrent Unit

GRU supports gating of the hidden state.

- Reset gates help capture short-term dependencies in sequences.
- Update gates help capture long-term dependencies in sequences.

$$R_t = \sigma \left( X_t W_{xr} + H_{t-1} W_{hr} + b_r \right)$$


$$Z_t = \sigma \left( X_t W_{xz} + H_{t-1} W_{hz} + b_z \right)$$

$$\tilde{H}_t = \tanh \left( X_t W_{xh} + \left( R_t \odot H_{t-1} \right) W_{hh} + b_h \right)$$

$$H_t = Z_t \odot H_{t-1} + \left( 1 - Z_t \right) \odot \tilde{H}_t$$

HE Jiayou July 7, 2022 6/29

## **LSTM**



σ

FC layer with activation function









### **LSTM**

The idea is similar to GRU.

$$I_{t} = \sigma \left( X_{t} W_{xi} + H_{t-1} W_{hi} + b_{i} \right)$$

$$F_{t} = \sigma \left( X_{t} W_{xf} + H_{t-1} W_{hf} + b_{f} \right)$$

$$O_{t} = \sigma \left( X_{t} W_{xo} + H_{t-1} W_{ho} + b_{o} \right)$$

$$\tilde{C}_{t} = \tanh \left( X_{t} W_{xc} + H_{t-1} W_{hc} + b_{c} \right)$$


$$C_{t} = F_{t} \odot C_{t-1} + I_{t} \odot \tilde{C}_{t}$$

$$H_{t} = O_{t} \odot \tanh(C_{t})$$



HE Jiayou July 7, 2022 8 / 29


### Encoder-Decoder



HE Jiayou July 7, 2022

### Encoder-Decoder

- Encoder:  $H_t = f(X_t, H_{t-1})$ ,  $C = g(H_1, \dots, H_t)$
- Decoder: to get  $P(Y_t|Y_1,\ldots,Y_{t-1},C)$ ,  $H_t=g(Y_{t-1},C,H_{t-1})$ .



◆□▶ ◆御▶ ◆差▶ ◆差▶ ○差 ○夕@@

HE Jiayou July 7, 2022 10 / 29

- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- 6 Conclusion



# **Attention Prompt**

A simple regression Problem:  $f \in \{(x_1, y_1), (x_2, y_2), \dots, (x_n, y_n)\}.$ 

Average Pooling:

$$f(x) = \frac{1}{n} \sum_{i=1}^{n} y_i$$

Attention Pooling:

$$f(x) = \sum_{i=1}^{n} \alpha(x, x_i) y_i$$

We call x a query and  $(x_i, y_i)$  a key-value pair.  $\alpha$  is the attention weight, which is the target.<sup>2</sup>

HE Jiayou July 7, 2022 12 / 29

<sup>&</sup>lt;sup>2</sup>Aston Zhang et al. "Dive into Deep Learning". In: CoRR abs/2106.11342 (2021). arXiv: 2106.11342. URL: https://arxiv.org/abs/2106.11342.

# Attention Prompt

• Nonparametric:

$$\alpha(x, x_i) = \frac{K(x - x_i)}{\sum_j K(x - x_j)}$$
$$K(u) = \frac{1}{\sqrt{2\pi}} \exp\left(-\frac{u^2}{2}\right)$$

• parametric: learnable Attention Scoring Function



HE Jiayou July 7, 2022 13/29

- RNN
- 2 Attention Prompt
- 3 Transformer
- 4 VIT
- Medical-Related
- Conclusion



### **Transformer**

- Relys entirely on multi-head self-attention
- Encoder-Decoder architecture
- Positional encoding


3

HE Jiayou July 7, 2022

15 / 29

<sup>&</sup>lt;sup>3</sup>Ashish Vaswani et al. "Attention Is All You Need". In: *CoRR* abs/1706.03762 (2017). arXiv: 1706.03762. URL: http://arxiv.org/abs/1706.03762.

### Architecture



#### Encoder:

N=6 layers Multi-head self-attention + feed forward

#### Decoder:

Masked Multi-head self-attention Multi-head attention

#### Others:

Positional Encoding Layer-normalization

# Scoring Function

#### Scaled Dot-Product Attention

$$Attention(Q, K, V) = \operatorname{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$

$$Q \in \mathbb{R}^{n \times d_k} \quad K \in \mathbb{R}^{m \times d_k} \quad V \in \mathbb{R}^{m \times d_v}$$

HE Jiayou July 7, 2022 17 / 29

### Multi-Head Attention

It is beneficial to linearly project Q, K, V to  $d_k, d_k, d_v$  dimensions h times.

$$Multihead(Q, K, V) = Concat(head_1, ..., head_n) W^O$$
  
where  $head_i = Attention(QW_i^Q, KW_i^K, VW_i^V)$ 



HE Jiavou July 7, 2022 18 / 29

## Self-Attention

Self-attention:

$$\{f(x_i), 1 \leq i \leq n\}$$
  
where  $f \in \{(x_i, x_i)\}$ 

19/29

HE Jiayou July 7, 2022

# Positional Encoding

For  $P \in \mathbb{R}^{n \times d}$ :


$$p_{pos,2i} = \sin\left(\frac{i}{10000^{2i/d}}\right)$$
$$p_{pos,2i+1} = \cos\left(\frac{i}{10000^{2i/d}}\right)$$


n length of sequence; d length of encoding. Give each position-embedding pair a unique value.



HE Jiayou July 7, 2022 20 / 29

# Recap






- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- 6 Conclusion




### VIT

# VIT Vision Transformer

## Split images into fixed-size patches






HE Jiayou July 7, 2022 23 / 29

- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- 6 Conclusion



### Attention UNet




Concat(Attention, upsample)

◆□▶ ◆□▶ ◆臺▶ ◆臺▶ ■ 900

25 / 29

HE Jiayou July 7, 2022

### Attention Unet



Using query g from a coarser scale. Resampler Trilinear interpolation is applied.<sup>5</sup>

HE Jiayou July 7, 2022

26 / 29

<sup>5</sup>Ozan Oktay et al. "Attention U-Net: Learning Where to Look for the Pancreas". In: CoRR abs/1804.03999 (2018). arXiv: 1804.03999. URL: http://arxiv.org/abs/1804.03999.

- RNN
- 2 Attention Prompt
- Transformer
- 4 VIT
- Medical-Related
- **6** Conclusion



### Inductive Bias

Component	Entities	Relations	Rel. inductive bias	Invariance
Fully connected	Units	All-to-all	Weak	-
Convolutional	Grid elements	Local	Locality	Spatial translation
Recurrent	Timesteps	Sequential	Sequentiality	Time translation
Graph network	Nodes	Edges	Arbitrary	Node, edge permutations

Peter W. Battaglia et al. "Relational inductive biases, deep learning, and graph networks". In: *CoRR* abs/1806.01261 (2018). arXiv: 1806.01261. URL: http://arxiv.org/abs/1806.01261

HE Jiayou July 7, 2022 28 / 29

- [1] Peter W. Battaglia et al. "Relational inductive biases, deep learning, and graph networks". In: CoRR abs/1806.01261 (2018). arXiv: 1806.01261. URL: http://arxiv.org/abs/1806.01261.
- [2] Alexey Dosovitskiy et al. "An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale". In: CoRR abs/2010.11929 (2020). arXiv: 2010.11929. URL: https://arxiv.org/abs/2010.11929.
- [3] Ozan Oktay et al. "Attention U-Net: Learning Where to Look for the Pancreas". In: CoRR abs/1804.03999 (2018). arXiv: 1804.03999. URL: http://arxiv.org/abs/1804.03999.
- [4] Ashish Vaswani et al. "Attention Is All You Need". In: CoRR abs/1706.03762 (2017). arXiv: 1706.03762. URL: http://arxiv.org/abs/1706.03762.
- [5] Aston Zhang et al. "Dive into Deep Learning". In: CoRR abs/2106.11342 (2021). arXiv: 2106.11342. URL: https://arxiv.org/abs/2106.11342.

HE Jiayou July 7, 2022 29 / 29