

NR Single Rx Chain Test

- **Platform:** MPSS HI platforms
- **适用平台:** 基于MPSS HI的平台
- **Description:** QTI provides 2 methods to help customers to verify NR single Rx chain sensitivity. One is through EFS config, the other is through QXDM Diag Command. Though it's single chain test, customers are suggested to have all 4 Rx paths connected to callbox by splitter.
 1. Through EFS config
 - Please submit a RFSW case in NR5G area to get EFS file
 - Put EFS file in designated path
 - Reset phone to start test
 2. Through Diag Command
 - Send command after ending a call, it takes effect in next new call
 - RX0 as single chain: send_data 75 122 18 64 0 1 2 3
 - RX1 as single chain: send_data 75 122 18 64 1 0 2 3
 - RX2 as single chain: send_data 75 122 18 64 2 3 0 1
 - RX3 as single chain: send_data 75 122 18 64 3 2 1 0
 - Disable single chain: send_data 75 122 18 64 0 0 0 0

NR Single Rx Chain Test

- **特性描述:** QT高通提供了两种方式来帮助客户进行NR单接收通路灵敏度测试。一种使利用EFS配置, 另一种是通过发Diag命令。

虽然是单接收通路, 客户还是需要通过功分器将4路NR的接收通路和仪器连接。

1. 通过EFS配置

请提一个RFSW case 领域为 NR5G 来获取 EFS 文件

将 EFS 文件放到指定位置

重启手机进行测试

2. 通过 Diag 命令

当NR call结束后发出命令, 下次新call的时候生效

RX0 as single chain: send_data 75 122 18 64 0 1 2 3

RX1 as single chain: send_data 75 122 18 64 1 0 2 3

RX2 as single chain: send_data 75 122 18 64 2 3 0 1

RX3 as single chain: send_data 75 122 18 64 3 2 1 0

Disable single chain: send_data 75 122 18 64 0 0 0 0

NR Single Rx Chain Test

- Customers can observe callbox measurement to get test result. Due to IP policy, if customer need to confirm whether single chain is working, please through RFSW case.
- 客户可以通过仪器测量结果来得观察灵敏度。由于IP政策，如果客户想要确认单接收通道是否正常工作，请通过case来进行确认。

- Case Problem Area

Case Type ?	Bug/Issue
Problem Area 1 ?	RF Software
Problem Area 2 ?	5G SUB-6 RF Software
Problem Area 3 ?	RX