Supplementary Material
How Hard Is the Attack? A Complexity-Theoretic Systematization of Machine Learning Security

Halil İbrahim Kanpak
Koç University

1. Classifying the corpus

This section reports the corpus in two layers. Tables 2 to 4 cross-tabulate features against one another, with works in the cells by citation number. Tables 5 and 6 give one row per work, so that every cell above is traceable to the paper behind it. Every value comes from a fixed vocabulary settled before the pass began.

The cross-tabulations are the layer that carries an argument, because in them an empty cell is a combination nobody has published. The value `none` is an answer and not a missing entry, recording that a work constrains no party at all. Of the 200 works classified so far, 33 state no resource bound on any party, and 0 fall outside the frame in the sense that deleting every resource restriction leaves the main claim unchanged.

This is a partial pass. 200 of the corpus's works are classified. The remainder are not yet placed.

TABLE 1: The corpus by pipeline phase (rows) against access level (columns). Each cell lists every work with that combination, by citation number. An empty cell is a combination no work in the corpus occupies.

phase	**hard label**	**scores**	**black box**	**white box**	**weights**	**gradients**	**channel**	**none**	***unassigned***	Σ
train time	[63]		[106], [147]	[69], [72], [138], [141], [167], [186], [196], [198]		[28]	[193]	[4], [12], [17], [22], [34], [36], [46], [71], [73], [81], [132], [161], [163], [169], [191], [192]		29
test time	[93]		[32], [58], [97], [98], [102], [159], [168], [175]	[6], [13], [49], [50], [55], [66], [67], [99], [144], [145], [174], [177], [178], [182], [185], [188]			[115]	[10], [40], [43], [51], [79], [86], [94], [109], [137], [143], [151], [152], [157], [171], [200]		41
post hoc		[16], [53], [54], [62], [87], [118], [123], [160], [173], [181], [197]	[52], [75], [78], [110], [125], [153], [172], [189]	[25], [59], [60], [96], [101], [127], [131], [135], [146], [158], [164], [183], [187], [194]	[122]	[128]		[64], [91], [150], [154], [180]	[165]	41
n/a		[80]						[1], [2], [3], [5], [7], [8], [9], [11], [14], [15], [18], [19], [20], [21], [23], [24], [26], [27], [29], [30], [31], [33], [35], [37], [38], [39], [41], [42], [44], [45], [47], [48], [56], [57], [61], [65], [68], [70], [74], [76], [77], [82], [83], [84], [85], [88], [89], [90], [92], [95], [100], [103], [104], [105], [107], [108], [111], [112], [113], [114], [116], [117], [119], [120], [121], [124], [126], [129], [130], [133], [134], [136], [139], [140], [142], [148], [149], [155], [156], [162], [166], [170], [176], [179], [184], [190], [195], [199]		89
Σ	2	12	18	38	1	2	2	124	1	200

TABLE 2: The corpus by constrained party (rows) against resource unit (columns). Each cell lists every work with that combination, by citation number. An empty cell is a combination no work in the corpus occupies. A dagger marks works where the resource appears only as a side condition rather than as a parameter the work assesses on purpose.

party	time	circuit size	queries	samples	memory	algo class	parameters	perturbation	corruption	rounds	privacy budget	circuit depth	success p
attacker	[11], [26], [33], [45], [57], [63], [64], [72], [75], [80], [82], [93], [101], [107], [118], [119], [127], [139], [148], [149], [181], [186], [193], [28], [54], [96], [175], [196], [198]†	[1], [23], [38], [48], [100], [102]	[5], [42], [52], [58], [123], [146], [53], [62], [97], [153], [173]†	[122], [165]†	[24], [84], [85], [111]	[21], [61], [90], [125], [190]		[6], [13], [50], [66], [67], [79], [94], [109], [115], [137], [143], [151], [152], [157], [171], [174], [177], [178], [182], [185], [188], [49], [55]†	[138], [141], [147], [161], [169]			[108]	
learner	[15], [19], [20], [31], [34], [36], [37], [40], [44], [47], [70], [73], [77], [81], [120], [124], [136], [142], [166], [179], [199]	[104]	[22]†	[7], [10], [29], [51], [71], [74], [76], [83], [89], [112], [113], [126], [129], [140], [144], [145], [184], [191]	[163]	[2], [3], [8], [17], [43], [56], [68], [92], [95], [105], [132], [176], [192]	[46], [103], [116]						
auditor	[59], [69], [106], [110], [131], [32], [197]†			[154], [200]		[35], [78], [117]							
mechanism	[27], [162]				[88], [134]	[195]†					[4], [164]†		
none													
Σ	59	7	12	22	7	22	3	23	5	0	2	1	0

TABLE 3: The corpus by resource unit (rows) against tightness of the bound (columns). Each cell lists every work with that combination, by citation number. An empty cell is a combination no work in the corpus occupies.

unit	**unstated**	**poly**	**quasi-poly**	**class**	**budget**	**conditional**	**exponent**	**measured**	Σ
time	[127], [197]	[27], [37], [40], [57], [59], [63], [64], [69], [73], [80], [81], [82], [93], [101], [106], [107], [110], [118], [119], [120], [124], [131], [142], [148], [149], [179], [181], [186], [193], [199]	[34]		[162], [198]	[11], [15], [20], [36], [44], [70]	[26], [32], [33], [45], [47], [77], [136], [139], [196]	[19], [28], [31], [54], [72], [75], [96], [166], [175]	59
circuit size		[102]	[1], [48], [100]		[38]	[104]	[23]		7
queries					[22], [52], [97], [146], [153]		[5], [42], [58], [123]	[53], [62], [173]	12
samples				[71], [191]	[10], [51], [144], [145], [200]		[7], [29], [74], [76], [83], [89], [112], [113], [122], [126], [129], [140], [154], [184]	[165]	22
memory					[163]	[88]	[24], [84], [85], [111], [134]		7
algo class				[2], [3], [8], [17], [21], [35], [43], [56], [61], [68], [78], [90], [92], [95], [105], [117], [125], [132], [176], [190], [192], [195]					22
parameters					[46], [103], [116]				3
perturbation					[6], [13], [49], [50], [55], [66], [67], [79], [94], [109], [115], [137], [143], [151], [152], [157], [171], [174], [177], [178], [182], [185], [188]				23
corruption					[138], [141], [147], [169]			[161]	5
rounds									0
privacy budget					[4], [164]				2
circuit depth							[108]		1
success prob									0
flops							[18], [114], [133], [156]		4
none	[9], [12], [14], [16], [25], [30], [39], [41], [60], [65], [86], [87], [91], [98], [99], [121], [128], [130], [135], [150], [155], [158], [159], [160], [167], [168], [170], [172], [180], [183], [187], [189], [194]								33
Σ	35	31	4	24	46	8	38	14	200

TABLE 4: The corpus by attack family (rows) against constrained party (columns). Each cell lists every work with that combination, by citation number. An empty cell is a combination no work in the corpus occupies.

family	**attacker**	**learner**	**auditor**	**mechanism**	**none**	Σ
membership	[54], [101], [122], [173], [186]		[197]		[16], [87], [91], [150], [160], [194]	12
attribute						0
reconstruct	[28], [64], [80], [118], [123], [146]				[25], [60], [135], [189]	10
distribution	[181], [193]					2
extract	[52], [53], [62], [75], [125]				[172]	6
invert						0
forge	[72], [85], [96], [127], [198]				[128], [167], [183]	8
evade	[6], [13], [49], [50], [55], [66], [67], [79], [93], [94], [97], [102], [109], [115], [137], [143], [151], [152], [157], [171], [174], [175], [177], [178], [182], [185], [188]	[10], [40], [43], [51], [81], [144], [145]	[32]		[98], [99]	37
evade audit	[58], [196]		[154]		[159], [180]	5
inject			[200]			1
poison	[138], [141], [147], [169]	[22], [71], [73], [191]				8
backdoor	[153], [161]		[59], [69], [106], [110], [131]		[12], [158], [187]	10
multiple					[130], [155]	2
none	[1], [5], [11], [21], [23], [24], [26], [33], [38], [42], [45], [48], [57], [61], [63], [82], [84], [90], [100], [107], [108], [111], [119], [139], [148], [149], [190]	[2], [3], [7], [8], [15], [17], [18], [19], [20], [29], [31], [34], [36], [37], [44], [46], [47], [56], [68], [70], [74], [76], [77], [83], [89], [92], [95], [103], [104], [105], [112], [113], [114], [116], [120], [124], [126], [129], [132], [133], [136], [140], [142], [156], [163], [166], [176], [179], [184], [192], [199]	[35], [78], [117]	[4], [27], [88], [134], [162], [195]	[9], [14], [30], [39], [41], [65], [121], [168], [170]	96
unassigned	[165]			[164]	[86]	3
Σ	86	62	12	7	33	200

TABLE 5: Per-work reference layer: attack scenario and threat model.

#	Target	Family	Phase	Access	Write	Frame
[91]	train data	membership	post hoc	none	read only	none
[160]	train data	membership	post hoc	scores	read only	none
[87]	train data	membership	post hoc	scores	read only	none
[186]	train data	membership	train time	white box	corpus	compute
[122]	train data	membership	post hoc	weights	read only	statistical
[173]	train data	membership	post hoc	scores	read only	compute
[197]	train data	membership	post hoc	scores	read only	compute
[54]	train data	membership	post hoc	scores	read only	compute
[16]	train data	membership	post hoc	scores	read only	none
[194]	train data	membership	post hoc	white box	read only	none
[150]	train data	membership	post hoc	none	none	none
[101]	train data	membership	post hoc	white box	read only	compute
[60]	train data	reconstruct	post hoc	white box	read only	none
[64]	train data	reconstruct	post hoc	none	read only	compute
[80]	train data	reconstruct	n/a	scores	read only	compute
[135]	train data	reconstruct	post hoc	white box	read only	none
[28]	train data	reconstruct	train time	gradients	read only	compute
[123]	train data	reconstruct	post hoc	scores	read only	compute
[146]	train data	reconstruct	post hoc	white box	read only	compute
[25]	train data	reconstruct	post hoc	white box	read only	none
[189]	train data	reconstruct	post hoc	black box	read only	none
[118]	train data	reconstruct	post hoc	scores	read only	compute
[181]	train data	distribution	post hoc	scores	read only	compute
[193]	train data	distribution	train time	channel	corpus	compute
[52]	parameters	extract	post hoc	black box	read only	compute
[172]	parameters	extract	post hoc	black box	read only	none
[75]	parameters	extract	post hoc	black box	read only	compute
[62]	parameters	extract	post hoc	scores	read only	compute
[125]	parameters	extract	post hoc	black box	read only	compute
[53]	parameters	extract	post hoc	scores	read only	compute
[183]	training run	forge	post hoc	white box	corpus	none
[85]	none	forge	n/a	none	none	compute
[128]	train data	forge	post hoc	gradients	corpus	none
[198]	training run	forge	train time	white box	model	compute
[96]	training run	forge	post hoc	white box	corpus	compute
[72]	training run	forge	train time	white box	model	compute
[127]	training run	forge	post hoc	white box	model	compute
[167]	training run	forge	train time	white box	corpus	none
[182]	outputs	evade	test time	white box	read only	capability
[55]	outputs	evade	test time	white box	read only	capability
[171]	outputs	evade	test time	none	read only	capability
[43]	outputs	evade	test time	none	read only	compute
[40]	outputs	evade	test time	none	none	compute
[109]	outputs	evade	test time	none	read only	capability
[94]	outputs	evade	test time	none	read only	capability
[10]	outputs	evade	test time	none	read only	statistical
[137]	outputs	evade	test time	none	read only	capability
[66]	outputs	evade	test time	white box	read only	capability
[152]	outputs	evade	test time	none	read only	capability
[93]	outputs	evade	test time	hard label	read only	compute
[102]	outputs	evade	test time	black box	read only	compute
[143]	outputs	evade	test time	none	read only	capability
[157]	outputs	evade	test time	none	read only	capability
[151]	outputs	evade	test time	none	read only	capability
[32]	outputs	evade	test time	black box	read only	compute
[99]	outputs	evade	test time	white box	read only	none
[98]	outputs	evade	test time	black box	read only	none
[79]	outputs	evade	test time	none	read only	capability

Table 5, continued

#	Target	Family	Phase	Access	Write	Frame
[67]	outputs	evade	test time	white box	read only	capability
[6]	outputs	evade	test time	white box	read only	capability
[49]	outputs	evade	test time	white box	read only	capability
[51]	outputs	evade	test time	none	read only	statistical
[188]	outputs	evade	test time	white box	read only	capability
[178]	outputs	evade	test time	white box	read only	capability
[174]	outputs	evade	test time	white box	read only	capability
[145]	outputs	evade	test time	white box	read only	statistical
[50]	outputs	evade	test time	white box	read only	capability
[185]	outputs	evade	test time	white box	read only	capability
[115]	outputs	evade	test time	channel	channel	capability
[177]	outputs	evade	test time	white box	read only	capability
[97]	outputs	evade	test time	black box	read only	compute
[175]	outputs	evade	test time	black box	read only	compute
[13]	outputs	evade	test time	white box	read only	capability
[144]	outputs	evade	test time	white box	none	statistical
[81]	none	evade	train time	none	none	compute
[180]	training run	evade audit	post hoc	none	none	none
[154]	training run	evade audit	post hoc	none	responses	statistical
[159]	outputs	evade audit	test time	black box	read only	none
[58]	outputs	evade audit	test time	black box	responses	compute
[196]	training run	evade audit	train time	white box	model	compute
[200]	outputs	inject	test time	none	channel	statistical
[169]	train data	poison	train time	none	corpus	capability
[141]	train data	poison	train time	white box	corpus	capability
[138]	train data	poison	train time	white box	corpus	capability
[147]	train data	poison	train time	black box	corpus	capability
[73]	train data	poison	train time	none	corpus	compute
[71]	train data	poison	train time	none	corpus	compute
[191]	train data	poison	train time	none	corpus	compute
[22]	train data	poison	train time	none	corpus	compute
[59]	parameters	backdoor	post hoc	white box	read only	compute
[158]	parameters	backdoor	post hoc	white box	read only	none
[153]	outputs	backdoor	post hoc	black box	read only	compute
[187]	parameters	backdoor	post hoc	white box	read only	none
[131]	parameters	backdoor	post hoc	white box	model	compute
[110]	parameters	backdoor	post hoc	black box	read only	compute
[106]	parameters	backdoor	train time	black box	model	compute
[12]	train data	backdoor	train time	none	corpus	none
[69]	parameters	backdoor	train time	white box	model	compute
[161]	parameters	backdoor	train time	none	corpus	capability
[130]	none	multiple	n/a	none	none	none
[155]	none	multiple	n/a	none	none	none
[134]	none	none	n/a	none	none	compute
[113]	none	none	n/a	none	none	compute
[9]	none	none	n/a	none	none	none
[45]	none	none	n/a	none	none	compute
[77]	none	none	n/a	none	none	compute
[17]	none	none	train time	none	none	compute
[35]	none	none	n/a	none	none	compute
[38]	none	none	n/a	none	none	compute
[111]	none	none	n/a	none	none	compute
[21]	none	none	n/a	none	none	compute
[44]	none	none	n/a	none	none	compute
[24]	none	none	n/a	none	none	compute
[61]	train data	none	n/a	none	none	compute
[119]	none	none	n/a	none	none	compute
[149]	none	none	n/a	none	none	compute
[114]	none	none	n/a	none	none	compute

Table 5, continued

#	Target	Family	Phase	Access	Write	Frame
[30]	none	none	n/a	none	none	none
[148]	train data	none	n/a	none	none	compute
[156]	none	none	n/a	none	none	compute
[63]	training run	none	train time	hard label	read only	compute
[1]	none	none	n/a	none	none	compute
[166]	none	none	n/a	none	none	compute
[4]	train data	none	train time	none	none	capability
[37]	none	none	n/a	none	none	compute
[70]	none	none	n/a	none	none	compute
[47]	none	none	n/a	none	none	compute
[14]	none	none	n/a	none	none	none
[88]	none	none	n/a	none	none	compute
[162]	train data	none	n/a	none	none	compute
[18]	none	none	n/a	none	none	compute
[29]	none	none	n/a	none	none	compute
[19]	none	none	n/a	none	none	compute
[95]	none	none	n/a	none	none	compute
[90]	none	none	n/a	none	none	compute
[36]	none	none	train time	none	none	compute
[15]	none	none	n/a	none	none	compute
[5]	none	none	n/a	none	none	compute
[26]	none	none	n/a	none	none	compute
[23]	none	none	n/a	none	none	compute
[11]	none	none	n/a	none	none	compute
[168]	outputs	none	test time	black box	corpus	none
[129]	none	none	n/a	none	none	compute
[104]	none	none	n/a	none	none	compute
[105]	none	none	n/a	none	none	compute
[83]	none	none	n/a	none	none	compute
[76]	none	none	n/a	none	none	compute
[142]	none	none	n/a	none	none	compute
[179]	none	none	n/a	none	none	compute
[31]	none	none	n/a	none	none	compute
[121]	none	none	n/a	none	none	none
[124]	none	none	n/a	none	none	compute
[195]	none	none	n/a	none	none	compute
[8]	none	none	n/a	none	none	compute
[78]	outputs	none	post hoc	black box	read only	compute
[39]	none	none	n/a	none	none	none
[92]	none	none	n/a	none	none	compute
[170]	none	none	n/a	none	none	none
[3]	none	none	n/a	none	none	compute
[68]	none	none	n/a	none	none	compute
[120]	none	none	n/a	none	none	compute
[184]	none	none	n/a	none	none	compute
[107]	none	none	n/a	none	none	compute
[56]	none	none	n/a	none	none	compute
[176]	none	none	n/a	none	none	compute
[192]	none	none	train time	none	none	compute
[65]	none	none	n/a	none	none	none
[2]	none	none	n/a	none	none	compute
[42]	none	none	n/a	none	none	compute
[190]	none	none	n/a	none	none	compute
[74]	none	none	n/a	none	none	compute
[103]	none	none	n/a	none	none	compute
[33]	none	none	n/a	none	none	compute
[139]	none	none	n/a	none	none	compute
[48]	none	none	n/a	none	none	compute
[100]	none	none	n/a	none	none	compute

Table 5, continued

#	Target	Family	Phase	Access	Write	Frame
[136]	none	none	n/a	none	none	compute
[34]	none	none	train time	none	none	compute
[57]	none	none	n/a	none	none	compute
[163]	none	none	train time	none	none	compute
[20]	none	none	n/a	none	none	compute
[7]	none	none	n/a	none	none	compute
[89]	none	none	n/a	none	none	compute
[117]	none	none	n/a	none	none	compute
[133]	none	none	n/a	none	none	compute
[27]	none	none	n/a	none	none	compute
[108]	none	none	n/a	none	none	compute
[140]	none	none	n/a	none	none	compute
[112]	none	none	n/a	none	none	compute
[126]	none	none	n/a	none	none	compute
[82]	none	none	n/a	none	none	compute
[84]	none	none	n/a	none	none	compute
[116]	none	none	n/a	none	none	compute
[46]	none	none	train time	none	none	compute
[132]	train data	none	train time	none	none	compute
[199]	none	none	n/a	none	none	compute
[41]	none	none	n/a	none	none	none
[164]	train data	·	post hoc	white box	read only	capability
[86]	outputs	·	test time	none	responses	none
[165]	train data	·	post hoc	·	read only	statistical

TABLE 6: Per-work reference layer: adversary assumptions and claim shape. Same rows and same order as Table 5.

#	Party	Unit	Tightness	Baseline	2nd party	2nd notion	Assessed	Quantifier	Antecedent
[91]	none	none	unstated	stated	none	none	·	empirical	stated
[160]	none	none	unstated	stated	none	none	·	empirical	stated
[87]	none	none	unstated	stated	none	none	·	empirical	stated
[186]	attacker	time	poly	stated	none	none	explicit	conditional	stated
[122]	attacker	samples	exponent	absent	samples	·	explicit	universal	stated
[173]	attacker	queries	measured	stated	none	none	implicit	empirical	stated
[197]	auditor	time	unstated	stated	none	none	implicit	conditional	stated
[54]	attacker	time	measured	stated	none	none	implicit	empirical	stated
[16]	none	none	unstated	absent	none	none	·	empirical	stated
[194]	none	none	unstated	stated	none	none	·	conditional	stated
[150]	none	none	unstated	stated	none	none	·	empirical	stated
[101]	attacker	time	poly	stated	none	queries	explicit	conditional	stated
[60]	none	none	unstated	stated	none	·	·	universal	stated
[64]	attacker	time	poly	stated	time	none	explicit	conditional	stated
[80]	attacker	time	poly	absent	perturbation	queries	explicit	universal	stated
[135]	none	none	unstated	stated	none	·	·	existential	stated
[28]	attacker	time	measured	absent	none	none	implicit	empirical	stated
[123]	attacker	queries	exponent	absent	samples	none	explicit	conditional	stated
[146]	attacker	queries	budget	absent	privacy budget	none	explicit	universal	stated
[25]	none	none	unstated	stated	none	none	·	conditional	stated
[189]	none	none	unstated	n/a	none	none	·	empirical	stated
[118]	attacker	time	poly	stated	none	queries	explicit	conditional	stated
[181]	attacker	time	poly	stated	·	none	explicit	conditional	stated
[193]	attacker	time	poly	stated	time	none	explicit	conditional	stated
[52]	attacker	queries	budget	absent	none	none	explicit	conditional	stated
[172]	none	none	unstated	absent	none	none	·	empirical	stated
[75]	attacker	time	measured	stated	none	none	explicit	empirical	stated
[62]	attacker	queries	measured	absent	none	none	implicit	empirical	stated
[125]	attacker	algo class	class	absent	none	none	explicit	existential	stated
[53]	attacker	queries	measured	absent	none	time	implicit	empirical	stated
[183]	none	none	unstated	n/a	none	none	·	existential	stated
[85]	attacker	memory	exponent	stated	memory	none	explicit	universal	stated
[128]	none	none	unstated	absent	none	none	·	empirical	stated
[198]	attacker	time	budget	n/a	time	none	implicit	conditional	stated
[96]	attacker	time	measured	absent	none	none	implicit	empirical	stated
[72]	attacker	time	measured	absent	none	none	explicit	empirical	stated
[127]	attacker	time	unstated	absent	none	none	explicit	conditional	stated
[167]	none	none	unstated	n/a	none	none	·	empirical	stated
[182]	attacker	perturbation	budget	stated	none	none	explicit	existential	none
[55]	attacker	perturbation	budget	n/a	none	none	implicit	empirical	none
[171]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[43]	learner	algo class	class	n/a	perturbation	·	explicit	existential	stated
[40]	learner	time	poly	stated	perturbation	none	explicit	conditional	stated
[109]	attacker	perturbation	budget	n/a	none	none	explicit	existential	stated
[94]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[10]	learner	samples	budget	n/a	none	·	explicit	universal	stated
[137]	attacker	perturbation	budget	n/a	none	·	explicit	universal	stated
[66]	attacker	perturbation	budget	n/a	none	none	explicit	universal	stated
[152]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[93]	attacker	time	poly	n/a	none	none	explicit	universal	stated
[102]	attacker	circuit size	poly	n/a	none	none	explicit	existential	stated
[143]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[157]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[151]	attacker	perturbation	budget	n/a	none	none	explicit	empirical	stated
[32]	auditor	time	exponent	stated	none	·	implicit	existential	stated
[99]	none	none	unstated	n/a	none	·	·	conditional	stated
[98]	none	none	unstated	n/a	none	none	·	empirical	stated

Table 6, continued

#	Party	Unit	Tightness	Baseline	2nd party	2nd notion	Assessed	Quantifier	Antecedent
[79]	attacker	perturbation	budget	n/a	samples	none	explicit	conditional	stated
[67]	attacker	perturbation	budget	n/a	none	none	explicit	conditional	stated
[6]	attacker	perturbation	budget	stated	none	none	explicit	existential	none
[49]	attacker	perturbation	budget	n/a	none	none	implicit	empirical	none
[51]	learner	samples	budget	n/a	none	none	explicit	universal	stated
[188]	attacker	perturbation	budget	n/a	none	none	explicit	universal	stated
[178]	attacker	perturbation	budget	n/a	none	none	explicit	empirical	stated
[174]	attacker	perturbation	budget	n/a	samples	none	explicit	existential	stated
[145]	learner	samples	budget	n/a	none	none	explicit	universal	stated
[50]	attacker	perturbation	budget	stated	none	time	explicit	empirical	stated
[185]	attacker	perturbation	budget	stated	none	none	explicit	existential	stated
[115]	attacker	perturbation	budget	n/a	samples	none	explicit	conditional	stated
[177]	attacker	perturbation	budget	n/a	samples	none	explicit	conditional	stated
[97]	attacker	queries	budget	stated	none	algo class	implicit	existential	none
[175]	attacker	time	measured	n/a	none	none	implicit	empirical	none
[13]	attacker	perturbation	budget	n/a	samples	none	explicit	universal	stated
[144]	learner	samples	budget	n/a	none	none	explicit	universal	stated
[81]	learner	time	poly	n/a	perturbation	none	explicit	conditional	stated
[180]	none	none	unstated	n/a	none	·	·	conditional	stated
[154]	auditor	samples	exponent	n/a	none	none	explicit	conditional	stated
[159]	none	none	unstated	n/a	none	none	·	existential	stated
[58]	attacker	queries	exponent	stated	none	time	explicit	existential	stated
[196]	attacker	time	exponent	n/a	none	·	implicit	existential	stated
[200]	auditor	samples	budget	n/a	none	none	explicit	conditional	stated
[169]	attacker	corruption	budget	stated	algo class	none	explicit	conditional	stated
[141]	attacker	corruption	budget	n/a	none	none	explicit	conditional	stated
[138]	attacker	corruption	budget	n/a	none	·	explicit	conditional	stated
[147]	attacker	corruption	budget	stated	none	perturbation	explicit	universal	stated
[73]	learner	time	poly	n/a	corruption	·	explicit	existential	stated
[71]	learner	samples	class	n/a	none	algo class	explicit	conditional	stated
[191]	learner	samples	class	n/a	none	algo class	explicit	universal	stated
[22]	learner	queries	budget	n/a	corruption	time	implicit	universal	stated
[59]	auditor	time	poly	stated	corruption	none	explicit	conditional	stated
[158]	none	none	unstated	n/a	none	·	·	existential	none
[153]	attacker	queries	budget	n/a	none	time	implicit	empirical	stated
[187]	none	none	unstated	n/a	none	none	·	existential	none
[131]	auditor	time	poly	stated	perturbation	none	explicit	existential	stated
[110]	auditor	time	poly	absent	corruption	samples	explicit	conditional	stated
[106]	auditor	time	poly	stated	none	none	explicit	existential	stated
[12]	none	none	unstated	n/a	none	none	·	empirical	none
[69]	auditor	time	poly	n/a	none	none	explicit	empirical	stated
[161]	attacker	corruption	measured	stated	none	·	explicit	empirical	stated
[130]	none	none	unstated	n/a	none	none	·	empirical	stated
[155]	none	none	unstated	n/a	none	none	·	empirical	stated
[134]	mechanism	memory	exponent	stated	none	·	explicit	existential	stated
[113]	learner	samples	exponent	stated	none	time	explicit	empirical	stated
[9]	none	none	unstated	n/a	none	none	·	conditional	stated
[45]	attacker	time	exponent	n/a	time	none	explicit	conditional	stated
[77]	learner	time	exponent	n/a	none	none	explicit	conditional	stated
[17]	learner	algo class	class	n/a	none	·	explicit	conditional	stated
[35]	auditor	algo class	class	n/a	none	none	explicit	universal	stated
[38]	attacker	circuit size	budget	n/a	circuit size	algo class	explicit	existential	stated
[111]	attacker	memory	exponent	n/a	memory	queries	explicit	universal	stated
[21]	attacker	algo class	class	n/a	none	algo class	explicit	conditional	stated
[44]	learner	time	conditional	n/a	none	algo class	explicit	conditional	stated
[24]	attacker	memory	exponent	n/a	memory	time	explicit	conditional	stated
[61]	attacker	algo class	class	stated	none	·	explicit	existential	stated
[119]	attacker	time	poly	n/a	none	none	explicit	conditional	stated
[149]	attacker	time	poly	n/a	none	none	explicit	conditional	stated

Table 6, continued

#	Party	Unit	Tightness	Baseline	2nd party	2nd notion	Assessed	Quantifier	Antecedent
[114]	learner	flops	exponent	stated	none	parameters	explicit	empirical	stated
[30]	none	none	unstated	n/a	none	none	·	empirical	stated
[148]	attacker	time	poly	stated	none	none	explicit	existential	stated
[156]	learner	flops	exponent	absent	none	parameters	explicit	conditional	stated
[63]	attacker	time	poly	stated	none	·	explicit	conditional	stated
[1]	attacker	circuit size	quasi-poly	stated	none	none	explicit	conditional	stated
[166]	learner	time	measured	stated	none	parameters	explicit	conditional	stated
[4]	mechanism	privacy budget	budget	n/a	none	none	explicit	empirical	stated
[37]	learner	time	poly	n/a	none	·	explicit	conditional	stated
[70]	learner	time	conditional	stated	none	algo class	explicit	conditional	stated
[47]	learner	time	exponent	stated	none	parameters	explicit	empirical	stated
[14]	none	none	unstated	n/a	none	none	·	empirical	none
[88]	mechanism	memory	conditional	stated	time	none	explicit	conditional	stated
[162]	mechanism	time	budget	stated	none	·	explicit	universal	stated
[18]	learner	flops	exponent	absent	none	parameters	explicit	conditional	stated
[29]	learner	samples	exponent	absent	none	parameters	explicit	conditional	stated
[19]	learner	time	measured	stated	none	none	explicit	conditional	stated
[95]	learner	algo class	class	stated	none	queries	explicit	universal	stated
[90]	attacker	algo class	class	stated	algo class	none	explicit	conditional	stated
[36]	learner	time	conditional	n/a	none	·	explicit	conditional	stated
[15]	learner	time	conditional	n/a	none	none	explicit	conditional	stated
[5]	attacker	queries	exponent	stated	queries	none	explicit	existential	stated
[26]	attacker	time	exponent	stated	time	none	explicit	conditional	stated
[23]	attacker	circuit size	exponent	n/a	none	none	explicit	existential	stated
[11]	attacker	time	conditional	n/a	none	none	explicit	conditional	stated
[168]	none	none	unstated	n/a	none	none	·	empirical	stated
[129]	learner	samples	exponent	stated	none	time	explicit	universal	stated
[104]	learner	circuit size	conditional	n/a	none	none	explicit	universal	stated
[105]	learner	algo class	class	n/a	none	·	explicit	universal	stated
[83]	learner	samples	exponent	n/a	none	algo class	explicit	conditional	stated
[76]	learner	samples	exponent	absent	none	algo class	explicit	conditional	stated
[142]	learner	time	poly	stated	none	·	explicit	conditional	stated
[179]	learner	time	poly	stated	perturbation	·	explicit	conditional	stated
[31]	learner	time	measured	stated	none	samples	explicit	empirical	stated
[121]	none	none	unstated	n/a	none	·	·	universal	stated
[124]	learner	time	poly	n/a	none	algo class	explicit	existential	stated
[195]	mechanism	algo class	class	n/a	none	time	implicit	conditional	stated
[8]	learner	algo class	class	n/a	none	samples	explicit	universal	stated
[78]	auditor	algo class	class	n/a	privacy budget	samples	explicit	existential	stated
[39]	none	none	unstated	n/a	none	none	·	conditional	stated
[92]	learner	algo class	class	n/a	none	none	explicit	universal	stated
[170]	none	none	unstated	n/a	none	none	·	universal	stated
[3]	learner	algo class	class	n/a	none	time	explicit	conditional	stated
[68]	learner	algo class	class	n/a	none	queries	explicit	universal	stated
[120]	learner	time	poly	n/a	none	none	explicit	conditional	stated
[184]	learner	samples	exponent	stated	none	none	explicit	conditional	stated
[107]	attacker	time	poly	n/a	privacy budget	none	explicit	conditional	stated
[56]	learner	algo class	class	n/a	none	none	explicit	universal	stated
[176]	learner	algo class	class	n/a	none	none	explicit	universal	stated
[192]	learner	algo class	class	n/a	none	·	explicit	conditional	stated
[65]	none	none	unstated	n/a	none	none	·	conditional	stated
[2]	learner	algo class	class	n/a	none	samples	explicit	existential	stated
[42]	attacker	queries	exponent	n/a	queries	none	explicit	universal	stated
[190]	attacker	algo class	class	stated	algo class	none	explicit	conditional	stated
[74]	learner	samples	exponent	n/a	none	algo class	explicit	conditional	stated
[103]	learner	parameters	budget	n/a	none	time	explicit	existential	stated
[33]	attacker	time	exponent	n/a	time	none	explicit	conditional	stated
[139]	attacker	time	exponent	n/a	none	none	explicit	conditional	stated
[48]	attacker	circuit size	quasi-poly	stated	none	none	explicit	conditional	stated

Table 6, continued

#	Party	Unit	Tightness	Baseline	2nd party	2nd notion	Assessed	Quantifier	Antecedent
[100]	attacker	circuit size	quasi-poly	stated	none	none	explicit	conditional	stated
[136]	learner	time	exponent	n/a	none	success prob	explicit	conditional	stated
[34]	learner	time	quasi-poly	n/a	none	algo class	explicit	existential	stated
[57]	attacker	time	poly	stated	none	none	explicit	existential	stated
[163]	learner	memory	budget	n/a	none	none	explicit	universal	stated
[20]	learner	time	conditional	n/a	corruption	algo class	explicit	conditional	stated
[7]	learner	samples	exponent	stated	none	algo class	explicit	universal	stated
[89]	learner	samples	exponent	n/a	none	time	explicit	universal	stated
[117]	auditor	algo class	class	n/a	none	·	explicit	conditional	stated
[133]	learner	flops	exponent	absent	none	parameters	explicit	empirical	stated
[27]	mechanism	time	poly	n/a	time	none	explicit	conditional	stated
[108]	attacker	circuit depth	exponent	n/a	none	queries	explicit	existential	stated
[140]	learner	samples	exponent	stated	none	algo class	explicit	universal	stated
[112]	learner	samples	exponent	stated	none	algo class	explicit	universal	stated
[126]	learner	samples	exponent	stated	none	time	explicit	conditional	stated
[82]	attacker	time	poly	n/a	privacy budget	none	explicit	universal	stated
[84]	attacker	memory	exponent	stated	memory	·	explicit	universal	stated
[116]	learner	parameters	budget	stated	none	samples	explicit	universal	stated
[46]	learner	parameters	budget	n/a	none	none	explicit	conditional	stated
[132]	learner	algo class	class	n/a	none	none	explicit	universal	stated
[199]	learner	time	poly	n/a	none	samples	explicit	existential	stated
[41]	none	none	unstated	n/a	none	none	·	empirical	stated
[164]	mechanism	privacy budget	budget	stated	none	none	implicit	universal	stated
[86]	none	none	unstated	n/a	none	none	·	empirical	stated
[165]	attacker	samples	measured	stated	none	none	implicit	empirical	stated

References

[1] D. Abram, A. Beimel, Y. Ishai, E. Kushilevitz, and V. Narayanan, "Cryptography from planted graphs: Security with logarithmic-size messages," in *IACR ePrint/*, 2023.

[2] E. Abbe, E. Boix-Adserà, and T. Misiakiewicz, "The merged-staircase property - a necessary and nearly sufficient condition for sgd learning of sparse functions on two-layer neural networks," arXiv:2202.08658, 2022.

[3] ——, "Sgd learning on neural networks - leap complexity and saddle-to-saddle dynamics," arXiv:2302.11055, 2023.

[4] M. Abadi, A. Chu, I. Goodfellow, H. B. McMahan, I. Mironov, K. Talwar, and L. Zhang, "Deep learning with differential privacy," in *CCS*, 2016.

[5] A. Afshar, G. Couteau, M. Mahmoody, and E. Sadeghi, "Fine-grained non-interactive key-exchange: Constructions and lower bounds," 2023.

[6] A. Athalye, N. Carlini, and D. Wagner, "Obfuscated gradients give a false sense of security — circumventing defenses to adversarial examples," in *ICML*, 2018.

[7] L. Arnaboldi, Y. Dandi, F. Krzakala, L. Pesce, and L. Stephan, "Repetita iuvant - data repetition allows sgd to learn high-dimensional multi-index functions," arXiv:2405.15459, 2024.

[8] G. B. Arous, R. Gheissari, and A. Jagannath, "Online stochastic gradient descent on non-convex losses from high-dimensional inference," arXiv:2003.10409, 2021.

[9] D. Alvarez-Melis, V. Garg, and A. T. Kalai, "Are gans overkill for nlp?" in *NeurIPS*, 2022.

[10] I. Attias and S. Hanneke, "Adversarially robust pac learnability of real-valued functions," arXiv:2206.12977, 2023.

[11] J. Alman, Y. Huang, and K. Yeo, "Fine-grained complexity in a world without cryptography," in *Eurocrypt*, 2025.

[12] G. Abad, M. Krček, S. Koffas, B. Tajalli, M. Arazzi, R. Riaño, X. Xu, Z. Liu, A. Nocera, and S. Picek, "Sok: The last line of defense — on backdoor defense evaluation," arXiv:2511.13143, 2025.

[13] H. Ashtiani, V. Pathak, and R. Urner, "Simplifying adversarially robust pac learning with tolerance," arXiv:2502.07232, 2025.

[14] D. Arp, E. Quiring, F. Pendlebury, A. Warnecke, F. Pierazzi, C. Wressnegger, L. Cavallaro, and K. Rieck, "Dos and don'ts of machine learning in computer security," in *USENIX Security*, 2022.

[15] J. Alman and Z. Song, "The fine-grained complexity of gradient computation for training large language models," arXiv:2402.04497, 2024.

[16] M. Aerni, J. Zhang, and F. Tramèr, "Evaluations of machine learning privacy defenses are misleading," in *ACM CCS*, 2024.

[17] A. S. Bandeira, A. E. Alaoui, S. B. Hopkins, T. Schramm, A. S. Wein, and I. Zadik, "The franz–parisi criterion and computational trade-offs in high dimensional statistics," arXiv:2205.09727, 2022.

[18] B. Bordelon, A. Atanasov, and C. Pehlevan, "A dynamical model of neural scaling laws," in *ICML*, 2024.

[19] ——, "How feature learning can improve neural scaling laws," in *ICLR*, 2025.

[20] M. Brennan and G. Bresler, "Reducibility and statistical-computational gaps from secret leakage," arXiv:2005.08099, 2020.

[21] M. Brennan, G. Bresler, S. B. Hopkins, J. Li, and T. Schramm, "Statistical query algorithms and low-degree tests are almost equivalent," in *COLT*, 2021.

[22] M.-F. Balcan, A. Blum, S. Hanneke, and D. Sharma, "Robustly-reliable learners under poisoning attacks," arXiv:2203.04160, 2022.

[23] C. Brzuska and G. Couteau, "On building fine-grained one-way functions from strong average-case hardness," in *EUROCRYPT*, 2022.

[24] C. Brzuska, G. Couteau, C. Egger, and W. Quach, "On bounded storage key agreement and one-way functions," in *TCC*, 2024.

[25] B. Balle, G. Cherubin, and J. Hayes, "Reconstructing training data with informed adversaries," in *IEEE S&P*, 2022.

[26] B. Bauer, G. Couteau, and E. Sadeghi, "Fine-grained non-interactive key exchange, revisited," 2024.

[27] M. Bun, Y.-H. Chen, and S. Vadhan, "Separating computational and statistical differential privacy in the client-server model," 2016.

[28] M. Balunović, D. I. Dimitrov, N. Jovanović, and M. Vechev, "Lamp: Extracting text from gradients with language model priors," in *NeurIPS*, 2022.

[29] Y. Bahri, E. Dyer, J. Kaplan, J. Lee, and U. Sharma, "Explaining neural scaling laws," arXiv:2102.06701, 2024.

[30] T. Besiroglu, E. Erdil, M. Barnett, and J. You, "Chinchilla scaling: A replication attempt," arXiv:2404.10102, 2024.

[31] B. Barak, B. L. Edelman, S. Goel, S. Kakade, E. Malach, and C. Zhang, "Hidden progress in deep learning - sgd learns parities near the computational limit," arXiv:2207.08799, 2022.

[32] S. Ball, G. Gluch, S. Goldwasser, F. Kreuter, O. Reingold, and G. N. Rothblum, "On the impossibility of separating intelligence from judgment: The computational intractability of filtering for ai alignment," arXiv:2507.07341, 2025.

[33] M. Ball, J. Garay, P. Hall, A. Kiayias, and G. Panagiotakos, "Towards permissionless consensus in the standard model via fine-grained complexity," 2024.

[34] R.-D. Buhai, J.-T. Hsieh, A. Jain, and P. K. Kothari, "The quasi-polynomial low-degree conjecture is false," in *FOCS*, 2025.

[35] B. Barak, S. B. Hopkins, J. Kelner, P. K. Kothari, A. Moitra, and A. Potechin, "A nearly tight sum-of-squares lower bound for the planted clique problem," in *FOCS*, 2016.

[36] A. Backurs, P. Indyk, and L. Schmidt, "On the fine-grained complexity of empirical risk minimization: Kernel methods and neural networks," arXiv:1704.02958, 2017.

[37] G. Bresler and T. Jiang, "Detection-recovery and detection-refutation gaps via reductions from planted clique," in *COLT*, 2023.

[38] A. Bogdanov, C. Jones, A. Rosen, and I. Zadik, "Low-degree security of the planted random subgraph problem," arXiv:2409.16227, 2024.

[39] H. Brown, K. Lee, F. Mireshghallah, R. Shokri, and F. Tramèr, "What does it mean for a language model to preserve privacy?" arXiv:2202.05520, 2022.

[40] S. Bubeck, Y. T. Lee, E. Price, and I. Razenshteyn, "Adversarial examples from cryptographic pseudo-random generators," arXiv:1811.06418, 2018.

[41] K. Balan, R. Learney, and T. Wood, "A framework for cryptographic verifiability of end-to-end ai pipelines," in *IWSPA '25*, 2025.

[42] B. Barak and M. Mahmoody-Ghidary, "Merkle puzzles are optimal — an $o(n^2)$-query attack on any key exchange from a random oracle," in *CRYPTO*, 2009.

[43] S. Bubeck, E. Price, and I. Razenshteyn, "Adversarial examples from computational constraints," arXiv:1805.10204, 2019.

[44] J. Bruna, O. Regev, M. J. Song, and Y. Tang, "Continuous lwe," in *STOC*, 2021.

[45] M. Ball, A. Rosen, M. Sabin, and P. N. Vasudevan, "Average-case fine-grained hardness," 2017.

[46] S. Bubeck and M. Sellke, "A universal law of robustness via isoperimetry," arXiv:2105.12806, 2021.

[47] D. Busbridge, A. Shidani, F. Weers, J. Ramapuram, E. Littwin, and R. Webb, "Distillation scaling laws," in *ICML*, 2025.

[48] B. Barak and A. Wigderson, "Public-key cryptography from different assumptions," in *IACR ePrint/335*, 2008.

[49] N. Carlini, A. Athalye, N. Papernot, W. Brendel, J. Rauber, D. Tsipras, I. Goodfellow, A. Mądry, and A. Kurakin, "On evaluating adversarial robustness," arXiv:1902.06705, 2019.

[50] F. Croce, M. Andriushchenko, V. Sehwag, E. Debenedetti, N. Flammarion, M. Chiang, P. Mittal, and M. Hein, "Robustbench — a standardized adversarial robustness benchmark," in *NeurIPS Datasets and Benchmarks*, 2021.

[51] D. Cullina, A. N. Bhagoji, and P. Mittal, "Pac-learning in the presence of evasion adversaries," arXiv:1806.01471, 2018.

[52] V. Chandrasekaran, K. Chaudhuri, I. Giacomelli, S. Jha, and S. Yan, "Exploring connections between active learning and model extraction," in *USENIX Security*, 2019.

[53] I. A. Canales-Martínez, J. Chávez-Saab, A. Hambitzer, F. Rodríguez-Henríquez, N. Satpute, and A. Shamir, "Polynomial time cryptanalytic extraction of neural network models," in *EUROCRYPT*, 2024.

[54] N. Carlini, S. Chien, M. Nasr, S. Song, A. Terzis, and F. Tramèr, "Membership inference attacks from first principles," in *IEEE S&P*, 2022.

[55] F. Croce, S. Gowal, T. Brunner, E. Shelhamer, M. Hein, and T. Cemgil, "Evaluating the adversarial robustness of adaptive test-time defenses," in *ICML*, 2022.

[56] A. Carpentier, S. M. Giancola, C. Giraud, and N. Verzelen, "Low-degree lower bounds via almost orthonormal bases," arXiv:2509.09353, 2025.

[57] R. Canetti, O. Goldreich, and S. Halevi, "The random oracle methodology, revisited," in *STOC*, 2004.

[58] M. Christ, S. Gunn, and O. Zamir, "Undetectable watermarks for language models," arXiv:2306.09194, 2023.

[59] P. Christiano, J. Hilton, V. Lecomte, and M. Xu, "Backdoor defense, learnability, and obfuscation," arXiv:2409.03077, 2025.

[60] R. Cummings, S. Hod, J. Sarathy, and M. Swanberg, "Attaxonomy: Unpacking differential privacy guarantees against practical adversaries," arXiv:2405.01716, 2024.

[61] K. Chaudhuri, J. Imola, and A. Machanavajjhala, "Capacity bounded differential privacy," arXiv:1907.02159, 2019.

[62] N. Carlini, M. Jagielski, and I. Mironov, "Cryptanalytic extraction of neural network models," in *CRYPTO*, 2020.

[63] R. Canetti and A. Karchmer, "Covert learning — how to learn with an untrusted intermediary," 2021.

[64] E. Cohen, H. Kaplan, Y. Mansour, S. Moran, K. Nissim, U. Stemmer, and E. Tsfadia, "Data reconstruction: When you see it and when you don't," 2024.

[65] S. Chakraborty, J. Qiu, H. Yuan, A. Koppel, D. Manocha, F. Huang, A. S. Bedi, and M. Wang, "Maxmin-rlhf — alignment with diverse human preferences (impossibility of single-reward rlhf)," arXiv:2402.08925, 2024.

[66] J. Cohen, E. Rosenfeld, and J. Z. Kolter, "Certified adversarial robustness via randomized smoothing," in *ICML*, 2019.

[67] Z. Cheng, J. Yang, W. Dai, and J. Sun, "Provable defense framework for llm jailbreaks via noise-augmented alignment (naat + css)," arXiv:2602.01587, 2026.

[68] A. Das, S. Gollapudi, R. Kumar, and R. Panigrahy, "On the learnability of deep random networks," arXiv:1904.03866, 2019.

[69] A. Draguns, A. Gritsevskiy, S. R. Motwani, C. Rogers-Smith, J. Ladish, and C. S. de Witt, "Unelicitable backdoors in language models via cryptographic transformer circuits," arXiv:2406.02619, 2024.

[70] J. Ding, Y. Hua, L. Slot, and D. Steurer, "Low degree conjecture implies sharp computational thresholds in stochastic block model," arXiv:2502.15024, 2025.

[71] I. Diakonikolas, G. Iakovidis, D. M. Kane, and L. Ren, "Algorithms and sq lower bounds for robustly learning real-valued multi-index models," arXiv:2505.21475, 2025.

[72] H. Deng, Y. Jiang, G. Yu, Q. Wang, X. Wang, B. Ma, W. Ni, and R. P. Liu, "Polo: Proof-of-learning and proof-of-ownership at once with chained watermarking," arXiv:2505.12296, 2026.

[73] I. Diakonikolas, G. Kamath, D. M. Kane, J. Li, A. Moitra, and A. Stewart, "Robust estimators in high dimensions without the computational intractability," arXiv:1604.06443, 2016.

[74] L. Defilippis, F. Krzakala, B. Loureiro, and A. Maillard, "A noise sensitivity exponent controls large statistical-to-computational gaps in single- and multi-index models," arXiv:2603.17896, 2026.

[75] A. Dziedzic, M. A. Kaleem, Y. S. Lu, and N. Papernot, "Increasing the cost of model extraction with calibrated proof of work," in *ICLR*, 2022.

[76] A. Damian, J. D. Lee, and J. Bruna, "The generative leap - sharp sample complexity for efficiently learning gaussian multi-index models," arXiv:2506.05500, 2025.

[77] M. Dalirrooyfard, A. Lincoln, B. Saha, and V. V. Williams, "Average-case hardness of parity problems: Orthogonal vectors, k-sum and more," arXiv:2503.21951, 2025.

[78] C. Domingo-Enrich and Y. Mroueh, "Auditing differential privacy in high dimensions with the kernel quantum rényi divergence," arXiv:2205.13941, 2022.

[79] D. I. Diochnos, S. Mahloujifar, and M. Mahmoody, "Lower bounds for adversarially robust pac learning," arXiv:1906.05815, 2019.

[80] I. Dinur and K. Nissim, "Revealing information while preserving privacy," 2003.

[81] A. Degwekar, P. Nakkiran, and V. Vaikuntanathan, "Computational limitations in robust classification and win-win results," in *COLT*, 2019.

[82] D. Desfontaines and B. Pejó, "Sok: Differential privacies," in *PoPETs*, 2020.

[83] A. Damian, L. Pillaud-Vivien, J. D. Lee, and J. Bruna, "Computational-statistical gaps in gaussian single-index models," arXiv:2403.05529, 2024.

[84] Y. Dodis, W. Quach, and D. Wichs, "Speak much, remember little: Cryptography in the bounded storage model, revisited," 2021.

[85] ——, "Authentication in the bounded storage model," 2022.

[86] E. Debenedetti, I. Shumailov, T. Fan, J. Hayes, N. Carlini, D. Fabian, C. Kern, C. Shi, A. Terzis, and F. Tramèr, "Defeating prompt injections by design (camel)," arXiv:2503.18813, 2025.

[87] M. Duan, A. Suri, N. Mireshghallah, S. Min, W. Shi, L. Zettlemoyer, Y. Tsvetkov, Y. Choi, D. Evans, and H. Hajishirzi, "Do membership inference attacks work on large language models?" in *COLM*, 2024.

[88] I. Dinur, U. Stemmer, D. P. Woodruff, and S. Zhou, "On differential privacy and adaptive data analysis with bounded space," 2023.

[89] Y. Dandi, E. Troiani, L. Arnaboldi, L. Pesce, L. Zdeborová, and F. Krzakala, "The benefits of reusing batches for gradient descent in two-layer networks - breaking the curse of information and leap exponents," arXiv:2402.03220, 2024.

[90] A. Degwekar, V. Vaikuntanathan, and P. N. Vasudevan, "Fine-grained cryptography," 2016.

[91] D. Das, J. Zhang, and F. Tramèr, "Blind baselines beat membership inference attacks for foundation models," in *DATA-FM workshop @ ICLR*, 2025.

[92] B. Even, C. Giraud, and N. Verzelen, "Computational lower bounds in latent models: Clustering, sparse-clustering, biclustering," arXiv:2506.13647, 2025.

[93] O. Etesami, S. Mahloujifar, and M. Mahmoody, "Computational concentration of measure — optimal bounds, reductions, and more," arXiv:1907.05401, 2020.

[94] A. Fawzi, H. Fawzi, and O. Fawzi, "Adversarial vulnerability for any classifier," in *NeurIPS*, 2018.

[95] V. Feldman, E. Grigorescu, L. Reyzin, S. S. Vempala, and Y. Xiao, "Statistical algorithms and a lower bound for detecting planted cliques," in *JACM*, 2017.

[96] C. Fang, H. Jia, A. Thudi, M. Yaghini, C. A. Choquette-Choo, N. Dullerud, V. Chandrasekaran, and N. Papernot, "Proof-of-learning is currently more broken than you think," arXiv:2208.03567, 2023.

[97] L. Fenaux and F. Kerschbaum, "Sok: Analyzing adversarial examples — a framework to study adversary knowledge," arXiv:2402.14937, 2024.

[98] M. A. Ferrag, N. Tihanyi, D. Hamouda, L. Maglaras, A. Lakas, and M. Debbah, "From prompt injections to protocol exploits: Threats in llm-powered ai agents workflows (imtm origin)," arXiv:2506.23260, 2025.

[99] S. S. Ghosal, S. Chakraborty, V. Singh, T. Guan, M. Wang, A. Velasquez, A. Beirami, F. Huang, D. Manocha, and A. S. Bedi, "Immune — improving safety against jailbreaks in multi-modal llms via inference-time alignment," arXiv:2411.18688, 2025.

[100] R. Ghosal, I. M. Hair, A. Jain, and A. Sahai, "Using the planted clique conjecture for cryptography: Public-key encryption from planted clique and noisy k-lin over expanders," in *STOC*, 2025.

[101] B. Ghazi, R. Ilango, P. Kamath, R. Kumar, and P. Manurangsi, "Towards separating computational and statistical differential privacy," arXiv:2301.00104, 2023.

[102] S. Garg, S. Jha, S. Mahloujifar, and M. Mahmoody, "Adversarially robust learning could leverage computational hardness," arXiv:1905.11564, 2020.

[103] S. Garg, S. Jha, S. Mahloujifar, M. Mahmoody, and M. Wang, "Overparameterization from computational constraints," arXiv:2208.12926, 2022.

[104] D. Gamarnik, A. Jagannath, and A. S. Wein, "Circuit lower bounds for the p-spin optimization problem," arXiv:2109.01342, 2022.

[105] ——, "Hardness of random optimization problems for boolean circuits, low-degree polynomials, and langevin dynamics," in *FOCS*, 2022.

[106] S. Goldwasser, M. P. Kim, V. Vaikuntanathan, and O. Zamir, "Planting undetectable backdoors in machine learning models," arXiv:2204.06974, 2022.

[107] A. Groce, J. Katz, and A. Yerukhimovich, "Limits of computational differential privacy in the client/server setting," in *TCC*, 2011.

[108] J. Guan and H. Montgomery, "On sequential functions and fine-grained cryptography," in *CRYPTO*, 2024.

[109] J. Gilmer, L. Metz, F. Faghri, S. S. Schoenholz, M. Raghu, M. Wattenberg, and I. Goodfellow, "The relationship between high-dimensional geometry and adversarial examples (adversarial spheres)," arXiv:1801.02774, 2018.

[110] S. Goldwasser, J. Shafer, N. Vafa, and V. Vaikuntanathan, "Oblivious defense in ml models: Backdoor removal without detection," arXiv:2411.03279, 2025.

[111] J. Guan and M. Zhandry, "Simple schemes in the bounded storage model," 2019.

[112] M. Glasgow, "Sgd finds then tunes features in two-layer neural networks with near-optimal sample complexity - a case study in the xor problem," arXiv:2309.15111, 2024.

[113] A. Ho, T. Besiroglu, E. Erdil, D. Owen, R. Rahman, Z. C. Guo, D. Atkinson, N. Thompson, and J. Sevilla, "Algorithmic progress in language models," arXiv:2403.05812, 2024.

[114] J. Hoffmann, S. Borgeaud, A. Mensch, E. Buchatskaya, T. Cai, E. Rutherford, D. de Las Casas, L. A. Hendricks, J. Welbl, A. Clark, T. Hennigan, E. Noland, K. Millican, G. van den Driessche, B. Damoc, A. Guy, S. Osindero, K. Simonyan, E. Elsen, J. W. Rae, O. Vinyals, and L. Sifre, "Training compute-optimal large language models (chinchilla)," arXiv:2203.15556, 2022.

[115] J. Hu, Y. Dong, Z. Ding, and X. Huang, "Enhancing robustness of llm-driven multi-agent systems through randomized smoothing," arXiv:2507.04105, 2025.

[116] Y. Han and D. Ghoshdastidar, "Transformers provably learn sparse xor with polylogarithmic parameters," arXiv:2502.07553, 2025.

[117] J.-T. Hsieh, D. M. Kane, P. K. Kothari, J. Li, S. Mohanty, and S. Tiegel, "Rigorous implications of the low-degree heuristic," in *STOC*, 2026.

[118] I. Haitner, N. Mazor, J. Silbak, and E. Tsfadia, "On the complexity of two-party differential privacy," arXiv:2108.07664, 2022.

[119] I. Haitner, N. Mazor, J. Silbak, E. Tsfadia, and C. Yan, "Computationally differentially private inner-product protocols imply oblivious transfer," arXiv:2502.15629, 2025.

[120] S. Hirahara and M. Nanashima, "Learning in pessiland via inductive inference," 2023.

[121] S. Hirahara and N. Shimizu, "Planted clique conjectures are equivalent," in *ECCC Report No. 58*, 2024.

[122] M. Haghifam, A. Smith, and J. Ullman, "The sample complexity of membership inference and privacy auditing," 2025.

[123] M. Hardt and J. Ullman, "Preventing false discovery in interactive data analysis is hard," arXiv:1408.1655, 2014.

[124] J. Holmgren and A. S. Wein, "Counterexamples to the low-degree conjecture," in *ITCS*, 2021.

[125] M. Jagielski, N. Carlini, D. Berthelot, A. Kurakin, and N. Papernot, "High accuracy and high fidelity extraction of neural networks," in *USENIX Security*, 2020.

[126] N. Joshi, H. Koubbi, T. Misiakiewicz, and N. Srebro, "Learning single-index models via harmonic decomposition," arXiv:2506.09887, 2025.

[127] H. Jia, M. Yaghini, C. A. Choquette-Choo, N. Dullerud, A. Thudi, V. Chandrasekaran, and N. Papernot, "Proof-of-learning: Definitions and practice," in *IEEE S&P*, 2021.

[128] Z. Kong, A. R. Chowdhury, and K. Chaudhuri, "Can membership inferencing be refuted?" arXiv:2303.03648, 2023.

[129] F. Kovačević, H. C. Ji, D. Wu, M. Soltanolkotabi, and M. Mondelli, "Full-batch gradient descent outperforms one-pass sgd - sample complexity separation in single-index learning," arXiv:2602.02431, 2026.

[130] R. Ko, J. Jeong, S. Zheng, C. Xiao, T.-W. Kim, M. Onizuka, and W.-Y. Shin, "Seven security challenges that must be solved in cross-domain multi-agent llm systems," arXiv:2505.23847, 2025.

[131] A. Kalavasis, A. Karbasi, A. Oikonomou, K. Sotiraki, G. Velegkas, and M. Zampetakis, "Injecting undetectable backdoors in obfuscated neural networks and language models," arXiv:2406.05660, 2024.

[132] S. P. Kasiviswanathan, H. K. Lee, K. Nissim, S. Raskhodnikova, and A. Smith, "What can we learn privately?" in *FOCS*, 2008.

[133] J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, and D. Amodei, "Scaling laws for neural language models," arXiv:2001.08361, 2020.

[134] H. Kaplan, Y. Mansour, K. Nissim, and U. Stemmer, "Separating adaptive streaming from oblivious streaming," arXiv:2101.10836, 2021.

[135] ——, "Bayesian perspective on memorization and reconstruction," 2025.

[136] D. Kühnemann, A. Polak, and A. Rosen, "The planted orthogonal vectors problem," arXiv:2505.00206, 2025.

[137] M. Lecuyer, V. Atlidakis, R. Geambasu, D. Hsu, and S. Jana, "Certified robustness to adversarial examples with differential privacy (pixeldp)," arXiv:1802.03471, 2019.

[138] S. Liu, A. C. Cullen, P. Montague, S. Erfani, and B. I. P. Rubinstein, "Multi-level certified defense against poisoning attacks in offline reinforcement learning," arXiv:2505.20621, 2025.

[139] R. LaVigne, A. Lincoln, and V. V. Williams, "Public-key cryptography in the fine-grained setting," in *CRYPTO*, 2019.

[140] J. D. Lee, K. Oko, T. Suzuki, and D. Wu, "Neural network learns low-dimensional polynomials with sgd near the information-theoretic limit," arXiv:2406.01581, 2024.

[141] Y. Lai, X. Xue, L. Shen, Y. Wu, G. Li, S. Guo, K. Zhou, and B. Xiao, "Provably robust adaptation for language-empowered foundation models (lefcert, lefcert-l, lefcert-c)," arXiv:2510.08659, 2025.

[142] S. Li, I. Zadik, and M. Zampetakis, "On the hardness of learning one hidden layer neural networks," arXiv:2410.03477, 2024.

[143] S. Mahloujifar, D. I. Diochnos, and M. Mahmoody, "The curse of concentration in robust learning — evasion and poisoning attacks from concentration of measure," in *AAAI*, 2019.

[144] O. Montasser, S. Hanneke, and N. Srebro, "Vc classes are adversarially robustly learnable, but only improperly," in *COLT*, 2019.

[145] ——, "Adversarially robust learning: A generic minimax optimal learner and characterization," arXiv:2209.07369, 2022.

[146] P. Mukherjee and S. Lokam, "On the query complexity of training data reconstruction in private learning," arXiv:2303.16372, 2024.

[147] S. Mahloujifar, M. Mahmoody, and A. Mohammed, "Universal multi-party poisoning attacks," in *ICML*, 2019.

[148] I. Mironov, O. Pandey, O. Reingold, and S. Vadhan, "Computational differential privacy," in *CRYPTO*, 2009.

[149] F. Meisingseth and C. Rechberger, "Relating definitions of computational differential privacy in wider parameter regimes," 2025.

[150] M. Meeus, I. Shilov, S. Jain, M. Faysse, M. Rei, and Y.-A. de Montjoye, "Sok: Membership inference attacks on llms are rushing nowhere (and how to fix it)," in *IEEE SaTML*, 2025.

[151] S. Mahloujifar, X. Zhang, M. Mahmoody, and D. Evans, "Empirically measuring concentration — fundamental limits on intrinsic robustness," in *NeurIPS*, 2019.

[152] S. Mahloujifar, "A complexity theoretic approach to adversarial machine learning," in *Research Statement / PhD Thesis Overview*, 2019.

[153] A. T. Ngo, A. Chattopadhyay, and S. Maitra, "Cryptographic backdoor for neural networks: Boon and bane," arXiv:2509.20714, 2025.

[154] M. Ngo and M. P. Kim, "Publicly-verifiable certificates for statistical algorithms," arXiv:2607.15528, 2026.

[155] N. Papernot, P. McDaniel, A. Sinha, and M. P. Wellman, "Sok: Security and privacy in machine learning," in *IEEE EuroS&P*, 2018.

[156] E. Paquette, C. Paquette, L. Xiao, and J. Pennington, "4+3 phases of compute-optimal neural scaling laws," arXiv:2405.15074, 2024.

[157] A. Pal, J. Sulam, and R. Vidal, "Adversarial examples might be avoidable — the role of data concentration in adversarial robustness," in *NeurIPS*, 2023.

[158] H. Qiu, H. Ma, Z. Zhang, A. Abuadbba, W. Kang, A. Fu, and Y. Gao, "Towards a critical evaluation of robustness for deep learning backdoor countermeasures," arXiv:2204.06273, 2022.

[159] A. Rao, M. Choudhury, and S. Aditya, "Jailbreak paradox: The achilles' heel of llms," arXiv:2406.12702, 2024.

[160] S. Rezaei and X. Liu, "On the difficulty of membership inference attacks," arXiv:2005.13702, 2021.

[161] J. Rando and F. Tramèr, "Universal jailbreak backdoors from poisoned human feedback," arXiv:2311.14455, 2023.

[162] Z. Ratliff and S. Vadhan, "A framework for differential privacy against timing attacks," arXiv:2409.05623, 2024.

[163] R. Raz, "Fast learning requires good memory: A time-space lower bound for parity learning," arXiv:1602.05161, 2016.

[164] M. Swanberg, M. S. M. S. Annamalai, J. Hayes, B. Balle, and A. Smith, "A unified framework for adversary-aware differential privacy bounds," arXiv:2507.08158, 2026.

[165] A. Suri and D. Evans, "Formalizing and estimating distribution inference risks," arXiv:2109.06024, 2022.

[166] B. Sorscher, R. Geirhos, S. Shekhar, S. Ganguli, and A. S. Morcos, "Beyond neural scaling laws, beating power law scaling via data pruning," in *NeurIPS*, 2022.

[167] M. Suliman, A. Halimi, S. R. Kadhe, N. Baracaldo, and D. Leith, "Towards a re-evaluation of data forging attacks in practice," arXiv:2411.05658, 2025.

[168] V. Siu, J. He, K. Montgomery, Z. Wang, N. Gong, C. Wang, and D. Song, "A framework for formalizing llm agent security," arXiv:2603.19469, 2026.

[169] J. Steinhardt, P. W. Koh, and P. Liang, "Certified defenses for data poisoning attacks," arXiv:1706.03691, 2017.

[170] S. Sonoda, K. Kasaura, Y. Mizuno, K. Tsukamoto, and N. Onda, "Lean formalization of generalization error bound by rademacher complexity and dudley's entropy integral," arXiv:2503.19605, 2026.

[171] F. Shpilevskiy, S. Lyu, K. D. Dvijotham, M. Lécuyer, and P.-A. Noël, "Adaptive diffusion denoised smoothing (adds)," arXiv:2507.08163, 2025.

[172] A. Shafran, I. Shumailov, M. A. Erdogdu, and N. Papernot, "Beyond labeling oracles: What does it mean to steal ml models?" arXiv:2310.01959, 2024.

[173] R. Shokri, M. Stronati, C. Song, and V. Shmatikov, "Membership inference attacks against machine learning models," arXiv:1610.05820, 2017.

[174] L. Schmidt, S. Santurkar, D. Tsipras, K. Talwar, and A. Mądry, "Adversarially robust generalization requires more data," arXiv:1804.11285, 2018.

[175] F. Suya, A. Suri, T. Zhang, J. Hong, Y. Tian, and D. Evans, "Sok: Pitfalls in evaluating black-box attacks," arXiv:2310.17534, 2024.

[176] T. Schramm and A. S. Wein, "Computational barriers to estimation from low-degree polynomials," in *Annals of Statistics*, 2022.

[177] E. Seferis, C. Wu, S. Kollias, S. Bensalem, and C.-H. Cheng, "Randomized smoothing meets vision-language models (rs-vlm)," arXiv:2509.16088, 2025.

[178] H. Salman, G. Yang, J. Li, P. Zhang, H. Zhang, I. Razenshteyn, and S. Bubeck, "Provably robust deep learning via adversarially trained smoothed classifiers (smoothadv)," in *NeurIPS*, 2019.

[179] M. J. Song, I. Zadik, and J. Bruna, "On the cryptographic hardness of learning single periodic neurons," arXiv:2106.10744, 2021.

[180] Y. Shavit, "What does it take to catch a chinchilla? verifying rules on large-scale neural network training via compute monitoring," arXiv:2303.11341, 2023.

[181] M. J. Song, "Cryptographic hardness of score estimation," arXiv:2404.03272, 2024.

[182] F. Tramèr, N. Carlini, W. Brendel, and A. Mądry, "On adaptive attacks to adversarial example defenses," in *NeurIPS*, 2020.

[183] A. Thudi, H. Jia, I. Shumailov, and N. Papernot, "On the necessity of auditable algorithmic definitions for machine unlearning," in *USENIX Security*, 2022.

[184] K. C. Tsiolis, A. Mousavi-Hosseini, and M. A. Erdogdu, "From information to generative exponent, learning rate induces phase transitions in sgd," arXiv:2510.21020, 2025.

[185] D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Mądry, "Robustness may be at odds with accuracy," arXiv:1805.12152, 2019.

[186] F. Villa, F. B. Durak, T. Kohno, T. Maharramli, and F. Roesner, "Extending the formalism and theoretical foundations of cryptography to ai," arXiv:2603.02590, 2026.

[187] A. K. Veldanda and S. Garg, "On evaluating neural network backdoor defenses," arXiv:2010.12186, 2020.

[188] E. Wong and J. Z. Kolter, "Provable defenses against adversarial examples via the convex outer adversarial polytope," in *ICML*, 2018.

[189] R. Wen, Y. Liu, M. Backes, and Y. Zhang, "Sok: Data reconstruction attacks against machine learning models: Definition, metrics, and benchmark," arXiv:2506.07888, 2025.

[190] Y. Wang, C. Su, J. Pan, and C. Xu, "Fine-grained non-interactive key-exchange without idealized assumptions, and lower bounds," in *Crypto*, 2024.

[191] P. Wang, N. Zarifis, I. Diakonikolas, and J. Diakonikolas, "Sample and computationally efficient robust learning of gaussian single-index models," arXiv:2411.05708, 2024.

[192] A. S. Wein, "Computational complexity of statistics: New insights from low-degree polynomials," in *Survey*, 2025.

[193] H. Xiao, G. E. Suh, and S. Devadas, "Formal privacy proof of data encoding: The possibility and impossibility of learnable obfuscation," in *CCS*, 2024.

[194] S. Yeom, I. Giacomelli, M. Fredrikson, and S. Jha, "Privacy risk in machine learning: Analyzing the connection to overfitting," in *CSF*, 2018.

[195] J. Yu, Y. He, A. Goyal, and S. Arora, "On the impossibility of retrain equivalence in machine unlearning," arXiv:2510.16629, 2025.

[196] B. Zhang, Z. Chen, C. Shen, and J. Li, "Verification of machine unlearning is fragile," in *ICML*, 2024.

[197] J. Zhang, D. Das, G. Kamath, and F. Tramèr, "Position: Membership inference attacks cannot prove that a model was trained on your data," arXiv:2409.19798, 2025.

[198] Z. Zhao, Z. Fang, X. Wang, X. Chen, H. Su, H. Xiao, and Y. Zhou, "Proof-of-learning with incentive security," arXiv:2404.09005, 2026.

[199] I. Zadik, M. J. Song, A. S. Wein, and J. Bruna, "Lattice-based methods surpass sum-of-squares in clustering," in *COLT*, 2022.

[200] K. Zhu, X. Yang, J. Wang, W. Guo, and W. Y. Wang, "Melon: Provable defense against indirect prompt injection attacks in ai agents," arXiv:2502.05174, 2025.