

# Dynamic Programming: The Rod Cutting Problem

Version of November 5, 2014



- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)
  - Problems have many solutions; we want the *best* one

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)
  - Problems have many solutions; we want the *best* one
- Main idea of DP

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)
  - Problems have many solutions; we want the *best* one
- Main idea of DP
  - 1 Analyze the structure of an optimal solution

- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)
  - Problems have many solutions; we want the *best* one
- Main idea of DP
  - 1 Analyze the structure of an optimal solution
  - 2 Recursively define the value of an optimal solution



- Dynamic Programming (DP) bears similarities to Divide and Conquer (D&C)
  - Both partition a problem into smaller subproblems and build solution of larger problems from solutions of smaller problems.
  - In D&C, work top-down. Know exact smaller problems that need to be solved to solve larger problem.
  - In D, (usually) work bottom-up. Solve *all* smaller size problems and build larger problem solutions from them.
    - In DP, many large subproblems reuse solution to same smaller problem.
  - DP often used for [optimization problems](#)
  - Problems have many solutions; we want the *best* one
- Main idea of DP
  - 1 Analyze the structure of an optimal solution
  - 2 Recursively define the value of an optimal solution
  - 3 Compute the value of an optimal solution (usually bottom-up)

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$
  - If we cut it into 4 pieces of length 1, we earn  $4 \cdot p_1 = 4$

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$
  - If we cut it into 4 pieces of length 1, we earn  $4 \cdot p_1 = 4$
  - If we cut it into 2 pieces of length 1 & a piece of length 2, we earn  $2 \cdot p_1 + p_2 = 9$

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$
  - If we cut it into 4 pieces of length 1, we earn  $4 \cdot p_1 = 4$
  - If we cut it into 2 pieces of length 1 & a piece of length 2, we earn  $2 \cdot p_1 + p_2 = 9$
  - If we cut it into 2 pieces of length 2, we can earn  $2 \cdot p_2 = 10$



# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$
  - If we cut it into 4 pieces of length 1, we earn  $4 \cdot p_1 = 4$
  - If we cut it into 2 pieces of length 1 & a piece of length 2, we earn  $2 \cdot p_1 + p_2 = 9$
  - If we cut it into 2 pieces of length 2, we can earn  $2 \cdot p_2 = 10$
  - There are more options, but the maximum revenue is 10

# Rod Cutting

- **Input:** We are given a rod of length  $n$  and a table of prices  $p_i$  for  $i = 1, \dots, n$ ;  $p_i$  is the price of a rod of length  $i$ .
- **Goal:** to determine the maximum revenue  $r_n$ , obtainable by cutting up the rod and selling the pieces
- **Example:**  $n = 4$  and  $p_1 = 1, p_2 = 5, p_3 = 8, p_4 = 9$ 
  - If we do not cut the rod, we can earn  $p_4 = 9$
  - If we cut it into 4 pieces of length 1, we earn  $4 \cdot p_1 = 4$
  - If we cut it into 2 pieces of length 1 & a piece of length 2, we earn  $2 \cdot p_1 + p_2 = 9$
  - If we cut it into 2 pieces of length 2, we can earn  $2 \cdot p_2 = 10$
  - There are more options, but the maximum revenue is 10
- In general, rod of length  $n$  can be cut in  $2^{n-1}$  different ways, since we can choose cutting, or not cutting, at all distances  $i$  ( $1 \leq i \leq n - 1$ ) from the left end

# Optimal Solution

- We can calculate the maximum revenue  $r_n$  in terms of optimal revenues for shorter rods

$$r_n = \max(p_n, r_1 + r_{n-1}, r_2 + r_{n-2}, \dots, r_{n-1} + r_1)$$

- $p_n$  if we do not cut at all
- $r_1 + r_{n-1}$  if we take the sum of optimal revenues for 1 and  $n-1$
- $r_2 + r_{n-2}$  if we take the sum of optimal revenues for 2 and  $n-2$
- ...

# Optimal Solution

- We can calculate the maximum revenue  $r_n$  in terms of optimal revenues for shorter rods

$$r_n = \max(p_n, r_1 + r_{n-1}, r_2 + r_{n-2}, \dots, r_{n-1} + r_1)$$

- $p_n$  if we do not cut at all
  - $r_1 + r_{n-1}$  if we take the sum of optimal revenues for 1 and  $n-1$
  - $r_2 + r_{n-2}$  if we take the sum of optimal revenues for 2 and  $n-2$
  - ...
- Another approach. Set  $r_0 = 0$  and

$$r_n = \max_{1 \leq i \leq n} (p_i + r_{n-i})$$

- Cut a piece of length  $i$ , with remainder of length  $n-i$
- Only the remainder, and not the first piece, may be further divided

# Recursive Top-down Implementation

Cut-Rod( $p, n$ )

```
if  $n = 0$  then
    | return 0;
end
 $q = -\infty$ ;
for  $i = 1$  to  $n$  do
    |  $q = \max(q, p[i] + \text{Cut-Rod}(p, n - i))$ ;
end
return  $q$ ;
```

# Recursive Top-down Implementation

Cut-Rod( $p, n$ )

```
if  $n = 0$  then
    | return 0;
end
 $q = -\infty$ ;
for  $i = 1$  to  $n$  do
    |  $q = \max(q, p[i] + \text{Cut-Rod}(p, n - i))$ ;
end
return  $q$ ;
```

Algorithm Time

# Recursive Top-down Implementation

Cut-Rod( $p, n$ )

```
if  $n = 0$  then
    | return 0;
end
 $q = -\infty$ ;
for  $i = 1$  to  $n$  do
    |  $q = \max(q, p[i] + \text{Cut-Rod}(p, n - i))$ ;
end
return  $q$ ;
```

## Algorithm Time

- $T(n)$ : the total number of calls made to Cut-Rod when called with rod length  $n$

# Recursive Top-down Implementation

## Cut-Rod( $p, n$ )

```
if  $n = 0$  then
    | return 0;
end
 $q = -\infty$ ;
for  $i = 1$  to  $n$  do
    |  $q = \max(q, p[i] + \text{Cut-Rod}(p, n - i))$ ;
end
return  $q$ ;
```

## Algorithm Time

- $T(n)$ : the total number of calls made to Cut-Rod when called with rod length  $n$

$$T(n) = \begin{cases} 1 + \sum_{0 \leq j \leq n-1} T(j), & \text{if } n > 0, \\ 1, & \text{if } n = 0. \end{cases}$$



# Recursive Top-down Implementation

## Cut-Rod( $p, n$ )

```
if  $n = 0$  then
    | return 0;
end
 $q = -\infty$ ;
for  $i = 1$  to  $n$  do
    |  $q = \max(q, p[i] + \text{Cut-Rod}(p, n - i))$ ;
end
return  $q$ ;
```

## Algorithm Time


- $T(n)$ : the total number of calls made to Cut-Rod when called with rod length  $n$

$$T(n) = \begin{cases} 1 + \sum_{0 \leq j \leq n-1} T(j), & \text{if } n > 0, \\ 1, & \text{if } n = 0. \end{cases}$$

- Induction  $\Rightarrow T(n) = 2^n$

# Explanation of Exponential Cost

- Algorithm calls same subproblem many times



- After solving a *subproblem*, store the solution

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**
- Two main methodologies: top-down and bottom-up

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**
- Two main methodologies: top-down and bottom-up
  - Corresponding algorithms have the same asymptotic cost, but bottom-up is usually faster in practice

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**
- Two main methodologies: top-down and bottom-up
  - Corresponding algorithms have the same asymptotic cost, but bottom-up is usually faster in practice
- Main idea of bottom-up DP



- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**
- Two main methodologies: top-down and bottom-up
  - Corresponding algorithms have the same asymptotic cost, but bottom-up is usually faster in practice
- Main idea of bottom-up DP
  - Don't wait until subproblem is encountered.
  - Sort the subproblems by size; solve smallest subproblems first

- After solving a *subproblem*, store the solution
  - Next time you encounter same subproblem, lookup the solution, instead of solving it again
  - Uses **space** to save **time**
- Two main methodologies: top-down and bottom-up
  - Corresponding algorithms have the same asymptotic cost, but bottom-up is usually faster in practice
- Main idea of bottom-up DP
  - Don't wait until subproblem is encountered.
  - Sort the subproblems by size; solve smallest subproblems first
  - Combine solutions of small subproblems to solve larger ones

# DP Solution for Rod Cutting

- $p_i$  are the problem inputs.
- $r_i$  is max profit from cutting rod of length  $i$ .
- Goal is to calculate  $r_n$

# DP Solution for Rod Cutting

- $p_i$  are the problem inputs.
- $r_i$  is max profit from cutting rod of length  $i$ .
- Goal is to calculate  $r_n$
- $r_i$  defined by
  - $r_1 = 1$  and  $r_n = \max_{1 \leq i \leq n} (p_i + r_{n-i})$

# DP Solution for Rod Cutting

- $p_i$  are the problem inputs.
- $r_i$  is max profit from cutting rod of length  $i$ .
- Goal is to calculate  $r_n$
- $r_i$  defined by
  - $r_1 = 1$  and  $r_n = \max_{1 \leq i \leq n} (p_i + r_{n-i})$
- Iteratively fill in  $r_i$  table by calculating  $r_1, r_2, r_3, \dots$
- $r_n$  is final solution

# DP Solution for Rod Cutting

- $p_i$  are the problem inputs.
- $r_i$  is max profit from cutting rod of length  $i$ .
- Goal is to calculate  $r_n$
- $r_i$  defined by
  - $r_1 = 1$  and  $r_n = \max_{1 \leq i \leq n} (p_i + r_{n-i})$
- Iteratively fill in  $r_i$  table by calculating  $r_1, r_2, r_3, \dots$
- $r_n$  is final solution

i	1	2	3	4	... ..	n
$r_i$	$p_1$				... ..	

# DP Bottom-up Implementation

## Bottom-Up-Cut-Rod( $p, n$ )

```
r[0] = 0; // Array r[0...n] stores the computed optimal values
for j = 1 to n do
    // Consider problems in increasing order of size
    q = -∞;
    for i = 1 to j do
        // To solve a problem of size j, we need to consider all
        // decompositions into i and j - i
        q = max(q, p[i] + r[j - i]);
    end
    r[j] = q;
end
return r[n];
```

## Bottom-Up-Cut-Rod( $p, n$ )

```
r[0] = 0; // Array r[0...n] stores the computed optimal values
for j = 1 to n do
    // Consider problems in increasing order of size
    q = -∞;
    for i = 1 to j do
        // To solve a problem of size j, we need to consider all
        // decompositions into i and j - i
        q = max(q, p[i] + r[j - i]);
    end
    r[j] = q;
end
return r[n];
```

- Cost:  $O(n^2)$



## Bottom-Up-Cut-Rod( $p, n$ )

```
r[0] = 0; // Array r[0...n] stores the computed optimal values
for j = 1 to n do
    // Consider problems in increasing order of size
    q = -∞;
    for i = 1 to j do
        // To solve a problem of size j, we need to consider all
        // decompositions into i and j - i
        q = max(q, p[i] + r[j - i]);
    end
    r[j] = q;
end
return r[n];
```

- Cost:  $O(n^2)$ 
  - The outer loop computes  $r[1], r[2], \dots, r[n]$  in this order

## Bottom-Up-Cut-Rod( $p, n$ )

```
r[0] = 0; // Array r[0...n] stores the computed optimal values
for j = 1 to n do
    // Consider problems in increasing order of size
    q = -∞;
    for i = 1 to j do
        // To solve a problem of size j, we need to consider all
        // decompositions into i and j - i
        q = max(q, p[i] + r[j - i]);
    end
    r[j] = q;
end
return r[n];
```

- Cost:  $O(n^2)$ 
  - The outer loop computes  $r[1], r[2], \dots, r[n]$  in this order
  - To compute  $r[j]$ , the inner loop uses all values  $r[0], r[1], \dots, r[j-1]$  (i.e.,  $r[j-i]$  for  $1 \leq i \leq j$ )

# Outputting the Cutting

- Algorithm only *computes*  $r_i$ . It does not output the cutting.
- Easy fix
  - When calculating  $r_j = \max_{1 \leq i \leq j} (p_i + r_{j-i})$   
store value of  $i$  that achieved this max in new array  $s[j]$ .
  - This  $j$  is the size of last piece in the optimal cutting.
- After algorithm is finished, can reconstruct optimal cutting by unrolling the  $s_j$ .

# Extended Implementation to Output the Decomposition

## Extended-Bottom-Up-Cut-Rod( $p, n$ )

```
// Array s[0...n] stores the optimal size of the first piece to
// cut off
r[0] = 0; // Array r[0...n] stores the computed optimal values
for j = 1 to n do
    q = -∞;
    for i = 1 to j do
        // Solve problem of size j
        if q < p[i] + r[j - i] then
            q = p[i] + r[j - i];
            s[j] = i; // Store the size of the first piece
        end
    end
    r[j] = q;
end
while n > 0 do
    // Print sizes of pieces
    Print s[n];
    n = n - s[n];
end
```