

Programming Assignment 4

Due date: **06 May 2022 23:59**

Notes

1. The problem counts 10 points, which contributes 10% of the overall credit of the course.
2. All submitted code will be compiled and tested on the lab 2 machines to evaluate the assignments.
3. Points may be deducted if your programs consistently achieve no speedup over the serial program.

Problem 1:

Please use MPI and CUDA to solve the problem.

Suppose A and B are binary matrix whose dimension is $n \times n$

Define \otimes is matrix multiplication under module 2. More specifically, if $C = A \otimes B$, it means

$$C[i][j] = \left(\sum_{k=0}^{n-1} A[i][k] * B[k][j] \right) \% 2,$$

Define \oplus is matrix addition under module 2. More specifically, if $C = A \oplus B$, it means

$$C[i][j] = (A[i][j] + B[i][j]) \% 2,$$

Where $i, j \in [0, n - 1]$ and $\%$ is remainder operation as in C++.

We define power operation as follow.

For all matrix A ,

$$A^m = \begin{cases} A, & m = 1 \\ A^{m-1} \otimes A, & m > 1 \end{cases}$$

Given m, A, B , please use MPI and CUDA to calculate C by following formula:

$$C = (A \otimes B^m) \oplus (A \otimes B^{m-1}) \oplus (A \otimes B^{m-2}) \dots \oplus (A \otimes B^1) \oplus (A)$$

Where $m \geq 1$

Sample code

The sample code is multiple.cpp. The load data part, sequential calculation part and the test part has been implemented. Add your code in specified area. You can add some new functions but not to modify existing statements. Do not output extra debug information.

Some small sample input data and large sample input data are provided for debugging. When testing, we will use some large input data.

Compile and run

A makefile is provided. You can use it to run the program. For example, use the command "make test_small_1" can run a test with a small dataset.

Each machine will have only one process. The program is run in at most 4 machines.

~~The three arguments are "number_of_block_in_a_grid", "number_of_thread_in_a_block", "data_file_name"~~

The argument is "data_file_name".

Update1

"number_of_block_in_a_grid", "number_of_thread_in_a_block" are deleted from the input command. You can use set any "number_of_block_in_a_grid" and "number_of_thread_in_a_block" in the code by yourself. But be careful that it should run on the server successfully.

The update of the sample code is from line 130 to line 149 in the main function. They are tag by "[update 1]".

The commands in makefile have been changed.