



# AVL Trees



Version of September 6, 2016



# Binary Search Trees



# Binary Search Trees





## Binary-search-tree property

For every node  $x$

- All keys in its left subtree are smaller than the key value in  $x$

# Binary Search Trees



## Binary-search-tree property

For every node  $x$

- All keys in its left subtree are smaller than the key value in  $x$
- All keys in its right subtree are larger than the key value in  $x$

# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
=  $\max(\text{children height}) + 1$

# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0

# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height



# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height = -1

# Height


The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
     $= \max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height = -1
  
- Tree operations typically take  
     $O(\text{height})$  time

# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf


- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height = -1
- Tree operations typically take  $O(\text{height})$  time



# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf


- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height = -1
- Tree operations typically take  $O(\text{height})$  time



# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf


- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height = -1
- Tree operations typically take  $O(\text{height})$  time



# Height

The **height** of a node in a tree is the number of edges on the longest downward path from the node to a leaf

- Node height  
=  $\max(\text{children height}) + 1$
- Leaves: height = 0
- Tree height = root height
- Empty tree: height =  $-1$
- Tree operations typically take  $O(\text{height})$  time



## Question

Let  $n$  be the size of a binary search tree. How can we keep its height  $O(\log n)$  under insertion and deletion?

# Balanced Binary Search Tree: AVL Tree


An **AVL** [Adelson-Velskii & Landis, 1962] tree is a binary search tree in which

- for every node in the tree, heights of its left and right subtrees differ by at most 1.


# Balanced Binary Search Tree: AVL Tree

An **AVL** [Adelson-Velskii & Landis, 1962] tree is a binary search tree in which

- for every node in the tree, heights of its left and right subtrees differ by at most 1.



non-AVL Tree



AVL Tree


- The *balance factor* of a node is the height of its right subtree minus the height of its left subtree.




# Balanced Binary Search Tree: AVL Tree

An **AVL** [Adelson-Velskii & Landis, 1962] tree is a binary search tree in which

- for every node in the tree, heights of its left and right subtrees differ by at most 1.



non-AVL Tree



AVL Tree

- The *balance factor* of a node is the height of its right subtree minus the height of its left subtree.
- A node with balance factor 1, 0 or  $-1$  is considered *balanced*.

# AVL Trees with Minimum Number of Nodes


Let  $n_h$  be the minimum number of nodes in an AVL tree of height  $h$



$$n_0 = 1$$

# AVL Trees with Minimum Number of Nodes

Let  $n_h$  be the minimum number of nodes in an AVL tree of height  $h$





$$n_0 = 1$$

$$n_1 = 2$$

# AVL Trees with Minimum Number of Nodes

Let  $n_h$  be the minimum number of nodes in an AVL tree of height  $h$



$$n_0 = 1$$

$$n_1 = 2$$


$$n_2 = n_1 + n_0 + 1 = 4$$

# AVL Trees with Minimum Number of Nodes


Let  $n_h$  be the minimum number of nodes in an AVL tree of height  $h$




$$n_0 = 1$$



$$n_1 = 2$$



$$n_2 = n_1 + n_0 + 1 = 4$$



$$n_3 = n_2 + n_1 + 1 = 7$$

# Height of AVL Tree

- Let  $n_h$  denote the minimum number of nodes in an AVL tree of height  $h$
- $n_0 = 1, n_1 = 2$  (base)
- $n_h = n_{h-1} + n_{h-2} + 1$

# Height of AVL Tree

- Let  $n_h$  denote the minimum number of nodes in an AVL tree of height  $h$
- $n_0 = 1, n_1 = 2$  (base)
- $n_h = n_{h-1} + n_{h-2} + 1$
- For any AVL tree of height  $h$  and size  $n$ ,

$$n \geq n_h = n_{h-1} + n_{h-2} + 1 > 2n_{h-2} > 4n_{h-4} > \cdots > 2^i n_{h-2i}$$

# Height of AVL Tree

- Let  $n_h$  denote the minimum number of nodes in an AVL tree of height  $h$
- $n_0 = 1, n_1 = 2$  (base)
- $n_h = n_{h-1} + n_{h-2} + 1$
- For any AVL tree of height  $h$  and size  $n$ ,

$$n \geq n_h = n_{h-1} + n_{h-2} + 1 > 2n_{h-2} > 4n_{h-4} > \cdots > 2^i n_{h-2i}$$

- If  $h$  is even, let  $i = h/2$ .  $\Rightarrow n > 2^{h/2} n_0 = 2^{h/2} \cdot 1 \Rightarrow h = O(\log n)$



# Height of AVL Tree

- Let  $n_h$  denote the minimum number of nodes in an AVL tree of height  $h$
- $n_0 = 1, n_1 = 2$  (base)
- $n_h = n_{h-1} + n_{h-2} + 1$
- For any AVL tree of height  $h$  and size  $n$ ,

$$n \geq n_h = n_{h-1} + n_{h-2} + 1 > 2n_{h-2} > 4n_{h-4} > \cdots > 2^i n_{h-2i}$$

- If  $h$  is even, let  $i = h/2$ .  $\Rightarrow n > 2^{h/2} n_0 = 2^{h/2} \cdot 1 \Rightarrow h = O(\log n)$
- If  $h$  is odd, let  $i = (h-1)/2$ .  $\Rightarrow n > 2^{(h-1)/2} n_1 = 2^{(h-1)/2} \cdot 2 \Rightarrow h = O(\log n)$

# Height of AVL Tree

- Let  $n_h$  denote the minimum number of nodes in an AVL tree of height  $h$
- $n_0 = 1, n_1 = 2$  (base)
- $n_h = n_{h-1} + n_{h-2} + 1$
- For any AVL tree of height  $h$  and size  $n$ ,

$$n \geq n_h = n_{h-1} + n_{h-2} + 1 > 2n_{h-2} > 4n_{h-4} > \cdots > 2^i n_{h-2i}$$

- If  $h$  is even, let  $i = h/2$ .  $\Rightarrow n > 2^{h/2} n_0 = 2^{h/2} \cdot 1 \Rightarrow h = O(\log n)$
- If  $h$  is odd, let  $i = (h-1)/2$ .  $\Rightarrow n > 2^{(h-1)/2} n_1 = 2^{(h-1)/2} \cdot 2 \Rightarrow h = O(\log n)$
- Thus, many operations (e.g., insertion, deletion, and search) on an AVL tree will take  $O(\log n)$  time

# AVL Trees and Fibonacci Numbers

We saw that  $n_h = n_{h-1} + n_{h-2} + 1$ .

Recall Fibonacci numbers satisfy  $f_h = f_{h-1} + f_{h-2}$ . Now compare

# AVL Trees and Fibonacci Numbers

We saw that  $n_h = n_{h-1} + n_{h-2} + 1$ .

Recall Fibonacci numbers satisfy  $f_h = f_{h-1} + f_{h-2}$ . Now compare

$h$	0	1	2	3	4	5	6	7	8
$n_h$	1	2	4	7	12	20	33	54	88
$f_h$	1	1	2	3	5	8	13	21	34

# AVL Trees and Fibonacci Numbers

We saw that  $n_h = n_{h-1} + n_{h-2} + 1$ .

Recall Fibonacci numbers satisfy  $f_h = f_{h-1} + f_{h-2}$ . Now compare

$h$	0	1	2	3	4	5	6	7	8
$n_h$	1	2	4	7	12	20	33	54	88
$f_h$	1	1	2	3	5	8	13	21	34

Lemma:

$$n_h = f_{h+2} - 1$$

# AVL Trees and Fibonacci Numbers

We saw that  $n_h = n_{h-1} + n_{h-2} + 1$ .

Recall Fibonacci numbers satisfy  $f_h = f_{h-1} + f_{h-2}$ . Now compare

$h$	0	1	2	3	4	5	6	7	8
$n_h$	1	2	4	7	12	20	33	54	88
$f_h$	1	1	2	3	5	8	13	21	34

Lemma:

$$n_h = f_{h+2} - 1$$

Proof: by induction

$$n_{h+1} = 1 + n_h + n_{h-1} = 1 + f_{h+2} - 1 + n_{h+1} - 1 = f_{h+3} - 1$$

Since  $f_h \sim c\phi^h$  for golden ratio  $\phi = \frac{1+\sqrt{5}}{2}$ , this also immediately provides alternative derivation that  $h = O(\log n)$ .

- Basically follows insertion strategy of binary search tree


- Basically follows insertion strategy of binary search tree
  - But may cause violation of AVL tree property



- Basically follows insertion strategy of binary search tree
  - But may cause violation of AVL tree property
- Restore the destroyed height balance if needed

# Insertion

- Basically follows insertion strategy of binary search tree
  - But may cause violation of AVL tree property
- Restore the destroyed height balance if needed



## Insertion: Observation

After an insertion, only nodes that are on the path from the insertion node to the root might have their balance altered

## Insertion: Observation


After an insertion, only nodes that are on the path from the insertion node to the root might have their balance altered

- Because only those nodes have their subtrees altered

# Insertion: Observation

After an insertion, only nodes that are on the path from the insertion node to the root might have their balance altered

- Because only those nodes have their subtrees altered



Insert 1

# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property

# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property
  - Case 1 (Left-Left case)
    - insert into the left subtree of the left child of  $A$

# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property
  - Case 1 (Left-Left case)
    - insert into the left subtree of the left child of  $A$
  - Case 2 (Left-Right case)
    - insert into the right subtree of the left child of  $A$



# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property
  - Case 1 (Left-Left case)
    - insert into the left subtree of the left child of  $A$
  - Case 2 (Left-Right case)
    - insert into the right subtree of the left child of  $A$
  - Case 3 (Right-Left case)
    - insert into the left subtree of the right child of  $A$


# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property
  - Case 1 (Left-Left case)
    - insert into the left subtree of the left child of  $A$
  - Case 2 (Left-Right case)
    - insert into the right subtree of the left child of  $A$
  - Case 3 (Right-Left case)
    - insert into the left subtree of the right child of  $A$
  - Case 4 (Right-Right case)
    - insert into the right subtree of the right child of  $A$



# Insertion: Four Cases

- Let  $A$  denote the *lowest node* violating AVL tree property
  - Case 1 (Left-Left case)
    - insert into the left subtree of the left child of  $A$
  - Case 2 (Left-Right case)
    - insert into the right subtree of the left child of  $A$
  - Case 3 (Right-Left case)
    - insert into the left subtree of the right child of  $A$
  - Case 4 (Right-Right case)
    - insert into the right subtree of the right child of  $A$
- Cases 1 and 4 are mirror image symmetries with respect to  $A$ , as are cases 2 and 3


# Insertion: Left-Left Case




# Insertion: Right-Right Case



- *Left rotation* with  $B$  as the pivot
- The new subtree rooted at  $B$  has height  $k+2$ , *exactly the same* height before the insertion
- The rest of the tree (if any) that was originally above node  $A$  always remains balanced




# Insertion: Left-Right Case



- Single rotation fails to fix it
- Subtree  $\beta$  is too tall


# Left-Right Case: Special Case

When subtree  $\alpha$ ,  $\beta$  and  $\gamma$  are empty,  $k = -1$ . Insert  $C$ :



# Left-Right Case: Special Case


When subtree  $\alpha$ ,  $\beta$  and  $\gamma$  are empty,  $k = -1$ . Insert  $C$ :




- Left rotation and then right rotation with  $C$  as the pivot.  
Done!



# Left-Right Case: General Case 1




# Left-Right Case: General Case 2




# Right-Left Case: Special Case

When subtree  $\alpha$ ,  $\beta$  and  $\gamma$  are empty,  $k = -1$ . Insert  $C$ :



# Right-Left Case: Special Case

When subtree  $\alpha$ ,  $\beta$  and  $\gamma$  are empty,  $k = -1$ . Insert  $C$ :



- Right rotation and then left rotation with  $C$  as the pivot.  
Done!

# Insertion: Summary

- **Left-Left case:** single rotation  
— Right rotation

# Insertion: Summary

- **Left-Left case:** single rotation
  - Right rotation
- **Left-Right case:** double rotation
  - Left rotation and then right rotation

# Insertion: Summary

- **Left-Left case:** single rotation  
— Right rotation
- **Left-Right case:** double rotation  
— Left rotation and then right rotation
- **Right-Left case:** double rotation  
— Right rotation and then left rotation

# Insertion: Summary

- **Left-Left case:** single rotation  
— Right rotation
- **Left-Right case:** double rotation  
— Left rotation and then right rotation
- **Right-Left case:** double rotation  
— Right rotation and then left rotation
- **Right-Right case:** single rotation  
— Left rotation



# Insertion: Summary

- **Left-Left case:** single rotation  
— Right rotation
- **Left-Right case:** double rotation  
— Left rotation and then right rotation
- **Right-Left case:** double rotation  
— Right rotation and then left rotation
- **Right-Right case:** single rotation  
— Left rotation

For each insertion, at most two rotations are needed to restore the height balance of the entire tree.

# Insertion: Summary

- **Left-Left case:** single rotation  
— Right rotation
- **Left-Right case:** double rotation  
— Left rotation and then right rotation
- **Right-Left case:** double rotation  
— Right rotation and then left rotation
- **Right-Right case:** single rotation  
— Left rotation

For each insertion, at most two rotations are needed to restore the height balance of the entire tree.

Note that in all cases, height of rebalanced subtree is unchanged!  
This means no further tree modifications are needed.

Delete a node as in ordinary binary search tree

Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it

Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it
- If not, replace it with either the largest in its left subtree or the smallest in its right subtree, and remove that node

Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it
- If not, replace it with either the largest in its left subtree or the smallest in its right subtree, and remove that node

Note: The replacement node has at most one subtree

Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it
- If not, replace it with either the largest in its left subtree or the smallest in its right subtree, and remove that node  
Note: The replacement node has at most one subtree
- Trace the path from the parent of removed node to root

Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it
- If not, replace it with either the largest in its left subtree or the smallest in its right subtree, and remove that node  
Note: The replacement node has at most one subtree
- Trace the path from the parent of removed node to root
- For each node along path, restore the height balance if needed by doing single or double rotations



Delete a node as in ordinary binary search tree

- If the node is a leaf, remove it
- If not, replace it with either the largest in its left subtree or the smallest in its right subtree, and remove that node  
Note: The replacement node has at most one subtree
- Trace the path from the parent of removed node to root
- For each node along path, restore the height balance if needed by doing single or double rotations

For each node along the path, restore the height balance if needed by doing single or double rotations

## Deletion (continued)

For each node along the path, restore the height balance if needed by doing single or double rotations

- Very similar to insertion with one major caveat

# Deletion (continued)

For each node along the path, restore the height balance if needed by doing single or double rotations

- Very similar to insertion with one major caveat
  - In insertion a (single/double) rotation restored balance *and* kept height of rebalanced subtree unchanged.  
⇒ Only *one* rotation needed.
  - In deletion, rotation restores *balance* but final *height* of rotated subtree might decrease by one. If this occurs, need to continue walking up path towards root, continuing to restoring balance by rotations when necessary.

## Deletion (continued)

For each node along the path, restore the height balance if needed by doing single or double rotations

- Very similar to insertion with one major caveat
  - In insertion a (single/double) rotation restored balance *and* kept height of rebalanced subtree unchanged.  
⇒ Only *one* rotation needed.
  - In deletion, rotation restores *balance* but final *height* of rotated subtree might decrease by one. If this occurs, need to continue walking up path towards root, continuing to restoring balance by rotations when necessary.
  - Since path has length  $O(h)$  this might require  $O(h) = O(\log n)$  rotations.

## Deletion (continued)

For each node along the path, restore the height balance if needed by doing single or double rotations


- Very similar to insertion with one major caveat
  - In insertion a (single/double) rotation restored balance *and* kept height of rebalanced subtree unchanged.  
⇒ Only *one* rotation needed.
  - In deletion, rotation restores *balance* but final *height* of rotated subtree might decrease by one. If this occurs, need to continue walking up path towards root, continuing to restoring balance by rotations when necessary.
  - Since path has length  $O(h)$  this might require  $O(h) = O(\log n)$  rotations.

⇒ Deletion can also be done in  $O(\log n)$  time.

# Deletion Example

Diagram below illustrates example in which subtree rooted at  $A$  has height  $k + 3$ . An item is deleted from subtree  $\gamma$ , reducing its height from  $k + 1$  to  $k$ , leading to an imbalance.

After a single rotation, the subtree is now rooted at  $B$  with no imbalance. But,  $B$  has height  $k + 2$ . This might cause an imbalance further up the tree, so the algorithm might need to continue walking upwards, correcting that imbalance.



AVL trees are one particular type of *Balanced* Search trees, yielding  $O(\log n)$  behavior for dictionary operations.

There are many other types of Balanced Search Trees, e.g.

- red-black trees
- *B*-trees
- $(a, b)$  trees  
(2, 3) and (2, 3, 4) trees are special cases
- treaps (randomized BSTs)
- splay Trees (only  $O(\log n)$  in amortized sense)