

More on Operators

David Rossiter and Gibson Lam

Outcomes

- After completing this presentation, you are expected to be able to:
 1. Explain the use of the various kinds of Python operators
 2. Write code to represent True or False using numbers, lists, tuples or strings
 3. Apply operator precedence in expressions

COMP1021

More on Operators

Page 2

Python Operators

- We already know we can do common maths things in Python, i.e. + - / *

```
>>> print(100 - 25 * 4 + 120 / 5)
24.0
```

- These things are called *operators*
- This presentation gives you summaries of different types of operators
- You have already used most of them
- We will also look at some related things

Arithmetic Operators

- Basic operators:

+ - / * %

- ‘Advanced’ operators:

** means ‘to the power of’
// means ‘do division,
return the integer result’
-x means the same as ‘-1 * x’

```
>>> 2**3
8
>>> 3**2
9
>>> 3//3
1
>>> 4//3
1
>>> 5//3
1
>>> 6//3
2
>>> 7//3
2
>>> 8//3
2
>>> x=10
>>> -x
-10
>>>
```

Comparison Operators

Reminder

- For comparing two values:
 - a < b returns True if a is less than b
 - a <= b returns True if a is less than or equal to b
 - a > b returns True if a is greater than b
 - a >= b returns True if a is greater than or equal to b
 - a == b returns True if a is equal to b
 - a != b returns True if a is not equal to b
- All of them return False otherwise

Logical Operators

Reminder

- Logical operators work with Boolean values, i.e. True or False
 - a and b if both condition a and condition b are True, the result is True; otherwise, it’s False
 - a or b if either condition a or condition b is True, the result is True; otherwise, it’s False
 - not a if a is True, then the result is False; if a is False, then the result is True

COMP1021

More on Operators

Page 6

Summary

Reminder

- Here is a summary of the input and output:

a	b	a and b	a or b	not a
True	True	True	True	False
True	False	False	True	False
False	True	False	True	True
False	False	False	False	True

COMP1021

More on Operators

Page 7

Using Other Things as True/False

- In Python:
 - Any number other than 0 means True
 - 0 means False
- An empty list [], tuple () or string "" means False
 - Non-empty means True

COMP1021

More on Operators

Page 8

Using Other Things as True/False

```
>>> if "^^":
    print("yes")

yes
>>> if "":
    print("yes")

>>>
```

Python sees
this as True

Python sees this
empty string as
False so nothing
is printed

Using the Equals Sign

- You use the equals sign to put things into a variable, i.e. `age = 25`
- Sometimes you may want to do something like this (adding one to the variable `count`):

```
count = count + 1
```

- When you are doing something to the **same** variable Python has a shortcut, like this:

```
count += 1
```

COMP1021

More on Operators

Page 10

Using Shortcuts with the Equals Sign

- You can use the equals sign with most arithmetic operators, for example:

```
calories = calories + 800 → calories += 800
pigs = pigs * 5 → pigs *= 5
cakes = cakes / students → cakes /= students
marks = marks - 20 → marks -= 20
hello = hello + "!" → hello += "!"
```

As you can see, this works for strings too, not just numerical values

Operators for Lists, Tuples and Strings

- These operators are used by lists, tuples and strings:
- | | |
|-------------------------|--|
| <code>x + y</code> | concatenates (=put together) two lists, tuples or strings |
| <code>x * n</code> | concatenates <code>n</code> copies of <code>x</code> |
| <code>a in x</code> | returns <code>True</code> if <code>a</code> is in collection <code>x</code> and <code>False</code> otherwise |
| <code>a not in x</code> | returns <code>False</code> if <code>a</code> is in collection <code>x</code> and <code>True</code> otherwise |

COMP1021

More on Operators

Page 12

Using 'in' with Strings

- Using the `in` operator you can test for a string inside another string, like this:

```
>>> if "shark" in "baby shark dance":
    print("yes")

yes
>>>
```

COMP1021

More on Operators

Page 13

Operator Precedence

- If we ask Python to calculate `2 + 3 * 4` what will the result be?
 - You might think the answer is `5 * 4` which is 20
 - You are wrong!
 - This is because `*` has *precedence* over `+`
 - So `3 * 4` will be calculated first, then the result (12) will be added to 2, so the answer is 14
- If you always use brackets, e.g. `2 + (3 * 4)`, then you don't need to worry about precedence, but you need to understand what happens when there aren't any brackets

The Precedence Table

Increasing precedence ↑	- Highest precedence -	} So if you use brackets () they override everything
	()	
	**	
	-x, +x	
	*, /, %, //	
	+, -	
	<, >, <=, >=, !=, ==	
	in, not in	
	logical not	
	logical and	
	logical or	
	- Lowest precedence -	

Precedence Example 1

`x = 17 / 2 * 3 + 2`

- `/` and `*` have higher precedence than `+`, so they are handled first
- `/` and `*` have equal precedence, so the one on the left (`/`) is evaluated first

• So the answer is:
`= ((17/2) * 3) + 2`
`= 27.5`

COMP1021

More on Operators

Page 16

Precedence Example 2

`x = 19 % 4 + 15 / 2 * 3`

- `%`, `/` and `*` have higher precedence than `+`, so they are handled first
- `%`, `/` and `*` have equal precedence, so the one on the left is evaluated first, which is `%`, then `/`, then `*`

• So the answer is:
`= (19%4) + ((15/2) * 3)`
`= 25.5`

COMP1021

More on Operators

Page 17

Precedence Example 3

`x = 17 / 2 % 2 * 3 * 3`

- `**` has a higher precedence than the others, so it is handled first
- `/`, `%`, and `*` have equal precedence, so the one on the left (`/`) is evaluated first, then `%`, then `*`

• So the answer is:
`= ((17/2) % 2) * (3*3)`
`= ((17/2) % 2) * 27`
`= 13.5`

COMP1021


More on Operators

Page 18

Precedence Example 4

```
english_is_spoken = True
need_visa = False
married_to_singapore_person = False
want_to_visit_singapore = True
visit_singapore = english_is_spoken \
    and not need_visa or married_to_singapore_person \
    and want_to_visit_singapore
print(visit_singapore)
```

- What is printed?




Precedence Example 4

```
english_is_spoken = True
need_visa = False
married_to_singapore_person = False
want_to_visit_singapore = True
visit_singapore = (english_is_spoken \
    and (not need_visa)) or (married_to_singapore_person \
    and want_to_visit_singapore)
print(visit_singapore)
```

- Here brackets have been added to indicate the order

(True and (not False)) or (False and True)



Precedence Example 4

```
eng(True and (not False)) or (False and True)
need_visa = (True and True) or (False and True)
married_to_singapore_person = True or False
want_to_visit_singapore = True
visit_singapore = (english_is_spoken \
    and (not need_visa)) or (married_to_singapore_person \
    and want_to_visit_singapore)
print(visit_singapore)
```

- Here brackets have been added to indicate the order