

# Voronoi and Delaunay Diagrams

Siu-Wing Cheng

Room 3514

Phone: 2358-6973

[scheng@cse.ust.hk](mailto:scheng@cse.ust.hk)

<http://www.cse.ust.hk/faculty/scheng>


Department of Computer Science and Engineering  
The Hong Kong University of Science and Technology  
Hong Kong

# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  Voronoi cells so that each cell consists of points closest to one site.



# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  **Voronoi cells** so that each cell consists of points closest to one site.






# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  **Voronoi cells** so that each cell consists of points closest to one site.







# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  **Voronoi cells** so that each cell consists of points closest to one site.








# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  **Voronoi cells** so that each cell consists of points closest to one site.




# Voronoi Diagram

Given  $n$  point sites, partition  $\mathbb{R}^2$  into  $n$  **Voronoi cells** so that each cell consists of points closest to one site.




# Examples



[www.amath.washington.edu/~dnlennon/voronoi/](http://www.amath.washington.edu/~dnlennon/voronoi/)




# Examples



[www.amath.washington.edu/~dnlennon/voronoi/](http://www.amath.washington.edu/~dnlennon/voronoi/)


# Examples



[www.amath.washington.edu/~dnlennon/voronoi/](http://www.amath.washington.edu/~dnlennon/voronoi/)


# Voronoi Diagram

In  $\mathbb{R}^3$ , the Voronoi cell  $V_p$  of a site  $p$  is a convex polyhedron.




# Voronoi Diagram

In  $\mathbb{R}^3$ , the Voronoi cell  $V_p$  of a site  $p$  is a convex polyhedron.




# Voronoi Diagram

In  $\mathbb{R}^3$ , the Voronoi cell  $V_p$  of a site  $p$  is a convex polyhedron.




# Voronoi Diagram

In  $\mathbb{R}^3$ , the Voronoi cell  $V_p$  of a site  $p$  is a convex polyhedron.



# Delaunay Triangulation



# Delaunay Triangulation in $\mathbb{R}^2$

Dual of the Voronoi diagram:

Voronoi edge  $V_{pq}$

Delaunay edge  $pq$

Voronoi vertex  $V_{pqr}$

Delaunay triangle  $pqr$

Equivalent definition: given  $k$  vertices,  $2 \leq k \leq 3$ , they form a Delaunay simplex iff they have an empty circumcircle.



# Delaunay Triangulation in $\mathbb{R}^2$

Dual of the Voronoi diagram:

Voronoi edge  $V_{pq}$

Delaunay edge  $pq$

Voronoi vertex  $V_{pqr}$

Delaunay triangle  $pqr$

Equivalent definition: given  $k$  vertices,  $2 \leq k \leq 3$ , they form a **Delaunay simplex** iff they have an **empty circumcircle**.

# Delaunay Triangulation in $\mathbb{R}^3$

Dual of the Voronoi diagram:

Voronoi facet  $V_{pq}$

Delaunay edge  $pq$

Voronoi edge  $V_{pqr}$

Delaunay triangle  $pqr$

Voronoi vertex  $V_{pqrs}$

Delaunay tetrahedron  $pqrs$

Equivalent definition: given  $k$  vertices,  $2 \leq k \leq 4$ , they form a Delaunay simplex iff they have an empty circumsphere.

Always defined, always a valid 3D triangulation, efficient implementation (e.g., CGAL <http://www.cgal.org>).

# Delaunay Triangulation in $\mathbb{R}^3$

Dual of the Voronoi diagram:

Voronoi facet  $V_{pq}$

Delaunay edge  $pq$

Voronoi edge  $V_{pqr}$

Delaunay triangle  $pqr$

Voronoi vertex  $V_{pqrs}$

Delaunay tetrahedron  $pqrs$

Equivalent definition: given  $k$  vertices,  $2 \leq k \leq 4$ , they form a **Delaunay simplex** iff they have an **empty circumsphere**.

Always defined, always a valid 3D triangulation, efficient implementation (e.g., CGAL <http://www.cgal.org>).

# Delaunay Triangulation in $\mathbb{R}^3$

Dual of the Voronoi diagram:

Voronoi facet  $V_{pq}$

Delaunay edge  $pq$

Voronoi edge  $V_{pqr}$

Delaunay triangle  $pqr$

Voronoi vertex  $V_{pqrs}$

Delaunay tetrahedron  $pqrs$

Equivalent definition: given  $k$  vertices,  $2 \leq k \leq 4$ , they form a **Delaunay simplex** iff they have an **empty circumsphere**.

Always defined, always a valid 3D triangulation, efficient implementation (e.g., CGAL <http://www.cgal.org>).

# Restricted Delaunay Triangulation in $\mathbb{R}^2$

- Given a curve  $S$  and points on  $S$ , a Delaunay edge  $e$  is **restricted Delaunay** if  $V_e$  intersects  $S$ .
- The **restricted Delaunay triangulation**  $T$  is the set of vertices and restricted Delaunay edges.

# Restricted Delaunay Triangulation in $\mathbb{R}^3$

- Given a surface  $S$  and points on  $S$ , a Delaunay edge or triangle  $\sigma$  is **restricted Delaunay** if  $V_\sigma$  intersects  $S$ .
- The **restricted Delaunay triangulation**  $T$  is the set of vertices, restricted Delaunay edges, and restricted Delaunay triangles.

# Topological Ball Property

Topological ball property:

- For any triangle  $pqr \in T$ ,  $V_{pqr} \cap S$  is a single point.
- For any edge  $pq \in T$ ,  $V_{pq} \cap S$  is a single arc.
- For any vertex  $p \in T$ ,  $V_p \cap S$  is a topological disk.

Theorem (Edelsbrunner & Shah)

*Given the topological ball property,  $T$  has the same topology as  $S$ .*