

Recursion

David Rossiter

Outcomes

- After completing this presentation, you are expected to be able to:
 1. Explain what recursion is
 2. Construct the recursion depth diagram of a recursive function


COMP1021

Recursion

Page 2


What is Recursion?

- A recursive function is one which calls itself
- Recursive functions are sometimes very useful for some computing tasks
- For example, you can use one cleverly written small recursive function instead of lots of lines of code



‘Pay It Forward’

- A movie about a boy who has been asked to come up with a plan that will change the world
- He comes up with the plan that when someone receives a good deed, he/she helps 3 different other people



COMP1021

Recursion

Page 4

‘Pay It Forward’ Pseudo-Code

```
def help(benefactor, person):  
    person receives help from benefactor  
    help(person, random_person1)  
    help(person, random_person2)  
    help(person, random_person3)
```



- The whole process starts with one person helping another, for example: `help(me, you)`
- The above example uses pseudo-code, but the rest of this presentation uses real Python code

COMP1021


Recursion

Page 5

Recursive Depths 1/2



- How many good deeds are done in total after 3 depths?
- You can see what we mean by *depth* in the following diagram:



COMP1021


Recursion

Page 6

Recursive Depths 2/2



- The answer is that when the maximum depth is 3, the total number of good deeds is:



A Recursive Function in Python


- Here is an example recursive function:

```
def printsonumbers(num):
    print(num)
    if num < 4:
        printsonumbers(num + 1)
```

`printsonumbers(0)`

The recursive function is started by running `printsonumbers(0)`


- This is the execution of the code `printsonumbers(0)`



- The result is **0 1 2 3 4**

Recursive Depth Diagram

- So for this example, the pattern of depth looks like this:



Recursive Functions and Iterative Code

- The recursive example discussed in the last few slides generates a result of: 0
1
2
3
4
- On the next slide we will show two *iterative* code examples which produce the same result
- 'Iterative' means 'looping without recursion'

Iterative Code Examples

- Iterative code example 1:


```
for num in range(0, 5):
    print(num)
```
- Iterative code example 2:


```
num = 0
while num < 5:
    print(num)
    num = num + 1
```
- You can write recursive code and iterative code which do the same thing
- However, sometimes it is easier to write things using recursion, as you will see later

Changing the Order

- Let's change the example recursive function by swapping two parts of the code:

```
def printsonumbers(num):
    if num < 4:
        printsonumbers(num + 1)
    print(num)

printsonumbers(0)
```

These two parts of code have been swapped

- This is the execution of the code `printsonumbers(0)`

```
printsonumbers(0)
def printsonumbers(0):
    printsonumbers(0 + 1)
    def printsonumbers(1):
        printsonumbers(1 + 1)
        def printsonumbers(2):
            printsonumbers(2 + 1)
            def printsonumbers(3):
                printsonumbers(3 + 1)
                def printsonumbers(4):
                    print(4)
                print(3)
            print(2)
        print(1)
    print(0)
```

There are no more function calls when this value becomes 4, because of the if statement

- The result is **4 3 2 1 0**, which is the opposite order compared to the previous program's result


Making Pictures with Recursion

- Recursive functions are used for lots of purposes
- One of them is to make computer graphics containing a lot of repetitions, like this:



- In the following slides, we will discuss using recursion to draw the above triangles, and to build a tree


The Sierpinski Triangle



- The computer graphics example shown on the previous slide is called the Sierpinski triangle
- Basically, we start with a black triangle
- We draw a white triangle in the middle area
- Then the process repeats itself for the three 'corner' black triangles


Drawing the Sierpinski Triangle

Depth = 0




Depth = 1

Depth = 2





The Sierpinski triangle, with a maximum depth of 5




Recursive Depths

- For this example, when the maximum depth is 2, this is what the depth diagram looks like:



The Recursive Tree

- We can also use recursion to draw a simple tree
- First, a main trunk is drawn
- Then the process repeats itself twice, to draw two branches




Drawing the Recursive Tree

Depth = 0

Depth = 1

Depth = 2

Depth = 3



1. Start with a main trunk

2. Branch to the left and right of trunk

3. Repeat step 2 for each branch

4. Keep on repeating step 2 the branches

The Recursive Function

- Here is the recursive function for building the tree:

```
def buildtree(current_depth):
    if current_depth <= max_depth:
        turtle.forward(branch_length)
        turtle.right(angle_between_branches / 2)
        buildtree(current_depth + 1)
        turtle.left(angle_between_branches)
        buildtree(current_depth + 1)
        turtle.right(angle_between_branches / 2)
        turtle.backward(branch_length)
```

Control
how 'deep' the tree is

Build the right child branch of the current branch

Build the left child branch of the current branch