

More on Operators

David Rossiter and Gibson Lam

Outcomes

- After completing this presentation, you are expected to be able to:
 1. Explain the use of the various kinds of Python operators
 2. Write code to represent `True` or `False` using numbers, lists, tuples or strings
 3. Apply operator precedence in expressions

Python Operators

- We already know we can do common maths things in Python, i.e. `+` `-` `/` `*`

```
>>> print(100 - 25 * 4 + 120 / 5)
24.0
```

- These things are called *operators*
- This presentation gives you summaries of different types of operators
- You have already used most of them
- We will also look at some related things

Arithmetic Operators

- Basic operators:
`+` `-` `/` `*` `%`
- ‘Advanced’ operators:
`**` means ‘to the power of’
`//` means ‘do division, return the integer result’
`-x` means the same as ‘`-1 * x`’

```
>>> 2**3
8
>>> 3**2
9
>>> 3//3
1
>>> 4//3
1
>>> 5//3
1
>>> 6//3
2
>>> 7//3
2
>>> 8//3
2
>>> x=10
>>> -x
-10
>>>
```

Comparison Operators

Reminder

- For comparing two values:
 - `a < b` returns `True` if `a` is less than `b`
 - `a <= b` returns `True` if `a` is less than or equal to `b`
 - `a > b` returns `True` if `a` is greater than `b`
 - `a >= b` returns `True` if `a` is greater than or equal to `b`
 - `a == b` returns `True` if `a` is equal to `b`
 - `a != b` returns `True` if `a` is not equal to `b`
- All of them return `False` otherwise

Logical Operators

Reminder

- Logical operators work with Boolean values, i.e. `True` or `False`
 - `a and b` if both condition `a` and condition `b` are `True`, the result is `True`; otherwise, it's `False`
 - `a or b` if either condition `a` or condition `b` is `True`, the result is `True`; otherwise, it's `False`
 - `not a` if `a` is `True`, then the result is `False`; if `a` is `False`, then the result is `True`

Summary

Reminder

- Here is a summary of the input and output:

a	b	a and b	a or b	not a
True	True	True	True	False
True	False	False	True	False
False	True	False	True	True
False	False	False	False	True

COMP1021

More on Operators

Page 7

Using Other Things as True/False

- In Python:
 - Any number other than 0 means True
 - 0 means False
- An empty list [], tuple () or string "" means False
 - Non-empty means True

COMP1021

More on Operators

Page 8

Using Other Things as True/False

```
>>> if "0":  
    print("yes")  
  
yes  
>>> if "":  
    print("yes")  
  
>>>
```

Python sees this as True

Python sees this empty string as False so nothing is printed

Using the Equals Sign

- You use the equals sign to put things into a variable, i.e. `age = 25`
- Sometimes you may want to do something like this (adding one to the variable count):
`count = count + 1`
- When you are doing something to the **same** variable Python has a shortcut, like this:

```
count += 1
```

COMP1021

More on Operators

Page 10

Using Shortcuts with the Equals Sign

- You can use the equals sign with most arithmetic operators, for example:

```
calories = calories + 800  ➡ calories += 800  
pigs = pigs * 5            ➡ pigs *= 5  
cakes = cakes / students  ➡ cakes /= students  
marks = marks - 20        ➡ marks -= 20  
hello = hello + "!"       ➡ hello += "!"
```

As you can see, this works for strings too, not just numerical values

Operators for Lists, Tuples and Strings

- These operators are used by lists, tuples and strings:
 - `x + y` concatenates (=put together) two lists, tuples or strings
 - `x * n` concatenates `n` copies of `x`
 - `a in x` returns True if `a` is in collection `x` and False otherwise
 - `a not in x` returns False if `a` is in collection `x` and True otherwise

COMP1021

More on Operators

Page 12

Using 'in' with Strings

- Using the `in` operator you can test for a string inside another string, like this:


```
>>> if "shark" in "baby shark dance":
    print("yes")

yes
>>>
```

Operator Precedence

- If we ask Python to calculate $2 + 3 * 4$ what will the result be?
 - You might think the answer is $5 * 4$ which is 20
 - You are wrong!
 - This is because $*$ has *precedence* over $+$
 - So $3 * 4$ will be calculated first, then the result (12) will be added to 2, so the answer is 14
- If you always use brackets, e.g. $2 + (3 * 4)$, then you don't need to worry about precedence, but you need to understand what happens when there aren't any brackets

The Precedence Table


Increasing precedence 	- Highest precedence -	
	()	} So if you use brackets () they override everything
	**	
	-x, +x	
	*, /, %, //	
	+, -	
	<, >, <=, >=, !=, ==	
	in, not in	
	logical not	
	logical and	
	logical or	
	- Lowest precedence -	

Precedence Example 1

$$x = 17 / 2 * 3 + 2$$


- $/$ and $*$ have higher precedence than $+$, so they are handled first
- So the answer is:
 $= ((17/2) * 3) + 2$
 $= 27.5$
- $/$ and $*$ have equal precedence, so the one on the left ($/$) is evaluated first

Precedence Example 2

$$x = 19 \% 4 + 15 / 2 * 3$$


- $\%$, $/$ and $*$ have higher precedence than $+$, so they are handled first
- So the answer is:
 $= (19\%4) + ((15/2) * 3)$
 $= 25.5$
- $\%$, $/$ and $*$ have equal precedence, so the one on the left is evaluated first, which is $\%$, then $/$, then $*$

Precedence Example 3

$$x = 17 / 2 \% 2 * 3 ** 3$$


- $**$ has a higher precedence than the others, so it is handled first
- So the answer is:
 $= ((17/2) \% 2) * (3 ** 3)$
- $/$, $\%$, and $*$ have equal precedence, so the one on the left ($/$) is evaluated first, then $\%$, then $*$
 $= 13.5$

Precedence Example 4

```
english_is_spoken = True
need_visa = False
married_to_singapore_person = False
want_to_visit_singapore = True
visit_singapore = english_is_spoken \
    and not need_visa or married_to_singapore_person \
    and want_to_visit_singapore
print(visit_singapore)
```

- What is printed?

- Highest precedence -
...
↑ logical not
logical and
logical or
- Lowest precedence -

Precedence Example 4

```
english_is_spoken = True
need_visa = False
married_to_singapore_person = False
want_to_visit_singapore = True
visit_singapore = (english_is_spoken \
    and (not need_visa)) or (married_to_singapore_person \
    and want_to_visit_singapore)
print(visit_singapore)
```

- Here brackets have been added to indicate the order
(True and (not False)) or (False and True)

- Highest precedence -
...
↑ logical not
logical and
logical or
- Lowest precedence -

Precedence Example 4

```
eng(True and (not False)) or (False and True)
need_visa = (True and True) or (False and True)
married_to_singapore_person = True or False
want_to_visit_singapore = True
visit_singapore = (english_is_spoken \
    and (not need_visa)) or (married_to_singapore_person \
    and want_to_visit_singapore)
print(visit_singapore)
```

- Here brackets have been added to indicate the order