

COMP4021
Internet Computing

A SPA Example

Gibson Lam

A Basic SPA Example

- In this presentation, we will take a look at a basic single-page application example
- It is a web page for managing students

Students Manager

Student Id	Name	Year of Study	Action	
20000000	<input type="text" value="Chan Mei Ho"/>	<input type="text" value="3"/>	<input type="button" value="Change"/>	<input type="button" value="Delete"/>
20000001	<input type="text" value="Chan Tai Man"/>	<input type="text" value="3"/>	<input type="button" value="Change"/>	<input type="button" value="Delete"/>
20000002	<input type="text" value="Kwan Siu Lai"/>	<input type="text" value="4"/>	<input type="button" value="Change"/>	<input type="button" value="Delete"/>
20000003	<input type="text" value="Poon Lik Hang"/>	<input type="text" value="4"/>	<input type="button" value="Change"/>	<input type="button" value="Delete"/>
<input type="text" value="Enter Student Id"/>	<input type="text" value="Enter Name"/>	<input type="text" value="Enter Year of Study"/>	<input type="button" value="+"/>	

Files in the Example

- The example has three files:

- `manager.html`

The frontend HTML page of the application

Browser



-
- `server.js`

The server program that contains the web server of the application


Server



- `students.json`

The JSON data of the students residing on the server

System Overview



The HTML Page

- The HTML page has a table that shows the current students in the system

Students Manager			
Student Id	Name	Year of Study	Action
20000000	<input type="text" value="Chan Mei Ho"/>	<input type="text" value="3"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000001	<input type="text" value="Chan Tai Man"/>	<input type="text" value="3"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000002	<input type="text" value="Kwan Siu Lai"/>	<input type="text" value="4"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000003	<input type="text" value="Poon Lik Hang"/>	<input type="text" value="4"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
<input type="text" value="Enter Student Id"/>	<input type="text" value="Enter Name"/>	<input type="text" value="Enter Year of Study"/>	<input data-bbox="1854 708 1883 730" type="button" value="+"/>

- You can change or delete individual students, or add new ones
- All of these are accomplished by sending AJAX requests to the server, without ever leaving the page

Using the Page

Students Manager

Student Id	Name	Year of Study	Action
20000000	<input type="text" value="Chan Mei Ho"/>	<input type="text" value="3"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000001	<input type="text" value="Chan Tai Man"/>	<input type="text" value="3"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000002	<input type="text" value="Kwan Siu Lai"/>	<input type="text" value="4"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
20000003	<input type="text" value="Poon Lik Hang"/>	<input type="text" value="4"/>	<input type="button" value="Change"/> <input type="button" value="Delete"/>
<input type="text" value="Enter Student Id"/>	<input type="text" value="Enter Name"/>	<input type="text" value="Enter Year of Study"/>	<input type="button" value="+"/>


Add a new student by filling in the information and then click on '+'

Change the information and click on 'Change' or delete a student by clicking on 'Delete'

Sending AJAX Requests

- All requests are sent using `fetch()`
- For example, to get the current students, this code is used:

*The server path to
get the students*




```
fetch("/students/all")  
  .then((response) => response.json())  
  .then((students) => {  
    ...Add the students  
in the table...  
  });
```

GET and POST Requests

- The previous example uses a GET request
- The other requests are POST requests as JSON data are sent to the server, e.g.:


```
fetch("/students/add", {  
  method: "POST",  
  headers: {"Content-type": "application/json"},  
  body: JSON.stringify({ id, name, year })  
})  
  .then((response) => response.json())  
  .then((result) => { ... });
```



*JSON data is sent to
the server in the 'add
student' request*

Updating the Student Table

- The HTML page makes requests to add, change or delete students
- Whenever changes are made, the HTML page updates the entire student table, i.e.
`<table>...</table>`




Adding HTML Using jQuery

- jQuery allows you to quickly add HTML by doing something like this:

```
$(...Parent...).append($(".HTML..."));
```

- For example, you can append a header to the end of the body using this code:



```
<html>  
  ><head>...</head>  
  <body></body>  
</html>
```

```
<html>  
  ><head>...</head>  
  <body>  
    <h1>Hi!</h1>  
  </body>  
</html>
```

```
$("body").append($(".<h1>Hi!</h1>"));
```


Inserting a Student

- The following code inserts a student into the table body:

```
<tr>
  <td>20000000</td>
  <td>
    <input id="name-20000000" value="Chan Mei Ho">
  </td>
  <td>
    <input id="year-20000000" value="3">
  </td>
  <td>
    <button class="change" data-id="20000000">Change</button>
    <span>&nbsp;</span>
    <button class="delete" data-id="20000000">Delete</button>
  </td>
</tr>
```

append() can be chained for jQuery objects

```
const student = $("<tr></tr>")
  .append($("<td>" + id + "</td>"))
  .append($("<td><input id='name-' + id + '' value='" +
    name + "'></td>"))
  .append($("<td><input id='year-' + id + '' value='" +
    year + "'></td>"))
  .append($("<td></td>")
    .append($("<button class='change' data-id='" + id +
      "'>Change</button>"))
    .append($("<span>&nbsp;</span>"))
    .append($("<button class='delete' data-id='" + id +
      "'>Delete</button>"))
  );
$("#table-body").append(student);
```

 An example in Chrome

The Server Endpoints

- Here are the specifications of the server endpoints, i.e. available access paths in the server:

Method	Path	Request Body	Response Body
GET	/students/all	-	JSON of students, e.g. { id: {name, year}, ... }
POST	/students/add	{id, name, year}	{ success: true }, or { error: "..." }
POST	/students/change	{id, name, year}	{ success: true }, or { error: "..." }
POST	/students/delete	{id}	{ success: true }

The Students JSON File

- The JSON file `students.js` is the 'database' of the application
- It stores the students in simple JSON format, as shown on the right:

```
{  
  "20000000": {  
    "name": "Chan Mei Ho",  
    "year": 3  
  },  
  "20000001": {  
    "name": "Chan Tai Man",  
    "year": 3  
  },  
  ...More students here...  
}
```

Using the File System Module

- On the server program, the JSON file is read every time a request is made
- If there are changes to the students, the data will be written back the file
- The `fs` (file system) module is needed to read and write files, which is imported by:

```
const fs = require("fs");
```

Reading and Writing Files

- The application uses `fs.readFileSync()` and `fs.writeFileSync()` to read and write files respectively
- There are also asynchronous, promise version of the two commands
- In this example, we use the synchronous functions to keep things simple but they may block the server execution if the JSON file is very large

Dealing With the JSON Files

- Here is the code to read and write the JSON file:
 - Reading

```
const students =  
  JSON.parse(fs.readFileSync("students.json"));
```

Convert to a JavaScript object before using

- Writing

```
fs.writeFileSync("students.json",  
  JSON.stringify(students, null, "  "));
```

Add spacing to the JSON content

Convert to JSON content before writing

The Get-Students Endpoint

- The code for the get-students endpoint does two things:
 1. Reading the JSON file
 2. Returning the students object as JSON data

```
app.get("/students/all", (req, res) => {  
  ①  const students =  
      JSON.parse(fs.readFileSync("students.json"));  
  
  ②  res.json(students);  
});
```

The Add-Student Endpoint

- The add-student endpoint does a bit more, which includes:

1. Reading the JSON body
2. Checking for duplicate id
3. Adding the student and writing the JSON file

```
app.post("/students/add", (req, res) => {  
  ① const { id, name, year } = req.body;  
    const students = JSON.parse(...);  
  
  ② if (students[id]) {  
    res.json({ error: "..."});  
    return;  
  }  
  
  ③ students[id] = { name, year };  
    fs.writeFileSync(...);  
  
    res.json({ success: true });  
  });
```

Return an error message

The Change/Delete Endpoints

- The change-student and delete-student endpoints are almost the same as the add-student endpoint
- The delete-student endpoint uses the `delete` keyword to delete a student in the `students` object, i.e.:

```
delete students[id];
```

where `id` is a key in the JavaScript object

Summary

- This example demonstrates the use of AJAX `fetch()` and a Node.js server to build a basic single-page application
- It does not have strict data validation so you may be able to break the system using some weird input values
- Nevertheless, this will be a good starting point for the work that you will do later in the server-side labs