



HEAT NO.	MK.	QTY.	SIZE	ITEM DESCRIPTION	WGT. (KG)	TAG
	1	1.272 m	89	PIPE, XH, ASTM A106 GR B SMLS, ASME B36.10, NACE MR0175/ISO 15156	19.5	
	2	0.447 m	89	PIPE, XH, ASTM A106 GR B SMLS, ASME B36.10, NACE MR0175/ISO 15156	6.9	
	3	5.687 m	89	PIPE, XH, ASTM A106 GR B SMLS, ASME B36.10, NACE MR0175/ISO 15156	86.8	
	4	2	89X33	BRANCHED OUTLET, SW, CL6000, ASTM A105N, MSS SP-97, NACE MR0175/ISO 15156	1.2	
	5	2	89	ELBOW, 90° LR, BW, XH, ASTM A234 WPB, ASME B16.9, NACE MR0175/ISO 15156	5.5	
	6	2	33	NIPPLE, SCH 160, ASTM A106 GR B SMLS, ASME B36.10, NACE MR0175/ISO 15156 PBE (100 MM LG)	3.4	
	7	2	33	PLUG, HEX HEAD, ASTM A105N, ASME B16.11, NACE MR0175/ISO 15156	0.7	
	8	2	89	FLANGE, WN, CL600 RF, XH, ASTM A105N, ASME B16.5, NACE MR0175/ISO 15156	16.4	
	9	1	89	GASKET, CL600, 3.2mm THK, SPIRAL WOUND 316SS GRAPHITE FILLED WINDINGS c/w 316SS INNER RING & CS OUTER CENTERING RING, ASME B16.20, NACE MR0175/ISO 15156	1.0	
	10	16	3/4X5	STUD, ASTM A193 GR B7M c/w (2) HEAVY HEX NUT, ASTM A194 GR 2HM, ASME B18.2.1/B18.31.2/B18.2.2, NACE MR0175/ISO 15156	2.0	
	11	2	33	VALVE, GATE, SW X THRD, CL800	9.6	33GA-C4-C5
	12	2	89	PIPE SHOE S1A2	8.0	S1A2
	13	1	89	GUIDE G3	1.0	G3
TOTAL WGT:					161	

1. DIMENSIONS DO NOT INCLUDE GASKETS.
2. DIMENSIONS INCLUDE A 0mm WELD GAP AT ALL BUTT WELDS UNLESS THE WELD GAP IS SHOWN SEPARATELY.
3. SEE SCOVAN LINE LIST FOR CODE OF CONSTRUCTION, NDE AND HYDROSTATIC TESTING REQUIREMENTS.
4. NPS 1.5 AND LESS DIMENSIONS TO BE CONFIRMED PRIOR TO FABRICATION.
5. ALL SCOVAN TAGS AND LINE NUMBERS EXCLUDING MANUAL VALVES WILL HAVE THE PREFIX "PRD0154".

MK.	TYPE	WELDER	WPS	DATE	MK.	TYPE	WELDER	WPS	DATE	MK.	TYPE	WELDER	WPS	DATE	MK.	TYPE	WELDER	WPS	DATE	MK.	TYPE	WELDER	WPS	DATE
A	BW				F	BW				K	SW													
B	OLET				G	BW				L	SW													
C	SW				H	BW				M	ATT													
D	SW				I	ATT				N	BW													
E	BW				J	OLET																		

CN. 017	MOD. NO.	WPS. SC0-022-P1 R.3
INSULATION 64H		PAINT -
LINE NO. 89-PE-C1C5-I0105		
CLIENT DRAWING NO. -		

[illegible]