

## Complete Chart of jQuery Selectors

Selector	Example	Selects
<a href="#">*</a>	\$("#**")	All elements
<a href="#">#id</a>	\$("#lastname")	The element with id="lastname"
<a href="#">.class</a>	\$(".intro")	All elements with class="intro"
<a href="#">.class.class</a>	\$(".intro,.demo")	All elements with the class "intro" or "demo"
<a href="#">element</a>	\$( <code>"p"</code> )	All <code>&lt;p&gt;</code> elements
<a href="#">el1,el2,el3</a>	\$( <code>"h1,div,p"</code> )	All <code>&lt;h1&gt;</code> , <code>&lt;div&gt;</code> and <code>&lt;p&gt;</code> elements
<a href="#">:first</a>	\$( <code>"p:first"</code> )	The first <code>&lt;p&gt;</code> element
<a href="#">:last</a>	\$( <code>"p:last"</code> )	The last <code>&lt;p&gt;</code> element
<a href="#">:even</a>	\$( <code>"tr:even"</code> )	All even <code>&lt;tr&gt;</code> elements
<a href="#">:odd</a>	\$( <code>"tr:odd"</code> )	All odd <code>&lt;tr&gt;</code> elements
<a href="#">:first-child</a>	\$( <code>"p:first-child"</code> )	All <code>&lt;p&gt;</code> elements that are the first child of their parent
<a href="#">:first-of-type</a>	\$( <code>"p:first-of-type"</code> )	All <code>&lt;p&gt;</code> elements that are the first <code>&lt;p&gt;</code> element of their parent
<a href="#">:last-child</a>	\$( <code>"p:last-child"</code> )	All <code>&lt;p&gt;</code> elements that are the last child of their parent
<a href="#">:last-of-type</a>	\$( <code>"p:last-of-type"</code> )	All <code>&lt;p&gt;</code> elements that are the last <code>&lt;p&gt;</code> element of their parent
<a href="#">:nth-child(n)</a>	\$( <code>"p:nth-child(2)"</code> )	All <code>&lt;p&gt;</code> elements that are the 2nd child of their parent
<a href="#">:nth-last-child(n)</a>	\$( <code>"p:nth-last-child(2)"</code> )	All <code>&lt;p&gt;</code> elements that are the 2nd child of their parent, counting from the last child
<a href="#">:nth-of-type(n)</a>	\$( <code>"p:nth-of-type(2)"</code> )	All <code>&lt;p&gt;</code> elements that are the 2nd <code>&lt;p&gt;</code> element of their parent
<a href="#">:nth-last-of-type(n)</a>	\$( <code>"p:nth-last-of-type(2)"</code> )	All <code>&lt;p&gt;</code> elements that are the 2nd <code>&lt;p&gt;</code> element of their parent, counting from the last child

<a href="#">:only-child</a>	\$( "p:only-child" )	All <p> elements that are the only child of their parent
<a href="#">:only-of-type</a>	\$( "p:only-of-type" )	All <p> elements that are the only child, of its type, of their parent
<a href="#">parent &gt; child</a>	\$( "div > p" )	All <p> elements that are a direct child of a <div> element
<a href="#">parent descendant</a>	\$( "div p" )	All <p> elements that are descendants of a <div> element
<a href="#">element + next</a>	\$( "div + p" )	The <p> element that are next to each <div> elements
<a href="#">element ~ siblings</a>	\$( "div ~ p" )	All <p> elements that appear after the <div> element
<a href="#">:eq(index)</a>	\$( "ul li:eq(3)" )	The fourth element in a list (index starts at 0)
<a href="#">:gt(no)</a>	\$( "ul li:gt(3)" )	List elements with an index greater than 3
<a href="#">:lt(no)</a>	\$( "ul li:lt(3)" )	List elements with an index less than 3
<a href="#">:not(selector)</a>	\$( "input:not(:empty)" )	All input elements that are not empty
<a href="#">:header</a>	\$( ":header" )	All header elements <h1>, <h2> ...
<a href="#">:animated</a>	\$( ":animated" )	All animated elements
<a href="#">:focus</a>	\$( ":focus" )	The element that currently has focus
<a href="#">:contains(text)</a>	\$( ":contains('Hello')" )	All elements which contains the text "Hello"
<a href="#">:has(selector)</a>	\$( "div:has(p)" )	All <div> elements that have a <p> element
<a href="#">:empty</a>	\$( ":empty" )	All elements that are empty
<a href="#">:parent</a>	\$( ":parent" )	All elements that are a parent of another element
<a href="#">:hidden</a>	\$( "p:hidden" )	All hidden <p> elements
<a href="#">:visible</a>	\$( "table:visible" )	All visible tables
<a href="#">:root</a>	\$( ":root" )	The document's root element

<a href="#">:lang(language)</a>	<code>\$( "p:lang(de)" )</code>	All <p> elements with a lang attribute value starting with "de"
<a href="#">[attribute]</a>	<code>\$( "[href]" )</code>	All elements with a href attribute
<a href="#">[attribute=value]</a>	<code>\$( "[href='default.htm']" )</code>	All elements with a href attribute value equal to "default.htm"
<a href="#">[attribute!=value]</a>	<code>\$( "[href!='default.htm']" )</code>	All elements with a href attribute value not equal to "default.htm"
<a href="#">[attribute\$=value]</a>	<code>\$( "[href\$='.jpg']" )</code>	All elements with a href attribute value ending with ".jpg"
<a href="#">[attribute =value]</a>	<code>\$( "[title='Tomorrow']" )</code>	All elements with a title attribute value equal to 'Tomorrow', or starting with 'Tomorrow' followed by a hyphen
<a href="#">[attribute^=value]</a>	<code>\$( "[title^='Tom']" )</code>	All elements with a title attribute value starting with "Tom"
<a href="#">[attribute~=value]</a>	<code>\$( "[title~='hello']" )</code>	All elements with a title attribute value containing the specific word "hello"
<a href="#">[attribute*=value]</a>	<code>\$( "[title*='hello']" )</code>	All elements with a title attribute value containing the word "hello"
<a href="#">:input</a>	<code>\$( ":input" )</code>	All input elements
<a href="#">:text</a>	<code>\$( ":text" )</code>	All input elements with type="text"
<a href="#">:password</a>	<code>\$( ":password" )</code>	All input elements with type="password"
<a href="#">:radio</a>	<code>\$( ":radio" )</code>	All input elements with type="radio"
<a href="#">:checkbox</a>	<code>\$( ":checkbox" )</code>	All input elements with type="checkbox"
<a href="#">:submit</a>	<code>\$( ":submit" )</code>	All input elements with type="submit"
<a href="#">:reset</a>	<code>\$( ":reset" )</code>	All input elements with type="reset"
<a href="#">:button</a>	<code>\$( ":button" )</code>	All input elements with type="button"
<a href="#">:image</a>	<code>\$( ":image" )</code>	All input elements with type="image"
<a href="#">:file</a>	<code>\$( ":file" )</code>	All input elements with type="file"
<a href="#">:enabled</a>	<code>\$( ":enabled" )</code>	All enabled input elements

<a href="#">:disabled</a>	<code>\$(":disabled")</code>	All disabled input elements
<a href="#">:selected</a>	<code>\$(":selected")</code>	All selected input elements
<a href="#">:checked</a>	<code>\$(":checked")</code>	All checked input elements