EXPERIMENT NO – 5

TITLE: Master/Slave concept in Jenkins

Objective: -

Create at least Two slaves in Jenkins and Run two different jobs in two slaves parallel.

- Creating 2 slaves in Jenkins.

Name ?

Slave1

Description ?

This is Slave - 1.

Number of executors ?

1

Remote root directory ?

E:\Slave1

Labels ?

Agent1

Usage ?

Use this node as much as possible ⌄

Launch method ?

Launch agent by connecting it to the controller ⌄

☐ Disable WorkDir ?

Custom WorkDir path ?

Internal data directory ?

remoting

☐ Fail if workspace is missing ?

☐ Use WebSocket ?

🚫 Either WebSocket mode is selected, or the TCP port for inbound agents must be enabled

Advanced...

Availability ?

Keep this agent online as much as possible ⌄   ?

- Connecting the slaves with the machine.

- Slave 2

- Slave-1 & Slave-2 connected to local machine.

- Create a maven build in Jenkins and connect it with slave-1.

- Build Generated.

Name	Date modified	Type	Size
remoting	10/27/2023 8:06 PM	File folder	
workspace	10/27/2023 8:34 PM	File folder	
agent	10/27/2023 8:06 PM	Executable Jar File	1,339 KB
maven3-interceptor-commons	10/27/2023 8:23 PM	Executable Jar File	8 KB
maven35-agent	10/27/2023 8:23 PM	Executable Jar File	9 KB
maven35-interceptor	10/27/2023 8:23 PM	Executable Jar File	24 KB