

Lab Exercise 2- Create Service in Kubernetes

Objective:

- Understand the syntax and structure of a Kubernetes Service definition file (YAML).

Prerequisites

- Kubernetes Cluster: Have a running Kubernetes cluster (locally using Minikube or kind, or a cloud-based service).
- kubectl: Install and configure kubectl to interact with your Kubernetes cluster.
- Basic Knowledge of YAML: Familiarity with YAML format will be helpful for understanding Kubernetes resource definitions.

Step-by-Step Guide

Service

To expose the Service on a port on each Node in the cluster, modify the Service type to NodePort.

Create a YAML file named ***service.yaml*** with the following content:

service.yaml

```
apiVersion: v1
kind: Service
metadata:
  name: my-service
spec:
  selector:
    app: my-app
  ports:
    - protocol: TCP
      port: 80
      targetPort: 80
      nodePort: 30001 # A specific port in the range 30000-32767
  type: NodePort
```

Explanation:

- The primary difference from the ClusterIP Service is the addition of nodePort, which specifies the static port on each Node.
- type: Set to NodePort, exposing the Service on a specific port across all Nodes.

Apply this YAML to create the NodePort Service:

```
kubectl apply -f service.yaml
```

Verify the Service:

```
kubectl get services
```

You should see the nodeport-service listed with a NodePort and details about the port exposed.