

SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The Hong Kong University of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 7401


Test Sponsor: The Hong Kong University of Science and Technology

Tested by: Information Technology Services Office

Test Date: Dec-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024



Results Table

Benchmark	Base										Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	OMP	32	8	96.4	23.3	97.1	23.2	98.1	22.9									
513.soma_t	OMP	32	8	171	21.7	173	21.3	169	21.8									
518.tealeaf_t	OMP	32	8	224	7.38	223	7.41	224	7.37									
519.clvleaf_t	OMP	32	8	235	7.03	234	7.07	234	7.06									
521.miniswp_t	OMP	32	8	154	10.4	154	10.4	154	10.4									
528.pot3d_t	OMP	32	8	320	6.64	320	6.64	320	6.64									
532.sph_exa_t	OMP	32	8	98.8	19.7	100	19.4	99.1	19.7									
534.hpgmgfv_t	OMP	32	8	134	8.80	142	8.28	134	8.79									
535.weather_t	OMP	32	8	28.5	113	28.7	113	28.3	114									

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The Hong Kong University of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The Hong Kong University of Science and Technology

Tested by: Information Technology Services Office

Test Date: Dec-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

Hardware Summary

Type of System: SMP
Compute Node: DELL PowerEdge R6625 (AMD EPYC 9754)
Interconnect: Cisco Nexus 9332D-GX2B
Compute Nodes Used: 1
Total Chips: 2
Total Cores: 256
Total Threads: 512
Total Memory: 768 GB
Total Accelerators: 0
Max. Peak Threads: --

Software Summary

Compiler: Intel(R) oneAPI DPC++/C++ Compiler
2025.0.4.20241205
MPI Library: Intel(R) MPI Library for Linux* OS
2021.14.20250213-0d7f579
Other MPI Info: --
Other Software: --
Base Parallel Model: OMP
Base Ranks Run: 32
Base Threads Run: 8
Peak Parallel Models: Not Run
Minimum Peak Ranks: --
Maximum Peak Ranks: --
Max. Peak Threads: --
Min. Peak Threads: --

Node Description: DELL PowerEdge R6625 (AMD EPYC 9754)

Hardware

Number of nodes: 1
Uses of the node: Compute
Vendor: Dell Inc.
Model: Dell PowerEdge R6625
CPU Name: AMD EPYC 9754
CPU(s) orderable: 2 chips
Chips enabled: 2
Cores enabled: 256
Cores per chip: 128
Threads per core: 2
CPU Characteristics: Base 2.25 GHz, Boost up to 3.1 GHz
CPU MHz: 2250
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: 256 MB I+D on chip per chip
16 MB shared / 8 cores
Other Cache: None
Memory: 768 GB (24 x 32 GB DDR5-4800 at 4800MHz)
Disk Subsystem: 2 x 2 TB SAS SSD (Raid 1)
Other Hardware: Immersion Cooling (Direct Liquid Cooling)
Accel Count: --
Accel Model: --
Accel Vendor: --
Accel Type: --
Accel Connection: --
Accel ECC enabled: --
Accel Description: --
Adapter: Mellanox ConnectX-6 HDR MT28908
Number of Adapters: 1
Slot Type: PCIe 4.0 x16

(Continued on next page)

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR MT28908
Adapter Driver: 24.10-2.1.8.0
Adapter Firmware: 20.41.1000
Operating System: Rocky Linux 9.5
5.14.0-503.40.1.el9_5.x86_64
-
Local File System: tmpfs
Shared File System: Dell OneFS via NFS v3
System State: Run level 5
Other Software: None

SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The Hong Kong University of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The Hong Kong University of Science and Technology

Tested by: Information Technology Services Office

Test Date: Dec-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

Node Description: DELL PowerEdge R6625 (AMD EPYC 9754)

Hardware (Continued)

Data Rate: 200 Gbit/s

Ports Used: 1

Interconnect Type: RoCE v2

Interconnect Description: Cisco Nexus 9332D-GX2B

Hardware

Vendor: Cisco
Model: Cisco Nexus 9332D-GX2B
Switch Model: RoCE v2 Ethernet Switch
Number of Switches:
Number of Ports: 32
Data Rate: 400 Gbit/s
Firmware: --
Topology: --
Primary Use: MPI & RDMA Traffic, NFS

Software

: --

Submit Notes

The config file option 'submit' was used.
mpirun -genval1 -np \${ranks} numactl -l \$command

General Notes

Environment variables set by runhpc before the start of the run:

```
I_MPI_PIN = "1"
I_MPI_PIN_DOMAIN = "numa"
I_MPI_PIN_RESPECT_CPUSET = "1"
I_MPI_PIN_RESPECT_HCA = "0"
OMP_DYNAMIC = "false"
OMP_PLACES = "cores"
OMP_PROC_BIND = "close"
```

Compiler Version Notes

```
=====
CXXC 532.sph_exa_t(base)
=====
```

Intel(R) oneAPI DPC++/C++ Compiler 2025.0.4 (2025.0.4.20241205)
Target: x86_64-unknown-linux-gnu
Thread model: posix

(Continued on next page)

SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The Hong Kong University of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The Hong Kong University of Science and Technology

Tested by: Information Technology Services Office

Test Date: Dec-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

Compiler Version Notes (Continued)

InstalledDir:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86_64_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-sn26au2eyxigpsati3gb5oxmtku6s5uo/compiler/2025.0/bin/compiler

Configuration file:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86_64_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-sn26au2eyxigpsati3gb5oxmtku6s5uo/compiler/2025.0/bin/compiler/./icpx.cfg

```
=====
CC  505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
    534.hpgmgfv_t(base)
=====
```

Intel(R) oneAPI DPC++/C++ Compiler 2025.0.4 (2025.0.4.20241205)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86_64_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-sn26au2eyxigpsati3gb5oxmtku6s5uo/compiler/2025.0/bin/compiler

Configuration file:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86_64_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-sn26au2eyxigpsati3gb5oxmtku6s5uo/compiler/2025.0/bin/compiler/./icx.cfg

```
=====
FC  519.clvleaf_t(base) 528.pot3d_t(base) 535.weather_t(base)
=====
```

ifx (IFX) 2025.0.4 20241205

Copyright (C) 1985-2024 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpiicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

Base Portability Flags

505.lbm_t: -lstdc++

513.soma_t: -lstdc++

518.tealeaf_t: -lstdc++

521.miniswp_t: -lstdc++

(Continued on next page)

SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The Hong Kong University of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021_tny_base = 14.9

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The Hong Kong University of Science and Technology

Tested by: Information Technology Services Office

Test Date: Dec-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

Base Portability Flags (Continued)

532.sph_exa_t: -std=c++14 -lstdc++

534.hpgmgfv_t: -lstdc++

Base Optimization Flags

C benchmarks:

-march=common-avx512 -Ofast -flto -ffast-math

-mprefer-vector-width=512 -qopenmp -ansi-alias

C++ benchmarks:

-march=common-avx512 -Ofast -flto -ffast-math

-mprefer-vector-width=512 -qopenmp -ansi-alias

Fortran benchmarks:

-march=common-avx512 -Ofast -flto -ffast-math

-mprefer-vector-width=512 -qopenmp -nostandard-realloc-lhs

-align array64byte

Base Other Flags

C benchmarks:

-Wno-incompatible-function-pointer-types

C++ benchmarks:

-Wno-incompatible-function-pointer-types

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.10 on 2025-12-22 14:07:58+0800.

Report generated on 2025-12-22 15:24:06 by hpc2021 PDF formatter v112.