

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The HK Univ. of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021\_tny\_base = 13.5

SPEChpc 2021\_tny\_peak = Not Run

hpc2021 License: 7401


Test Sponsor: The HK Univ. of Science and Technology

Tested by: Information Technology Services Office

Test Date: May-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024



## Results Table

Benchmark	Base								Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio
505.lbm_t	MPI	256	1	<u>99.4</u>	<u>22.6</u>	99.4	22.6	99.5	22.6							
513.soma_t	MPI	256	1	262	14.1	<b>262</b>	<b>14.1</b>	263	14.1							
518.tealeaf_t	MPI	256	1	225	7.34	225	7.34	<b>225</b>	<b>7.34</b>							
519.clvleaf_t	MPI	256	1	235	7.02	235	7.01	<b>235</b>	<b>7.02</b>							
521.miniswp_t	MPI	256	1	183	8.73	<b>184</b>	<b>8.68</b>	186	8.62							
528.pot3d_t	MPI	256	1	305	6.97	<b>305</b>	<b>6.97</b>	306	6.95							
532.sph_exa_t	MPI	256	1	102	19.0	<b>102</b>	<b>19.0</b>	102	19.1							
534.hpgmgfv_t	MPI	256	1	135	8.70	135	8.71	<b>135</b>	<b>8.70</b>							
535.weather_t	MPI	256	1	38.4	84.1	36.1	89.3	<b>36.5</b>	<b>88.3</b>							

SPEChpc 2021\_tny\_base = 13.5

SPEChpc 2021\_tny\_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

**HKUST HPC Infra. Center: Dell AMD 9754**

(Test Sponsor: The HK Univ. of Science and Technology)

**Dell PowerEdge R6625**

**AMD EPYC 9754 (2 x 128-Core)**

**SPEChpc 2021\_tny\_base = 13.5**

**SPEChpc 2021\_tny\_peak = Not Run**

**hpc2021 License:** 7401

**Test Sponsor:** The HK Univ. of Science and Technology

**Tested by:** Information Technology Services Office

**Test Date:** May-2025

**Hardware Availability:** Sep-2024

**Software Availability:** Sep-2024

## Hardware Summary

Type of System: SMP  
Compute Node: DELL PowerEdge R6625 (AMD EPYC 9754)  
Interconnect: Cisco Nexus 9332D-GX2B  
Compute Nodes Used: 1  
Total Chips: 2  
Total Cores: 256  
Total Threads: 512  
Total Memory: 768 GB  
Total Accelerators: 0  
Max. Peak Threads: --

## Software Summary

Compiler: Intel(R) oneAPI DPC++/C++ Compiler  
2025.0.4.20241205  
MPI Library: Intel(R) MPI Library for Linux\* OS  
2021.14.20250213-0d7f579  
Other MPI Info: --  
Other Software: --  
Base Parallel Model: MPI  
Base Ranks Run: 256  
Base Threads Run: 1  
Peak Parallel Models: Not Run  
Minimum Peak Ranks: --  
Maximum Peak Ranks: --  
Max. Peak Threads: --  
Min. Peak Threads: --

## Node Description: DELL PowerEdge R6625 (AMD EPYC 9754)

### Hardware

Number of nodes: 1  
Uses of the node: Compute  
Vendor: Dell Inc.  
Model: Dell PowerEdge R6625  
CPU Name: AMD EPYC 9754  
CPU(s) orderable: 2 chips  
Chips enabled: 2  
Cores enabled: 256  
Cores per chip: 128  
Threads per core: 2  
CPU Characteristics: Base 2.25 GHz, Boost up to 3.1 GHz  
CPU MHz: 2250  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 1 MB I+D on chip per core  
L3 Cache: 256 MB I+D on chip per chip  
16 MB shared / 8 cores  
Other Cache: None  
Memory: 768 GB (24 x 32 GB DDR5-4800 at 4800MHz)  
Disk Subsystem: 2 x 2 TB SAS SSD (Raid 1)  
Other Hardware: Immersion Cooling (Direct Liquid Cooling)  
Accel Count: --  
Accel Model: --  
Accel Vendor: --  
Accel Type: --  
Accel Connection: --  
Accel ECC enabled: --  
Accel Description: --  
Adapter: Mellanox ConnectX-6 HDR MT28908  
Number of Adapters: 1  
Slot Type: PCIe 4.0 x16

(Continued on next page)

### Software

Accelerator Driver: None  
Adapter: Mellanox ConnectX-6 HDR MT28908  
Adapter Driver: 24.10-2.1.8.0  
Adapter Firmware: 20.41.1000  
Operating System: Rocky Linux 9.5  
5.14.0-503.40.1.el9\_5.x86\_64  
git-0970460-ID94f55d9  
Local File System: tmpfs  
Shared File System: Dell OneFS via NFS v3  
System State: Run level 5  
Other Software: None

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The HK Univ. of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021\_tny\_base = 13.5

SPEChpc 2021\_tny\_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The HK Univ. of Science and Technology

Tested by: Information Technology Services Office

Test Date: May-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

## Node Description: DELL PowerEdge R6625 (AMD EPYC 9754)

### Hardware (Continued)

Data Rate: 200 Gbit/s

Ports Used: 1

Interconnect Type: RoCE v2

## Interconnect Description: Cisco Nexus 9332D-GX2B

### Hardware

Vendor: Cisco  
Model: Cisco Nexus 9332D-GX2B  
Switch Model: RoCE v2 Ethernet Switch  
Number of Switches:  
Number of Ports: 32  
Data Rate: 400 Gbit/s  
Firmware: --  
Topology: --  
Primary Use: MPI & RDMA Traffic, NFS

### Software

: --

## Submit Notes

The config file option 'submit' was used.  
mpirun -np \$rank \$command

## General Notes

Environment variables set by runhpc before the start of the run:

```
I_MPI_PIN = "1"  
I_MPI_PIN_CELL = "core"  
I_MPI_PIN_PROCESSOR_LIST = "all"  
I_MPI_PIN_RESPECT_HCA = "0"
```

Additional Information:

```
Command line: align_va_addr=on amd_pstate=passive audit=0  
cgroup_no_v1=all cgroup_no_v1=named clocksource=tsc crashkernel=0  
debugfs=on default_hugepagesz=2M hugetlb_free_vmemmap=1 iommu=pt  
ipv6.disable=1 mitigations=off net.naming-scheme=v238 numa_balancing=disable  
selinux=0 tsc=reliable workqueue.default_affinity_scope=numa
```

## Compiler Version Notes

```
=====
```

```
CXXC 532.sph_exa_t(base)
```

```
-----
```

(Continued on next page)

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The HK Univ. of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021\_tny\_base = 13.5

SPEChpc 2021\_tny\_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The HK Univ. of Science and Technology

Tested by: Information Technology Services Office

Test Date: May-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

## Compiler Version Notes (Continued)

Intel(R) oneAPI DPC++/C++ Compiler 2025.0.4 (2025.0.4.20241205)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86\_64\_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-6frph2hu6pm6omjaqjksd4rf53ylgjfa/compiler/2025.0/bin/compiler

Configuration file:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86\_64\_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-6frph2hu6pm6omjaqjksd4rf53ylgjfa/compiler/2025.0/bin/compiler/./icpx.cfg

=====  
CC 505.lbm\_t(base) 513.soma\_t(base) 518.tealeaf\_t(base) 521.miniswp\_t(base)  
534.hpgmgfv\_t(base)  
=====

Intel(R) oneAPI DPC++/C++ Compiler 2025.0.4 (2025.0.4.20241205)

Target: x86\_64-unknown-linux-gnu

Thread model: posix

InstalledDir:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86\_64\_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-6frph2hu6pm6omjaqjksd4rf53ylgjfa/compiler/2025.0/bin/compiler

Configuration file:

/opt/shared/.spack-edge/opt/spack/linux-rocky9-x86\_64\_v4/gcc-11.5.0/spack/intel-oneapi-compilers-2025.0.4-6frph2hu6pm6omjaqjksd4rf53ylgjfa/compiler/2025.0/bin/compiler/./icpx.cfg

=====  
FC 519.clvleaf\_t(base) 528.pot3d\_t(base) 535.weather\_t(base)  
=====

ifx (IFX) 2025.0.4 20241205

Copyright (C) 1985-2024 Intel Corporation. All rights reserved.

## Base Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

## Base Portability Flags

505.lbm\_t: -lstdc++

(Continued on next page)

# SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

HKUST HPC Infra. Center: Dell AMD 9754

(Test Sponsor: The HK Univ. of Science and Technology)

Dell PowerEdge R6625

AMD EPYC 9754 (2 x 128-Core)

SPEChpc 2021\_tny\_base = 13.5

SPEChpc 2021\_tny\_peak = Not Run

hpc2021 License: 7401

Test Sponsor: The HK Univ. of Science and Technology

Tested by: Information Technology Services Office

Test Date: May-2025

Hardware Availability: Sep-2024

Software Availability: Sep-2024

## Base Portability Flags (Continued)

```
513.soma_t: -lstdc++
518.tealeaf_t: -lstdc++
521.miniswp_t: -lstdc++
532.sph_exa_t: -std=c++14 -lstdc++
534.hpgmgfv_t: -lstdc++
```

## Base Optimization Flags

C benchmarks:

```
-march=common-avx512 -Ofast -flto -ffast-math
-mprefer-vector-width=512 -qopt-streaming-stores always -ansi-alias
```

C++ benchmarks:

```
-march=common-avx512 -Ofast -flto -ffast-math
-mprefer-vector-width=512 -qopt-streaming-stores always -ansi-alias
```

Fortran benchmarks:

```
-march=common-avx512 -Ofast -flto -ffast-math
-mprefer-vector-width=512 -qopt-streaming-stores always
-nostandard-realloc-lhs -align array64byte
```

## Base Other Flags

C benchmarks:

```
-Wno-incompatible-function-pointer-types
```

C++ benchmarks:

```
-Wno-incompatible-function-pointer-types
```

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEChpc2021 v1.1.8 on 2025-05-23 09:17:32+0800.

Report generated on 2025-05-23 10:38:51 by hpc2021 PDF formatter v112.