UNIVERSITY OF
CHEMISTRY AND TECHNOLOGY
PRAGUE

Institute of Thermomechanics, Czech Academy of Sciences

Department of Waves in Solids

Air flow in the urban area of Hsinchu city

REPORT FROM THE STUDENT INTERNSHIP

AUTHOR	**Ing. Tomáš Hlavatý**
PROGRAMME	**NARLabs student internship programme**
YEAR	**2023**

Summary

Abstract of the report will be there

Acknowledgements

Acknowledgements for supervisors and the NARLabs.

Contents

1 Introduction

The present work arose as the part of the authors student internship in Taiwan National Applied Research Laboratories (NARLabs). The report was written out in National Center for High-performance Computing.

2 Mathematical model

In the present work, the air-flow in the inhabited area is investigated together with the transport of the pollution emerging on the main road. The chosen simulation approach is a segregated one: (i) a steady state velocity field is pre-calculated using Navier-Stokes equations, and (ii) it is used in scalar transport equation to simulate advancement of the pollution.

The present section describing the used mathematical model is structured as follows: (i) a model geometry and a computational mesh generation are presented, (ii) used boundary conditions are summarized and (iii) the governing equations are briefly outlined.

2.1 Model geometry generation and boundary conditions

As stated, the air flow and the spread of the pollution in the inhabited area is of an interest. A studied part of the city is $L_\mathrm{l} = 500\,\mathrm{m}$ long, $L_\mathrm{w} = 500\,\mathrm{m}$ wide, and the highest building is $L_\mathrm{h} = 105\,\mathrm{m}$ tall. The available *stl* file together with its dimensions and the orientation in the chosen Cartesian coordinate system is depicted in Figure 1.



Figure 1: Studied city geometry (used *stl* file) with its dimensions and chosen Cartesian coordinate system.

Computational mesh Computational mesh was prepared using the OpenFOAM `blockMesh` and `snappyHexMesh` utilities. The computational domain dimensions were determined based on the review by Pantusheva et al. [1]. In particular, we introduce both upstream, and downstream buffers in front of, and behind the city, which are in order $L_\mathrm{CFDu} = 5\,L_\mathrm{h}$, and $L_\mathrm{CFDd} = 10\,L_\mathrm{h}$ long. Furthermore, the computational domain is $L_\mathrm{CFDh} = 6\,L_\mathrm{h}$ high. The y-normal slices cut in the middle of the used computational mesh are shown in Figure 2. Note the grading of the computational mesh in the z-direction, and its refinement in the vicinity of the city.



Figure 2: y-normal slices through the half of the computational mesh.

Boundary conditions The model behavior in the computational domain (Ω) is described by partial differential equations outlined in the following subsection 2.2 (Governing equations). However, these need to be supplied with the consistent boundary conditions on the Ω boundary, $\partial\Omega$. As depicted in Figure 3, the computational domain boundary is split into (i) *inlet* ($\partial\Omega_{\mathrm{i}}$), (ii) *outlet* ($\partial\Omega_{\mathrm{o}}$), (iii) *ground* ($\partial\Omega_{\mathrm{g}}$), (iv) *sides* ($\partial\Omega_{\mathrm{s}}$), and (v) *top* ($\partial\Omega_{\mathrm{t}}$).



Figure 3: Boundaries of the computational domain.

Used boundary conditions are utilized from [1, 2] and summarized in Table 1.

Table 1: Used boundary conditions.

variable	Ω_{i}	Ω_{o}	Ω_{g}	Ω_{s}	Ω_{t}
$\boldsymbol{u}$	fixedValue	inletOutlet	noSlip	slip	slip
p	zeroGrad	totalPressure	zeroGrad	zeroGrad	zeroGrad
k	turbIntKinEngInlet	zeroGrad	kqRWallFunction	zeroGrad	zeroGrad
ε	turbMixDissRateInlet	zeroGrad	epsWallFunction	zeroGrad	zeroGrad
ν_{t}	fixedValue	zeroGrad	nutkWallFunction	zeroGrad	zeroGrad
y_{P}	zeroGrad	zeroGrad	fixedValue	zeroGrad	zeroGrad

2.2 Governing equations

The description of the chosen governing equations can be split into two parts, (i) air-flow governing equations, and (ii) the pollution

2.3 Developed OpenFOAMCase python class documentation

3 Computational environment

NCHC servers use Singularity container platform [3] and Slurm workload manager [4] to run user-defined tasks. Thus,

(i) custom singularity container, which includes necessary packages installed and compiled inside, is prepared, and

(ii) Slurm task (which runs within the container) is prepared and run at the computational server.

3.1 Preparation of the singularity container

Assuming you have super-user permission and singularity installed on local (see step-by-step guide in [5]), a preparation of the singularity container image from docker ubuntu:latest release can be done as follows:

1. Navigate outside the home directory and work here, e.g.:

   ```
   mkdir /tmp/
   mkdir /tmp/test
   cd /tmp/test/
   ```

2. New container (`./ubuntu`) can be built from ubuntu docker repository using:

   ```
   sudo singularity build --sandbox ./ubuntu docker://ubuntu:latest
   ```

   NOTE: `--sandbox` flag allows to write into container later

Shell inside container can be opened using:

```
sudo singularity shell ./ubuntu --writable
```

where `--writable` flag again allows to write into container and install packages here.

Openfoam.org/v10 and other used packages can be installed inside the container as:

```
apt update
apt install python3 python3-pip wget vim software-properties-common
    python3-tk    pip3 install matplotlib
sh -c "wget -O - https://dl.openfoam.org/gpg.key >
    /etc/apt/trusted.gpg.d/openfoam.asc"
add-apt-repository http://dl.openfoam.org/ubuntu
apt update
apt install openfoam10
```

Compilation of the custom solver inside container is done as follows:

1. Source OpenFOAM in the container shell:

   `. /opt/openfoam10/etc/bashrc`

2. Navigate to solver folder, e.g.:

   `cd /tmp/pollutionFoam`

3. Compile solver executing:

   `wmake`.

When everything is installed, the `.sif` container file can be built from prepared `/tmp/test/ubuntu` directory using:

```
sudo singularity build /tmp/test/ubuntu.sif /tmp/test/ubuntu/
```

Following the above listed guideline, singularity container image `ubuntu.sif` is created. This can be uploaded to NCHC servers and used as described in following subsection.

3.2 Preparation of Slurm control script and running the task

4 Numerical experiments

Some nice results her.

5 Conclusions

And conclusion here

6 Nomenclature

c_i	....	Molar concentration of i-th molar specie
c_T	....	Total molar concentration
Co	....	Courant number
d	....	Diameter
D_i	....	Molar diffusivity of i-th molar specie
D_i^eff	....	Effective molar diffusivity of i-th molar specie
$\boldsymbol{d}_\mathrm{PN}$	....	Vector connecting centroids of P and N
f	....	Face of the cell
$\boldsymbol{f}_b$	....	Body forces acting on cell
$\boldsymbol{g}$	....	Gravitational acceleration
h	....	Specific enthalpy
I	....	Time interval
I^h	....	Discretized time interval
m	....	Number of discretized FV cells
M	....	Molar mass
n	....	Number of species
$\boldsymbol{n}$	....	Outer normal vector
$\boldsymbol{n}_f$	....	Outer normal vector of the face f
p	....	Pressure
p_ref	....	Reference pressure
$\tilde{p}$	....	Kinematic pressure
Q	....	Computational domain
r_i	....	Reaction source of the i-th molar specie
R^g	....	Universal gas constant
Re	....	Reynolds number
s_ϕ	....	Source of the ϕ
$\boldsymbol{S}_f$	....	Face area vector
t	....	Time
T	....	Temperature
T_ref	....	Reference temperature
$\boldsymbol{u} = (u, v, w)$	....	Velocity
y_i	....	Molar fraction of the i-molar specie
α	....	Heat transfer coefficient
ε	....	Porosity
Γ_ϕ	....	Diffusivity of ϕ
κ	....	Permeability
λ	....	Heat conductivity
μ	....	Dynamic viscosity
ν	....	Kinematic viscosity
Ω	....	Domain
Ω^h	....	Discretized domain
Ω_P^h	....	Cell P
$\delta\Omega_i^h$	....	Volume of the cell
$\partial\Omega$	....	Domain boundary
ϕ	....	Intensive tensorial quantity
ϕ_P	....	Value of ϕ in the cell centroid of cell P

ϕ_f	....	Value of ϕ in the face centroid of face f
$\mathbf{\Phi}_\phi$	....	Flux intensity of ϕ
$\mathbf{\Phi}_{\phi,\mathrm{conv}}$	....	Convective flux intensity of ϕ
$\mathbf{\Phi}_{\phi,\mathrm{diff}}$	....	Diffusive flux intensity of ϕ
ρ	....	Fluid mass density
Σ	....	Total stress tensor
τ	....	Tortuosity
$\boldsymbol{\tau}$	....	Viscous stress tensor
∇	....	Nabla differential operator

References

[1] Mariya Pantusheva et al. "Air Pollution Dispersion Modelling in Urban Environment Using CFD: A Systematic Review". In: *Atmosphere* 13.10 (2022). DOI: `10.3390/atmos13101640`.

[2] Rakesh Kadaverugu et al. "Improving accuracy in simulation of urban wind flows by dynamic downscaling WRF with OpenFOAM". In: *Urban Climate* 38 (2021), p. 100912. DOI: `https://doi.org/10.1016/j.uclim.2021.100912`.

[3] SingularityCE Project Contributors. *SingularityCE User Guide*. `https://docs.sylabs.io/guides/main/user-guide.pdf`. Accessed: 20-2-2023.

[4] Andy B. Yoo, Morris A. Jette and Mark Grondona. "SLURM: Simple Linux Utility for Resource Management". In: *Job Scheduling Strategies for Parallel Processing*. 2003.

[5] SingularityCE Project Contributors. *SingularityCE Installation*. `https://docs.sylabs.io/guides/3.0/user-guide/installation.html`. Accessed: 20-2-2023.

Potencial appendix here.