

# RBE549 - Homework 4

Keith Chester

Due date: September 29, 2022

## Problem 0

## Problem 1

## Problem 2

In this problem, we are looking at a Hough Transform problem where  $x$ ,  $y$ ,  $b$ ,  $c$ ,  $m$ , and  $n$  may be positive or negative real numbers. 2 points in  $(x, y)$  space are given by  $P_1 = (2, 4)$  and  $P_2 = (4, 3)$ .

### A

First, we are tasked with finding  $L_1$  and  $L_2$ , the lines associated in  $(m, b)$  space corresponding to  $P_1$  and  $P_2$ .

For this we must first solve for  $m$  and  $b$  to form lines for  $(m, b)$  space. Given that  $y = mx + b$ , we have:

$$L_1 : 4 = 2m + b \tag{1}$$

$$L_1 : b = -2m + 4 \tag{2}$$

$$L_2 : 3 = 4m + b \tag{3}$$

$$L_2 : b = -4m + 3 \tag{4}$$

### B

Next we are tasked with finding the intersection of these lines. Thus we can set  $L_1 = L_2$  and find:

$$-2m + 4 = -4m + 3 \tag{5}$$

$$1 = -2m \tag{6}$$

$$m = -\frac{1}{2} \tag{7}$$

...and then solve for  $b$  using our discovered  $m$ :

$$b = -2\left(-\frac{1}{2}\right) + 4 = 5 \tag{8}$$

Thus we find a point in  $(m, b)$  space such that  $L_1 = L_2$  at  $(-\frac{1}{2}, 5)$ .

### C

In this section, we are then asked what line connects both  $P_1$  and  $P_2$ . This line is what we discovered in part B, wherein we found the intersection of  $L_1$  and  $L_2$ :  $y = -\frac{1}{2}x + 5$ .

## D

We are tasked on finding where  $L_3$ , which passes through  $(m, b)$  space of  $(0, 0)$  and find the corresponding  $P_3$  with it. For this we solve the intersection along the  $b$  axis. Since  $b = -mx + y$ , we get  $0 = -0x + y$  and thus  $y = 0$ .

Now that we know  $y = 0$ , we can solve for  $x$ :

$$0 = -\frac{1}{2}x + 5 \quad (9)$$

$$x = 10 \quad (10)$$

Now that we have the point  $P_3 = (10, 0)$  we can translate this back to  $(m, b)$  space:

$$b = -mx + y \quad (11)$$

$$b = -10m + 0 \quad (12)$$

...which is our resulting  $L_3$ .

## Problem 3

## Problem 4

In this problem we are tasked with answering questions about Feature Detectors.

### A

In the SIFT detector, the local histogram of edge directions is computed; we are asked to explain briefly how this information is used and why it is needed. My response:

The edge directions allow us to identify and track the features (and thus objects) within a given image while being agnostic to a given image's lighting and, combined with other techniques, can even provide orientation agnostic labels to identify with.

### B

We are asked why in the HoG feature detector the  $128 \times 64$  window (height, width) is utilized. This is because the original HoG was focused on detecting humans - this window was discovered to be the most likely to properly frame humans in their dataset (twice as tall as wide) and thus used.