
AIRCHILD
MICONDUCTOR®

July 2008

IP31/TIP31A/TIP31B/TIP31C
PN Epitaxial Silicon Transistor

atures
Complementary to TIP32/TIP32A/TIP32B/TIP32C



1. Base 2. Collector 3. Emitter

solute Maximum Ratings T_C=25°C unless otherwise noted


Symbol	Parameter	Value	Units
CBO	Collector-Base Voltage : TIP31	40	V
	: TIP31A	60	V
	: TIP31B	80	V
	: TIP31C	100	V
CEO	Collector-Emitter Voltage : TIP31	40	V
	: TIP31A	60	V
	: TIP31B	80	V
	: TIP31C	100	V
EBO	Emitter-Base Voltage	5	V
	Collector Current (DC)	3	A
P	Collector Current (Pulse)	5	A
	Base Current	1	A
C	Collector Dissipation (T_C=25°C)	40	W
	Collector Dissipation (T_a=25°C)	2	W
J	Junction Temperature	150	°C
STG	Storage Temperature	- 65 ~ 150	°C

TIP31/TIP31A/TIP31B/TIP31C — NPN Epitaxial Silicon Transistor

life.augmented

TIP120, TIP121, TIP122
TIP125, TIP127
Datasheet

Low voltage complementary power Darlington transistors



TO-220

Features
- Low collector-emitter saturation voltage
- Complementary NPN - PNP transistors

Application
- General purpose linear and switching

Description
The devices are manufactured in planar technology with "base island" layout and monolithic Darlington configuration. The resulting transistors show exceptional high gain performance coupled with very low saturation voltage.



