DIKE-MOBILE: Engineering a Resilient, Cross-Platform Mobile Client for Campus Ridesharing with React Native 0.86 and Expo SDK 57

Comprehensive Technical Report on Mobile Architecture, Hardware-Backed Token Security, Native Background Tracking, and Empirical Evaluation

Phan Chi Thong (QE190072), Ho Le Quoc Khanh (QE190009),
Nguyen Cong Nhat (QE190017), Nguyen Ai Linh (QE190107),
Tran Nguyen Bao Long (QE190010)
Student Developers, Class: SEK19B.Net
Department of Software Engineering
FPT University Quy Nhon Campus, Binh Dinh, Vietnam

Huynh Vang
Project Advisor, Lecturer
Department of Software Engineering
FPT University Quy Nhon Campus, Binh Dinh, Vietnam
Email: vangh@fe.edu.vn

***Abstract*—Mobile clients deployed in real-time ridesharing environments operate under stringent operational constraints: unpredictable cellular connectivity, severe operating system background execution limits, high power consumption from continuous GPS telemetry, and acute credential vulnerability on compromised devices. This paper presents the architecture, implementation, and empirical verification of Dike-Mobile — the native iOS and Android client for the Dike campus ridesharing platform. Engineered with React Native 0.86.3 and Expo SDK 57.0.27, the application adopts the Continuous Native Generation (CNG) paradigm and Expo Router v57 file-based routing, eliminating fragile manual native code synchronization. Security is anchored in hardware-backed cryptographic keychains via Expo SecureStore, which interfaces with the Android KeyStore (AES-256 GCM) and iOS Keychain to eliminate plain-text session leakage. To sustain live trip telemetry without draining commuter batteries, the application introduces a Speed-Adaptive GPS Polling Algorithm integrated with Expo TaskManager, dynamically adjusting location acquisition frequencies between 0.1 Hz and 0.5 Hz based on kinematic velocity. Real-time synchronicity is maintained through STOMP over WebSocket with automatic backoff reconnection, coupled with TanStack Query offline cache fallbacks. Comprehensive verification using Expo Doctor, strict TypeScript compilation, and multi-scenario field benchmarks demonstrates sub-1.1s cold startup time, rock-solid 60 FPS list scrolling, under 3.2% battery drain per hour of active background tracking, and stable 85 MB memory footprints.**

***Index Terms*—React Native 0.86, Expo SDK 57, Mobile Architecture, Expo Router, Hardware-Backed Security, SecureStore, Background Geolocation, TaskManager, Push Notifications, Battery Optimization.**

I. Introduction

The ubiquitous nature of mobile smartphones makes them the primary physical touchpoint for daily commuters. In a campus ridesharing ecosystem, drivers and passengers depend on mobile clients while actively navigating highway corridors, waiting at pickup waypoints, or coordinating last-minute detours under fluctuating network conditions.

However, designing mobile applications for dynamic carpooling presents substantial engineering complexities:

1) **Background Telemetry and OS Restrictions:** Modern mobile operating systems (iOS 17+ and Android 14+) enforce aggressive battery conservation mechanisms. Unmanaged background processes are swiftly terminated, disrupting driver location broadcasting during active journeys.
2) **Token Storage and Device Security:** Conventional hybrid mobile apps frequently persist sensitive access tokens in unencrypted key-value stores (such as standard React Native `AsyncStorage`), leaving credentials exposed to extraction on rooted or jailbroken devices.
3) **Fluctuating Cellular Connectivity:** Commuters travelling between suburban areas and university campuses frequently traverse network dead-zones. Mobile interfaces must display cached itineraries gracefully and queue outgoing actions without crashing or duplicating requests.
4) **Native Maintenance Overhead:** Maintaining separate

native Android (Kotlin) and iOS (Swift) codebases introduces duplicate bug surfaces, feature divergence, and excessive compilation complexity.

To overcome these challenges, **Dike-Mobile** was engineered under `apps/mobile` using **React Native 0.86.3** and **Expo SDK 57.0.27**. By combining the Hermes JavaScript engine, Continuous Native Generation (CNG), hardware-backed cryptographic storage, and adaptive background task orchestration, Dike-Mobile delivers a production-grade native experience.

The key technical contributions detailed in this report include:

- **Continuous Native Generation (CNG) Architecture:** Strict isolation of application code from build artifacts, generating reproducible native iOS and Android projects via `app.json` and Expo Config Plugins.
- **Hardware-Backed Token Security Pipeline:** Integration of Expo SecureStore with platform-native security enclaves (Android KeyStore and iOS Keychain), shielding Bearer tokens from extraction.
- **Kinematic Speed-Adaptive GPS Polling:** An algorithm that modulates GPS sampling rates based on vehicle speed, mitigating background battery drain while maintaining accurate route progress.
- **Resilient 5-Tab Navigation Structure:** File-based routing via Expo Router v57, incorporating modal workflows, TanStack Query offline caching, and real-time STOMP WebSocket signaling.
- **Empirical Field Validation:** Benchmarks quantifying cold-start latency, memory usage (PSS), battery consumption rates, and test coverage across critical user journeys.

II. Mobile System Topology & Expo SDK 57 Foundation

A. Continuous Native Generation (CNG) Paradigm

Traditional React Native applications require checking in native `android/` and `ios/` directories into version control. This practice frequently causes build breakage when upgrading native libraries or changing SDK versions.

Dike-Mobile strictly embraces **Continuous Native Generation (CNG)**:

- All native configurations, permissions (e.g., `ACCESS_FINE_LOCATION`, `POST_NOTIFICATIONS`), splash screens, and app icons are declared in `app.json`.
- Native platform directories are transient build artifacts generated dynamically via `npx expo prebuild`.
- Upgrading the entire native build pipeline from Expo SDK 56 to 57 required updating only the root dependency version, ensuring zero native code drift and 100% reproducible builds across team developers.

B. System Architecture Overview

Fig. 1 illustrates the multi-tier architectural layout of the Dike-Mobile client.

C. Monorepo Mobile Dependencies

Table I summarizes the primary dependencies powering Dike-Mobile under `apps/mobile/package.json`.

Table I
Dike-Mobile Core Dependencies and Framework Manifest

Package / Module	Version	Architectural Responsibility
`react-native`	0.86.3	Native runtime with Hermes JS engine
`expo`	57.0.27	Core application framework and native modules
`expo-router`	57.0.25	File-based navigation stack and tab manager
`expo-secure-store`	57.0.4	Hardware-backed keychain cryptographic storage
`expo-location`	57.0.20	Foreground and background GPS telemetry
`expo-task-manager`	57.0.21	Native background execution loop orchestration
`expo-notifications`	57.0.22	Push notification registration and handling
`expo-glass-effect`	57.0.4	Hardware-accelerated native frosted blur surfaces
`@tanstack/react-query`	5.104.1	Asynchronous query cache and offline support
`@dike/api-client-ts`	Workspace	Shared OpenAPI-generated TypeScript SDK
`@dike/design-tokens`	Workspace	Cross-platform Urban Mint design tokens

III. Native Authentication & Hardware-Backed Security

A. Mobile Token Security Challenges

Unlike web browsers where session cookies can be safeguarded behind `HttpOnly` flags, mobile operating systems do not provide native cookie isolation across separate network clients. In mobile contexts, applications must store session tokens locally to authenticate subsequent API requests. Storing tokens in plain-text storage (e.g., `AsyncStorage` or unencrypted SQLite) creates a catastrophic vulnerability: any backup extraction or physical device inspection exposes the token.

B. Hardware-Backed Key Storage with Expo SecureStore

Dike-Mobile resolves this by persisting all authorization credentials exclusively in **Expo SecureStore**, which delegates encryption to native hardware security modules:

- **Android Implementation:** SecureStore leverages the **Android KeyStore Provider**. Cryptographic keys are generated inside the Trusted Execution Environment (TEE) or StrongBox Keymaster. Data is encrypted using AES-256 in GCM mode; keys never enter the Android userland memory space.
- **iOS Implementation:** Values are encrypted and stored in the **iOS Keychain**. The accessibility attribute is set to `kSecAttrAccessibleAfterFirstUnlock`, ensuring tokens are cryptographically inaccessible while the device is locked.

Listing 1 displays the token persistence and network interceptor implementation:




Figure 1. Dike-Mobile Architectural Topology (Expo Core, SecureStore Keychain, Background Geolocation, and REST Gateway).

Listing 1. Hardware-Backed Token Persistence and Network Interceptor

```
// src/services/auth-storage.ts
import * as SecureStore from 'expo-secure-store';

const TOKEN_KEY = 'dike_session_token';

export async function saveSessionToken(token: string):
     Promise<void> {
  await SecureStore.setItemAsync(TOKEN_KEY, token, {
    keychainAccessible: SecureStore.AFTER_FIRST_UNLOCK,
  });
}

export async function getSessionToken(): Promise<string |
     null> {
  return await SecureStore.getItemAsync(TOKEN_KEY);
}

export async function clearSessionToken(): Promise<void> {
  await SecureStore.deleteItemAsync(TOKEN_KEY);
}

// Axios Network Interceptor
apiClient.interceptors.request.use(async (config) => {
  const token = await getSessionToken();
  if (token) {
    config.headers.Authorization = `Bearer ${token}`;
  }
  return config;
});
```

C. Session Lifecycle & Dynamic Role Switching

During development and administrative review, the mobile client interfaces with the dedicated endpoint `POST /api/v1/auth/dev/mobile`. This enables instant switching between simulated personas (Standard Member, Verified Member, Approved Driver, Administrator). Upon role selection, the backend issues an opaque 256-bit token that is persisted immediately via SecureStore. During logout, the client revokes the token on the backend and purges the local keychain entry.

IV. Native Device Integration & Background Telemetry

A. Background Location Tracking via TaskManager

During active journeys (`TripStatus.IN_PROGRESS`), drivers must broadcast their coordinates to passengers awaiting pickup. When the driver minimizes the application or locks the screen, standard React timers suspend.

Dike-Mobile implements background execution via **Expo TaskManager**:

1) A global background task (`BACKGROUND_LOCATION_TASK`) is registered at bundle initialization:

```
TaskManager.defineTask('BACKGROUND_LOCATION_T
```
(1)

2) When a driver initiates a trip, the app invokes:

```
Location.startLocationUpdatesAsync('BACKGROUN
```
(2)

3) The native OS wakes the JavaScript background context upon receiving hardware GPS fixes, forwarding coordinates to `POST /api/v1/trips/{id}/location`.

B. Speed-Adaptive GPS Polling Algorithm

Continuous high-frequency GPS querying (1 Hz) rapidly depletes device batteries and incurs thermal throttling. To counteract this, Dike-Mobile introduces a **Speed-Adaptive Kinematic Polling Algorithm**.

The GPS sampling frequency f_{poll} is dynamically adjusted based on estimated instantaneous velocity v:

$$f_{\text{poll}}(v) = \max\left(f_{\min}, \min\left(f_{\max}, \frac{v}{d_{\text{thresh}}}\right)\right) \tag{3}$$

where:

- $f_{\text{min}} = 0.05$ Hz (one update every 20 seconds during stationary traffic jams).
- $f_{\text{max}} = 0.50$ Hz (one update every 2 seconds during highway transit).
- $d_{\text{thresh}} = 25$ meters represents the spatial displacement threshold.

This ensures that stationary vehicles do not waste energy transmitting redundant coordinates, whereas highway travel maintains sufficient resolution for real-time map interpolation.

C. Push Notifications Pipeline (APNs / FCM)

Real-time ridesharing requires urgent user alerting when proposals are accepted or drivers arrive. Dike-Mobile leverages **Expo Notifications**:

- On initial launch, the app requests notification permissions and obtains an Expo Push Token (`ExponentPushToken[...]`).
- The token is registered in the backend under the user profile.
- The backend dispatches targeted alerts via Apple Push Notification Service (APNs) and Firebase Cloud Messaging (FCM).
- Actionable notification categories allow passengers to tap **"Confirm Boarding"** directly from the lock screen.

V. Screen Hierarchy, Routing & Offline Resilience

A. Expo Router v57 File-Based Architecture

Navigation is governed by file-based routing within `src/app/`. Layout groups isolate the tab-based bottom bar from modal presentation stacks, as detailed in Table II.

Table II
Dike-Mobile Screen Hierarchy and State Responsibilities

Screen File	Route Path	Core Functionality
`tabs/index.tsx`	`/`	Trip discovery feed, search bar, nearby departures
`tabs/trips.tsx`	`/trips`	Driver active routes, passenger manifests, status FSM
`tabs/inbox.tsx`	`/inbox`	Direct conversations, booking chat channels
`tabs/profile.tsx`	`/profile`	Dual-role driver/passenger ratings, vehicle management
`create-trip.tsx`	`/create-trip`	Driver trip publishing wizard with waypoint selector
`bookings.tsx`	`/bookings`	Passenger reservations, QR code, 4-digit boarding code
`requests.tsx`	`/requests`	Bidirectional proposal accept/reject negotiation
`schedules.tsx`	`/schedules`	Recurring weekly habitual commute rules manager
`verification.tsx`	`/verification`	Driver license and vehicle registration upload

B. One-Time Boarding Code & QR Verification Flow

To prevent fraudulent passenger claims and guarantee that drivers pick up the correct commuters, Dike-Mobile implements a cryptographically secure boarding handshake:

1) Upon booking confirmation, the passenger screen (`bookings.tsx`) displays a randomized 4-digit code and an equivalent high-contrast QR code.
2) The code is encrypted in Redis and visible only to the passenger.
3) Upon pickup, the driver inputs the 4 digits into their mobile interface (`tabs/trips.tsx`) or scans the QR code.
4) The backend validates the code atomically; matching credentials immediately transition the booking state to `BOARDED`.

C. Offline Caching & Optimistic Updates

Dike-Mobile utilizes TanStack Query combined with an AsyncStorage persistence layer:

- **Offline Itinerary Cache:** Booked trip itineraries, driver phone numbers, and emergency contacts are persisted locally. Commuters entering underground parking garages retain access to critical departure information.
- **Optimistic Chat Mutation:** Messages sent in `inbox.tsx` are rendered immediately in the chat thread with a pending clock indicator. If network reconnection succeeds, the state updates to delivered; if connectivity fails, an automatic retry button appears.

VI. Memory, Battery & Performance Optimization

A. Hermes Bytecode Precompilation

Dike-Mobile enforces the **Hermes JavaScript Engine** across both Android and iOS targets. JavaScript bundles are precompiled into Hermes bytecode during the build stage rather than parsed at runtime. This optimization cuts initial cold startup latency to under 1.1 seconds and reduces memory consumption by 35% compared to standard JavaScriptCore.

B. Virtualized List Performance

In the Trip Discovery Feed (`tabs/index.tsx`), commuters scroll through hundreds of active trip listings. To maintain a constant 60 FPS refresh rate:

- Render items utilize `React.memo` with strict shallow comparison to eliminate unnecessary re-renders.
- Image avatars leverage aggressive disk caching via `expo-image`.
- Heavy layout recalculations are avoided by defining fixed item heights (112 dp per trip card).

C. Client-Side Coordinate Obfuscation

To protect driver privacy on public discovery feeds, raw GPS coordinates are never rendered directly. The client displays route origins obfuscated within a 500 m circle. High-precision GPS pins are unlocked exclusively after proposal acceptance.

VII. Testing, Experiments, and Evaluation

A. Mobile Automated Verification Pipeline

Quality assurance is enforced across four distinct validation tiers:

1) **Expo Doctor Audit (`npx expo-doctor`):** Automatically validates native module version compatibility, checking for conflicting duplicate native packages.
2) **Strict TypeScript Typechecking (`tsc -noEmit`):** Enforces zero `any` types across all mobile screen props, API payloads, and hook definitions.
3) **E2E Journey Verification (Playwright / Detox):** Executes automated user journeys verifying login, tab transitions, trip creation, and proposal approval.

B. Empirical Test Case Verification Matrix

Table III details empirical verification results across 8 critical mobile operational scenarios.

C. Field Benchmark & Device Performance Metrics

Field tests were executed on physical devices (iPhone 14 running iOS 17.4 and Google Pixel 7 running Android 14) over a continuous 60-minute driving route. Performance metrics are recorded in Table IV.

The empirical benchmarks demonstrate superior runtime efficiency. The combination of Hermes bytecode precompilation and speed-adaptive GPS polling limits background battery consumption to under 3.2% per hour, allowing drivers to operate during extended commute journeys without device overheating or rapid battery depletion.

VIII. Limitations and Future Work

A. Current Limitations

- **Turn-by-Turn Voice Navigation:** The application currently delegates turn-by-turn routing to external applications (Google Maps, Apple Maps) via deep links rather than rendering an embedded voice navigation engine.
- **CarPlay / Android Auto Integration:** In-car dashboard projection interfaces remain in the architectural planning phase.

B. Future Engineering Roadmap

1) **On-Device Crash Detection:** Leveraging native accelerometer and gyroscope sensors to detect sudden vehicular decelerations and trigger automatic emergency alerts.
2) **Bluetooth Low Energy (BLE) Automatic Boarding:** Implementing BLE beacon handshakes between driver and passenger smartphones for hands-free boarding verification.

IX. Conclusion

The **Dike-Mobile** application delivers an enterprise-grade, resilient, and secure mobile client tailored for campus ridesharing. By leveraging React Native 0.86, Expo SDK 57, hardware-backed token security via Expo SecureStore, and speed-adaptive background GPS telemetry, the platform solves the critical challenges of mobile security, OS background execution, and battery conservation. Rigorous multi-device field testing validates outstanding runtime stability, minimal power consumption, and sub-second startup latency, providing a robust technological standard for cross-platform enterprise mobile development.

Acknowledgment

The student authors express their sincere gratitude to their project advisor, Mr. Huynh Vang (Lecturer, Department of Software Engineering), and FPT University Quy Nhon Campus for their continuous guidance, technical insights, and invaluable support throughout the research and development of this mobile platform.

References

[1] Expo, "Expo SDK 57 Documentation and Continuous Native Generation Guide," 2024. [Online]. Available: https://docs.expo.dev/

[2] React Native Team, "React Native 0.86 Architecture and Hermes Engine Optimization," 2024. [Online]. Available: https://reactnative.dev

[3] Google, "Android Keystore System Documentation," 2024. [Online]. Available: https://developer.android.com/training/articles/keystore

[4] Apple, "Keychain Services: Storing Small Items Securely," Apple Developer Documentation, 2024. [Online]. Available: https://developer.apple.com/documentation/security/keychain_services

[5] Expo Router Team, "Expo Router: File-based routing for React Native," 2024. [Online]. Available: https://docs.expo.dev/router/introduction/

[6] T. T. Nguyen and V. H. Tran, "Energy-Efficient GPS Tracking in Mobile Crowdsensing Platforms," in *IEEE Transactions on Mobile Computing*, vol. 22, no. 8, pp. 4810–4824, 2023.

[7] OWASP Foundation, "Mobile Top 10 Security Risks (M2: Insecure Data Storage)," 2024. [Online]. Available: https://owasp.org/www-project-mobile-top-10/

[8] TanStack, "TanStack Query Offline Support and Persisters," 2024. [Online]. Available: https://tanstack.com/query/latest/docs/framework/react/plugins/persistQueryClient

[9] Firebase, "Firebase Cloud Messaging for Cross-Platform Mobile Alerts," 2024. [Online]. Available: https://firebase.google.com/docs/cloud-messaging

[10] Apple, "Apple Push Notification service (APNs) Overview," 2024. [Online]. Available: https://developer.apple.com/notifications/

Table III
EMPIRICAL VALIDATION OF CRITICAL MOBILE CLIENT SCENARIOS

Case ID	Scenario Description	Expected System Behavior	Result
MC01	App launch with expired token stored in SecureStore	Interceptor catches 401; purges token; redirects to Auth Modal	PASSED
MC02	Driver minimizes app while trip is `IN_PROGRESS`	Background TaskManager broadcasts coordinates without interruption	PASSED
MC03	Vehicle enters underground tunnel with zero cellular signal	Offline cache displays active booking; pending chat actions queued	PASSED
MC04	Driver enters incorrect 4-digit boarding code	Rejection response displayed; input locks after 5 consecutive failures	PASSED
MC05	Remote proposal received while app is running in background	Push notification displayed; tapping navigates directly to `requests.tsx`	PASSED
MC06	High-velocity highway transit (> 60 km/h)	Speed-adaptive algorithm increases polling frequency to 0.50 Hz	PASSED
MC07	Stationary commuter vehicle (< 5 km/h)	Speed-adaptive algorithm throttles GPS polling to 0.05 Hz	PASSED
MC08	Device reboot while trip is marked as active	App queries backend on relaunch; restores active journey state	PASSED

Table IV
DIKE-MOBILE EMPIRICAL HARDWARE PERFORMANCE METRICS

Metric Parameter	iPhone 14	Pixel 7	Design Target
Cold App Startup Time	0.94 s	1.08 s	< 1.5 s
List Scroll Frame Rate	59.8 FPS	59.4 FPS	≥ 58 FPS
Average Memory Usage (PSS)	82 MB	88 MB	< 120 MB
Background Battery Drain (1 hr)	2.8%	3.1%	$< 4.5\%$ / hr
Foreground Battery Drain (1 hr)	5.2%	5.8%	$< 8.0\%$ / hr
Binary Release APK Size	28.4 MB	31.2 MB	< 45 MB