Dike Testing Document

Test strategy, recorded results and acceptance plan
PRN232 | SEK19B.Net | 31 October 2026

Team member	Student ID
Phan Chi Thông	QE190072
Hồ Lê Quốc Khánh	QE190009
Nguyễn Công Nhất	QE190017
Nguyễn Ái Linh	QE190107
Trần Nguyễn Bảo Long	QE190010

Project advisor: Huynh Vang | vangh@fe.edu.vn

Scope and objectives

This document covers the Next.js website, Spring Boot backend, shared API contract and static mobile checks. It distinguishes executed checks from planned scenarios and unfinished acceptance. The main risks are unauthorized access, stale client state, invalid lifecycle transitions, duplicate operations and incorrect seat allocation.

Test environment

Documented prerequisites: Node.js 24.21.0, pnpm 12.9.1, Java 21, Maven Wrapper 3.9.10 and Docker. The recorded unit, typecheck and contract runs used Node.js 24.21.0. Docker Engine was unavailable, so Testcontainers integration tests were not executed.

Source and version scope

Repository: https://github.com/hlqkhanh/Dike-v2
Recorded branch: codex/free-demo-deployment
Recorded HEAD: d46c8916e44f14e0dc844f88817c8ae50abdeac4

The working tree included uncommitted edits. HEAD does not identify all local changes. The remote repository and hosted applications were not verified to match every local change.

Test methods

Vitest checks web logic; JUnit, Mockito and architecture checks exercise backend code; Playwright checks controlled browser workflows; Testcontainers is intended for real database integration; the generated client check compares the stored OpenAPI contract with TypeScript. Existing scripts alone are not evidence of a passing run.

Recorded execution results

Check	Recorded result
Web unit tests	PASS: 5 files, 23 tests
Workspace typechecking	PASS: web, mobile and shared packages
OpenAPI and generated client	PASS: contract check exit 0
Backend unit and architecture	PASS: 228 tests; 0 failures, errors or skips
Selected web E2E	PASS: 38 tests in approximately 3.1 minutes
Hosted web and OpenAPI	PASS: HTTP 200
API liveness and readiness	PASS: HTTP 200; status UP
Testcontainers integration	BLOCKED: Docker Engine unavailable
Full E2E and overall gate	NOT RUN: complete E2E, build and pnpm check
Load, devices and Google OAuth	NOT RUN: 500-user load, physical devices and complete Google login

The selected E2E run used auth-guard.spec.ts and unified-ride-flow.spec.ts with two workers, across Chromium and mobile Chromium. These specifications use mock API responses. They verify browser behavior, not a complete web-API-database journey. Mobile Chromium is a browser viewport, not the Expo application on Android or iOS.

Commands used for successful checks

```
pnpm --filter @dike/web test

pnpm -r --if-present typecheck

pnpm api:check

.\mvnw.cmd -B -ntp -DskipITs test

pnpm --filter @dike/web exec playwright test

  auth-guard.spec.ts unified-ride-flow.spec.ts --workers=2
```

The Playwright command is shown across two lines for readability; run it as one command. Install dependencies first with pnpm install --frozen-lockfile. Testcontainers requires a running Docker Engine and Maven verify. The complete pnpm check gate must be run separately before claiming it passes.

Hosted check

At approximately 17:32 on 31 October 2026 (Asia/Saigon), the website returned HTTP 200. Backend liveness, readiness and OpenAPI also returned HTTP 200; both health responses contained status UP. URLs are supplied in Deployment_Links.txt. This check did not exercise authenticated business operations.

Test scenarios and traceability 1

The rows below are planned scenarios and traceability. A passing suite does not mean every manual scenario or provider integration has been accepted.

ID	Action and expected outcome	Coverage and execution scope
AUTH-01	Open a protected route without a session. **Expected:** Redirect to login and do not expose private page content.	auth-guard.spec.ts; selected suite passed
AUTH-02	Complete Google sign-in, refresh, then log out. **Expected:** Session persists while valid and is revoked after logout.	Hosted end-to-end acceptance not run
AUTH-03	Send a missing or invalid mobile credential. **Expected:** Reject access; do not grant a default identity.	MobileSessionTransportTest and MobileSessionIdResolverTest
AUTH-04	Send a mutation from an untrusted origin. **Expected:** Block the request under the configured origin policy.	TrustedOriginFilterTest and SecurityConfigurationTest
AUTH-05	Expire the session while using a protected flow. **Expected:** Show the expected recovery or sign-in state.	Session-expiry unit tests and selected auth-guard E2E
PROFILE-01	Read or change a profile with different users. **Expected:** Apply ownership and profile visibility rules.	ProfileServiceTest and ProfileSocialPolicyTest
SOCIAL-01	Request friendship, respond, unfriend and block. **Expected:** Update relationships and revoke access when required.	SocialServiceTest; complete social E2E not run
PLAN-01	Create recurring schedules and exceptions. **Expected:** Validate time/date rules and avoid duplicate intents.	ScheduleServiceTest and TravelIntentMaterializerTest
PLAN-02	Request places or routes when a provider fails. **Expected:** Return an explicit error without fabricating a route.	PlaceServiceTest and RoutePlanningServiceTest
POST-01	Use driver/passenger forms with existing route data. **Expected:** Retain route context and open the correct form.	unified-ride-flow.spec.ts; selected suite passed
POST-02	Submit an incompatible pickup place or time. **Expected:** Return compatibility information and a valid reason.	PickupCompatibilityServiceTest and RidePostPickupResponseTest

Test scenarios and traceability 2

The rows below are planned scenarios and traceability. A passing suite does not mean every manual scenario or provider integration has been accepted.

ID	Action and expected outcome	Coverage and execution scope
POST-03	Inspect a post discussion using different identities. **Expected:** Restrict content and actions to the authorized users.	Post discussion E2E exists; full suite not run
RIDE-01	Accept an eligible proposal. **Expected:** Create the booking and update seat availability.	RideServiceTest; real database acceptance still required
RIDE-02	Compete concurrently for the final seat. **Expected:** Commit only valid results and never exceed capacity.	RideAcceptanceIT; blocked by Docker availability
RIDE-03	Repeat an acceptance or use stale state. **Expected:** Avoid duplicate booking and report conflict correctly.	RideAcceptanceIT and RideLifecycleTest; integration not run
MSG-01	Send and read messages as a nonparticipant. **Expected:** Permit conversation members only.	MessagingServiceTest and RealtimeTicketServiceTest
EVENT-01	Fail outbox processing and retry. **Expected:** Preserve the event and avoid duplicated business effects.	OutboxWorkerTest; MongoFoundationIT not run
ADMIN-01	Use a normal member against administrative actions. **Expected:** Deny unauthorized access and audit valid admin actions.	Backend security tests; complete admin E2E not run
UI-01	Repeat browser workflows at desktop/mobile viewport. **Expected:** Keep navigation and form actions usable.	38 selected E2E tests across two browser projects
UI-02	Run accessibility assertions on key screens. **Expected:** Meet the specific assertions in the automated suite.	accessibility.spec.ts exists; full suite not run
MOB-01	Exercise native login, maps and post details. **Expected:** Show correct navigation and map state on devices.	Static typecheck passed; native acceptance not run
DEPLOY-01	GET web, API health and OpenAPI URLs. **Expected:** Receive HTTP 200 and healthy API status.	Recorded probes passed; business acceptance separate

Acceptance and defect handling

Before broader release, execute the complete browser suite and integrated journeys with real API/database state, then run Maven verify and the complete pnpm check gate on the same source snapshot. Verify provider integrations, deployment version alignment and physical Android/iOS behavior. Record defects with reproduction steps, expected/actual behavior, environment, severity and evidence. Do not change NOT RUN or BLOCKED to PASS merely because a test file exists.

The hosted demo disables OTP, storage and routing. Expected demo restrictions do not demonstrate functioning production adapters. No measured 500-user capacity, Core Web Vitals, mobile battery/FPS or cold-start performance is claimed.