# LIBRELANE FLOW

*A practical guide to chip design flow*

Daniel Arevalos

Fakultät 07 – Hochschule München

# Table of Contents

# What is Librelane?

An open-source, configurable digital ASIC flow built on open-source EDA tools, designed for education and real-world chip design.



**Information on:** Librelane, OpenROAD

**More**

# Architectural Overview

# Config File

```
{
  "DESIGN_NAME": "my_design",
  "VERILOG_FILES": [
    "src/my_design.v"
  ],
  "CLOCK_PORT": "clk",
  "CLOCK_PERIOD": 10,

  "FP_CORE_UTIL": 50,
  "FP_ASPECT_RATIO": 1.0

  "PL_TARGET_DENSITY": 0.55,
}
```

**More Information on:** Config File

- ▶ Design Definition: Defines the logical identity of the design and specifies the RTL sources that will be used as input for the flow.
- ▶ Clock Definition: Describes the main clock interface and timing target that guide synthesis, timing analysis, and optimization throughout the flow.
- ▶ Floorplanning (High-level): Sets high-level constraints that shape the core area, controlling utilization and overall layout proportions.
- ▶ Placement Control: Guides how densely standard cells are packed during placement to balance area efficiency and routability.

# Macros

```json
"MACROS": {
  "your_module": {
    "gds": "path/your_module.gds",
    "lef": "path/your_module.lef",
    "nl":  "path/your_module.pnl.v",

    "lib": {
      "nom_typ_1p20V_25C":   "path/your_module.lib",
      "nom_fast_1p32V_m40C": "path/your_module.lib",
      "nom_slow_1p08V_125C": "path/your_module.lib"
    },

    "spef": {
      "nom_typ_1p20V_25C": "path/your_module.spef"
    },

    "instances": {
      "inst_0": { "location": [640, 630], "orientation": "N" },
      "inst_1": { "location": [440, 430], "orientation": "N" }
    }
  }
}
```

► A physical abstract view (LEF) to define area, pins, and routing blockages.
► A final layout (GDS) used for stream-out and sign-off verification.
► A logical netlist to connect the macro at the top level.
► Timing models across relevant corners for chip-level timing analysis.
► Optional parasitic information to improve accuracy during sign-off.
► Fixed placement information when the macro must be placed explicitly.

# Classic vs Chip flow

```
{
"meta": {
        "version": 3,
        "flow": "Classic"
    },
    ...
}
```

```
{
"meta": {
        "version": 3,
        "flow": "Chip"
    },
    ...
}
```





**Librelane Flow – A practical guide to chip design flow**

# Steps

▶ The flow is organized as a sequence of well-defined steps, each performing a specific transformation or verification task.

▶ Each step operates on the design state, progressively refining it from RTL to a manufacturable layout.

▶ Steps can include analysis, transformation, validation, or checking stages.

▶ The execution order is predefined, but individual steps can be enabled, disabled, or customized.

▶ Intermediate results are stored, allowing inspection, debugging, and visualization at any stage of the flow.



**HM**

**Librelane Flow – A practical guide to chip design flow**

Daniel Arevalos – Fakultät 07 – Hochschule München

# Quick tutorial - Classic Flow

counter_8bit.v

```
{
module counter_8bit (
        input  logic       clk_i,
        input  logic       rst_ni,
        output logic [7:0] count_o
);

        always_ff @(posedge clk_i) begin
                if (!rst_ni) begin
                    count_o <= '0;
                end else begin
                    count_o <= count_o + 1;
                end
        end

endmodule
}
```

config.json

```
{
    "DESIGN_NAME": "counter_8bit",
    "VERILOG_FILES": [
        "src/counter_8bit.v"
    ],

    "CLOCK_PORT": "clk",
    "CLOCK_PERIOD": 10,

    "FP_CORE_UTIL": 50,
    "FP_ASPECT_RATIO": 1.0,

    "PL_TARGET_DENSITY": 0.55
}
```

CLI

```
export PDK=ihp-sg13g2
librelane -pdk ihp-sg13g2 config.json
```

# Visualization of Results

```
librelane --last-run config.json --flow OpenInOpenROAD

runs/<run_tag>
|-- final
|-- tmp
|-- error.log
|-- info.log
|-- resolved.json
|-- warning.log
|-- 01-verilator-lint
|-- 02-checker-linttimingconstructs
|-- 03-checker-linterrors
|-- 04-yosys-jsonheader
|-- 05-yosys-synthesis
|-- 06-checker-yosysunmappedcells
|-- 07-checker-yosyssynthchecks
|-- 08-openroad-checksdcfiles
|-- 09-openroad-staprepnr
|-- 10-openroad-floorplan
|-- 11-odb-setpowerconnections
|-- 12-odb-manualmacroplacement
|-- 13-openroad-cutrows
|-- 14-openroad-tapendcapinsertion
|-- 15-openroad-globalplacementskipio
    .
    .
    .
```



![HM logo]

**Librelane Flow – A practical guide to chip design flow**

# Quick tutorial - Chip Flow

▶ Full-chip design integrating two 8-bit counter macros.

▶ Macros are reused from the Classic flow and instantiated at the top level.

▶ Shared clock and reset, producing a 16-bit output.

▶ Dedicated core and IO power pads.