CNS Lab - 7

Name: H M Mythreya

SRN: PES2UG20CS130

Labsetup



Attacker: 10.0.2.5



Victim: 10.0.2.6

Step1: Configure DNS Server on Attacker machine

hosts

```
127.0.0.1       www.SOPLab.com
127.0.0.1       www.SOPLabAttacker.com
127.0.0.1       www.SOPLabCollabtive.com

127.0.0.1       www.OriginalphpMyAdmin.com

127.0.0.1       www.CSRFLabElgg.com
127.0.0.1       www.XSSLabElgg.com
127.0.0.1       www.SeedLabElgg.com
10.0.2.6        www.heartbleedlabelgg.com
127.0.0.1       www.WTLabElgg.com

127.0.0.1       www.wtmobilestore.com
127.0.0.1       www.wtshoestore.com
127.0.0.1       www.wtelectronicsstore.com
127.0.0.1       www.wtcamerastore.com

127.0.0.1       www.wtlabadserver.com

# The following lines are desirable for IPv6 capable hosts
::1     localhost ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
ff02::3 ip6-allhosts
```

Step2: Warmup exercise



Step2a: Login and send boby a message



Step2b: Run attack.py code until sensitive information can be found



Login details is leaked

Running a few more times, the private message is also leaked



Step3:Investigate the fundamental cause of the Heartbleed attack



python /home/seed/attack.pywww.heartbleedlabelgg.com --length 40
(Only 40 bytes of extra data is captured)



python /home/seed/attack.pywww.heartbleedlabelgg.com --l 0x012B
(0x012B=299 bytes)

Step4:Find the boundary value of the payload length variable.



Payload length 22 bytes



Payload length 23 bytes

Since payload length of 22 bytes returns no extra data but 23 bytes returns some extra data, the boundary value is 22 bytes.