


# Crypto Lab – 9

Name: H M Mythreya

SRN: PES2UG20CS130

## Setting up docker

```
seed@Mythreya_PES2UG20CS130~/.../Labsetup$docker-compose up
WARNING: Found orphan containers (host1-192.168.60.5, host2-192.168.60.6, hostA-
10.9.0.5, seed-router, host3-192.168.60.7) for this project. If you removed or r
enamed this service in your compose file, you can run this command with the --re
move-orphans flag to clean it up.
Creating www-10.9.0.80 ... done
Attaching to www-10.9.0.80
www-10.9.0.80 | * Serving Flask app "/app/www"
www-10.9.0.80 | * Environment: production
www-10.9.0.80 |     WARNING: This is a development server. Do not use it in a pro
duction deployment.
www-10.9.0.80 |     Use a production WSGI server instead.
www-10.9.0.80 | * Debug mode: off
www-10.9.0.80 | * Running on http://0.0.0.0:80/ (Press CTRL+C to quit)
www-10.9.0.80 | 10.9.0.1 - - [27/Nov/2022 16:13:13] "GET / HTTP/1.1" 200 -
www-10.9.0.80 | 10.9.0.1 - - [27/Nov/2022 16:13:13] "GET /favicon.ico HTTP/1.1"
404 -
```




# Task 1: Accessing website with proper mac


*Calculating mac using sha256sum*

*uid:key pair used → 1005:xciujk*

```
seed@Mythreya_PES2UG20CS130~/.../Labsetup$echo -n "xciujk:myname=mythreya_cs130&uid=1005&lscmd=1" | sha256sum
b451c562082cd93cf5fbc028ab7928df85ac28786cf006d02c1c5a53b848f651 -
```



*We can see the contents of secret.txt by sending a query “download=secret.txt”*




## Task 2: Construct padding for sha256

```
seed@Mythreya_PES2UG20CS130~/.../Labsetup$python3
Python 3.8.5 (default, Jul 28 2020, 12:59:40)
[GCC 9.3.0] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> payload = bytearray("xciujk:myname=mythreya_cs130&uid=1005&lscmd=1","utf-8"
)
>>> le = (len(payload)*8).to_bytes(8,"big")
>>> padding = b"\x80" + b"\x00"
File "<stdin>", line 1
padding = b"\x80" + b"\x00"
^
SyntaxError: EOL while scanning string literal
>>> padding = b"\x80" + b"\x00" * (64-len(payload)-1-8) + le
>>> print("".join("\x{:02x}".format(x) for x in padding))
\x80\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x00\x01\x70
>>> print("".join("%x{:02x}".format(x) for x in padding))
%80%00%00%00%00%00%00%00%00%00%00%00%00%00%00%00%01%70
>>>
```

## Task 3

*New hash generated after padding:*

```
seed@Mythreya_PES2UG20CS130~/.../week9$gcc hle.c -o hle -lcrypto
seed@Mythreya_PES2UG20CS130~/.../week9$./hle
12ca51bd6a3aaf124b07ce4649f0c4d14f858bc83e641d76294c3fa1fa5dd255
seed@Mythreya_PES2UG20CS130~/.../week9$
```



### Hash Length Extension Attack Lab


Yes, your MAC is valid

File Content

TOP SECRET.

DO NOT DISCLOSE.

### Generating Hash without uid:key pair



With the help of sha256 padding we can access the secret.txt without the need to know uid:key pair.