

H M Mythreya

PES2UG20CS130

MPCA-Lab Week-7

Task 1: Display hexadecimal digits [0-9,A-F] on the 8-segment display. Also display PES on the 8-segment display

Code:

```
.data
    zero: .byte 0b11101101
    one: .byte 0b01100000
    two: .byte 0b01101110
    three: .byte 0b11111010
    four: .byte 0b00110011
    five: .byte 0b10101011
    six: .byte 0b10101111
    seven: .byte 0b01110000
    eight: .byte 0b11101111
    nine: .byte 0b11100011

    A: .byte 0b11100111
    B: .byte 0b00101111
    C: .byte 0b10001101
    D: .byte 0b01101110
    E: .byte 0b10001111
    F: .byte 0b10000111

.text
begin:
    mov r0,#0
    mov r2,#0

while:
    swi 0x202
    cmp r0,#1
    beq loop1
    cmp r0,#2
    beq loop2
    b while

loop1:
    mov r5,#16
    ldr r1,=zero

back1:
    ldrb r0,[r1]
    swi 0x200
    bl delay
    add r1,r1,#1
    sub r5,r5,#1
    cmp r5,#0
    bne back1
    b while
```

```

loop2:
    mov r5,#16
    ldr r1,=F

back2:
    ldrb r0,[r1]
    swi 0x200
    bl delay
    sub r1,r1,#1
    sub r5,r5,#1
    cmp r5,#0
    bne back2
    b while

delay:
    mov r4,#1

loop3:
    sub r4,r4,#1
    cmp r4,#0
    bge loop3
    mov pc,lr

```

The screenshot shows the EmbestBoardPlugin GUI with the following components:

- RegistersView:** Displays the state of registers R0 through R15. R14 (lr) is highlighted in red with the value 0x000105c. R15 (pc) is highlighted in red with the value 0x0001070. The CPSR Register shows various flags like Negative (N), Zero (Z), Carry (C), Overflow (V), etc.
- PluginUI View:** Contains a visual representation of the board with buttons for values 0.0 to 1.3. A green bar is visible on the right.
- hex.s:** Displays the assembly code for the program, including labels like back2, delay, and loop3.
- OutputView:** Shows the console output, including the message "Loading assembly language file X:\sem4\MPCA\LAB\week7\hex.s".

The screenshot shows the EmbestBoardPlugin GUI after execution. The registers and assembly code are updated as follows:

- RegistersView:** R0 is now 0x00000ed. R14 (lr) is highlighted in red with the value 0x0001034. R15 (pc) is highlighted in red with the value 0x0001070. The CPSR Register shows updated flag values.
- PluginUI View:** The visual representation of the board is updated, showing a different state for the buttons and the green bar.
- hex.s:** The assembly code is the same, but the execution flow has progressed to the end of the program.
- OutputView:** The console output shows the message "Loading assembly language file X:\sem4\MPCA\LAB\week7\hex.s".

RegistersView

General Purpose

Floating Point

Hexadecimal

Unsigned Decimal

Signed Decimal






R0 : 000000c7
R1 : 0000109b
R2 : 00000000
R3 : 00000000
R4 : 00000000
R5 : 00000010
R6 : 00000000
R7 : 00000000
R8 : 00000000
R9 : 00000000
R10 (s1) : 00000000
R11 (fp) : 00000000
R12 (ip) : 00000000
R13 (sp) : 00005400
R14 (lr) : 0000105c
R15 (pc) : 00001070

CPSR Register
Negative (N) : 0
Zero (Z) : 1
Carry (C) : 1
Overflow (V) : 0
IRQ Disable : 1
FIQ Disable : 1
Thumb (T) : 0
CPU Mode : System

0x600000df

PluginUIView

EmbestBoardPlugin

0.0

0.1

0.2


0.3

1.0

1.1

1.2

1.3



hex.s

```

0000104C:E59F1034      ldr r1,=F
00001050:                back2:
00001050:E5D10000      ldrb r0,[r1]
00001054:EF000200      swi 0x200
00001058:EB000004      bl delay
0000105C:E2411001      sub r1,r1,#1
00001060:E2455001      sub r5,r5,#1
00001064:E3550000      cmp r5,#0
00001068:1AFFFFF8      bne back2
0000106C:EAF7FFE5      b while
00001070:                delay:
00001070:E3A04001      mov r4,#1
00001074:                loop3:
00001074:E2444001      sub r4,r4,#1
00001078:E3540000      cmp r4,#0
0000107C:AAFFFFFC      bge loop3
0000107C:AAFFFFFC      mov pc,lr

```

OutputView

Console

Stdin/Stdout/Stderr

Loading assembly language file X:\sem4\MPCA\LAB\week7\hex.s

RegistersView

General Purpose

Floating Point

Hexadecimal

Unsigned Decimal

Signed Decimal






R0 : 0000008f
R1 : 0000109a
R2 : 00000000
R3 : 00000000
R4 : ffffffff
R5 : 00000002
R6 : 00000000
R7 : 00000000
R8 : 00000000
R9 : 00000000
R10 (s1) : 00000000
R11 (fp) : 00000000
R12 (ip) : 00000000
R13 (sp) : 00005400
R14 (lr) : 00001034
R15 (pc) : 00001070

CPSR Register
Negative (N) : 0
Zero (Z) : 0
Carry (C) : 1
Overflow (V) : 0
IRQ Disable : 1
FIQ Disable : 1
Thumb (T) : 0
CPU Mode : System

0x200000df

PluginUIView

EmbestBoardPlugin

0.0

0.1

0.2


0.3

1.0

1.1

1.2

1.3



hex.s

```

0000104C:E59F1034      ldr r1,=F
00001050:                back2:
00001050:E5D10000      ldrb r0,[r1]
00001054:EF000200      swi 0x200
00001058:EB000004      bl delay
0000105C:E2411001      sub r1,r1,#1
00001060:E2455001      sub r5,r5,#1
00001064:E3550000      cmp r5,#0
00001068:1AFFFFF8      bne back2
0000106C:EAF7FFE5      b while
00001070:                delay:
00001070:E3A04001      mov r4,#1
00001074:                loop3:
00001074:E2444001      sub r4,r4,#1
00001078:E3540000      cmp r4,#0
0000107C:AAFFFFFC      bge loop3
0000107C:AAFFFFFC      mov pc,lr

```

OutputView

Console

Stdin/Stdout/Stderr

Loading assembly language file X:\sem4\MPCA\LAB\week7\hex.s

RegistersView

General Purpose

Floating Point

Hexadecimal

Unsigned Decimal

Signed Decimal






R0 : 000000ab
R1 : 00001091
R2 : 00000000
R3 : 00000000
R4 : ffffffff
R5 : 0000000b
R6 : 00000000
R7 : 00000000
R8 : 00000000
R9 : 00000000
R10 (s1) : 00000000
R11 (fp) : 00000000
R12 (ip) : 00000000
R13 (sp) : 00005400
R14 (lr) : 00001034
R15 (pc) : 00001070

CPSR Register
Negative (N) : 0
Zero (Z) : 0
Carry (C) : 1
Overflow (V) : 0
IRQ Disable : 1
FIQ Disable : 1
Thumb (T) : 0
CPU Mode : System

0x200000df

PluginUIView

EmbestBoardPlugin

0.0

0.1

0.2


0.3

1.0

1.1

1.2

1.3



hex.s

```

0000104C:E59F1034      ldr r1,=F
00001050:                back2:
00001050:E5D10000      ldrb r0,[r1]
00001054:EF000200      swi 0x200
00001058:EB000004      bl delay
0000105C:E2411001      sub r1,r1,#1
00001060:E2455001      sub r5,r5,#1
00001064:E3550000      cmp r5,#0
00001068:1AFFFFF8      bne back2
0000106C:EAF7FFE5      b while
00001070:                delay:
00001070:E3A04001      mov r4,#1
00001074:                loop3:
00001074:E2444001      sub r4,r4,#1
00001078:E3540000      cmp r4,#0
0000107C:AAFFFFFC      bge loop3
0000107C:AAFFFFFC      mov pc,lr

```

OutputView

Console

Stdin/Stdout/Stderr

Loading assembly language file X:\sem4\MPCA\LAB\week7\hex.s

Task 2: Move a string from RIGHT to LEFT on the LCD display panel. Display your name on the LCD Panel

Code:

```
.data
    str: .asciz "MYTHREYA\n"

.text
    mov r0,#25
    mov r1,#3
    ldr r2,str

loop:
    cmp r0,#0
    beq exit
    swi 0x204
    sub r0,r0,#1
    swi 0x206
    b loop

exit:
    swi 0x01
```

The screenshot shows the RegistersView window on the left and the PluginUIView window on the right. The RegistersView window displays the PC register at 0x000101c. The PluginUIView window shows a 4x4 grid of buttons (0.0-1.3) and a green LCD display showing 'MYTHREYA'.

The screenshot shows the RegistersView window on the left and the PluginUIView window on the right. The RegistersView window displays the PC register at 0x0001018. The PluginUIView window shows a 4x4 grid of buttons (0.0-1.3) and a green LCD display showing 'MYTHREYA'.