COALA
EXECUTION WALKTHROUGH

50+ PAGE
SOURCE-LEVEL TRACE

Travel planner - plan-first procedure

A complete source-level trace using the exact use-case route travel-plan-first and the sample goal shown in this document.

This guide follows the request through the HTTP boundary, request validation, session creation or resumption, action registration, context construction, the configured decision procedure, every cycle, and the serialized result. The document intentionally treats the offline scripted model as deterministic fixtures, not as an LLM.

Use case: Travel planner - plan-first procedure
Based on the supplied project source tree. Code excerpts identify source file and line ranges. Simulated provider results are labeled as such.

Purpose: follow every call from HTTP arrival through each decision cycle to the final response, and understand what every significant method does with its inputs and state.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

How to use this walkthrough

Read the method-call ledger top to bottom. A call is listed only when the current implementation makes it, while framework dispatch supplied by Spring is labeled as framework behavior rather than invented application code. Pages that show source excerpts cite the project-relative file and line span so you can open the same implementation in the ZIP.

Each cycle is traced from the latest observation through planning, selected action validation, execution, working-memory updates, event creation, and the check that determines whether the loop continues. If a cycle does not call the language model, the guide says so explicitly.

Code-level interpretation

- “Scripted fixture” means a hard-coded deterministic response chosen by operation marker, cycle number, or simple string checks.
- “Working-memory write” means a key/value update to the per-run WorkingMemory object, not a durable database commit.
- “Long-term memory” here is a session-scoped in-process store; it survives later requests using the returned session ID only while the application process and session remain alive.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 25-45)

```
 */
public abstract class AbstractLoopingDecisionProcedure implements CoalaDecisionProcedure {
    public static final int MAX_GOAL_CHARACTERS = 4_000;

    @Override
    public final AgentRunResult run(String goal, AgentContext context, ActionRegistry actions, int maxCycles) {
        if (goal == null || goal.isBlank()) throw new IllegalArgumentException("goal must not be blank");
        if (goal.length() > MAX_GOAL_CHARACTERS) throw new IllegalArgumentException("goal must be no more than "
         + MAX_GOAL_CHARACTERS + " characters");
        goal = goal.trim();
        if (maxCycles < 1 || maxCycles > 100) throw new IllegalArgumentException("maxCycles must be between 1
        and 100");

        context.workingMemory().put("goal", goal.trim());
        context.workingMemory().put("latest_observation", "User request received: " + goal.trim());
        List<DecisionEvent> events = new ArrayList<>();
        String finalObservation = "";

        for (int cycle = 1; cycle <= maxCycles; cycle++) {
            context.setCycle(cycle);
            String observation = context.workingMemory().getString("latest_observation", "");
            events.add(new DecisionEvent(cycle, DecisionStage.OBSERVATION,
                    truncate(observation, 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The exact incoming request

The walkthrough assumes the request body below, omits maxCycles so the service uses the configured default (normally 8), and omits sessionId so the server creates a new opaque session. This is a deliberate first-run path: it lets the trace show session creation before context construction.

The user goal is: Plan a trip to Paris next month for 3 nights under CAD 1400; check calendar first.. The goal remains the task text in working memory; the framework does not convert it into a typed domain object before the selected decision procedure reasons about it.

State and observable values

Field	Value / meaning
HTTP method/path	POST /api/use-cases/travel-plan-first/run
Request JSON	{"goal":"Plan a trip to Paris next month for 3 nights under CAD 1400; check calendar first."}
maxCycles	null in JSON; service default is injected from coala.run.max-cycles (default 8)
sessionId	omitted; SessionMemoryStore creates a UUID session

Actual source excerpt: dev/coala/api/RunRequest.java (source lines 1-15)

```
package dev.coala.api;

public record RunRequest(String goal, Integer maxCycles, String sessionId) {
    public RunRequest {
        if (goal == null || goal.isBlank()) throw new IllegalArgumentException("goal must not be blank");
        if (goal.length() > 4_000) throw new IllegalArgumentException("goal must be no more than 4000
        characters");
        if (maxCycles != null && (maxCycles < 1 || maxCycles > 100)) {
            throw new IllegalArgumentException("maxCycles must be between 1 and 100");
        }
        if (sessionId != null && !sessionId.isBlank()
                && !sessionId.trim().matches("[A-Za-z0-9._-]{1,64}")) {
            throw new IllegalArgumentException("sessionId must be 1-64 characters using letters, digits, '.',
        '_' or '-'.");
        }
    }
}
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

What this example does - and does not - prove

The use case terminates in 6 decision cycles by executing present_itinerary in cycle 6. It demonstrates the mechanics of the configured decision procedure and action boundary, not the factual correctness of a production integration.

A non-binding itinerary for Paris from 2026-11-05 to 2026-11-08, with CAD 640 flight, CAD 390 hotel, CAD 160 local estimate, CAD 1,190 subtotal, CAD 1,400 cap, and a fixture-only within-budget check. No reservation, payment, or live calendar lookup occurs.


No real search provider, airline, hotel, calendar, ticketing platform, identity service, or financial system is called by this demo path. The simulated results are appropriate for explaining control flow, not for making real-world decisions.

Important boundary
A successful terminal action only means that the action returned terminal=true. It does not mean the external-world task was performed by a real provider.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

A single visual map of the full call chain

This is the route for this use case. It is a call map, not a new CoALA architectural component. The API guard is application infrastructure; the decision procedure, memory, action execution, and observation loop are the framework side of the route.



Important boundary
The arrows mean “control passes to”; they do not mean every box is a Java method. Some steps are framework dispatch or a group of calls explained on subsequent pages.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The terminology used in the call ledger

A decision cycle is one iteration of AbstractLoopingDecisionProcedure.run: set the cycle number, record the current observation, clear stale plan-selection keys, ask the configured procedure for one next action, validate it, execute it, write its result as the latest observation, then stop or continue.

A reasoning call is a call through ReasoningAction.reason to the configured LanguageModel. Different procedures make different numbers of reasoning calls per cycle. The deliberative procedure usually reasons once for candidate proposal and once for evaluation; the plan-first procedure reasons to make the plan and can then reuse stored plan steps without another model call; the iterative procedure reasons once per cycle.

A selected action is a structured ActionCall with an actionId and string arguments. It is not executable code generated by the model. The ActionRegistry resolves it to a pre-registered implementation and validates its declared argument contract.

Actual source excerpt: dev/coala/core/PlanDecision.java (source lines 1-31)

```
package dev.coala.core;

import java.util.List;
import java.util.Objects;

/** Result of planning one next action, including structured candidates/evaluations when available. */
public record PlanDecision(
        ActionCall selectedAction,
        List<ActionCall> candidates,
        List<Double> evaluationScores,
        List<DecisionEvent> events) {

    public PlanDecision {
        Objects.requireNonNull(selectedAction, "selectedAction");
        candidates = candidates == null || candidates.isEmpty() ? List.of(selectedAction) :
        List.copyOf(candidates);
        evaluationScores = evaluationScores == null ? List.of() : List.copyOf(evaluationScores);
        events = events == null ? List.of() : List.copyOf(events);
        if (!candidates.contains(selectedAction)) {
            throw new IllegalArgumentException("selectedAction must be present in the planned candidate list");
        }
        if (!evaluationScores.isEmpty() && evaluationScores.size() != candidates.size()) {
            throw new IllegalArgumentException("evaluationScores must be empty or contain one score per
        candidate");
        }
        if (evaluationScores.stream().anyMatch(score -> score == null || !Double.isFinite(score))) {
            throw new IllegalArgumentException("evaluation scores must be finite numbers");
        }
    }

    /** Direct/iterative decision procedures may propose one candidate without explicit evaluation. */
    public PlanDecision(ActionCall selectedAction, List<DecisionEvent> events) {
        this(selectedAction, List.of(selectedAction), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

HTTP entry: the request as received by the app guard

The first application-owned method for an /api request is ApiGuardFilter.doFilterInternal, inherited from Spring's OncePerRequestFilter. The framework calls it in the servlet filter chain. It checks rate-limit allowance first; if a bearer token is configured, it validates Authorization; then it bounds and buffers the request body. Only after those checks does it invoke filterChain.doFilter.

For this sample, the default server address is loopback and the token is blank in the local demo configuration, so the bearer-token branch is disabled. The rate limit and maximum request-byte checks still exist. A deployment bound to a non-loopback address fails construction unless COALA_API_TOKEN is configured.

Method-call ledger

01	OncePerRequestFilter dispatches to shouldNotFilter(request).
02	shouldNotFilter checks URI begins with contextPath + /api/.
03	doFilterInternal calls allowRate(remoteAddress).
04	If configuredToken is nonempty, validBearerToken(Authorization) runs.
05	enforceRequestSize reads at most maxRequestBytes + 1 and may reject oversized bodies.
06	filterChain.doFilter(boundedRequest, response) passes control to Spring MVC.

Actual source excerpt: dev/coala/api/ApiGuardFilter.java (source lines 62-96)

```
    @Override
    protected boolean shouldNotFilter(HttpServletRequest request) {
        String apiPrefix = request.getContextPath() + "/api/";
        return !request.getRequestURI().startsWith(apiPrefix);
    }

    @Override
    protected void doFilterInternal(HttpServletRequest request, HttpServletResponse response, FilterChain
        filterChain)
            throws ServletException, IOException {
        if (!allowRate(request.getRemoteAddr())) {
            writeProblem(response, HttpServletResponse.SC_TOO_MANY_REQUESTS,
                    "Rate limit exceeded", "Too many API requests from this client. Retry after the current
        minute window.");
            return;
        }

        // Authenticate before consuming a request body. A rejected caller should not
        // be able to force the application to buffer up to the request-size limit.
        if (configuredToken.length > 0 && !validBearerToken(request.getHeader("Authorization"))) {
            response.setHeader("WWW-Authenticate", "Bearer");
            writeProblem(response, HttpServletResponse.SC_UNAUTHORIZED,
                    "Unauthorized", "A valid bearer token is required for this API.");
            return;
        }

        HttpServletRequest boundedRequest;
        try {
            boundedRequest = enforceRequestSize(request, response);
        } catch (IOException ex) {
            writeProblem(response, HttpServletResponse.SC_BAD_REQUEST,
                    "Invalid request body", "The request body could not be read.");
            return;
        }
        if (boundedRequest == null) return;
        filterChain.doFilter(boundedRequest, response);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The rate-limit branch is independent from CoALA

allowRate keys the in-memory request counter by remote address and uses a 60-second monotonic-time window. A new address gets a bucket with request count one; a current bucket is accepted only while its count is below requestsPerMinute; old buckets are pruned periodically. This is a small application-shell guard, not a cognitive action and not part of the decision procedure.

If the bucket map is full and cannot add a new client bucket, the filter rejects rather than growing its map without bound. A rejected request receives an application/problem+json response and does not reach the controller. That means there will be no session, context, memory retrieval, model call, or decision cycle for a rejected request.

Actual source excerpt: dev/coala/api/ApiGuardFilter.java (source lines 104-125)

```
    private boolean allowRate(String remoteAddress) {
        String key = remoteAddress == null || remoteAddress.isBlank() ? "unknown" : remoteAddress;
        long now = System.nanoTime();
        AtomicBoolean accepted = new AtomicBoolean(false);
        buckets.compute(key, (ignored, current) -> {
            if (current == null && buckets.size() >= MAX_RATE_LIMIT_BUCKETS) {
                accepted.set(false);
                return null;
            }
            if (current == null || now - current.windowStartedAt >= WINDOW_NANOS) {
                accepted.set(true);
                return new RateBucket(now, 1);
            }
            if (current.requests >= requestsPerMinute) return current;
            accepted.set(true);
            return new RateBucket(current.windowStartedAt, current.requests + 1);
        });

        if (requestCounter.incrementAndGet() % 256 == 0 || buckets.size() > MAX_RATE_LIMIT_BUCKETS) {
            pruneRateBuckets(now);
        }
        return accepted.get();
```

Important boundary
The in-memory rate limiter is process-local. A clustered deployment would need a shared rate-limit implementation, but the framework’s CoALA decision-cycle semantics would not change.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The request-size guard and replayable body wrapper

enforceRequestSize only buffers methods that may carry a body (POST, PUT, PATCH). It first rejects a declared Content-Length over the configured limit, then reads no more than maxRequestBytes + 1 bytes so chunked bodies without a useful Content-Length are still bounded. If the body is too large, it sends 413 and returns null; doFilterInternal returns without calling the next filter.

For a bounded body, CachedBodyRequestWrapper wraps the original request so the dispatcher and JSON converter can read the bytes after the guard has already consumed them. The wrapper constructs a new ByteArrayInputStream for each getInputStream call. This keeps the guard from breaking normal JSON deserialization.

Code-level interpretation

- A request larger than the limit exits before CoalaController.run.
- A well-sized request is handed forward through filterChain.doFilter, not directly to the controller by this method.

Actual source excerpt: dev/coala/api/ApiGuardFilter.java (source lines 128-145)

```
    private HttpServletRequest enforceRequestSize(HttpServletRequest request, HttpServletResponse response)
        throws IOException {
        String method = request.getMethod();
        boolean mayHaveBody = "POST".equalsIgnoreCase(method) || "PUT".equalsIgnoreCase(method)
                || "PATCH".equalsIgnoreCase(method);
        if (!mayHaveBody) return request;
        if (request.getContentLengthLong() > maxRequestBytes) {
            writeProblem(response, HttpServletResponse.SC_REQUEST_ENTITY_TOO_LARGE,
                    "Request too large", "The request body exceeds the configured size limit.");
            return null;
        }
        byte[] body = request.getInputStream().readNBytes(maxRequestBytes + 1);
        if (body.length > maxRequestBytes) {
            writeProblem(response, HttpServletResponse.SC_REQUEST_ENTITY_TOO_LARGE,
                    "Request too large", "The request body exceeds the configured size limit.");
            return null;
        }
        return new CachedBodyRequestWrapper(request, body);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Spring MVC dispatch reaches CoalaController.run

After the filter passes the wrapped request, Spring MVC matches POST /api/use-cases/{id}/run to CoalaController.run. Spring binds the path segment to id and deserializes the JSON body into RunRequest. No application code in the agent core manually parses the HTTP body.

The controller itself is deliberately thin: it delegates use-case semantics to DemoUseCaseService. It does not know which cognitive procedure is selected, which actions are registered, or how working memory is managed.

Method-call ledger

01	Spring route matches @RequestMapping("/api") + @PostMapping("/use-cases/{id}/run").
02	Jackson creates RunRequest from JSON.
03	CoalaController.run(id, request) reads request.goal(), request.maxCycles(), request.sessionId().
04	useCases.run(...) performs application-specific routing.

Actual source excerpt: dev/coala/api/CoalaController.java (source lines 17-29)

```
public class CoalaController {
    private final DemoUseCaseService useCases;

    public CoalaController(DemoUseCaseService useCases) { this.useCases = useCases; }

    @GetMapping("/use-cases")
    public List<DemoUseCaseDescriptor> listUseCases() { return useCases.list(); }

    @PostMapping("/use-cases/{id}/run")
    public UseCaseRunResponse run(@PathVariable String id, @RequestBody RunRequest request) {
        return useCases.run(id, request.goal(), request.maxCycles(), request.sessionId());
    }
}
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

RunRequest performs early input validation

RunRequest is a Java record, so its compact constructor runs when the JSON converter constructs the record. The goal cannot be null or blank and cannot exceed 4,000 characters. maxCycles, if present, must be between 1 and 100. sessionId, if present and nonblank, is restricted to a short safe alphabet and 64 characters.

These checks are distinct from the AbstractLoopingDecisionProcedure validation. The DTO protects the HTTP boundary; the procedure repeats critical goal and cycle bounds because it is a reusable core entry point that may also be called without HTTP.

Actual source excerpt: dev/coala/api/RunRequest.java (source lines 1-15)

```
package dev.coala.api;

public record RunRequest(String goal, Integer maxCycles, String sessionId) {
    public RunRequest {
        if (goal == null || goal.isBlank()) throw new IllegalArgumentException("goal must not be blank");
        if (goal.length() > 4_000) throw new IllegalArgumentException("goal must be no more than 4000
        characters");
        if (maxCycles != null && (maxCycles < 1 || maxCycles > 100)) {
            throw new IllegalArgumentException("maxCycles must be between 1 and 100");
        }
        if (sessionId != null && !sessionId.isBlank()
                && !sessionId.trim().matches("[A-Za-z0-9._-]{1,64}")) {
            throw new IllegalArgumentException("sessionId must be 1-64 characters using letters, digits, '.',
        '_' or '-'.");
        }
    }
}
```

Important boundary
Input schema validation does not establish that the user is authorized for the content of a goal. Demo session IDs are capabilities for demo memory resumption, not a substitute for application authentication.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Invalid requests and internal failures take different paths

ApiExceptionHandler maps malformed JSON and validation-related IllegalArgumentException to a 400 response; a missing or expired session is 404; provider failures are 502; invalid model output is 502; action execution failures and planning failures become sanitized 500 responses. The response avoids provider URLs, prompts, credentials, and nested exception details.

The exception boundary matters for the trace: if an action fails, AbstractLoopingDecisionProcedure wraps runtime failures as ActionExecutionException; CoalaAgent publishes a generic run-failed trace event to listeners and rethrows; the API advice converts that exception to a stable response. In this example the deterministic fixtures finish normally, so this error path is not taken.

Actual source excerpt: dev/coala/api/ApiExceptionHandler.java (source lines 18-78)

```
@ExceptionHandler(IllegalArgumentException.class)
ProblemDetail badRequest(IllegalArgumentException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(HttpStatus.BAD_REQUEST, ex.getMessage());
    detail.setTitle("Invalid request");
    return detail;
}

@ExceptionHandler(HttpMessageNotReadableException.class)
ProblemDetail unreadableRequest(HttpMessageNotReadableException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.BAD_REQUEST, "The request body must be valid JSON and satisfy the request schema.");
    detail.setTitle("Invalid request body");
    return detail;
}

@ExceptionHandler(NoSuchElementException.class)
ProblemDetail sessionNotFound(NoSuchElementException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(HttpStatus.NOT_FOUND, ex.getMessage());
    detail.setTitle("Session not found");
    return detail;
}

@ExceptionHandler(LanguageModelException.class)
ProblemDetail languageModelFailure(LanguageModelException ex) {
    // Do not expose provider URLs, credentials, response bodies, or nested exception details.
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.BAD_GATEWAY, "The configured language-model provider could not complete the
    request.");
    detail.setTitle("Language-model provider failure");
    return detail;
}

@ExceptionHandler(InvalidModelOutputException.class)
ProblemDetail invalidModelOutput(InvalidModelOutputException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.BAD_GATEWAY, "The language-model response did not satisfy the required
    structured-output contract.");
    detail.setTitle("Invalid language-model response");
    return detail;
}

@ExceptionHandler(ActionExecutionException.class)
ProblemDetail actionExecutionFailure(ActionExecutionException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.INTERNAL_SERVER_ERROR, "The selected action failed while executing.");
    detail.setTitle("Action execution failed");
    return detail;
}

@ExceptionHandler(PlanningExhaustedException.class)
ProblemDetail planningExhausted(PlanningExhaustedException ex) {
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.INTERNAL_SERVER_ERROR, "The agent could not select an action within its configured
    planning-attempt limit.");
    detail.setTitle("Planning exhausted");
    return detail;
}

@ExceptionHandler(DecisionProcedureException.class)
ProblemDetail decisionFailure(DecisionProcedureException ex) {
    // This is an application/agent failure, not a user input validation error.
    ProblemDetail detail = ProblemDetail.forStatusAndDetail(
            HttpStatus.INTERNAL_SERVER_ERROR, "The agent decision procedure could not complete the
    request.");
    detail.setTitle("Agent execution failed");
```

Important boundary
The report traces the successful simulation. Error paths are described separately, not silently substituted into the successful cycle ledger.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

DemoUseCaseService.run is the use-case router

DemoUseCaseService.run first checks the ID against the explicit allow-list of six supported demos. It chooses maxCycles from the request or configured default, validates that bound, and acquires the requested/new session. A switch expression then dispatches to the case-specific builder: research uses runResearch, travel uses runTravel, and support uses runSupport.

This switch is where use-case-specific wiring lives. The reusable procedures do not know what “Paris,” a research source, or a support ticket means. They only see a bounded goal, a working-memory context, an action registry, and a procedure-specific planning algorithm.

Method-call ledger

01	Check useCaseId against six allowed strings.
02	Compute boundedCycles = request maxCycles or defaultMaxCycles.
03	sessionMemoryStore.acquire(requestedSessionId).
04	Dispatch to runResearch / runTravel / runSupport for this guide.
05	Wrap result with new UseCaseRunResponse(session.sessionId(), result).

Actual source excerpt: dev/coala/demo/DemoUseCaseService.java (source lines 78-97)

```
public UseCaseRunResponse run(String useCaseId, String goal, Integer maxCycles, String requestedSessionId) {
    if (!List.of("dialogue-direct", "coding-iterative", "puzzle-deliberative",
            "research-deliberative", "travel-plan-first", "support-iterative").contains(useCaseId)) {
        throw new IllegalArgumentException("Unknown use case id: " + useCaseId);
    }
    int boundedCycles = maxCycles == null ? defaultMaxCycles : maxCycles;
    if (boundedCycles < 1 || boundedCycles > 100) throw new IllegalArgumentException("maxCycles must be
    between 1 and 100");
    SessionMemoryStore.Session session = sessionMemoryStore.acquire(requestedSessionId);
    AgentRunResult result = switch (useCaseId) {
        case "dialogue-direct" -> runAgent(useCaseId, direct,
                List.of(new DialogueReplyAction()), goal, boundedCycles, session);
        case "coding-iterative" -> runCoding(goal, boundedCycles, session);
        case "puzzle-deliberative" -> runPuzzle(goal, boundedCycles, session);
        case "research-deliberative" -> runResearch(goal, boundedCycles, session);
        case "travel-plan-first" -> runTravel(goal, boundedCycles, session);
        case "support-iterative" -> runSupport(goal, boundedCycles, session);
        default -> throw new IllegalArgumentException("Unknown use case id: " + useCaseId);
    };
    return new UseCaseRunResponse(session.sessionId(), result);
}
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The first request creates a session; later requests must resume it

SessionMemoryStore.acquire returns createSession when requestedSessionId is null or blank. createSession generates a random UUID not selected by the caller, seeds an InMemoryLongTermMemory with three demo records, stores the session in a bounded LRU map, and returns a Session containing the id and memory reference. If a nonblank ID is provided, acquire only resumes an existing unexpired entry; it does not let the caller invent or reserve a chosen ID.

For this walkthrough, assume no session ID. The session ID appears in the response envelope, and a later request can send it back to resume long-term memory. WorkingMemory is different: AgentContextFactory creates a fresh WorkingMemory for each run.

Actual source excerpt: dev/coala/demo/SessionMemoryStore.java (source lines 48-94)

```
            throw new IllegalArgumentException("sessionId must be 1-64 characters using letters, digits, '.',
        '_' or '-'.");
        }

        long now = System.nanoTime();
        evictExpired(now);
        Entry entry = sessions.get(sessionId);
        if (entry == null) {
            throw new NoSuchElementException("Session not found or expired. Start a new session without
        providing a sessionId.");
        }
        entry.lastAccessNanos = now;
        return new Session(sessionId, entry.memory);
    }

    /** Creates a new session ID generated by the server; callers cannot choose or reserve an ID. */
    public synchronized Session createSession() {
        long now = System.nanoTime();
        evictExpired(now);
        String sessionId;
        do {
            sessionId = UUID.randomUUID().toString();
        } while (sessions.containsKey(sessionId));
        Entry entry = new Entry(createSeededMemory(), now);
        sessions.put(sessionId, entry);
        evictExcessSessions();
        return new Session(sessionId, entry.memory);
    }

    public synchronized int activeSessionCount() {
        evictExpired(System.nanoTime());
        return sessions.size();
    }

    private void evictExpired(long now) {
        Iterator<Map.Entry<String, Entry>> iterator = sessions.entrySet().iterator();
        while (iterator.hasNext()) {
            Entry entry = iterator.next().getValue();
            if (now - entry.lastAccessNanos >= idleTtlNanos) iterator.remove();
        }
    }

    private void evictExcessSessions() {
        Iterator<Map.Entry<String, Entry>> iterator = sessions.entrySet().iterator();
        while (sessions.size() > maxSessions && iterator.hasNext()) {
            iterator.next();
            iterator.remove(); // LRU eviction; in-flight runs retain their local memory reference.
        }
    }
```

Important boundary
The store is in-process memory. A restart or eviction loses the demo session, so it should not be described as durable production persistence.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Travel uses a scoped namespace but does not retrieve memory in its planner

runTravel creates MemoryNamespace("travel-plan-first", sessionId, "demo", "travel"). It then registers six actions: calendar check, flight search, hotel search, itinerary drafting, episodic learning, and itinerary presentation. It does not call ensureSeed and the PlanFirstDecisionProcedure does not invoke MemoryRetrievalAction in its current implementation.

The scoped session memory is still relevant because learn_episode writes into the AgentContext namespace in cycle 5. That episode can be retrieved by a later deliberative procedure that shares an appropriate scope, but this plan-first run does not use it as input to its initial plan.

State and observable values

Field	Value / meaning
agentId	travel-plan-first
domain	travel
retrieval this run	none in PlanFirstDecisionProcedure
learning this run	one episodic record in cycle 5

Actual source excerpt: dev/coala/demo/DemoUseCaseService.java (source lines 126-135)

```
    private AgentRunResult runTravel(String goal, int maxCycles, SessionMemoryStore.Session session) {
        MemoryNamespace namespace = namespace("travel-plan-first", session.sessionId(), "travel");
        return runAgent("travel-plan-first", planFirst, List.of(
                TravelGroundingActions.checkCalendar(),
                TravelGroundingActions.searchFlights(),
                TravelGroundingActions.searchHotels(),
                TravelGroundingActions.draftItinerary(),
                new EpisodicMemoryLearningAction(),
                TravelGroundingActions.presentItinerary()), goal, maxCycles, session, namespace);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The selected case wires actions into a reusable procedure

The use-case builder calls runAgent with agent id travel-plan-first, procedure plan-first-revisable, its six/four/three registered actions, the goal, max-cycle limit, session and namespace. The action list defines the allow-list: the model can propose only IDs in that list, and ActionRegistry resolves each ID to the registered object.

For research, the action instances are WebSearchGroundingAction backed by SimulatedWebSearchProvider, formatEvidenceBrief, EpisodicMemoryLearningAction, and deliverResearchBrief. For travel, the six action IDs correspond to the six plan steps. For support, three action IDs support classification and two possible terminal outcomes.

State and observable values

Field	Value / meaning
procedure	case-specific selection
action registry	constructed from only the actions passed to runAgent
context factory	creates fresh WorkingMemory and resolves this session memory
max cycles	request/configured maximum; run terminates earlier if action is terminal

Actual source excerpt: dev/coala/demo/DemoUseCaseService.java (source lines 145-168)

```
    private AgentRunResult runAgent(String agentId, CoalaDecisionProcedure procedure,
                                    List<? extends CoalaAction> actions, String goal, int maxCycles,
                                    SessionMemoryStore.Session session) {
        return runAgent(agentId, procedure, actions, goal, maxCycles, session, MemoryNamespace.DEFAULT);
    }

    private AgentRunResult runAgent(String agentId, CoalaDecisionProcedure procedure,
                                    List<? extends CoalaAction> actions, String goal, int maxCycles,
                                    SessionMemoryStore.Session session, MemoryNamespace namespace) {
        AgentContextFactory contextFactory = AgentContextFactory.scoped(request -> session.longTermMemory());
        CoalaAgentDefinition definition = CoalaAgentDefinition.of(agentId, procedure, actions, contextFactory,
        maxCycles);
        CoalaAgent agent = new CoalaAgent(definition);
        return agent.run(new AgentRunRequest(goal, session.sessionId(), "demo", namespace));
    }

    private static MemoryNamespace namespace(String agentId, String sessionId, String domain) {
        return new MemoryNamespace(agentId, sessionId, "demo", domain);
    }

    private static void ensureSeed(SessionMemoryStore.Session session, MemoryNamespace namespace,
                                   String seedId, String content) {
        boolean exists = session.longTermMemory().list(namespace, 1_000).stream()
                .anyMatch(record -> seedId.equals(record.metadata().get("demoSeed")));
        if (!exists) {
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

runAgent creates context policy and the runtime facade

runAgent creates AgentContextFactory.scoped(request -> session.longTermMemory()). On each agent run, the factory returns an AgentContext with new WorkingMemory, the scoped LongTermMemory, namespace, session ID, and principal. The service calls CoalaAgentDefinition.of to build the definition and ActionRegistry, then `new CoalaAgent(definition)` and `agent.run(new AgentRunRequest(...))`.

The definition makes the selected procedure, action allow-list, context factory, and max-cycle bound explicit. In this current demo wiring, trace listeners and completion listeners default to empty lists; no post-run hook is registered by this service path.

Actual source excerpt: dev/coala/demo/DemoUseCaseService.java (source lines 145-168)

```
    private AgentRunResult runAgent(String agentId, CoalaDecisionProcedure procedure,
                                    List<? extends CoalaAction> actions, String goal, int maxCycles,
                                    SessionMemoryStore.Session session) {
        return runAgent(agentId, procedure, actions, goal, maxCycles, session, MemoryNamespace.DEFAULT);
    }

    private AgentRunResult runAgent(String agentId, CoalaDecisionProcedure procedure,
                                    List<? extends CoalaAction> actions, String goal, int maxCycles,
                                    SessionMemoryStore.Session session, MemoryNamespace namespace) {
        AgentContextFactory contextFactory = AgentContextFactory.scoped(request -> session.longTermMemory());
        CoalaAgentDefinition definition = CoalaAgentDefinition.of(agentId, procedure, actions, contextFactory,
        maxCycles);
        CoalaAgent agent = new CoalaAgent(definition);
        return agent.run(new AgentRunRequest(goal, session.sessionId(), "demo", namespace));
    }

    private static MemoryNamespace namespace(String agentId, String sessionId, String domain) {
        return new MemoryNamespace(agentId, sessionId, "demo", domain);
    }

    private static void ensureSeed(SessionMemoryStore.Session session, MemoryNamespace namespace,
                                   String seedId, String content) {
        boolean exists = session.longTermMemory().list(namespace, 1_000).stream()
                .anyMatch(record -> seedId.equals(record.metadata().get("demoSeed")));
        if (!exists) {
```

Important boundary
The CoalaAgent facade is reusable, but this demo service currently constructs a new definition and agent facade for each request instead of registering six long-lived agent instances.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

AgentContextFactory creates one run-local state container

AgentContextFactory.scoped applies the resolver to AgentRunRequest and always creates `new WorkingMemory()`. This is why the current cycle state such as latest_observation, plan.candidates, travel.flight_options, or research.brief is not automatically carried into the next HTTP run. Only the supplied long-term memory object is shared across requests in a session.

The namespace, sessionId and principal are copied into AgentContext. These values travel with memory operations; the namespace is what makes the scoped retrieval/write boundaries meaningful. The current demo principal is the literal `demo`, which is not user authentication.

Actual source excerpt: dev/coala/core/agent/AgentContextFactory.java (source lines 1-25)

```
package dev.coala.core.agent;

import dev.coala.core.AgentContext;
import dev.coala.core.WorkingMemory;
import dev.coala.core.memory.LongTermMemory;

import java.util.Objects;
import java.util.function.Function;
import java.util.function.Supplier;

/** Creates isolated per-run working memory and supplies appropriately scoped long-term memory. */
@FunctionalInterface
public interface AgentContextFactory {
    AgentContext create(AgentRunRequest request);

    static AgentContextFactory isolated(Supplier<? extends LongTermMemory> memorySupplier) {
        Objects.requireNonNull(memorySupplier, "memorySupplier");
        return request -> new AgentContext(new WorkingMemory(), Objects.requireNonNull(memorySupplier.get(),
        "memory supplier returned null"), request.namespace(), request.sessionId(), request.principal());
    }

    static AgentContextFactory scoped(Function<AgentRunRequest, ? extends LongTermMemory> memoryResolver) {
        Objects.requireNonNull(memoryResolver, "memoryResolver");
        return request -> new AgentContext(new WorkingMemory(),
        Objects.requireNonNull(memoryResolver.apply(request), "memory resolver returned null"),
        request.namespace(), request.sessionId(), request.principal());
    }
}
```

Important boundary
A real multitenant app must resolve principal and tenant identity from authenticated application context, not from a caller-controlled string.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

CoalaAgent.run creates run identity and calls the procedure

CoalaAgent.run(AgentRunRequest) creates a random run UUID and calls definition.contextFactory().create(request). It publishes RUN_STARTED to trace listeners, invokes `definition.decisionProcedure().run(goal, context, actions, maxCycles)`, publishes each returned DecisionEvent, invokes completion listeners, publishes RUN_COMPLETED, and returns the AgentRunResult.

The trace listener list is empty in this use-case builder, so publish iterates zero listeners. The method still owns the instrumentation boundary. If a runtime exception escapes, it publishes a generic RUN_FAILED trace without exposing the exception message, then rethrows it for the API exception handler.

Method-call ledger

01	Create runId UUID.
02	Create run-local AgentContext using AgentContextFactory.
03	Publish RUN_STARTED (no-op with the current empty listener list).
04	Call the selected CoalaDecisionProcedure.run(...).
05	Publish returned decision events (also no-op with no listeners).
06	Run completion listeners if any; none are configured here.
07	Return AgentRunResult or rethrow a sanitized-trace failure.

Actual source excerpt: dev/coala/core/agent/CoalaAgent.java (source lines 18-48)

```
    public AgentRunResult run(String goal) { return run(AgentRunRequest.goal(goal)); }

    public AgentRunResult run(AgentRunRequest request) {
        UUID runId = UUID.randomUUID();
        AgentContext context = definition.contextFactory().create(request);
        if (context == null) throw new IllegalStateException("AgentContextFactory returned null");
        publish(new DecisionTrace(runId, id(), request.sessionId(), "RUN_STARTED", null, "", "Agent run
        started", null));
        try {
            AgentRunResult result = definition.decisionProcedure().run(request.goal(), context,
                    definition.actions(), definition.maxCycles());
            for (DecisionEvent event : result.events()) publish(DecisionTrace.from(runId, id(),
        request.sessionId(), event));
            for (AgentRunCompletionListener listener : definition.completionListeners()) {
                try { listener.onCompleted(result, context); }
                catch (RuntimeException ignored) { /* Learning hooks are opt-in and cannot rewrite the completed
         result. */ }
            }
            publish(new DecisionTrace(runId, id(), request.sessionId(), "RUN_COMPLETED",
        result.cyclesExecuted(),
                    result.terminationReason().name(), "Agent run completed", null));
            return result;
        } catch (RuntimeException ex) {
            // Do not leak exception messages, prompts, tokens, or action arguments to generic traces.
            publish(new DecisionTrace(runId, id(), request.sessionId(), "RUN_FAILED", context.cycle(),
                    ex.getClass().getSimpleName(), "Agent run failed; inspect controlled application logs",
        null));
            throw ex;
        }
    }

    private void publish(DecisionTrace trace) {
        for (DecisionTraceListener listener : definition.traceListeners()) {
            try { listener.onTrace(trace); }
            catch (RuntimeException ignored) { /* Observability must not change decision semantics. */ }
        }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The shared decision loop initializes working memory

AbstractLoopingDecisionProcedure.run is the shared execution skeleton. It rejects blank or oversized goals and maxCycles outside 1..100, trims the goal, then writes goal and the initial latest_observation string into WorkingMemory. The first loop iteration begins at cycle one; each cycle stores that number on AgentContext.

Before planning, it records an OBSERVATION event and clears transient plan-selection fields so a previous cycle's candidate or selected_action cannot masquerade as the current decision. It does not clear domain outputs such as web_search.results, research.brief, travel.calendar, or support.triage; those are intentionally retained within the same run.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 25-60)

```
 */
public abstract class AbstractLoopingDecisionProcedure implements CoalaDecisionProcedure {
    public static final int MAX_GOAL_CHARACTERS = 4_000;

    @Override
    public final AgentRunResult run(String goal, AgentContext context, ActionRegistry actions, int maxCycles) {
        if (goal == null || goal.isBlank()) throw new IllegalArgumentException("goal must not be blank");
        if (goal.length() > MAX_GOAL_CHARACTERS) throw new IllegalArgumentException("goal must be no more than "
         + MAX_GOAL_CHARACTERS + " characters");
        goal = goal.trim();
        if (maxCycles < 1 || maxCycles > 100) throw new IllegalArgumentException("maxCycles must be between 1
        and 100");

        context.workingMemory().put("goal", goal.trim());
        context.workingMemory().put("latest_observation", "User request received: " + goal.trim());
        List<DecisionEvent> events = new ArrayList<>();
        String finalObservation = "";

        for (int cycle = 1; cycle <= maxCycles; cycle++) {
            context.setCycle(cycle);
            String observation = context.workingMemory().getString("latest_observation", "");
            events.add(new DecisionEvent(cycle, DecisionStage.OBSERVATION,
                    truncate(observation, 240)));

            // Do not let a previous cycle's plan be mistaken for the current selection.
            context.workingMemory().put("plan.candidates", null);
            context.workingMemory().put("plan.evaluations", null);
            context.workingMemory().put("plan.selectedAction", null);
            context.workingMemory().put("plan.selectionRejected", null);
            context.workingMemory().put("plan.last_rejection", null);
            context.workingMemory().put("plan.previousRejectedCandidates", null);
            context.workingMemory().put("selected_action", null);
            context.workingMemory().put("selected_action_id", null);
            context.workingMemory().put("selected_action_arguments", null);

            PlanDecision plan;
            try {
                plan = planNextAction(context, actions);
```

Important boundary
The observation is the action result from the preceding cycle, not an automatic dump of all working memory.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

ActionRegistry is an allow-list, not an LLM tool executor

ActionRegistry’s constructor rejects null entries, blank IDs, descriptor/action ID mismatches, duplicates, and empty registries. `require(id)` resolves a string only from this registry. `validate(call)` calls require and then the registered action’s validate method, which enforces required/optional argument definitions, allowed fields, value type/length/range constraints, and contract consistency.

The model returns an ActionCall, which is data. No generated shell command, Java, script, or arbitrary reflection target is executed. The selected registered object is the one whose execute method the base loop calls.

Actual source excerpt: dev/coala/core/ActionRegistry.java (source lines 13-48)

```
    public ActionRegistry(Collection<? extends CoalaAction> actionList) {
        Objects.requireNonNull(actionList, "actionList");
        Map<String, CoalaAction> found = new LinkedHashMap<>();
        for (CoalaAction action : actionList) {
            if (action == null) throw new IllegalArgumentException("Action list contains null");
            if (action.id() == null || action.id().isBlank()) throw new IllegalArgumentException("Action id must
             not be blank");
            ActionDescriptor descriptor = action.descriptor();
            if (!action.id().equals(descriptor.id())) {
                throw new IllegalArgumentException("Action descriptor id does not match action id: " +
        action.id());
            }
            if (found.putIfAbsent(action.id(), action) != null) {
                throw new IllegalArgumentException("Duplicate action id: " + action.id());
            }
        }
        if (found.isEmpty()) throw new IllegalArgumentException("At least one action is required");
        this.actions = Collections.unmodifiableMap(new LinkedHashMap<>(found));
    }

    public CoalaAction require(String id) {
        CoalaAction action = actions.get(id);
        if (action == null) throw new DecisionProcedureException("Unknown action id proposed by the model: " +
        id);
        return action;
    }

    /** Resolve the action against the allow-list and enforce its declared argument contract. */
    public CoalaAction validate(ActionCall call) {
        CoalaAction action = require(call.actionId());
        action.validate(call);
        return action;
    }

    public List<ActionDescriptor> descriptors() {
        return actions.values().stream().map(CoalaAction::descriptor).toList();
    }
```

Important boundary
For higher-risk production actions, input validation must be followed by authorization and approval policy checks at the action boundary.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

ActionCall and ActionOutputParser make the model output structured

ActionCall is an immutable record: actionId plus string-valued arguments. Its constructor rejects missing IDs, excessive argument counts, oversized keys/values, and excessive aggregate argument text. The parser uses Jackson 3 strict features to reject duplicate JSON object keys and trailing JSON values.

Each procedure chooses its parser method: parseAction for one action, parseCandidates for at least two distinct alternatives, parseEvaluation for one finite score per candidate plus rejectAll, or parseActionPlan for a bounded list of steps. Only the shape chosen by the procedure is accepted; the parser never executes model output.

Actual source excerpt: dev/coala/core/action/ActionOutputParser.java (source lines 20-71)

```
public final class ActionOutputParser {
    private final ObjectMapper mapper;

    public ActionOutputParser() {
        // Jackson 3 is Spring Boot 4's default. Reject duplicate object keys and
        // trailing JSON values so ambiguous model output fails closed.
        this.mapper = JsonMapper.builder()
                .enable(DeserializationFeature.FAIL_ON_READING_DUP_TREE_KEY)
                .enable(DeserializationFeature.FAIL_ON_TRAILING_TOKENS)
                .build();
    }

    public ActionCall parseAction(String raw) {
        JsonNode root = parseJson(raw, "action proposal");
        requireObject(root, "Action JSON must be an object.");
        requireOnlyFields(root, Set.of("actionId", "arguments"), "action proposal");
        JsonNode actionId = root.get("actionId");
        if (actionId == null || !actionId.isTextual() || actionId.asText().isBlank()) {
            throw new InvalidModelOutputException("Action JSON must contain a non-empty string 'actionId'.");
        }
        return buildActionCall(actionId.asText(), parseArguments(root.get("arguments")));
    }

    /** Parses a set of at least two distinct alternatives. */
    public List<ActionCall> parseCandidates(String raw, int maxCandidates) {
        if (maxCandidates < 2) throw new IllegalArgumentException("maxCandidates must be at least 2");
        JsonNode root = parseJson(raw, "candidate proposal");
        requireObject(root, "Candidate JSON must be an object.");
        requireOnlyFields(root, Set.of("candidates"), "candidate proposal");
        JsonNode candidates = root.get("candidates");
        if (candidates == null || !candidates.isArray() || candidates.size() < 2) {
            throw new InvalidModelOutputException("Candidate JSON must contain at least two alternatives in a
        'candidates' array.");
        }
        if (candidates.size() > maxCandidates) {
            throw new InvalidModelOutputException("Model proposed " + candidates.size()
                    + " candidates; configured limit is " + maxCandidates + ".");
        }
        List<ActionCall> parsed = new ArrayList<>();
        Set<ActionCall> seen = new HashSet<>();
        for (JsonNode candidate : candidates) {
            requireObject(candidate, "Every candidate must be a JSON object.");
            requireOnlyFields(candidate, Set.of("actionId", "arguments"), "candidate action");
            JsonNode id = candidate.get("actionId");
            if (id == null || !id.isTextual() || id.asText().isBlank()) {
                throw new InvalidModelOutputException("Every candidate must contain a non-empty 'actionId'.");
            }
            ActionCall call = buildActionCall(id.asText(), parseArguments(candidate.get("arguments")));
            if (!seen.add(call)) {
                throw new InvalidModelOutputException("Candidate set contains duplicate action calls; propose
        distinct alternatives.");
            }
            parsed.add(call);
        }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

WorkingMemory.put/get/snapshot are state-changing operations, not passive maps

WorkingMemory is the active symbolic state for one run. put(key, value) first rejects null/blank keys and calls freeze(value) before taking the write lock. freeze accepts a small set of scalar types and recursively copies Maps, Lists and Sets into unmodifiable collections. This prevents a caller from mutating a nested map after it has been stored. Unsupported objects, non-string map keys, and null items inside collections fail fast rather than silently entering prompt state.

A top-level null has a different meaning from a null nested value: put(key, null) removes the key. The procedure relies on that behavior to clear stale plan.candidates, selected_action, and reasoning.latest. get(key) returns an Optional under the read lock; getString maps a present value through Object.toString or uses a fallback; snapshot returns an unmodifiable copy of the current top-level map. renderForPrompt renders a detached snapshot after releasing the lock, so prompt formatting does not hold the lock while doing string work.

For each cycle, the state must be read as a sequence of snapshots and writes. For example, after a search action writes web_search.results, cycle 2 does not reconstruct those results from the prior observation; it sees the domain key preserved in the same WorkingMemory object. A new HTTP request creates a new WorkingMemory, even when its sessionId resumes the same long-term memory.

Method-call ledger

01	WorkingMemory.put(key, value) checks the key.
02	freeze(value) defensively copies and freezes supported nested collections.
03	Acquire writeLock; if safeValue == null remove key, otherwise put key/value.
04	get(key) acquires readLock and returns Optional.ofNullable(values.get(key)).
05	getString(key, fallback) converts present values with Object.toString; absent keys use fallback.
06	snapshot() returns an unmodifiable copy made under readLock.
07	renderForPrompt calls snapshot, then formats outside the lock.

State and observable values

Field	Value / meaning
top-level null	means remove that key
nested null	rejected inside maps/lists/sets
cross-cycle	same WorkingMemory for all cycles in one run
cross-request	not retained; only long-term memory is shared by session

Actual source excerpt: dev/coala/core/WorkingMemory.java (source lines 20-105)

```
    private final ReentrantReadWriteLock lock = new ReentrantReadWriteLock();
    private final LinkedHashMap<String, Object> values = new LinkedHashMap<>();

    public void put(String key, Object value) {
        if (key == null || key.isBlank()) throw new IllegalArgumentException("key must not be blank");
        Object safeValue = value == null ? null : freeze(value);
        lock.writeLock().lock();
        try {
            if (safeValue == null) values.remove(key);
            else values.put(key, safeValue);
        } finally {
            lock.writeLock().unlock();
        }
    }

    /**
     * Working memory is symbolic state. Defensively freeze supported collection
     * types so snapshots/getters cannot be mutated through nested object references.
     */
    private Object freeze(Object value) {
        if (value instanceof String || value instanceof Boolean || value instanceof Byte
                || value instanceof Short || value instanceof Integer || value instanceof Long
                || value instanceof Float || value instanceof Double || value instanceof BigInteger
                || value instanceof BigDecimal || value instanceof Enum<?>) {
            return value;
        }
        if (value instanceof Map<?, ?> map) {
            Map<String, Object> frozen = new LinkedHashMap<>();
            map.forEach((key, nestedValue) -> {
                if (!(key instanceof String textKey) || textKey.isBlank()) {
                    throw new IllegalArgumentException("Working-memory map keys must be non-blank strings");
                }
                if (nestedValue == null) throw new IllegalArgumentException("Nested working-memory values must
        not be null");
                frozen.put(textKey, freeze(nestedValue));
            });
            return Collections.unmodifiableMap(frozen);
```

```
        }
        if (value instanceof List<?> list) {
            List<Object> frozen = new ArrayList<>(list.size());
            for (Object item : list) {
                if (item == null) throw new IllegalArgumentException("Nested working-memory values must not be
        null");
                frozen.add(freeze(item));
            }
            return Collections.unmodifiableList(frozen);
        }
        if (value instanceof Set<?> set) {
            Set<Object> frozen = new LinkedHashSet<>();
            for (Object item : set) {
                if (item == null) throw new IllegalArgumentException("Nested working-memory values must not be
        null");
                frozen.add(freeze(item));
            }
            return Collections.unmodifiableSet(frozen);
        }
        throw new IllegalArgumentException("Unsupported working-memory value type: " +
        value.getClass().getName());
    }

    public Optional<Object> get(String key) {
        lock.readLock().lock();
        try {
            return Optional.ofNullable(values.get(key));
        } finally {
            lock.readLock().unlock();
        }
    }

    public String getString(String key, String fallback) {
        return get(key).map(Object::toString).orElse(fallback);
    }

    public Map<String, Object> snapshot() {
        lock.readLock().lock();
        try {
            return Collections.unmodifiableMap(new LinkedHashMap<>(values));
        } finally {
            lock.readLock().unlock();
        }
    }

    public String renderForPrompt() {
        // Values are frozen on entry; format a detached snapshot without holding the lock.
        Map<String, Object> detached = snapshot();
        StringBuilder out = new StringBuilder();
        detached.forEach((key, value) -> out.append(key).append(" = ").append(value).append('\n'));
        return out.toString();
    }
}
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Argument contracts are two layers: shape, then action-specific validation

ActionOutputParser first enforces the JSON/data shape. ActionCall then bounds the action ID, number of arguments, key length, value length, and aggregate argument text. ActionRegistry.validate resolves the ID only against the registered allow-list and calls CoalaAction.validate. The default CoalaAction contract builds ActionArgumentDefinition entries from requiredArguments and optionalArguments; a concrete action can override argumentDefinitions to declare INTEGER, DECIMAL, BOOLEAN, ENUM, or URI types and length limits.

ActionArgumentDefinition.validate checks one value: null is rejected; excessive length is rejected; required blank values are rejected; an optional blank value returns early; then the selected type parser runs. INTEGER uses Long.parseLong, DECIMAL uses BigDecimal with precision/scale bounds, BOOLEAN accepts only true/false, ENUM checks exact membership, and URI requires an absolute URI. CoalaAction.validate additionally rejects unknown argument names and missing required names before validating each supplied value.

These contracts validate syntax and allowed fields; they do not prove a value is semantically appropriate. For example, an integer maxResults can parse successfully but still exceed a provider cap, so WebSearchGroundingAction applies its own domain check. Likewise, travel search actions separately require the calendar.checked precondition. Validation must not be mistaken for authorization or approval.

Method-call ledger

01	ActionRegistry.validate(ActionCall) calls require(actionId).
02	require finds the registered CoalaAction or rejects an unknown ID.
03	CoalaAction.validate checks the call is non-null and builds the action’s definitions.
04	Build allowed and required name sets; reject duplicate/null definitions.
05	Reject unknown argument keys and missing required keys.
06	For each supplied argument, ActionArgumentDefinition.validate checks length and required blankness.
07	Switch on ValueType to parse and validate the typed string.
08	Concrete execute method performs domain preconditions after contract validation.

Actual source excerpt: dev/coala/core/ActionArgumentDefinition.java (source lines 1-66)

```
package dev.coala.core;

import java.math.BigDecimal;
import java.net.URI;
import java.util.LinkedHashSet;
import java.util.Set;

/** Typed input contract for a registered action. This is an implementation-level validation aid. */
public record ActionArgumentDefinition(
        String name,
        ValueType type,
        String description,
        boolean required,
        Set<String> allowedValues,
        int maxLength) {

    public enum ValueType { STRING, INTEGER, DECIMAL, BOOLEAN, ENUM, URI }

    public ActionArgumentDefinition {
        if (name == null || name.isBlank() || name.length() > ActionCall.MAX_ARGUMENT_KEY_LENGTH)
            throw new IllegalArgumentException("Argument name must be non-blank and at most " +
        ActionCall.MAX_ARGUMENT_KEY_LENGTH + " characters");
        if (type == null) throw new IllegalArgumentException("Argument type is required");
        description = description == null ? "" : description;
        allowedValues = allowedValues == null ? Set.of() : Set.copyOf(new LinkedHashSet<>(allowedValues));
        if (maxLength < 1 || maxLength > ActionCall.MAX_ARGUMENT_VALUE_LENGTH)
            throw new IllegalArgumentException("maxLength must be between 1 and " +
        ActionCall.MAX_ARGUMENT_VALUE_LENGTH);
        if (type == ValueType.ENUM && allowedValues.isEmpty()) throw new IllegalArgumentException("ENUM
        arguments must declare allowedValues");
        if (type != ValueType.ENUM && !allowedValues.isEmpty()) throw new IllegalArgumentException("Only ENUM
        arguments may declare allowedValues");
    }

    public static ActionArgumentDefinition requiredString(String name, String description) {
        return new ActionArgumentDefinition(name, ValueType.STRING, description, true, Set.of(), 4_000);
    }
    public static ActionArgumentDefinition optionalString(String name, String description) {
        return new ActionArgumentDefinition(name, ValueType.STRING, description, false, Set.of(), 4_000);
    }

    public void validate(String value) {
        if (value == null) throw new DecisionProcedureException("Argument '" + name + "' must not be null.");
        if (value.length() > maxLength) throw new DecisionProcedureException("Argument '" + name + "' exceeds
        its maximum length of " + maxLength + ".");
        if (required && value.isBlank()) throw new DecisionProcedureException("Required argument '" + name + "'
        must not be blank.");
        if (value.isBlank() && !required) return;
```

```
        try {
            switch (type) {
                case STRING -> { }
                case INTEGER -> Long.parseLong(value.trim());
                case DECIMAL -> {
                    BigDecimal decimal = new BigDecimal(value.trim());
                    if (decimal.precision() > 100 || Math.abs(decimal.scale()) > 100) throw new
        NumberFormatException("numeric value outside supported precision");
                }
                case BOOLEAN -> {
                    if (!value.equalsIgnoreCase("true") && !value.equalsIgnoreCase("false")) throw new
        IllegalArgumentException("must be true or false");
                }
                case ENUM -> {
                    if (!allowedValues.contains(value)) throw new IllegalArgumentException("must be one of " +
        allowedValues);
                }
                case URI -> {
                    URI uri = URI.create(value.trim());
                    if (!uri.isAbsolute()) throw new IllegalArgumentException("must be an absolute URI");
                }
            }
        } catch (RuntimeException ex) {
            throw new DecisionProcedureException("Argument '" + name + "' is not a valid " + type + " value: " +
         ex.getMessage(), ex);
        }
    }
}
```

Important boundary
The actual interface validation continues in CoalaAction.java; argument validation is one part of an action boundary, not a substitute for safety rules inside the action.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Strict JSON parsing has its own nested call path

ActionOutputParser is not a single “parse JSON” call. parseAction, parseCandidates, parseEvaluation and parseActionPlan each invoke parseJson first, then requireObject, requireOnlyFields, and their specific structure checks. They call parseArguments to force every model-supplied argument to be a JSON string, then buildActionCall. buildActionCall delegates final size/shape constraints to the ActionCall constructor and converts an IllegalArgumentException into InvalidModelOutputException.

parseJson rejects null/blank strings and outputs over 64,000 characters. It optionally removes exactly one outer fenced JSON block only when the closing fence is well formed and no trailing content remains. Jackson’s configured strict mapper then reads the JSON tree; malformed JSON, duplicate keys, or trailing JSON values become InvalidModelOutputException. This exception is caught by the API advice and returned as a sanitized 502 for invalid model output.

Different procedures use different parsers. Iterative reasoning uses parseAction for one action object. Deliberative planning uses parseCandidates, which requires at least two distinct ActionCall values, then parseEvaluation, which requires one finite numeric score per candidate plus a boolean rejectAll. Plan-first uses parseActionPlan, which enforces a non-empty bounded steps array. Parsing never resolves the action implementation and never executes anything; ActionRegistry performs the next validation step.

Method-call ledger

01	Procedure receives raw string from ReasoningAction.reason.
02	Call the procedure-specific parser: parseAction / parseCandidates / parseEvaluation / parseActionPlan.
03	parseJson checks empty/size/fenced form and invokes Jackson readTree.
04	requireObject rejects scalar/array roots where an object is required.
05	requireOnlyFields rejects unknown JSON properties.
06	Procedure-specific code validates arrays, booleans, scores, IDs, or step counts.
07	parseArguments converts only textual JSON values into Map<String,String>.
08	buildActionCall invokes ActionCall constructor and translates contract errors.
09	Procedure/loop next passes ActionCall to ActionRegistry.validate; only then can execution happen.

Actual source excerpt: dev/coala/core/action/ActionOutputParser.java (source lines 20-205)

```
public final class ActionOutputParser {
    private final ObjectMapper mapper;

    public ActionOutputParser() {
        // Jackson 3 is Spring Boot 4's default. Reject duplicate object keys and
        // trailing JSON values so ambiguous model output fails closed.
        this.mapper = JsonMapper.builder()
                .enable(DeserializationFeature.FAIL_ON_READING_DUP_TREE_KEY)
                .enable(DeserializationFeature.FAIL_ON_TRAILING_TOKENS)
                .build();
    }

    public ActionCall parseAction(String raw) {
        JsonNode root = parseJson(raw, "action proposal");
        requireObject(root, "Action JSON must be an object.");
        requireOnlyFields(root, Set.of("actionId", "arguments"), "action proposal");
        JsonNode actionId = root.get("actionId");
        if (actionId == null || !actionId.isTextual() || actionId.asText().isBlank()) {
            throw new InvalidModelOutputException("Action JSON must contain a non-empty string 'actionId'.");
        }
        return buildActionCall(actionId.asText(), parseArguments(root.get("arguments")));
    }

    /** Parses a set of at least two distinct alternatives. */
    public List<ActionCall> parseCandidates(String raw, int maxCandidates) {
        if (maxCandidates < 2) throw new IllegalArgumentException("maxCandidates must be at least 2");
        JsonNode root = parseJson(raw, "candidate proposal");
        requireObject(root, "Candidate JSON must be an object.");
        requireOnlyFields(root, Set.of("candidates"), "candidate proposal");
        JsonNode candidates = root.get("candidates");
        if (candidates == null || !candidates.isArray() || candidates.size() < 2) {
            throw new InvalidModelOutputException("Candidate JSON must contain at least two alternatives in a
        'candidates' array.");
        }
        if (candidates.size() > maxCandidates) {
            throw new InvalidModelOutputException("Model proposed " + candidates.size()
                    + " candidates; configured limit is " + maxCandidates + ".");
        }
        List<ActionCall> parsed = new ArrayList<>();
        Set<ActionCall> seen = new HashSet<>();
        for (JsonNode candidate : candidates) {
            requireObject(candidate, "Every candidate must be a JSON object.");
            requireOnlyFields(candidate, Set.of("actionId", "arguments"), "candidate action");
            JsonNode id = candidate.get("actionId");
            if (id == null || !id.isTextual() || id.asText().isBlank()) {
                throw new InvalidModelOutputException("Every candidate must contain a non-empty 'actionId'.");
            }
```

```
        ActionCall call = buildActionCall(id.asText(), parseArguments(candidate.get("arguments")));
        if (!seen.add(call)) {
            throw new InvalidModelOutputException("Candidate set contains duplicate action calls; propose
    distinct alternatives.");
        }
        parsed.add(call);
    }
    return List.copyOf(parsed);
}

/**
 * Parses an explicit selection decision and one score per candidate. rejectAll=true
 * means no candidate is selected and planning returns to proposal.
 */
public CandidateEvaluation parseEvaluation(String raw, int expectedCandidates) {
    if (expectedCandidates < 2) throw new IllegalArgumentException("expectedCandidates must be at least 2");
    JsonNode root = parseJson(raw, "candidate evaluation");
    requireObject(root, "Evaluation JSON must be an object.");
    requireOnlyFields(root, Set.of("rejectAll", "scores"), "candidate evaluation");
    JsonNode reject = root.get("rejectAll");
    if (reject == null || !reject.isBoolean()) {
        throw new InvalidModelOutputException("Evaluation JSON must contain boolean 'rejectAll'.");
    }
    JsonNode scoreNode = root.get("scores");
    if (scoreNode == null || !scoreNode.isArray() || scoreNode.isEmpty()) {
        throw new InvalidModelOutputException("Evaluation JSON must contain a non-empty 'scores' array.");
    }
    if (scoreNode.size() != expectedCandidates) {
        throw new InvalidModelOutputException("Evaluator returned " + scoreNode.size() + " score(s) for " +
    expectedCandidates + " candidate(s).");
    }
    List<Double> scores = new ArrayList<>();
    for (JsonNode score : scoreNode) {
        if (!score.isNumber()) throw new InvalidModelOutputException("Every candidate score must be
    numeric.");
        double value = score.asDouble();
        if (!Double.isFinite(value)) throw new InvalidModelOutputException("Candidate scores must be finite
    numbers.");
        scores.add(value);
    }
    return new CandidateEvaluation(reject.asBoolean(), scores);
}


/** Parses a bounded structured plan of executable action calls. */
public List<ActionCall> parseActionPlan(String raw, int maxSteps) {
    if (maxSteps < 1 || maxSteps > 20) throw new IllegalArgumentException("maxSteps must be 1..20");
    JsonNode root = parseJson(raw, "action plan");
    requireObject(root, "Plan JSON must be an object.");
    requireOnlyFields(root, Set.of("steps"), "action plan");
    JsonNode steps = root.get("steps");
    if (steps == null || !steps.isArray() || steps.isEmpty() || steps.size() > maxSteps)
        throw new InvalidModelOutputException("Plan must contain between 1 and " + maxSteps + " steps.");
    List<ActionCall> parsed = new ArrayList<>();
    for (JsonNode candidate : steps) {
        requireObject(candidate, "Every plan step must be an object.");
        requireOnlyFields(candidate, Set.of("actionId", "arguments"), "plan step");
        JsonNode id = candidate.get("actionId");
        if (id == null || !id.isTextual() || id.asText().isBlank()) throw new
    InvalidModelOutputException("Each plan step requires a non-empty actionId.");
        parsed.add(buildActionCall(id.asText(), parseArguments(candidate.get("arguments"))));
    }
    return List.copyOf(parsed);
}

public ActionQualityEvaluation parseQualityEvaluation(String raw) {
    JsonNode root = parseJson(raw, "action quality evaluation");
    requireObject(root, "Quality evaluation JSON must be an object.");
    requireOnlyFields(root, Set.of("accepted", "score", "feedback"), "quality evaluation");
    JsonNode accepted = root.get("accepted"), score = root.get("score"), feedback = root.get("feedback");
    if (accepted == null || !accepted.isBoolean() || score == null || !score.isNumber() || feedback == null
    || !feedback.isTextual())
        throw new InvalidModelOutputException("Quality evaluation requires boolean accepted, numeric score
    and string feedback.");
    double value = score.asDouble();
    if (!Double.isFinite(value) || value < 0 || value > 1) throw new InvalidModelOutputException("Quality
    score must be finite and between 0 and 1.");
    String note = feedback.asText();
    if (note.length() > 1_000) note = note.substring(0, 997) + "...";
    return new ActionQualityEvaluation(accepted.asBoolean(), value, note);
}

/** Retained as a utility for tests and callers that only need score parsing. */
public List<Double> parseScores(String raw) {
    JsonNode root = parseJson(raw, "candidate evaluation");
    requireObject(root, "Evaluation JSON must be an object.");
    requireOnlyFields(root, Set.of("scores"), "candidate score result");
    JsonNode scores = root.get("scores");
    if (scores == null || !scores.isArray() || scores.isEmpty()) {
        throw new InvalidModelOutputException("Evaluation JSON must contain a non-empty 'scores' array.");
    }
    List<Double> result = new ArrayList<>();
    for (JsonNode score : scores) {
        if (!score.isNumber() || !Double.isFinite(score.asDouble())) {
            throw new InvalidModelOutputException("Every candidate score must be a finite number.");
        }
        result.add(score.asDouble());
    }
    return List.copyOf(result);
}
```

```
private Map<String, String> parseArguments(JsonNode node) {
    if (node == null || node.isNull() || !node.isObject()) {
        throw new InvalidModelOutputException("'arguments' must be a JSON object.");
    }
    if (node.size() > ActionCall.MAX_ARGUMENTS) {
        throw new InvalidModelOutputException("Action JSON contains too many arguments.");
    }
    Map<String, String> args = new LinkedHashMap<>();
    node.fields().forEachRemaining(entry -> {
        JsonNode value = entry.getValue();
        if (!value.isTextual()) {
            throw new InvalidModelOutputException("Action argument '" + entry.getKey() + "' must be a
    string.");
        }
        args.put(entry.getKey(), value.asText());
    });
    return Map.copyOf(args);
}


private ActionCall buildActionCall(String actionId, Map<String, String> arguments) {
    try {
        return new ActionCall(actionId, arguments);
    } catch (IllegalArgumentException ex) {
        throw new InvalidModelOutputException("Action proposal violates the action-call data contract: " +
    ex.getMessage(), ex);
    }
}

private void requireOnlyFields(JsonNode node, Set<String> allowed, String description) {
    var fields = node.fields();
    while (fields.hasNext()) {
        String field = fields.next().getKey();
        if (!allowed.contains(field)) {
            throw new InvalidModelOutputException("Unexpected field '" + field + "' in " + description +
    ".");
        }
    }
}

private void requireObject(JsonNode node, String message) {
    if (node == null || !node.isObject()) throw new InvalidModelOutputException(message);
}

private JsonNode parseJson(String raw, String description) {
    if (raw == null || raw.isBlank()) throw new InvalidModelOutputException("Empty " + description + "
    output.");
    if (raw.length() > 64_000) throw new InvalidModelOutputException(description + " exceeds the maximum
    allowed size.");
    String text = raw.trim();
    if (text.startsWith("```")) {
        int firstNewline = text.indexOf('\n');
```

Important boundary
A syntactically valid action JSON can still name an unregistered action or fail an action’s value contract. The parser, registry and concrete action each protect a different boundary.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

ReasoningAction.reason assembles a bounded, sanitized prompt

LlmReasoningAction increments a per-run reasoning.call_count and enforces its configured maximum. It asks PromptContextPolicy for keys that can be shown to the current operation, builds a bounded WorkingMemoryPromptContext, sanitizes the goal and full prompt using configured redaction patterns, and sends only the final prompt to LanguageModel.generate.

It rejects empty or excessively large model output, then stores reasoning.last_operation and reasoning.latest. The procedure-specific caller parses that string into an ActionCall, candidate list, evaluation, or plan, and clears reasoning.latest on the successful path so raw JSON does not remain as long-term state.

Method-call ledger

01	Read reasoning.call_count from WorkingMemory and enforce budget.
02	Select operation-specific prompt context with PromptContextPolicy.requestFor.
03	Build and bound a view using WorkingMemoryPromptContextBuilder.build.
04	Sanitize goal and complete assembled prompt.
05	Call LanguageModel.generate(prompt).
06	Reject empty/oversized output; store operation and raw output temporarily.

Actual source excerpt: dev/coala/core/action/LlmReasoningAction.java (source lines 35-79)

```
        }
        this.maxCallsPerRun = maxCallsPerRun;
        this.promptContextBuilder = Objects.requireNonNull(promptContextBuilder, "promptContextBuilder");
        this.promptContextPolicy = Objects.requireNonNull(promptContextPolicy, "promptContextPolicy");
    }

    @Override
    public String reason(String operation, String instruction, AgentContext context) {
        int callCount = Integer.parseInt(context.workingMemory().getString("reasoning.call_count", "0"));
        if (callCount >= maxCallsPerRun) {
            throw new DecisionProcedureException("Maximum reasoning-call budget exhausted for this run (" +
        maxCallsPerRun + ").");
        }
        context.workingMemory().put("reasoning.call_count", callCount + 1);
        WorkingMemoryPromptContextBuilder.Request request = promptContextPolicy.requestFor(operation, context);
        if (request == null) throw new IllegalStateException("PromptContextPolicy returned null for " +
        operation);
        WorkingMemoryPromptContextBuilder.PromptContext memoryView =
        promptContextBuilder.build(context.workingMemory(), request);
        String prompt = "You are performing an internal CoALA reasoning action.\n"
                + "OPERATION=" + operation + "\n"
                + "CYCLE=" + context.cycle() + "\n"
                + "GOAL=" + promptContextBuilder.sanitizeText(context.workingMemory().getString("goal", ""),
        request) + "\n"
                + "WORKING_MEMORY_BEGIN\n" + memoryView.rendered()
                + "WORKING_MEMORY_END\n"
                + instruction + "\n"
                + "Return only the requested result. Do not perform an external action yourself.";
        String generated;
        try {
            generated = languageModel.generate(promptContextBuilder.sanitizeText(prompt, request));
        } catch (LanguageModelException ex) {
            throw ex;
        } catch (RuntimeException ex) {
            throw new LanguageModelException("Language-model provider call failed for operation " + operation +
        ".", ex);
        }
        if (generated == null || generated.isBlank()) {
            throw new LanguageModelException("Language-model provider returned an empty response for operation "
         + operation + ".");
        }
        String normalized = generated.trim();
        if (normalized.length() > MAX_MODEL_OUTPUT_CHARACTERS) {
            throw new InvalidModelOutputException("Language-model output exceeds the maximum allowed size of "
                    + MAX_MODEL_OUTPUT_CHARACTERS + " characters.");
        }
        context.workingMemory().put("reasoning.last_operation", operation);
        context.workingMemory().put("reasoning.latest", normalized);
        return normalized;
    }
}
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

PromptContextPolicy and WorkingMemoryPromptContextBuilder restrict context

The default prompt policy is an allow-list of named working-memory keys such as goal, latest_observation, retrieved_memories, plan candidates/evaluations, and domain-specific result keys. It can add approved namespaces such as web_search.*, research.*, travel.*, and support.*. It does not serialize every key automatically.

WorkingMemoryPromptContextBuilder snapshots memory, filters to allowed keys, rejects explicitly denied or credential-like key names, renders values, applies secret redaction patterns, and truncates at a bounded size. These steps reduce accidental prompt disclosure but do not make arbitrary user content trustworthy or replace data classification.

Actual source excerpt: dev/coala/core/PromptContextPolicy.java (source lines 12-33)

```
            keys.add("goal", "latest_observation", "latest_action", "retrieved_memories", "plan.candidates",
                    "plan.evaluations", "plan.last_rejection", "plan.previousRejectedCandidates",
        "plan.first_steps",
                    "plan.refinementCandidate", "plan.refinementEvaluation", "reasoning.call_count",
                    "reasoning.last_operation", "reflection.latest", "interaction.pending",
        "interaction.answer",
                    "retrieved_skills", "web_search.results", "calculator.lastResult",
        "calculator.lastExpression",
                    "research.topic", "research.brief", "research.source_count", "research.final",
                    "travel.calendar", "travel.destination", "travel.flight_options", "travel.hotel_options",
                    "travel.proposed_itinerary", "travel.estimate_cad", "travel.calendar.checked",
                    "travel.budget_cad", "travel.within_budget", "support.triage");
                // Built-in grounding actions use a per-action namespace for outputs. Include those
                // non-sensitive result keys dynamically without dumping unrelated working memory.
                context.workingMemory().snapshot().keySet().stream()
                        .filter(key -> key.startsWith("http.") || key.startsWith("workspace.") ||
        key.startsWith("web_search."))
                        .forEach(key -> keys.add(key));
                return new WorkingMemoryPromptContextBuilder.Request(keys.values(), java.util.Set.of(),
                        WorkingMemoryPromptContextBuilder.defaultRedactionPatterns(), 12_000, true);
            };
        }

        final class SetBuilder {
            private final java.util.Set<String> values = new java.util.LinkedHashSet<>();
            void add(String... names) { java.util.Collections.addAll(values, names); }
```

Important boundary
Model prompts contain user goals and tool observations. Treat both as untrusted input and keep action authorization in code rather than in prompt instructions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

ScriptedLanguageModel selects deterministic fixtures

ScriptedLanguageModel is not an LLM. It parses the OPERATION marker and CYCLE integer from the prompt, then switches to a fixed fixture function. In the research path it chooses candidate JSON or scores based on whether the prompt contains `format_evidence_brief`; in travel it creates a fixed plan; in support it checks cycle and simple keywords in the goal.

This is a design choice for offline repeatability. It makes the examples good for teaching call sequencing and parsing, but it does not prove that a real model will always choose these actions, score these candidates similarly, or extract destinations and budgets correctly.

Actual source excerpt: dev/coala/llm/ScriptedLanguageModel.java (source lines 22-47)

```
        return switch (operation) {
            case "DIRECT_ACTION" -> "{\"actionId\":\"respond\",\"arguments\":{\"text\":\"This is the
        direct-action demo response. The request was handled by one selected dialogue grounding action; enable
        the openai profile to use an actual LLM.\"}}";
            case "PLAN_FIRST" -> planFirst(prompt);
            case "ITERATIVE_NEXT_ACTION" -> iterativeAction(cycle, prompt);
            case "PROPOSE_CANDIDATES" -> prompt.contains("format_evidence_brief") ? researchCandidates(cycle,
        prompt) : puzzleCandidates(cycle);
            case "EVALUATE_CANDIDATES" -> prompt.contains("format_evidence_brief") ? researchScores(cycle) :
        puzzleScores(cycle);
            default -> throw new IllegalArgumentException("Scripted adapter has no fixture for operation=" +
        operation);
        };
    }

    private String extractOperation(String prompt) {
        Matcher matcher = Pattern.compile("OPERATION=([A-Z_]+)").matcher(prompt);
        if (!matcher.find()) throw new IllegalArgumentException("Prompt has no OPERATION marker.");
        return matcher.group(1);
    }

    private int extractCycle(String prompt) {
        Matcher matcher = CYCLE.matcher(prompt);
        return matcher.find() ? Integer.parseInt(matcher.group(1)) : 1;
    }

    private String extractGoal(String prompt) {
        Matcher matcher = GOAL.matcher(prompt);
        return matcher.find() ? matcher.group(1).trim() : "the requested topic";
    }
```

Important boundary
The OpenAI profile changes the provider adapter; it does not remove the need for the same parser, action registry, state checks, limits and tests.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

What the offline language-model adapter actually calls

LanguageModel.generate(prompt) is the seam used by the cognitive framework. In the offline profile, the object behind that interface is ScriptedLanguageModel. Its generate method does not invoke a remote model: it calls extractOperation(prompt), extractCycle(prompt), and extractGoal(prompt), then routes the operation marker through a switch to the matching fixture method.

For this research run the operation marker is PROPOSE_CANDIDATES or EVALUATE_CANDIDATES and the cycle number chooses the fixed candidate or score JSON. For travel, operation PLAN_FIRST routes to planFirst(prompt), which calls extractDestination and extractBudget and constructs a six-step JSON plan. For support, ITERATIVE_NEXT_ACTION routes through iterativeAction to supportAction; the latter branches on cycle number and simple keywords in extractGoal(prompt).

This page is critical when interpreting the trace: a method named generate does not imply an LLM request. Spring AI is not contacted in this default profile. If the OpenAI profile is enabled, the provider adapter implements LanguageModel with a remote model call; the surrounding prompt assembly, parsing, action registry, procedure and execution path remain the same, but the exact returned JSON may differ.

Method-call ledger

01	LlmReasoningAction.reason calls languageModel.generate(sanitizedPrompt).
02	ScriptedLanguageModel.generate extracts operation marker.
03	extractCycle reads CYCLE=<integer>; extractGoal reads the GOAL line.
04	switch routes to planFirst, iterativeAction, researchCandidates, researchScores, or another fixture method.
05	The chosen fixture returns a JSON string; it has not called any action.
06	The procedure-specific parser validates that string before an ActionCall can be selected.

State and observable values

Field	Value / meaning
Research	operation + cycle determine the canned candidates/scores
Travel	PLAN_FIRST + regex-extracted destination/budget determine fixed plan JSON
Support	cycle 1 returns classification; cycle 2 uses goal keywords to return escalation
Provider I/O	none in scripted profile

Actual source excerpt: dev/coala/llm/ScriptedLanguageModel.java (source lines 19-58)

```
    public String generate(String prompt) {
        String operation = extractOperation(prompt);
        int cycle = extractCycle(prompt);
        return switch (operation) {
            case "DIRECT_ACTION" -> "{\"actionId\":\"respond\",\"arguments\":{\"text\":\"This is the
        direct-action demo response. The request was handled by one selected dialogue grounding action; enable
        the openai profile to use an actual LLM.\"}}";
            case "PLAN_FIRST" -> planFirst(prompt);
            case "ITERATIVE_NEXT_ACTION" -> iterativeAction(cycle, prompt);
            case "PROPOSE_CANDIDATES" -> prompt.contains("format_evidence_brief") ? researchCandidates(cycle,
        prompt) : puzzleCandidates(cycle);
            case "EVALUATE_CANDIDATES" -> prompt.contains("format_evidence_brief") ? researchScores(cycle) :
        puzzleScores(cycle);
            default -> throw new IllegalArgumentException("Scripted adapter has no fixture for operation=" +
        operation);
        };
    }

    private String extractOperation(String prompt) {
        Matcher matcher = Pattern.compile("OPERATION=([A-Z_]+)").matcher(prompt);
        if (!matcher.find()) throw new IllegalArgumentException("Prompt has no OPERATION marker.");
        return matcher.group(1);
    }

    private int extractCycle(String prompt) {
        Matcher matcher = CYCLE.matcher(prompt);
        return matcher.find() ? Integer.parseInt(matcher.group(1)) : 1;
    }

    private String extractGoal(String prompt) {
        Matcher matcher = GOAL.matcher(prompt);
        return matcher.find() ? matcher.group(1).trim() : "the requested topic";
    }

    private String extractDestination(String prompt) {
        Matcher matcher = DESTINATION.matcher(extractGoal(prompt));
        if (!matcher.find()) return "Paris";
        String result = matcher.group(1).trim();
        // Fixture-only parser stops at common temporal/prepositional phrases.
        result = result.replaceFirst("(?i)\\s+(next|this|on|for|within|with|from|during)\\b.*$", "").trim();
```

```
        if (result.isBlank()) return "Paris";
        return result.length() > 40 ? result.substring(0, 40) : result;
    }

    private String planFirst(String prompt) {
```

Important boundary
Fixture behavior is deterministic and should not be described as semantic LLM reasoning. It is used so every method call and observation can be reproduced offline.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Procedure-specific prompt and result parsing

The procedure’s code writes an instruction string containing a required operation marker and the allowed action catalog. LlmReasoningAction wraps this instruction with goal, cycle and selected working-memory view. The scripted model returns JSON; ActionOutputParser enforces the expected data structure; the procedure then validates action IDs against the active ActionRegistry.

That layered validation is intentional: prompt wording guides the model, JSON parsing checks the schema, ActionCall checks bounded string values, and ActionRegistry checks whether the specific action exists and accepts those arguments. The action adapter still checks domain preconditions such as calendar.checked before performing simulated inventory search.

Actual source excerpt: dev/coala/core/action/ActionOutputParser.java (source lines 35-70)

```
        requireOnlyFields(root, Set.of("actionId", "arguments"), "action proposal");
        JsonNode actionId = root.get("actionId");
        if (actionId == null || !actionId.isTextual() || actionId.asText().isBlank()) {
            throw new InvalidModelOutputException("Action JSON must contain a non-empty string 'actionId'.");
        }
        return buildActionCall(actionId.asText(), parseArguments(root.get("arguments")));
    }

    /** Parses a set of at least two distinct alternatives. */
    public List<ActionCall> parseCandidates(String raw, int maxCandidates) {
        if (maxCandidates < 2) throw new IllegalArgumentException("maxCandidates must be at least 2");
        JsonNode root = parseJson(raw, "candidate proposal");
        requireObject(root, "Candidate JSON must be an object.");
        requireOnlyFields(root, Set.of("candidates"), "candidate proposal");
        JsonNode candidates = root.get("candidates");
        if (candidates == null || !candidates.isArray() || candidates.size() < 2) {
            throw new InvalidModelOutputException("Candidate JSON must contain at least two alternatives in a
        'candidates' array.");
        }
        if (candidates.size() > maxCandidates) {
            throw new InvalidModelOutputException("Model proposed " + candidates.size()
                    + " candidates; configured limit is " + maxCandidates + ".");
        }
        List<ActionCall> parsed = new ArrayList<>();
        Set<ActionCall> seen = new HashSet<>();
        for (JsonNode candidate : candidates) {
            requireObject(candidate, "Every candidate must be a JSON object.");
            requireOnlyFields(candidate, Set.of("actionId", "arguments"), "candidate action");
            JsonNode id = candidate.get("actionId");
            if (id == null || !id.isTextual() || id.asText().isBlank()) {
                throw new InvalidModelOutputException("Every candidate must contain a non-empty 'actionId'.");
            }
            ActionCall call = buildActionCall(id.asText(), parseArguments(candidate.get("arguments")));
            if (!seen.add(call)) {
                throw new InvalidModelOutputException("Candidate set contains duplicate action calls; propose
        distinct alternatives.");
            }
            parsed.add(call);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

ActionResult, WorkingMemory and events determine loop progression

An action returns ActionResult with observation, terminal and awaitingInput. AbstractLoopingDecisionProcedure writes latest_action and latest_observation from that result and emits EXECUTION or LEARNING depending on action.kind. If awaitingInput is true, it returns AWAITING_INPUT; if terminal is true, it returns TERMINAL_ACTION; otherwise the next cycle starts until maxCycles is reached.

The public AgentRunResult contains procedure id, goal, final observation, number of cycles, termination reason and events. This result is what DemoUseCaseService wraps with the sessionId and what the controller serializes to JSON.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 90-121)

```
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
     external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
    run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
    cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

The API return path does not alter the final agent observation

Once CoalaDecisionProcedure.run returns AgentRunResult, CoalaAgent returns that same result after its optional trace/listener hooks. DemoUseCaseService.run creates `new UseCaseRunResponse(session.sessionId(), result)`. CoalaController returns the record and Spring serializes it to JSON.

The finalObservation field is the observation returned by the last selected action. For these examples it is intentionally different by domain: the full evidence brief for research, the itinerary text for travel, and the escalation guidance for support.

State and observable values

Field	Value / meaning
Envelope	UseCaseRunResponse
sessionId	Opaque server-generated value for follow-up calls
run.procedure	Procedure id string
run.cyclesExecuted	6
run.terminationReason	TERMINAL_ACTION
run.finalObservation	Use-case-specific final action observation

Actual source excerpt: dev/coala/demo/UseCaseRunResponse.java (source lines 1-6)

```
package dev.coala.demo;

import dev.coala.core.AgentRunResult;

/** API envelope allowing the caller to resume the same long-term-memory session later. */
public record UseCaseRunResponse(String sessionId, AgentRunResult run) {}
```

Important boundary
Cycle events are explanations of stages, not a complete method profiler. The pages in this document add the finer method-call ledger that events alone do not contain.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 1 / 1 - decide whether the plan must be created or revised

Cycle 1 begins with latest_observation = User request received: Plan a trip to Paris next month for 3 nights under CAD 1400; check calendar first.. `plan.first_steps` is absent, so readPending returns an empty ArrayList. The default replanCondition checks lowercase observation text for failure:, error:, or needs_replan; the initial observation does not match. Because pending is empty, the procedure must create a plan.

PlanFirstDecisionProcedure builds an instruction saying “a plan is a proposal, not execution,” calls reasoning.reason("PLAN_FIRST", prompt, context), and passes the output to ActionOutputParser.parseActionPlan with maxSteps=8. The scripted adapter sees check_calendar and draft_itinerary in the catalog and emits the following six ordered steps.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run calls planNextAction(context, actions).
02	PlanFirstDecisionProcedure reads latest_observation and calls readPending(null) -> empty list.
03	replanCondition.test(observation) returns false.
04	pending.isEmpty() is true, so format ActionCatalogFormatter.format(actions.descriptors()).
05	ReasoningAction.reason("PLAN_FIRST", prompt, context) -> LlmReasoningAction -> ScriptedLanguageModel.planFirst.
06	ActionOutputParser.parseActionPlan(raw, 8) parses the list of steps.

State and observable values

Field	Value / meaning
reasoning operation	PLAN_FIRST - only plan-generation call in this successful run
parsed plan steps	6
selected step	check_calendar
planned dates	Scripted fixture: 2026-11-05 to 2026-11-08, not derived from goal

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-62)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
```

Important boundary
The scripted plan is a demo fixture. In a live LLM profile, a plan is a model proposal and still must pass all JSON, action allow-list and argument checks.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 1 / 2 - the stored plan step becomes a single ActionCall

The exact fixture JSON returned from ScriptedLanguageModel.planFirst is shown below. It was built from the action IDs exposed by this run's catalog and a simple regex over the goal. extractDestination captures "Paris" before the temporal phrase "next month"; extractBudget finds the digits after "CAD", yielding 1400. Those are fixture parsing rules, not general destination/date/budget understanding.

parseActionPlan rejects an empty plan, more than eight steps, malformed step objects, unknown fields and invalid argument maps. The procedure then calls actions.validate on every step and refuses any plan step whose action kind is not GROUNDING or LEARNING. Only after every step validates does it write plan.first_steps and take the first item.

Method-call ledger

01	ScriptedLanguageModel.extractGoal -> extractDestination -> jsonEscape -> extractBudget.
02	ScriptedLanguageModel.planFirst returns the six-step JSON plan.
03	ActionOutputParser.parseActionPlan validates root and step count/shape.
04	For each step: ActionRegistry.validate checks ID and typed argument contract.
05	Check action.kind is GROUNDING or LEARNING.
06	WorkingMemory.put("plan.first_steps", all step maps); remove first step.

State and observable values

Field	Value / meaning
full proposed plan	{"steps":[{"actionId":"check_calendar","arguments":{}},{"actionId":"search_flights","arguments":{"destination":"Paris","origin":"YUL"}},{"actionId":"search_hotels","arguments":{"destination":"Paris","checkIn":"2026-11-05","nights":"3"}},{"actionId":"draft_itinerary","arguments":{"budgetCad":"1400"}},{"actionId":"learn_episode","arguments":{"content":"Travel workflow lesson: check the calendar before inventory searches and never book from mock results.","success":"true","importance":"0.6","source":"travel-demo"}},{"actionId":"present_itinerary","arguments":{}}]}
first selected action	check_calendar with no arguments
plan preserved for later cycles	yes; remaining five steps are stored

Actual source excerpt: dev/coala/llm/ScriptedLanguageModel.java (source lines 57-88)

```
    private String planFirst(String prompt) {
        if (!prompt.contains("check_calendar") || !prompt.contains("draft_itinerary")) {
            throw new IllegalArgumentException("Scripted adapter has no PLAN_FIRST fixture for this action
        catalogue.");
        }
        String destination = jsonEscape(extractDestination(prompt));
        String budget = extractBudget(prompt);
        return "{\"steps\":["
                + "{\"actionId\":\"check_calendar\",\"arguments\":{}},"
                + "{\"actionId\":\"search_flights\",\"arguments\":{\"destination\":\"" + destination +
        "\",\"origin\":\"YUL\"}},"
                + "{\"actionId\":\"search_hotels\",\"arguments\":{\"destination\":\"" + destination +
        "\",\"checkIn\":\"2026-11-05\",\"nights\":\"3\"}},"
                + "{\"actionId\":\"draft_itinerary\",\"arguments\":{\"budgetCad\":\"" + budget + "\"}},"
                + "{\"actionId\":\"learn_episode\",\"arguments\":{\"content\":\"Travel workflow lesson: check
        the calendar before inventory searches and never book from mock
        results.\",\"success\":\"true\",\"importance\":\"0.6\",\"source\":\"travel-demo\"}},"
                + "{\"actionId\":\"present_itinerary\",\"arguments\":{}}]}";
    }

    private String iterativeAction(int cycle, String prompt) {
        if (prompt.contains("check_calendar") && prompt.contains("draft_itinerary")) return travelAction(cycle,
        prompt);
        if (prompt.contains("classify_support_case") && prompt.contains("escalate_case")) return
        supportAction(cycle, prompt);
        return iterativeCodingAction(cycle);
    }

    private String travelAction(int cycle, String prompt) {
        String destination = jsonEscape(extractDestination(prompt));
        return switch (cycle) {
            case 1 -> "{\"actionId\":\"check_calendar\",\"arguments\":{}}";
            case 2 -> "{\"actionId\":\"search_flights\",\"arguments\":{\"destination\":\"" + destination +
        "\",\"origin\":\"YUL\"}}";
            case 3 -> "{\"actionId\":\"search_hotels\",\"arguments\":{\"destination\":\"" + destination +
        "\",\"checkIn\":\"2026-11-05\",\"nights\":\"3\"}}";
            case 4 -> "{\"actionId\":\"draft_itinerary\",\"arguments\":{}}";
            case 5 -> "{\"actionId\":\"learn_episode\",\"arguments\":{\"content\":\"Travel workflow lesson:
        check the calendar before inventory searches and never book from mock
        results.\",\"success\":\"true\",\"importance\":\"0.6\",\"source\":\"travel-demo\"}}";
            default -> "{\"actionId\":\"present_itinerary\",\"arguments\":{}}";
        };
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 1 / 3 - execute check_calendar

The common loop executes the registered implementation for check_calendar. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

The only model call for this successful run occurs while creating the six-step plan in cycle 1. The parser validates every planned action before the first step executes. The selected step is check_calendar.

The action observation is: Mock calendar checked: the illustrative 2026-11-05 to 2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.

Method-call ledger

01	ActionRegistry.validate(ActionCall("check_calendar", arguments)) returns registered object.
02	check_calendar.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	check_calendar
arguments	{}
observation	Mock calendar checked: the illustrative 2026-11-05 to 2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/demo/action/TravelGroundingActions.java (source lines 17-34)

```
public final class TravelGroundingActions {
    private TravelGroundingActions() { }

    public static GroundingAction checkCalendar() {
        return action("check_calendar", "Check the mock calendar before searching travel inventory.", Set.of(),
        Set.of(), ActionRisk.LOW,
                (call, context) -> {
                    Map<String, Object> calendar = Map.of("window", "2026-11-05 to 2026-11-08", "conflicts",
        "none in fixture", "status", "simulated");
                    context.workingMemory().put("travel.calendar", calendar);
                    context.workingMemory().put("travel.calendar.checked", true);
                    return ActionResult.continueWith("Mock calendar checked: the illustrative 2026-11-05 to
        2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.");
                });
    }

    public static GroundingAction searchFlights() {
        return action("search_flights", "Search synthetic flight options after the calendar check.",
        Set.of("destination"), Set.of("origin"), ActionRisk.LOW,
                (call, context) -> {
                    if (!Boolean.parseBoolean(context.workingMemory().getString("travel.calendar.checked",
        "false"))) {
                        return ActionResult.continueWith("needs_replan: calendar availability must be checked
        before flight search; no provider query was made.");
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 1 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
travel.calendar	{window: 2026-11-05 to 2026-11-08, conflicts: none in fixture, status: simulated}
travel.calendar.checked	true
remaining plan steps	5
latest_action	check_calendar
latest_observation	Mock calendar checked: the illustrative 2026-11-05 to 2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.
plan.first_steps	5 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 1 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: Mock calendar checked: the illustrative 2026-11-05 to 2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.. Next control transfer: Cycle 2 reads the pending plan and selects search_flights.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	1
terminal?	no
replan marker present?	no
next action	Cycle 2 reads the pending plan and selects search_flights.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 2 / 1 - decide whether the plan must be created or revised

Cycle 2 begins with latest_observation = Mock calendar checked: the illustrative 2026-11-05 to 2026-11-08 window has no seeded conflict. Dates are a fixture, not a live calendar result.. At the previous cycle the procedure already stored the plan remainder in plan.first_steps. readPending reconstructs each stored map as an ActionCall by reading actionId and a Map of string arguments; it returns a new ArrayList so removing the selected step does not mutate the immutable snapshot accidentally.

The default replan predicate looks only for failure:, error:, or needs_replan in the latest action observation. This cycle's observation has none of those markers, so pending is nonempty and revise=false. Therefore the branch that calls reasoning.reason("PLAN_FIRST", ...) is skipped. No new prompt, ScriptedLanguageModel call, or JSON plan parsing happens in cycles 2-6.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run sets the cycle number and calls planNextAction.
02	WorkingMemory.getString("latest_observation", "").
03	readPending(workingMemory.get("plan.first_steps").orElse(null)) reconstructs ActionCalls.
04	replanCondition.test(observation) returns false for this observation.
05	pending is nonempty, so no PLAN_FIRST reasoning call is made.
06	selected = pending.remove(0); remaining steps are written back.

State and observable values

Field	Value / meaning
pending before selection	5 step(s)
replan condition	false
new model call	none
selected step	search_flights
remaining after selection	4 step(s)

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
This is an important contrast with iterative and deliberative procedures: this cycle reuses the stored plan, so the model is not asked again unless a configured replan marker appears.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 2 / 2 - the stored plan step becomes a single ActionCall

The remaining step selected in cycle 2 is search_flights, with arguments {"destination":"Paris","origin":"YUL"}. The procedure removed it from the in-memory pending list, wrote the reduced list to plan.first_steps, and wrote plan.selectedAction as a map with actionId and arguments. The common base loop will validate this chosen ActionCall again before execution and commit selected_action, selected_action_id and selected_action_arguments.

There is no need to ask the model to restate an already validated plan step. This reuse is what makes plan-first a distinct decision shape: the first planning pass emits a sequence; later cycles execute one step and only revise when the current observation matches the configured failure/error/needs_replan predicate.

Method-call ledger

01	selected = pending.remove(0).
02	WorkingMemory.put("plan.first_steps", remaining steps).
03	WorkingMemory.put("plan.selectedAction", state(selected)).
04	PlanDecision(selected, [selected], no evaluation scores, events).
05	AbstractLoopingDecisionProcedure validates selected action again before execute.

State and observable values

Field	Value / meaning
action ID	search_flights
arguments	{"destination":"Paris","origin":"YUL"}
evaluation scores	none: plan-first does not evaluate each step separately
selected action	one preplanned step

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 59-69)

```
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 2 / 3 - execute search_flights

The common loop executes the registered implementation for search_flights. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

PlanFirstDecisionProcedure reads plan.first_steps, tests the prior observation against the replan predicate, and reuses the plan because the observation contains no failure:, error:, or needs_replan marker. It selects the first pending step without calling reasoning or ScriptedLanguageModel.

The action observation is: Mock flight search returned two synthetic round-trip fares for Paris: CAD 640 and CAD 710. No airline was contacted.

Method-call ledger

01	ActionRegistry.validate(ActionCall("search_flights", arguments)) returns registered object.
02	search_flights.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	search_flights
arguments	{"destination":"Paris","origin":"YUL"}
observation	Mock flight search returned two synthetic round-trip fares for Paris: CAD 640 and CAD 710. No airline was contacted.
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/demo/action/TravelGroundingActions.java (source lines 35-62)

```
                }
                String destination = call.argument("destination", "Paris");
                String origin = call.argument("origin", "YUL");
                List<Map<String, Object>> options = List.of(
                        Map.of("name", "Fixture flight A", "route", origin + " to " + destination,
    "priceCad", 640, "detail", "round trip; sample fare"),
                        Map.of("name", "Fixture flight B", "route", origin + " to " + destination,
    "priceCad", 710, "detail", "round trip; sample fare"));
                context.workingMemory().put("travel.flight_options", options);
                context.workingMemory().put("travel.destination", destination);
                return ActionResult.continueWith("Mock flight search returned two synthetic round-trip fares
     for " + destination + ": CAD 640 and CAD 710. No airline was contacted.");
            });
    }

    public static GroundingAction searchHotels() {
        return action("search_hotels", "Search synthetic lodging options after the calendar check.",
        Set.of("destination"), Set.of("checkIn", "nights"), ActionRisk.LOW,
                (call, context) -> {
                    if (!Boolean.parseBoolean(context.workingMemory().getString("travel.calendar.checked",
        "false"))) {
                        return ActionResult.continueWith("needs_replan: calendar availability must be checked
        before hotel search; no provider query was made.");
                    }
                    String destination = call.argument("destination",
        context.workingMemory().getString("travel.destination", "Paris"));
                    String checkIn = call.argument("checkIn", "2026-11-05");
                    String nights = call.argument("nights", "3");
                    List<Map<String, Object>> options = List.of(
                            Map.of("name", "Fixture hotel A", "destination", destination, "checkIn", checkIn,
        "nights", nights, "totalCad", 390, "detail", "sample total"),
                            Map.of("name", "Fixture hotel B", "destination", destination, "checkIn", checkIn,
        "nights", nights, "totalCad", 460, "detail", "sample total"));
                    context.workingMemory().put("travel.hotel_options", options);
                    return ActionResult.continueWith("Mock hotel search returned two synthetic lodging totals:
        CAD 390 and CAD 460. No property was contacted.");
                });
    }
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 2 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
travel.flight_options	Two map entries: fixture A CAD 640; fixture B CAD 710
travel.destination	Paris
remaining plan steps	4
latest_action	search_flights
latest_observation	Mock flight search returned two synthetic round-trip fares for Paris: CAD 640 and CAD 710. No airline was contacted.
plan.first_steps	4 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 2 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: Mock flight search returned two synthetic round-trip fares for Paris: CAD 640 and CAD 710. No airline was contacted.. Next control transfer: Cycle 3 reuses the remaining plan and selects search_hotels.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	2
terminal?	no
replan marker present?	no
next action	Cycle 3 reuses the remaining plan and selects search_hotels.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 3 / 1 - decide whether the plan must be created or revised

Cycle 3 begins with latest_observation = Mock flight search returned two synthetic round-trip fares for Paris: CAD 640 and CAD 710. No airline was contacted.. At the previous cycle the procedure already stored the plan remainder in plan.first_steps. readPending reconstructs each stored map as an ActionCall by reading actionId and a Map of string arguments; it returns a new ArrayList so removing the selected step does not mutate the immutable snapshot accidentally.

The default replan predicate looks only for failure:, error:, or needs_replan in the latest action observation. This cycle's observation has none of those markers, so pending is nonempty and revise=false. Therefore the branch that calls reasoning.reason("PLAN_FIRST", ...) is skipped. No new prompt, ScriptedLanguageModel call, or JSON plan parsing happens in cycles 2-6.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run sets the cycle number and calls planNextAction.
02	WorkingMemory.getString("latest_observation", "").
03	readPending(workingMemory.get("plan.first_steps").orElse(null)) reconstructs ActionCalls.
04	replanCondition.test(observation) returns false for this observation.
05	pending is nonempty, so no PLAN_FIRST reasoning call is made.
06	selected = pending.remove(0); remaining steps are written back.

State and observable values

Field	Value / meaning
pending before selection	4 step(s)
replan condition	false
new model call	none
selected step	search_hotels
remaining after selection	3 step(s)

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
This is an important contrast with iterative and deliberative procedures: this cycle reuses the stored plan, so the model is not asked again unless a configured replan marker appears.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 3 / 2 - the stored plan step becomes a single ActionCall

The remaining step selected in cycle 3 is search_hotels, with arguments {"destination":"Paris","checkIn":"2026-11-05","nights":"3"}. The procedure removed it from the in-memory pending list, wrote the reduced list to plan.first_steps, and wrote plan.selectedAction as a map with actionId and arguments. The common base loop will validate this chosen ActionCall again before execution and commit selected_action, selected_action_id and selected_action_arguments.

There is no need to ask the model to restate an already validated plan step. This reuse is what makes plan-first a distinct decision shape: the first planning pass emits a sequence; later cycles execute one step and only revise when the current observation matches the configured failure/error/needs_replan predicate.

Method-call ledger

01	selected = pending.remove(0).
02	WorkingMemory.put("plan.first_steps", remaining steps).
03	WorkingMemory.put("plan.selectedAction", state(selected)).
04	PlanDecision(selected, [selected], no evaluation scores, events).
05	AbstractLoopingDecisionProcedure validates selected action again before execute.

State and observable values

Field	Value / meaning
action ID	search_hotels
arguments	{"destination":"Paris","checkIn":"2026-11-05","nights":"3"}
evaluation scores	none: plan-first does not evaluate each step separately
selected action	one preplanned step

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 59-69)

```
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 3 / 3 - execute search_hotels

The common loop executes the registered implementation for search_hotels. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

The pending plan provides the destination, check-in date and three-night duration. The action checks the calendar flag again before it fabricates results; if the guard was false it would return needs_replan and would not populate hotel inventory.

The action observation is: Mock hotel search returned two synthetic lodging totals: CAD 390 and CAD 460. No property was contacted.

Method-call ledger

01	ActionRegistry.validate(ActionCall("search_hotels", arguments)) returns registered object.
02	search_hotels.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	search_hotels
arguments	{"destination":"Paris","checkIn":"2026-11-05","nights":"3"}
observation	Mock hotel search returned two synthetic lodging totals: CAD 390 and CAD 460. No property was contacted.
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/demo/action/TravelGroundingActions.java (source lines 63-89)

```
    public static GroundingAction draftItinerary() {
        return action("draft_itinerary", "Combine calendar, flight and hotel observations into a non-binding
        travel proposal and compare it with the stated budget cap.", Set.of(), Set.of("budgetCad"),
        ActionRisk.LOW,
                (call, context) -> {
                    if (!Boolean.parseBoolean(context.workingMemory().getString("travel.calendar.checked",
        "false"))
                            || context.workingMemory().get("travel.flight_options").isEmpty()
                            || context.workingMemory().get("travel.hotel_options").isEmpty()) {
                        return ActionResult.continueWith("needs_replan: the draft requires calendar, flight and
        hotel observations; no itinerary was finalized.");
                    }
                    String destination = context.workingMemory().getString("travel.destination", "Paris");
                    Object calendarObject = context.workingMemory().get("travel.calendar").orElse(Map.of());
                    Object flightsObject =
        context.workingMemory().get("travel.flight_options").orElse(List.of());
                    Object hotelsObject = context.workingMemory().get("travel.hotel_options").orElse(List.of());
                    int flight = minAmount(flightsObject, "priceCad", 640);
                    int hotel = minAmount(hotelsObject, "totalCad", 390);
                    int local = 160;
                    int total = flight + hotel + local;
                    int budget;
                    try { budget = Integer.parseInt(call.argument("budgetCad", "1400")); }
                    catch (NumberFormatException ex) { throw new IllegalArgumentException("budgetCad must be a
        whole number of CAD", ex); }
                    if (budget < 1 || budget > 1_000_000) throw new IllegalArgumentException("budgetCad must be
        between 1 and 1000000");
                    boolean withinBudget = total <= budget;
                    String window = calendarObject instanceof Map<?, ?> map && map.get("window") != null ?
        String.valueOf(map.get("window")) : "dates unconfirmed";
                    String itinerary = "Proposed trip to " + destination + "\n"
                            + "Date window: " + window + " (mock calendar fixture)\n"
                            + "Flight: lowest fixture fare CAD " + flight + "\n"
                            + "Hotel: lowest fixture total CAD " + hotel + "\n"
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 3 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
travel.hotel_options	Two map entries: fixture A CAD 390; fixture B CAD 460
travel.calendar.checked	still true
remaining plan steps	3
latest_action	search_hotels
latest_observation	Mock hotel search returned two synthetic lodging totals: CAD 390 and CAD 460. No property was contacted.
plan.first_steps	3 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 3 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: Mock hotel search returned two synthetic lodging totals: CAD 390 and CAD 460. No property was contacted.. Next control transfer: Cycle 4 selects draft_itinerary.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	3
terminal?	no
replan marker present?	no
next action	Cycle 4 selects draft_itinerary.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 4 / 1 - decide whether the plan must be created or revised

Cycle 4 begins with latest_observation = Mock hotel search returned two synthetic lodging totals: CAD 390 and CAD 460. No property was contacted.. At the previous cycle the procedure already stored the plan remainder in plan.first_steps. readPending reconstructs each stored map as an ActionCall by reading actionId and a Map of string arguments; it returns a new ArrayList so removing the selected step does not mutate the immutable snapshot accidentally.

The default replan predicate looks only for failure:, error:, or needs_replan in the latest action observation. This cycle's observation has none of those markers, so pending is nonempty and revise=false. Therefore the branch that calls reasoning.reason("PLAN_FIRST", ...) is skipped. No new prompt, ScriptedLanguageModel call, or JSON plan parsing happens in cycles 2-6.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run sets the cycle number and calls planNextAction.
02	WorkingMemory.getString("latest_observation", "").
03	readPending(workingMemory.get("plan.first_steps").orElse(null)) reconstructs ActionCalls.
04	replanCondition.test(observation) returns false for this observation.
05	pending is nonempty, so no PLAN_FIRST reasoning call is made.
06	selected = pending.remove(0); remaining steps are written back.

State and observable values

Field	Value / meaning
pending before selection	3 step(s)
replan condition	false
new model call	none
selected step	draft_itinerary
remaining after selection	2 step(s)

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
This is an important contrast with iterative and deliberative procedures: this cycle reuses the stored plan, so the model is not asked again unless a configured replan marker appears.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 4 / 2 - the stored plan step becomes a single ActionCall

The remaining step selected in cycle 4 is draft_itinerary, with arguments {"budgetCad":"1400"}. The procedure removed it from the in-memory pending list, wrote the reduced list to plan.first_steps, and wrote plan.selectedAction as a map with actionId and arguments. The common base loop will validate this chosen ActionCall again before execution and commit selected_action, selected_action_id and selected_action_arguments.

There is no need to ask the model to restate an already validated plan step. This reuse is what makes plan-first a distinct decision shape: the first planning pass emits a sequence; later cycles execute one step and only revise when the current observation matches the configured failure/error/needs_replan predicate.

Method-call ledger

01	selected = pending.remove(0).
02	WorkingMemory.put("plan.first_steps", remaining steps).
03	WorkingMemory.put("plan.selectedAction", state(selected)).
04	PlanDecision(selected, [selected], no evaluation scores, events).
05	AbstractLoopingDecisionProcedure validates selected action again before execute.

State and observable values

Field	Value / meaning
action ID	draft_itinerary
arguments	{"budgetCad":"1400"}
evaluation scores	none: plan-first does not evaluate each step separately
selected action	one preplanned step

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 59-69)

```
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 4 / 3 - execute draft_itinerary

The common loop executes the registered implementation for draft_itinerary. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

The action first checks calendar, flight options and hotel options all exist. minAmount picks the lowest fixture fare CAD 640 and hotel total CAD 390; local estimate is 160, so the subtotal is 640 + 390 + 160 = CAD 1,190. budgetCad is parsed as an integer, constrained to 1..1,000,000, and compared with total.

The action observation is: Assembled a draft itinerary from working-memory observations; illustrative subtotal CAD 1190. No reservation was made.

Method-call ledger

01	ActionRegistry.validate(ActionCall("draft_itinerary", arguments)) returns registered object.
02	draft_itinerary.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	draft_itinerary
arguments	{"budgetCad":"1400"}
observation	Assembled a draft itinerary from working-memory observations; illustrative subtotal CAD 1190. No reservation was made.
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/demo/action/TravelGroundingActions.java (source lines 90-119)

```
                        + "Local transport/food estimate: CAD " + local + "\n"
                        + "Illustrative subtotal: CAD " + total + "\n"
                        + "Budget cap: CAD " + budget + "\n"
                        + "Budget check: " + (withinBudget ? "WITHIN budget" : "OVER budget") + " (computed
    from fixture totals)\n"
                        + "Calendar conflicts: none in the fixture; real availability is unverified.\n"
                        + "Safety boundary: this is a draft only. No booking, payment or external account
    change occurred.";
                context.workingMemory().put("travel.proposed_itinerary", itinerary);
                context.workingMemory().put("travel.estimate_cad", total);
                context.workingMemory().put("travel.budget_cad", budget);
                context.workingMemory().put("travel.within_budget", withinBudget);
                return ActionResult.continueWith("Assembled a draft itinerary from working-memory
    observations; illustrative subtotal CAD " + total + ". No reservation was made.");
            });
    }

    public static GroundingAction presentItinerary() {
        return action("present_itinerary", "Return the draft itinerary to the user without making any
        reservation.", Set.of(), Set.of(), ActionRisk.LOW,
                (call, context) ->
        ActionResult.finish(context.workingMemory().getString("travel.proposed_itinerary",
                        "No itinerary could be prepared because required calendar/flight/hotel observations are
        missing.")));
    }

    private static int minAmount(Object raw, String key, int fallback) {
        if (!(raw instanceof List<?> list)) return fallback;
        int min = Integer.MAX_VALUE;
        for (Object item : list) if (item instanceof Map<?, ?> map && map.get(key) instanceof Number number) min
         = Math.min(min, number.intValue());
        return min == Integer.MAX_VALUE ? fallback : min;
    }

    private static GroundingAction action(String id, String description, Set<String> required, Set<String>
        optional,
                                          ActionRisk risk, BiFunction<ActionCall, AgentContext, ActionResult>
        operation) {
        return new GroundingAction() {
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 4 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
travel.estimate_cad	1190
travel.budget_cad	1400
travel.within_budget	true
remaining plan steps	2
latest_action	draft_itinerary
latest_observation	Assembled a draft itinerary from working-memory observations; illustrative subtotal CAD 1190. No reservation was made.
plan.first_steps	2 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 4 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: Assembled a draft itinerary from working-memory observations; illustrative subtotal CAD 1190. No reservation was made.. Next control transfer: Cycle 5 selects learn_episode.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	4
terminal?	no
replan marker present?	no
next action	Cycle 5 selects learn_episode.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 5 / 1 - decide whether the plan must be created or revised

Cycle 5 begins with latest_observation = Assembled a draft itinerary from working-memory observations; illustrative subtotal CAD 1190. No reservation was made.. At the previous cycle the procedure already stored the plan remainder in plan.first_steps. readPending reconstructs each stored map as an ActionCall by reading actionId and a Map of string arguments; it returns a new ArrayList so removing the selected step does not mutate the immutable snapshot accidentally.

The default replan predicate looks only for failure:, error:, or needs_replan in the latest action observation. This cycle's observation has none of those markers, so pending is nonempty and revise=false. Therefore the branch that calls reasoning.reason("PLAN_FIRST", ...) is skipped. No new prompt, ScriptedLanguageModel call, or JSON plan parsing happens in cycles 2-6.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run sets the cycle number and calls planNextAction.
02	WorkingMemory.getString("latest_observation", "").
03	readPending(workingMemory.get("plan.first_steps").orElse(null)) reconstructs ActionCalls.
04	replanCondition.test(observation) returns false for this observation.
05	pending is nonempty, so no PLAN_FIRST reasoning call is made.
06	selected = pending.remove(0); remaining steps are written back.

State and observable values

Field	Value / meaning
pending before selection	2 step(s)
replan condition	false
new model call	none
selected step	learn_episode
remaining after selection	1 step(s)

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
This is an important contrast with iterative and deliberative procedures: this cycle reuses the stored plan, so the model is not asked again unless a configured replan marker appears.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 5 / 2 - the stored plan step becomes a single ActionCall

The remaining step selected in cycle 5 is learn_episode, with arguments {"content":"Travel workflow lesson: check the calendar before inventory searches and never book from mock results.","success":"true","importance":"0.6","source":"travel-demo"}. The procedure removed it from the in-memory pending list, wrote the reduced list to plan.first_steps, and wrote plan.selectedAction as a map with actionId and arguments. The common base loop will validate this chosen ActionCall again before execution and commit selected_action, selected_action_id and selected_action_arguments.

There is no need to ask the model to restate an already validated plan step. This reuse is what makes plan-first a distinct decision shape: the first planning pass emits a sequence; later cycles execute one step and only revise when the current observation matches the configured failure/error/needs_replan predicate.

Method-call ledger

01	selected = pending.remove(0).
02	WorkingMemory.put("plan.first_steps", remaining steps).
03	WorkingMemory.put("plan.selectedAction", state(selected)).
04	PlanDecision(selected, [selected], no evaluation scores, events).
05	AbstractLoopingDecisionProcedure validates selected action again before execute.

State and observable values

Field	Value / meaning
action ID	learn_episode
arguments	{"content":"Travel workflow lesson: check the calendar before inventory searches and never book from mock results.","success":"true","importance":"0.6","source":"travel-demo"}
evaluation scores	none: plan-first does not evaluate each step separately
selected action	one preplanned step

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 59-69)

```
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 5 / 3 - execute learn_episode

The common loop executes the registered implementation for learn_episode. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

The plan includes learning as an explicit executable step. EpisodicMemoryLearningAction sanitizes the provided content, reads importance 0.6 and metadata success/source, creates a MemoryRecord of type EPISODIC in the travel namespace, and stores it in the session memory.

The action observation is: Stored one episodic experience in long-term memory.

Method-call ledger

01	ActionRegistry.validate(ActionCall("learn_episode", arguments)) returns registered object.
02	learn_episode.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	learn_episode
arguments	{"content":"Travel workflow lesson: check the calendar before inventory searches and never book from mock results.","success":"true","importance":"0.6","source":"travel-demo"}
observation	Stored one episodic experience in long-term memory.
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/core/learning/EpisodicMemoryLearningAction.java (source lines 24-51)

```
    @Override public ActionRisk risk() { return ActionRisk.LOW; }
    @Override public List<ActionArgumentDefinition> argumentDefinitions() {
        return List.of(ActionArgumentDefinition.optionalString("content", "Explicit episode content; defaults to
         a summary of the current goal and latest action/observation."),
                new ActionArgumentDefinition("success", ActionArgumentDefinition.ValueType.ENUM, "Outcome
        label", false, Set.of("true", "false", "unknown"), 10),
                new ActionArgumentDefinition("importance", ActionArgumentDefinition.ValueType.DECIMAL,
        "Importance from 0 to 1", false, Set.of(), 10),
                ActionArgumentDefinition.optionalString("source", "Optional provenance label"));
    }
    @Override public void validate(ActionCall call) {
        LearningAction.super.validate(call);
        String value = call.argument("importance", "0.5");
        try { double n = Double.parseDouble(value); if (n < 0 || n > 1 || !Double.isFinite(n)) throw new
        NumberFormatException(); }
        catch (NumberFormatException ex) { throw new DecisionProcedureException("importance must be a number
        between 0 and 1"); }
    }
    @Override public ActionResult execute(ActionCall call, AgentContext context) {
        String content = call.argument("content", "");
        if (content.isBlank()) {
            content = "Goal: " + context.workingMemory().getString("goal", "(unknown)")
                    + " | Latest action: " + context.workingMemory().getString("latest_action", "(none)")
                    + " | Outcome: " + context.workingMemory().getString("latest_observation", "(no
        observation)");
        }
        content = MemoryTextSanitizer.sanitize(content, MemoryRecord.MAX_CONTENT_CHARACTERS);
        if (content.isBlank()) throw new DecisionProcedureException("Episode content is empty after
        sanitization");
        double importance = Double.parseDouble(call.argument("importance", "0.5"));
        Map<String, String> metadata = new LinkedHashMap<>();
        metadata.put("success", MemoryTextSanitizer.sanitize(call.argument("success", "unknown"),
        MemoryRecord.MAX_METADATA_VALUE_CHARACTERS));
        metadata.put("source", MemoryTextSanitizer.sanitize(call.argument("source", "decision-cycle"),
        MemoryRecord.MAX_METADATA_VALUE_CHARACTERS));
        context.longTermMemory().store(MemoryRecord.of(MemoryType.EPISODIC, content, context.namespace(),
        metadata, importance));
        return ActionResult.continueWith("Stored one episodic experience in long-term memory.");
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 5 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
long-term memory	Adds one EPISODIC record under travel namespace
working memory	Plan steps continue; itinerary remains stored
remaining plan steps	1
latest_action	learn_episode
latest_observation	Stored one episodic experience in long-term memory.
plan.first_steps	1 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 5 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: Stored one episodic experience in long-term memory.. Next control transfer: Cycle 6 selects present_itinerary and terminates.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	5
terminal?	no
replan marker present?	no
next action	Cycle 6 selects present_itinerary and terminates.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 6 / 1 - decide whether the plan must be created or revised

Cycle 6 begins with latest_observation = Stored one episodic experience in long-term memory.. At the previous cycle the procedure already stored the plan remainder in plan.first_steps. readPending reconstructs each stored map as an ActionCall by reading actionId and a Map of string arguments; it returns a new ArrayList so removing the selected step does not mutate the immutable snapshot accidentally.

The default replan predicate looks only for failure:, error:, or needs_replan in the latest action observation. This cycle's observation has none of those markers, so pending is nonempty and revise=false. Therefore the branch that calls reasoning.reason("PLAN_FIRST", ...) is skipped. No new prompt, ScriptedLanguageModel call, or JSON plan parsing happens in cycles 2-6.

Method-call ledger

01	AbstractLoopingDecisionProcedure.run sets the cycle number and calls planNextAction.
02	WorkingMemory.getString("latest_observation", "").
03	readPending(workingMemory.get("plan.first_steps").orElse(null)) reconstructs ActionCalls.
04	replanCondition.test(observation) returns false for this observation.
05	pending is nonempty, so no PLAN_FIRST reasoning call is made.
06	selected = pending.remove(0); remaining steps are written back.

State and observable values

Field	Value / meaning
pending before selection	1 step(s)
replan condition	false
new model call	none
selected step	present_itinerary
remaining after selection	0 step(s)

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
    @Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
        String observation = context.workingMemory().getString("latest_observation", "");
        List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
        boolean revise = replanCondition.test(observation);
        if (pending.isEmpty() || revise) {
            if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
        current memory/observations. "
                    + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
        value\"}}]}. "
                    + "Only use the following registered actions and valid argument contracts: " +
        formatter.format(actions.descriptors()) + ". "
                    + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                    + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
        "");
            List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
        maxSteps);
            for (ActionCall step : proposed) {
                var action = actions.validate(step);
                if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                    throw new DecisionProcedureException("Plan step must target a registered grounding or
        learning action: " + step.actionId());
            }
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
This is an important contrast with iterative and deliberative procedures: this cycle reuses the stored plan, so the model is not asked again unless a configured replan marker appears.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 6 / 2 - the stored plan step becomes a single ActionCall

The remaining step selected in cycle 6 is present_itinerary, with arguments {}. The procedure removed it from the in-memory pending list, wrote the reduced list to plan.first_steps, and wrote plan.selectedAction as a map with actionId and arguments. The common base loop will validate this chosen ActionCall again before execution and commit selected_action, selected_action_id and selected_action_arguments.

There is no need to ask the model to restate an already validated plan step. This reuse is what makes plan-first a distinct decision shape: the first planning pass emits a sequence; later cycles execute one step and only revise when the current observation matches the configured failure/error/needs_replan predicate.

Method-call ledger

01	selected = pending.remove(0).
02	WorkingMemory.put("plan.first_steps", remaining steps).
03	WorkingMemory.put("plan.selectedAction", state(selected)).
04	PlanDecision(selected, [selected], no evaluation scores, events).
05	AbstractLoopingDecisionProcedure validates selected action again before execute.

State and observable values

Field	Value / meaning
action ID	present_itinerary
arguments	{}
evaluation scores	none: plan-first does not evaluate each step separately
selected action	one preplanned step

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 59-69)

```
            pending = new ArrayList<>(proposed);
            context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
            context.workingMemory().put("reasoning.latest", null);
        }
        ActionCall selected = pending.remove(0);
        context.workingMemory().put("plan.first_steps",
        pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("plan.selectedAction", state(selected));
        List<DecisionEvent> events = List.of(
                new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
        (pending.size() + 1) + " step(s) before selecting the next one."),
                new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
        step: " + selected.actionId() + "."));
        return new PlanDecision(selected, List.of(selected), List.of(), events);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 6 / 3 - execute present_itinerary

The common loop executes the registered implementation for present_itinerary. The action's code is not chosen dynamically: the model/plan only supplies an action ID and arguments, while the ActionRegistry points that ID to the Java implementation below. This action returns an ActionResult; it does not directly invoke the next action.

The final action reads travel.proposed_itinerary, falling back to a failure-style explanatory message if no itinerary exists, and returns ActionResult.finish. The base loop writes the full itinerary to latest_observation and finalObservation, appends a terminal event, and returns the result immediately.

The action observation is: the full itinerary text shown on the outcome page

Method-call ledger

01	ActionRegistry.validate(ActionCall("present_itinerary", arguments)) returns registered object.
02	present_itinerary.execute(call, context) runs the action-specific implementation.
03	That implementation reads current working memory, validates domain preconditions, computes or records its output, and returns ActionResult.
04	The loop receives the observation from ActionResult.

State and observable values

Field	Value / meaning
selected action	present_itinerary
arguments	{}
observation	Full itinerary
provider mode	synthetic / deterministic fixture

Actual source excerpt: dev/coala/demo/action/TravelGroundingActions.java (source lines 120-134)

```
            @Override public String id() { return id; }
            @Override public String description() { return description; }
            @Override public Set<String> requiredArguments() { return required; }
            @Override public Set<String> optionalArguments() { return optional; }
            @Override public ActionRisk risk() { return risk; }
            @Override public List<ActionArgumentDefinition> argumentDefinitions() {
                List<ActionArgumentDefinition> defs = new ArrayList<>();
                required.stream().sorted().forEach(key -> defs.add(ActionArgumentDefinition.requiredString(key,
        key)));
                optional.stream().sorted().forEach(key -> defs.add(ActionArgumentDefinition.optionalString(key,
        key)));
                return List.copyOf(defs);
            }
            @Override public boolean idempotent() { return true; }
            @Override public ActionResult execute(ActionCall call, AgentContext context) { return
        operation.apply(call, context); }
        };
    }
```

Important boundary
No real provider call is made. The calendar, fare and hotel data are values created inside TravelGroundingActions.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 6 / 4 - working-memory changes made by the action

WorkingMemory is a run-local, typed key/value store. The selected action can read earlier observations written by other actions; then it adds this step's output under domain-specific keys. Separately, after the action returns, AbstractLoopingDecisionProcedure writes latest_action and latest_observation for the next cycle.

The action-specific state change for this cycle is described below. It is distinct from plan.first_steps, which is the remaining plan sequence, and from selected_action, which records the action selected just before execution.

State and observable values

Field	Value / meaning
finalObservation	Full draft itinerary text
cyclesExecuted	6
terminationReason	TERMINAL_ACTION
reservations made	0
latest_action	present_itinerary
latest_observation	Full itinerary string
plan.first_steps	0 step(s) remain after this action

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 84-99)

```
            context.workingMemory().put("plan.selectedAction", toActionState(plan.selectedAction()));
            // Figure 3A describes parsed action names and arguments being written back
            // to working memory and then used to execute the selected action.
            context.workingMemory().put("selected_action", Map.of(
                    "actionId", selected.actionId(),
                    "arguments", selected.arguments()));
            context.workingMemory().put("selected_action_id", selected.actionId());
            context.workingMemory().put("selected_action_arguments", selected.arguments());
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Cycle 6 / 5 - end-of-cycle checks and next control transfer

After execution, the base loop appends a DecisionEvent whose stage is LEARNING for a learning action and EXECUTION for grounding actions. It checks awaitingInput first; none of the six travel actions returns awaitingInput. It then checks result.terminal. Only present_itinerary returns ActionResult.finish, so cycles 1-5 continue and cycle 6 terminates.

Latest observation after execution is: the full draft itinerary. Next control transfer: No cycle 7 occurs because the terminal result returns from run.

For plan-first, a nonterminal observation is checked by replanCondition at the start of the next cycle. No observation in this successful scenario includes failure:, error:, or needs_replan, so the remaining plan is consumed without another LLM call.

Method-call ledger

01	ActionResult returned to AbstractLoopingDecisionProcedure.run.
02	WorkingMemory.put("latest_action", selected.actionId()).
03	WorkingMemory.put("latest_observation", result.observation()).
04	Append EXECUTION or LEARNING DecisionEvent with a summary truncated to 240 chars.
05	Check awaitingInput; false for this action.
06	Check result.terminal; true only for cycle 6.

State and observable values

Field	Value / meaning
cycle	6
terminal?	yes
replan marker present?	no
next action	No cycle 7 occurs because the terminal result returns from run.

Actual source excerpt: dev/coala/core/procedure/AbstractLoopingDecisionProcedure.java (source lines 92-121)

```
            try {
                ActionResult result = action.execute(selected, context);
                finalObservation = result.observation();
                context.workingMemory().put("latest_action", selected.actionId());
                context.workingMemory().put("latest_observation", result.observation());
                events.add(new DecisionEvent(cycle, action.kind() == dev.coala.core.ActionKind.LEARNING
                        ? DecisionStage.LEARNING : DecisionStage.EXECUTION,
                        selected.actionId() + " -> " + truncate(result.observation(), 240)));
                if (result.awaitingInput()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Action is awaiting a user or
         external input; resume the interaction in a later request."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.AWAITING_INPUT, events);
                }
                if (result.terminal()) {
                    events.add(new DecisionEvent(cycle, DecisionStage.TERMINATION, "Selected action marked the
        run complete."));
                    return new AgentRunResult(id(), goal, finalObservation, cycle,
                            TerminationReason.TERMINAL_ACTION, events);
                }
            } catch (LanguageModelException ex) {
                throw ex;
            } catch (RuntimeException ex) {
                throw new ActionExecutionException("Action '" + selected.actionId() + "' failed at cycle " +
        cycle, ex);
            }
        }

        events.add(new DecisionEvent(maxCycles, DecisionStage.TERMINATION,
                "Safety bound reached: maxCycles=" + maxCycles + "."));
        return new AgentRunResult(id(), goal, finalObservation, maxCycles,
                TerminationReason.MAX_CYCLES_REACHED, events);
    }
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Final outcome: what the caller actually receives

A non-binding itinerary for Paris from 2026-11-05 to 2026-11-08, with CAD 640 flight, CAD 390 hotel, CAD 160 local estimate, CAD 1,190 subtotal, CAD 1,400 cap, and a fixture-only within-budget check. No reservation, payment, or live calendar lookup occurs.

The response envelope is UseCaseRunResponse(sessionId, AgentRunResult). Spring/Jackson serializes the record fields; the controller does not rewrite or summarize the agent’s final observation. The public event stream shows high-level stages and short observation summaries, while the full finalObservation preserves the final action output.

State and observable values

Field	Value / meaning
procedure	plan-first-revisable
cyclesExecuted	6
terminationReason	TERMINAL_ACTION
final action	present_itinerary
session id	UUID returned by the service
event list	observation and planning stages plus execution/learning and termination

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Read the event list as a stage trace, not a method profiler

DecisionEvent has cycle, stage and summary. The base loop records OBSERVATION and EXECUTION/LEARNING, and each procedure contributes its own planning events. Research explicitly contributes RETRIEVAL, REASONING, PROPOSAL, EVALUATION and SELECTION stages. Travel records proposal/selection for each plan step; the JSON plan-generation internal model call is not a separate public event object. Support records REASONING, PROPOSAL and SELECTION for each next-action selection.

The event summary is intentionally truncated before inclusion, and the CoalaAgent trace-listener interface is unused by this demo setup. That is why this guide expands the internal method calls beyond the API event list.

Actual source excerpt: dev/coala/core/DecisionEvent.java (source lines 1-7)

```
package dev.coala.core;

public record DecisionEvent(int cycle, DecisionStage stage, String summary) {
    public DecisionEvent {
        summary = summary == null ? "" : summary;
    }
}
```

Important boundary
If a production application needs span-level latency, tokens, tool telemetry or correlation IDs, implement a trace listener or observability adapter; do not expect DecisionEvent alone to be a full distributed trace.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Failure path: invalid model output

A malformed action JSON string fails in ActionOutputParser before an action can execute. A candidate JSON with fewer than two candidates fails `parseCandidates`; unsupported action IDs fail `ActionRegistry.require`; arguments not satisfying the registered definitions fail CoalaAction.validate. The base loop maps an invalid selected action into InvalidModelOutputException when validation is performed on the selected ActionCall.

For research, a bad proposer/evaluator result may be retried by the deliberative procedure up to maxProposalAttempts for DecisionProcedureException cases; exhaustion raises PlanningExhaustedException. For travel, an invalid plan never executes its first step because every step is parsed and validated before `plan.first_steps` is committed. For support, invalid single-action output fails before the mock classification/escalation action runs.

State and observable values

Field	Value / meaning
No action execution?	yes, if parse/validation fails before execute
HTTP behavior	sanitized 502 for invalid model output; some planning errors map to 500
state risk	no real external side effect in these mock adapters

Actual source excerpt: dev/coala/core/action/ActionOutputParser.java (source lines 35-70)

```
        requireOnlyFields(root, Set.of("actionId", "arguments"), "action proposal");
        JsonNode actionId = root.get("actionId");
        if (actionId == null || !actionId.isTextual() || actionId.asText().isBlank()) {
            throw new InvalidModelOutputException("Action JSON must contain a non-empty string 'actionId'.");
        }
        return buildActionCall(actionId.asText(), parseArguments(root.get("arguments")));
    }

    /** Parses a set of at least two distinct alternatives. */
    public List<ActionCall> parseCandidates(String raw, int maxCandidates) {
        if (maxCandidates < 2) throw new IllegalArgumentException("maxCandidates must be at least 2");
        JsonNode root = parseJson(raw, "candidate proposal");
        requireObject(root, "Candidate JSON must be an object.");
        requireOnlyFields(root, Set.of("candidates"), "candidate proposal");
        JsonNode candidates = root.get("candidates");
        if (candidates == null || !candidates.isArray() || candidates.size() < 2) {
            throw new InvalidModelOutputException("Candidate JSON must contain at least two alternatives in a
        'candidates' array.");
        }
        if (candidates.size() > maxCandidates) {
            throw new InvalidModelOutputException("Model proposed " + candidates.size()
                    + " candidates; configured limit is " + maxCandidates + ".");
        }
        List<ActionCall> parsed = new ArrayList<>();
        Set<ActionCall> seen = new HashSet<>();
        for (JsonNode candidate : candidates) {
            requireObject(candidate, "Every candidate must be a JSON object.");
            requireOnlyFields(candidate, Set.of("actionId", "arguments"), "candidate action");
            JsonNode id = candidate.get("actionId");
            if (id == null || !id.isTextual() || id.asText().isBlank()) {
                throw new InvalidModelOutputException("Every candidate must contain a non-empty 'actionId'.");
            }
            ActionCall call = buildActionCall(id.asText(), parseArguments(candidate.get("arguments")));
            if (!seen.add(call)) {
                throw new InvalidModelOutputException("Candidate set contains duplicate action calls; propose
        distinct alternatives.");
            }
            parsed.add(call);
```

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Failure path: action precondition requests replanning

TravelGroundingActions.searchFlights and searchHotels check travel.calendar.checked. If false, they return an observation containing `needs_replan` and explicitly say no provider query was made. PlanFirstDecisionProcedure's default replanCondition detects this token at the start of the next cycle and discards the remaining step list, stores plan.replaced_steps, and requests a revised plan from reasoning.

draft_itinerary similarly returns needs_replan if the calendar, flight inventory, or hotel inventory observations are missing. This is a useful distinction between planning intent and execution reality: an action result can invalidate the previously proposed plan, and the next cycle reacts to the observation rather than blindly continuing.

Actual source excerpt: dev/coala/core/procedure/PlanFirstDecisionProcedure.java (source lines 42-69)

```
@Override protected PlanDecision planNextAction(AgentContext context, ActionRegistry actions) {
    String observation = context.workingMemory().getString("latest_observation", "");
    List<ActionCall> pending = readPending(context.workingMemory().get("plan.first_steps").orElse(null));
    boolean revise = replanCondition.test(observation);
    if (pending.isEmpty() || revise) {
        if (revise && !pending.isEmpty()) context.workingMemory().put("plan.replaced_steps",
    pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        String prompt = "Create a plan of 1 to " + maxSteps + " executable NEXT ACTIONS for the goal, using
    current memory/observations. "
                + "Return strict JSON {\"steps\":[{\"actionId\":\"...\",\"arguments\":{\"key\":\"string
    value\"}}]}. "
                + "Only use the following registered actions and valid argument contracts: " +
    formatter.format(actions.descriptors()) + ". "
                + "A plan is a proposal, not execution. Prefer short plans. JSON only."
                + (revise ? " Previous observation suggests the old plan needs revision: " + observation :
    "");
        List<ActionCall> proposed = parser.parseActionPlan(reasoning.reason("PLAN_FIRST", prompt, context),
    maxSteps);
        for (ActionCall step : proposed) {
            var action = actions.validate(step);
            if (action.kind() != ActionKind.GROUNDING && action.kind() != ActionKind.LEARNING)
                throw new DecisionProcedureException("Plan step must target a registered grounding or
    learning action: " + step.actionId());
        }
        pending = new ArrayList<>(proposed);
        context.workingMemory().put("plan.first_steps",
    pending.stream().map(PlanFirstDecisionProcedure::state).toList());
        context.workingMemory().put("reasoning.latest", null);
    }
    ActionCall selected = pending.remove(0);
    context.workingMemory().put("plan.first_steps",
    pending.stream().map(PlanFirstDecisionProcedure::state).toList());
    context.workingMemory().put("plan.selectedAction", state(selected));
    List<DecisionEvent> events = List.of(
            new DecisionEvent(context.cycle(), DecisionStage.PROPOSAL, "Prepared/reused a plan with " +
    (pending.size() + 1) + " step(s) before selecting the next one."),
            new DecisionEvent(context.cycle(), DecisionStage.SELECTION, "Selected the first remaining plan
    step: " + selected.actionId() + "."));
    return new PlanDecision(selected, List.of(selected), List.of(), events);
```

Important boundary
The successful travel simulation never takes this branch because check_calendar is first and all fixtures return valid observations. The branch is present as a safe recovery path.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

Run it locally and compare the returned trace

Start the application with the deterministic default profile, POST the exact request from page 3, and preserve the returned sessionId. Inspect the run fields: procedure should match this document, cyclesExecuted should be the expected terminal cycle count, terminationReason should be TERMINAL_ACTION, and the finalObservation should match the action result described in the cycle ledger.

For a second request that needs persistent session memory, send the returned sessionId. A made-up session ID is rejected rather than created. For actual OpenAI integration, configure the project’s openai profile and API key; that changes the provider behind LanguageModel, not the action catalog or procedure semantics.

Method-call ledger

01	./mvnw -B clean verify (first run the full Maven test suite).
02	./mvnw spring-boot:run (deterministic profile by default).
03	POST /api/use-cases/travel-plan-first/run with request JSON from page 3.
04	Check returned procedure, cyclesExecuted, terminationReason, finalObservation and events.
05	Save returned sessionId if you want to resume that demo session.

TRAVEL PLANNER - PLAN-FIRST PROCEDURE / SOURCE-LEVEL EXECUTION TRACE

What the guide proved and what remains outside the simulation

The successful trace proves the source-code path for this fixture: how request fields become a run request, how the service assembles the procedure and action allow-list, how each planning method returns structured action data, how the base loop validates and executes the selected registered action, how the observation becomes next-cycle state, and how terminal=true returns AgentRunResult.

It does not prove correctness of an actual LLM’s reasoning, current web facts, real calendar access, real travel availability, airline/hotel booking, account security, ticket creation, durable memory after restart, or production authorization. Those require real adapters plus integration/security tests. The simulated provider must be labeled as simulated until replaced and verified.

Important boundary
The implementation described in this report is the supplied source snapshot. If the code changes, regenerate the walkthroughs so line references and output fixtures remain accurate.