

Prop clase ck velocidad convergencia uniforme fourier

Proposición 1. Sea $k \in \mathbb{N}$ y $f \in \mathcal{C}^k([-1/2, 1/2])$ 1-periódica

$$\implies \exists C_k < \infty : \forall N \in \mathbb{N} : \|S_N f - f\|_\infty \leq \frac{C_k}{N^{k-1/2}}.$$

Demostración: Por el lem-serie-fourier-derivada/Lema 1, $\forall n \in \mathbb{Z} \setminus \{0\} : \widehat{f^{(k)}}(n) = (2\pi i n)^k \widehat{f}(n)$. Además, como $f \in \mathcal{C}^k([-1/2, 1/2]) \subset \mathcal{L}^2([-1/2, 1/2])$, por Plancherel, tenemos que

$$\int_{-\frac{1}{2}}^{\frac{1}{2}} |f^{(k)}(x)|^2 dx = \sum_{n \in \mathbb{Z}} |\widehat{f^{(k)}}(n)|^2 = \sum_{n \in \mathbb{Z}} 4^k \pi^{2k} |n|^{2k} |\widehat{f}(n)|^2. \quad (1)$$

Por otro lado, por la prop-criterio-dini/??, $\sum_{n \in \mathbb{Z}} \widehat{f}(n) e^{2\pi i n x} = \lim_{N \rightarrow \infty} S_N f(x) = f(x)$.

Entonces,

$$\begin{aligned} \|S_N f - f\|_\infty &= \left\| \sum_{|n| > N} \widehat{f}(n) e^{2\pi i n x} \right\|_\infty \leq \sum_{|n| > N} |\widehat{f}(n)| = \sum_{|n| > N} |\widehat{f}(n)| |n|^k \cdot \frac{1}{|n|^k} \\ &\stackrel{\text{C-S}}{\leq} \left(\sum_{|n| > N} |\widehat{f}(n)|^2 |n|^{2k} \right)^{1/2} \left(\sum_{|n| > N} \frac{1}{|n|^{2k}} \right)^{1/2} \end{aligned}$$

Ahora, usando la ecuación (??), tenemos que

$$\begin{aligned} \|S_N f - f\|_\infty &\leq \frac{1}{2^k \pi^k} \left(\int_{-\frac{1}{2}}^{\frac{1}{2}} |f^{(k)}(x)|^2 dx \right)^{1/2} \left(2 \sum_{n=N+1}^{\infty} \frac{1}{n^{2k}} \right)^{1/2} \\ &\leq \frac{\sqrt{2}}{2^k \pi^k} \left(\int_{-\frac{1}{2}}^{\frac{1}{2}} |f^{(k)}(x)|^2 dx \right)^{1/2} \left(\int_N^{\infty} \frac{1}{x^{2k}} dx \right)^{1/2} \\ &= \frac{\sqrt{2}}{2^k \pi^k} \left(\int_{-\frac{1}{2}}^{\frac{1}{2}} |f^{(k)}(x)|^2 dx \right)^{1/2} \left(\frac{1}{(2k-1)N^{2k-1}} \right)^{1/2} = \frac{C_k}{N^{k-1/2}}, \end{aligned}$$

$$\text{donde } C_k = \frac{\sqrt{2}}{2^k \pi^k \sqrt{2k-1}} \left(\int_{-\frac{1}{2}}^{\frac{1}{2}} |f^{(k)}(x)|^2 dx \right)^{1/2} < \infty. \quad \blacksquare$$

Temporary page!

L^AT_EX was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it.

If you rerun the document (without altering it) this surplus page will go away, because L^AT_EX now knows how many pages to expect for this document.