

Jira Tickets — List Type & Tier

Programme: Crime Common Platform (CPP) — Modern by Default

Team: Listing / Hearing

Service: `cpp-context-hearing` (hearing tickets) + listing services (listing tickets)

Work delivering LPT-2400–2404: intended for `feature/ptph-detail`, but currently **uncommitted in the `cpp-context-hearing` working tree with `main` checked out** — the `feature/ptph-detail` branch itself carries no PTPH commits yet.

Status last verified against the code: **2026-07-30** (endpoints, payloads and headers below read off the RAML, JSON schemas/examples, handlers and Drools rules in the working tree)

Key	Summary	Type	Status	Assignee
LPT-2400	[BE] [hearing] create domain objects and enums for capturing list type and tier	Story	Done	Unassigned
LPT-2401	[BE] [hearing] create endpoint for capturing list type and tier	Story	Done	Unassigned
LPT-2402	[BE] [hearing] create endpoint for deleting list type and tier	Story	Done	Unassigned
LPT-2403	[BE] [hearing] create endpoint for editing list type and tier	Story	Done	Unassigned
LPT-2404	[BE] [hearing] create endpoint for finalizing list type and tier	Story	Done	Unassigned
LPT-2405	[BE] [listing] when next hearing is being created from a seeding hearing, retrieve tier/listType info from hearing context and store it in the listing payload	Story	New	Unassigned
LPT-2406	[BE] [listing] Endpoints used by court calendar need to return the list type and tier info	Story	New ¹	Unassigned

Delivery note: LPT-2400 through LPT-2404 are **implemented** in the hearing context — the full CQRS slice exists for save / finalise / delete (command API → handler → aggregate delegate → domain events → event listener → view store), plus access-control rules, RAML/JSON schemas and unit tests. LPT-2405 and LPT-2406 are listing-side follow-ups **not** started here.

¹ LPT-2406 stays open: its hearing-context enabler (`GET /hearings/{hearingId}/ptph-detail` → `hearing.get-ptph-detail`) is done, but the court-calendar-facing listing endpoints have not been changed.

Implemented artefacts (verified 2026-07-29):

Layer	Artefact
Domain types	<code>hearing-domain-common</code> : <code>Tier</code> , <code>ListType</code> , <code>SavePtphDetailCommand</code>
Domain events	<code>hearing-domain-event</code> : <code>PtphDetailSaved</code> , <code>PtphDetailFinalised</code> , <code>PtphDetailDeleted</code>
Aggregate	<code>HearingPtphDetailDelegate</code> + wiring in <code>HearingAggregate</code> / <code>HearingAggregateMomento</code>
Command API	<code>HearingCommandApi.savePtphDetail</code> / <code>finalisePtphDetail</code> / <code>deletePtphDetail</code> ; 3 media types on <code>POST /hearings/{hearingId}</code>
Command handler	<code>PtphDetailCommandHandler</code> (<code>hearing.command.save/finalise/delete-ptph-detail</code>)
Event listener	<code>PtphDetailEventListener</code> (upsert on saved, flag on finalised, row removal on deleted)
View store	<code>PtphDetail</code> entity, <code>PtphDetailRepository</code> , Liquibase <code>137-create-ptph-detail.xml</code>
Query side	<code>GET /hearings/{hearingId}/ptph-detail</code> → <code>hearing.get-ptph-detail</code> , <code>HearingQueryView.getPtphDetail</code> , <code>PtphDetailResponse</code>
Access control	Command + query Drools rules mirroring <code>hearing.set-trial-type</code> groups

Endpoint summary:

Ticket	Method	Path	Media type (<code>Content-Type</code> / <code>Accept</code>)	Response
LPT-2401 / LPT-2403	POST	<code>/hearing-command-api/command/api/rest/hearing/hearings/{hearingId}</code>	<code>application/vnd.hearing.save-ptph-detail+json</code>	202 Accepted, empty body

Ticket	Method	Path	Media type (<code>Content-Type</code> / <code>Accept</code>)	Response
LPT-2404	POST	<code>/hearing-command-api/command/api/rest/hearing/hearings/{hearingId}</code>	<code>application/vnd.hearing.finalise-ptph-detail+json</code>	202 Accepted, empty body
LPT-2402	POST	<code>/hearing-command-api/command/api/rest/hearing/hearings/{hearingId}</code>	<code>application/vnd.hearing.delete-ptph-detail+json</code>	202 Accepted, empty body
LPT-2406 (enabler)	GET	<code>/hearing-query-api/query/api/rest/hearing/hearings/{hearingId}/ptph-detail</code>	<code>application/vnd.hearing.get-ptph-detail+json</code>	200 OK + JSON body

Common headers. All four endpoints go through the standard framework/API-gateway header contract – the media type carries the operation (there is no separate action name header), and `CJSCPPUID` carries the logged-in user id used by the Drools access-control rules (`uk.gov.justice.services.common.http.HeaderConstants.USER_ID`).

Header	Commands (POST)	Query (GET)
<code>Content-Type</code>	the <code>application/vnd.hearing.<name>+json</code> media type	n/a
<code>Accept</code>	<code>application/json</code>	<code>application/vnd.hearing.get-ptph-detail+json</code>
<code>CJSCPPUID</code>	user id (UUID) – required, drives access control	same

All four are granted to the same groups as `hearing.set-trial-type`: `Listing Officers`, `Court Clerks`, `Legal Advisers`, `Judiciary`, `Court Associate`, `Deputies`, `DJMC`, `Judge`, `Recorders`, `Court Administrators`.

Schema note (worth a follow-up). `hearing.save-ptph-detail` requires `hearingId` in the request body as well as in the path (`"required": ["hearingId","tier"]`, `additionalProperties: false`). `hearing.set-trial-type` – the precedent this slice follows – omits `hearingId` from the command-API schema and relies on the framework injecting the path parameter into the payload. `finalise` / `delete` follow the `set-trial-type` precedent (empty body). So the save call currently must repeat the id, and the finalise/delete calls must **not** send it (`additionalProperties: false` rejects it).

LPT-2400 — [BE] [hearing] create domain objects and enums for capturing list type and tier

Type: Story · Status: Done · Assignee: Unassigned

Description: Create the domain value types that model tier and list type so they can be captured, stored and emitted as events on a hearing.

Scope of work:

- `Tier` enum (`TIER_1` ... `TIER_7`) in `hearing-domain-common`.
- `ListType` enum: `TYPE_1_FIXED` ("1F") / `TYPE_2_FLEXIBLE` ("2F").
- `SavePtpDetailCommand` command DTO.
- Domain events `PtpDetailSaved` / `PtpDetailFinalised` / `PtpDetailDeleted` (`hearing-domain-event`), `@Event("hearing.ptph-detail-saved|-finalised|-deleted")`, tier/list type carried as String.

Acceptance criteria:

- Enums expose the seven tiers and the two list types with their codes.
- Events are serialisable (`@JsonCreator` / `@JsonProperty`) and carry `hearingId` (+ tier/listType/keyReason on the saved event).
- Unit test covers event construction.

Status:  **Done** — `Tier`, `ListType` and `SavePtpDetailCommand` in `hearing-domain-common`; the three events in `hearing-domain-event` with `PtpDetailSavedTest` covering construction.

Endpoint detail

No HTTP endpoint — this ticket delivers domain types only. The artefacts it produces appear on the wire as **domain events** on `jms:topic:hearing.event`, consumed by `PtpDetailEventListener` (subscription `subscriptions-descriptor.yaml`).

Event name	Media type	Payload
<code>hearing.ptph-detail-saved</code>	<code>application/vnd.hearing.ptph-detail-saved+json</code>	<code>hearingId</code> , <code>tier</code> , <code>listType</code> , <code>keyReason</code>
<code>hearing.ptph-detail-finalised</code>	<code>application/vnd.hearing.ptph-detail-finalised+json</code>	<code>hearingId</code>
<code>hearing.ptph-detail-deleted</code>	<code>application/vnd.hearing.ptph-detail-deleted+json</code>	<code>hearingId</code>

Sample event payloads (`hearing-event-listener/src/yaml/json/`):

```
// hearing.ptph-detail-saved
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_2",
  "listType": "TYPE_1_FIXED",
  "keyReason": "reason"
}
```

```
// hearing.ptph-detail-finalised / hearing.ptph-detail-deleted
{ "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" }
```

Enum values carried as String: `tier` ∈ `TIER_1` ... `TIER_7`; `listType` ∈ `TYPE_1_FIXED` ("1F") / `TYPE_2_FLEXIBLE` ("2F"). `tier`, `listType` and `keyReason` are all nullable on the saved event.

LPT-2401 — [BE] [hearing] create endpoint for capturing list type and tier

Type: Story · Status: Done · Assignee: Unassigned

Description: Provide the command endpoint that captures a tier and (optional) list type against a seeding hearing, persisting them to the view store.

Scope of work (full CQRS slice for "save"):

- `POST /hearings/{hearingId}` media type `application/vnd.hearing.save-ptph-detail+json` → `hearing.save-ptph-detail` → handler `hearing.command.save-ptph-detail`.
- `PtphDetailCommandHandler.save`, `HearingAggregate` delegate emits `PtphDetailSaved`, `PtphDetailEventListener` upserts the `ha_ptph_detail` row.
- RAML + JSON schema/example on both command-API and handler layers.

Acceptance criteria:

- Request accepts `{ tier, listType?, keyReason? }`; `tier` required.
- `TYPE_1_FIXED` requires a non-blank `keyReason`; `TYPE_2_FLEXIBLE` must not carry one.
- Returns 202; the values are persisted and readable via LPT-2406's query.
- Access granted to the same roles as `hearing.set-trial-type`.

Status:  **Done** — media type + RAML mapping wired, `HearingCommandApi.savePtphDetail` → `PtphDetailCommandHandler.savePtphDetail` → `HearingPtphDetailDelegate.savePtphDetail` → `PtphDetailEventListener` upsert of the `ha_ptph_detail` row. `tier` is required by the schema; the Type-1 key-reason rule is enforced in `PtphDetailCommandHandler.resolveKeyReason`. Implemented as an upsert, so the same command also satisfies LPT-2403 editing.

Endpoint detail

`POST /hearing-command-api/command/api/rest/hearing/hearings/{hearingId}`

Item	Value
Path parameter	<code>hearingId</code> — UUID of the seeding hearing
Content-Type	<code>application/vnd.hearing.save-ptph-detail+json</code>
Accept	<code>application/json</code>
CJSCPPUID	logged-in user id (UUID) — required for access control
Action name	<code>hearing.save-ptph-detail</code> → handler command <code>hearing.command.save-ptph-detail</code>
Response	202 Accepted, empty body

Request headers:

```
POST /hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4 HTTP/1.1
Host: <gateway-host>
Content-Type: application/vnd.hearing.save-ptph-detail+json
Accept: application/json
CJSCPPUID: 4a2b1e6c-1f3d-4a9e-9c11-6f0f2f9c7d31
```

Sample payload — Type 1 (fixed date), `keyReason` mandatory:

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_2",
  "listType": "TYPE_1_FIXED",
  "keyReason": "Trial fixed date required by court order"
}
```

Sample payload — Type 2 (flexible date), no `keyReason` :

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_5",
  "listType": "TYPE_2_FLEXIBLE"
}
```

Sample payload — tier only (list type chosen later):

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_1"
}
```

Field rules (`json/schema/hearing.save-ptph-detail.json`, `additionalProperties: false`):

Field	Required	Values
<code>hearingId</code>	yes	UUID — must match the path parameter
<code>tier</code>	yes	<code>TIER_1</code> ... <code>TIER_7</code>
<code>listType</code>	no	<code>TYPE_1_FIXED</code> <code>TYPE_2_FLEXIBLE</code>
<code>keyReason</code>	conditional	required (non-blank) when <code>listType = TYPE_1_FIXED</code> ; ignored/nulled for any other list type

curl:

```
curl -i -X POST \
  "$GATEWAY/hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" \
  -H "Content-Type: application/vnd.hearing.save-ptph-detail+json" \
  -H "CJSCPPUID: $USER_ID" \
  -d '{"hearingId":"92ff0722-c287-11e9-9cb5-2a2ae2dbcce4","tier":"TIER_2","listType":"TYPE_1_FIXED","keyReason":"Trial fixed date required by court order"}'
```

Internal hop — command handler (`message://command/handler/message/hearing`), media type `application/vnd.hearing.command.save-ptph-detail+json` , same payload shape:

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_2",
  "listType": "TYPE_1_FIXED",
  "keyReason": "Trial fixed date required by court order"
}
```

Error behaviour: a blank/absent `keyReason` with `listType = TYPE_1_FIXED` throws from `PtphDetailCommandHandler.resolveKeyReason` ("keyReason is required when listType is TYPE_1_FIXED"); saving against

a finalised record is rejected by `HearingPtpDetailDelegate.savePtpDetail`. Both surface as command-side failures, not as a 4xx on the POST (the POST has already returned 202).

LPT-2402 — [BE] [hearing] create endpoint for deleting list type and tier

Type: Story · **Status:** Done · **Assignee:** Unassigned

Description: Provide the command endpoint that deletes all captured tier/list-type information for a hearing, returning it to a blank state.

Scope of work:

- `POST /hearings/{hearingId}` media type `application/vnd.hearing.delete-ptph-detail+json` → `hearing.command.delete-ptph-detail`.
- Aggregate emits `PtphDetailDeleted`; listener removes the view-store row.

Acceptance criteria:

- Delete is permitted in any state (draft or finalised).
- Clears tier, list type, key reason and the finalised flag.
- Returns 202; subsequent query shows nothing saved.
- Access granted to the same roles as `hearing.set-trial-type`.

Status:  **Done** — `PtphDetailCommandHandler.deletePtphDetail` emits `PtphDetailDeleted` with no state precondition (so it works draft or finalised); the delegate clears tier / list type / key reason / finalised on the aggregate and the listener removes the view-store row.

Endpoint detail

```
POST /hearing-command-api/command/api/rest/hearing/hearings/{hearingId}
```

Item	Value
Path parameter	<code>hearingId</code> — UUID of the seeding hearing
Content-Type	<code>application/vnd.hearing.delete-ptph-detail+json</code>
Accept	<code>application/json</code>
CJSCPPUID	logged-in user id (UUID) — required for access control
Action name	<code>hearing.delete-ptph-detail</code> → handler command <code>hearing.command.delete-ptph-detail</code>
Response	202 Accepted, empty body

Request headers:

```
POST /hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4 HTTP/1.1
Host: <gateway-host>
Content-Type: application/vnd.hearing.delete-ptph-detail+json
Accept: application/json
CJSCPPUID: 4a2b1e6c-1f3d-4a9e-9c11-6f0f2f9c7d31
```

Sample payload — empty object; the hearing is identified by the path parameter, which the framework injects into the payload for the handler. The schema is `additionalProperties: false` with no declared properties, so sending `hearingId` in the body would be **rejected**:

```
{ }
```

curl:

```
curl -i -X POST \
  "$GATEWAY/hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" \
  -H "Content-Type: application/vnd.hearing.delete-ptph-detail+json" \
  -H "CJSCPPUID: $USER_ID" \
  -d '{}'
```

Internal hop — `application/vnd.hearing.command.delete-ptph-detail+json`, with the path parameter now present in the payload:

```
{ "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" }
```

Effect: emits `hearing.ptph-detail-deleted`; `PtphDetailEventListener` removes the `ha_ptph_detail` row, so the LPT-2406 query subsequently reports a blank record — `HearingService.getPtphDetail` returns `PtphDetailResponse(null, null, null, false)`, i.e. no tier / list type / key reason and `"finalised": false`.

LPT-2403 — [BE] [hearing] create endpoint for editing list type and tier

Type: Story · **Status:** Done · **Assignee:** Unassigned

Description: Allow captured tier/list-type values to be changed while the record is not yet finalised (the screen "Change" links).

Scope of work:

- Editing reuses the LPT-2401 capture command as an **upsert** — re-posting `hearing.save-ptph-detail` overwrites the current values.

Acceptance criteria:

- Re-saving replaces the previously stored tier / list type / key reason.
- Editing is **rejected once the record is finalised** (immutability — see LPT-2404).
- The Type 1 key-reason rule from LPT-2401 applies to edits too.

Status:  **Done** — satisfied by the LPT-2401 upsert command; immutability-after-finalise is enforced in `HearingPtphDetailDelegate.savePtphDetail`, which rejects a save once the momento is finalised.

Endpoint detail

No separate endpoint — editing re-posts the LPT-2401 save command:

```
POST /hearing-command-api/command/api/rest/hearing/hearings/{hearingId}
Content-Type: application/vnd.hearing.save-ptph-detail+json
Accept: application/json
CJSCPPUID: <user id UUID>
→ 202 Accepted
```

Sample payload — change the tier of an already-saved (not finalised) record; the whole record is replaced, so send every field you want to keep:

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_4",
  "listType": "TYPE_1_FIXED",
  "keyReason": "Trial fixed date required by court order"
}
```

Sample payload — change list type Type 1 → Type 2; omitting `keyReason` is correct here, and any `keyReason` sent alongside `TYPE_2_FLEXIBLE` is discarded by `resolveKeyReason`:

```
{
  "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4",
  "tier": "TIER_4",
  "listType": "TYPE_2_FLEXIBLE"
}
```

Semantics: replace, not merge — the emitted `PtphDetailSaved` carries exactly the posted values, and `PtphDetailEventListener` upserts the `ha_ptph_detail` row from them. Omitting `listType` on an edit therefore **clears** a previously stored list type. Once the record is finalised (LPT-2404) this command is rejected by the aggregate delegate; delete (LPT-2402) is then the only permitted operation.

LPT-2404 – [BE] [hearing] create endpoint for finalizing list type and tier

Type: Story · Status: Done · Assignee: Unassigned

Description: Provide the command endpoint that finalises (locks) the tier/list-type information so it can no longer be edited.

Scope of work:

- `POST /hearings/{hearingId}` media type `application/vnd.hearing.finalise-ptph-detail+json` → `hearing.command.finalise-ptph-detail`.
- Aggregate emits `PtphDetailFinalised`; listener sets `finalised = true`.

Acceptance criteria:

- Finalise is **rejected unless both a tier and a list type are present**.
- Finalise is rejected if the record is already finalised.
- After finalisation, save/edit (LPT-2401/2403) is rejected; only delete (LPT-2402) is permitted.
- The `finalised` flag is exposed by the query (LPT-2406).
- Access granted to the same roles as `hearing.set-trial-type`.

Status:  **Done** — `PtphDetailCommandHandler.finalisePtphDetail` emits `PtphDetailFinalised`; `HearingPtphDetailDelegate.finalisePtphDetail` rejects the command when either tier or list type is missing, and when the record is already finalised. The listener sets `finalised = true`, exposed by `hearing.get-ptph-detail`.

Endpoint detail

```
POST /hearing-command-api/command/api/rest/hearing/hearings/{hearingId}
```

Item	Value
Path parameter	<code>hearingId</code> — UUID of the seeding hearing
Content-Type	<code>application/vnd.hearing.finalise-ptph-detail+json</code>
Accept	<code>application/json</code>
CJSCPPUID	logged-in user id (UUID) — required for access control
Action name	<code>hearing.finalise-ptph-detail</code> → handler command <code>hearing.command.finalise-ptph-detail</code>
Response	<code>202 Accepted</code> , empty body

Request headers:

```
POST /hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4 HTTP/1.1
Host: <gateway-host>
Content-Type: application/vnd.hearing.finalise-ptph-detail+json
Accept: application/json
CJSCPPUID: 4a2b1e6c-1f3d-4a9e-9c11-6f0f2f9c7d31
```

Sample payload — empty object (the hearing comes from the path parameter; the schema is `additionalProperties: false` with no declared properties, so sending `hearingId` in the body would be **rejected**):

```
{ }
```

curl:

```
curl -i -X POST \
  "$GATEWAY/hearing-command-api/command/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" \
  -H "Content-Type: application/vnd.hearing.finalise-ptph-detail+json" \
  -H "CJSCPPUID: $USER_ID" \
  -d '{}'
```

Internal hop — `application/vnd.hearing.command.finalise-ptph-detail+json`:

```
{ "hearingId": "92ff0722-c287-11e9-9cb5-2a2ae2dbcce4" }
```

Preconditions (enforced in `HearingPtphDetailDelegate.finalisePtphDetail`, command-side — the POST itself has already returned 202):

- rejected unless **both** `tier` and `listType` are already saved;
- rejected if the record is already finalised.

Effect: emits `hearing.ptph-detail-finalised`; the listener sets `finalised = true` on the `ha_ptph_detail` row, which the LPT-2406 query then reports as `"finalised": true`. From that point save/edit is rejected and only delete is permitted.

LPT-2405 — [BE] [listing] retrieve tier/listType from hearing context when creating the next hearing from a seeding hearing

Type: Story · **Status:** New · **Assignee:** Unassigned

Description: When a next hearing is created from a seeding hearing, the listing side must retrieve the tier/list-type information from the hearing context and store it in the listing payload, so it travels with the newly created hearing.

Scope of work (indicative — to be designed):

- On next-hearing creation from a seeding hearing, call the hearing-context query (LPT-2406 / `hearing.get-ptph-detail`) for the seeding hearing.
- Map tier/list type/key reason into the listing payload/model.
- Handle the case where the seeding hearing has no tier/list type (or is not finalised) — define expected behaviour.

Acceptance criteria (to refine):

- Next hearing created from a seeding hearing carries the seeding hearing's tier/list type.
- Behaviour defined for absent / non-finalised source data.

Status:  **Not started** — listing-side, separate service/repo. Depends on the hearing-context query delivered under LPT-2406.

LPT-2406 — [BE] [listing] court-calendar endpoints must return list type and tier info

Type: Story · Status: New · Assignee: Unassigned

Description: The endpoints consumed by the court calendar must return the tier and list-type information for hearings.

Scope of work (indicative — to be designed):

- Hearing context already exposes `GET /hearings/{hearingId}/ptph-detail` (`hearing.get-ptph-detail`) returning `{ tier, listType, keyReason, finalised }` — delivered under this feature and available as the source of truth.
- Extend the court-calendar-facing listing endpoints to surface tier/list type in their responses (either by including the fields directly or by calling the hearing-context query).

Acceptance criteria (to refine):

- Court-calendar endpoints return tier and list type (and finalised flag) for each relevant hearing.
- Field naming/shape agreed with the calendar consumers.

Status:  **Partially enabled — still open.** The hearing-context read model and query are done (`GET /hearings/{hearingId}/ptph-detail` → `hearing.get-ptph-detail`, `HearingQueryView.getPtphDetail`, `PtphDetailResponse`, query Drools rule). The listing / court-calendar endpoint changes are **not** done.

Endpoint detail — hearing-context enabler (implemented)

```
GET /hearing-query-api/query/api/rest/hearing/hearings/{hearingId}/ptph-detail
```

Item	Value
Path parameter	<code>hearingId</code> — UUID of the seeding hearing
Accept	<code>application/vnd.hearing.get-ptph-detail+json</code>
CJSCPPUID	logged-in user id (UUID) — required for access control
Action name	<code>hearing.get-ptph-detail</code>
Response	<code>200 OK</code> , <code>Content-Type: application/vnd.hearing.get-ptph-detail+json</code>

Request headers:

```
GET /hearing-query-api/query/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4/ptph-detail
HTTP/1.1
Host: <gateway-host>
Accept: application/vnd.hearing.get-ptph-detail+json
CJSCPPUID: 4a2b1e6c-1f3d-4a9e-9c11-6f0f2f9c7d31
```

No request body (GET).

Sample response — finalised record:

```
{
  "tier": "TIER_2",
  "listType": "TYPE_1_FIXED",
  "keyReason": "Trial fixed date required by court order",
  "finalised": true
}
```

Sample response — saved but not yet finalised, tier only:

```
{
  "tier": "TIER_1",
  "finalised": false
}
```

Sample response — nothing saved (or deleted): `HearingService.getPtphDetail` returns `PtphDetailResponse(null, null, null, false)`, so only the `finalised` flag is meaningful:

```
{
  "finalised": false
}
```

Response fields (`json/schema/hearing.get-ptph-detail.json`, `additionalProperties: false`):

Field	Required	Type
<code>tier</code>	no	string (<code>TIER_1</code> ... <code>TIER_7</code>) or null
<code>listType</code>	no	string (<code>TYPE_1_FIXED</code> <code>TYPE_2_FLEXIBLE</code>) or null
<code>keyReason</code>	no	string or null
<code>finalised</code>	yes	boolean

curl:

```
curl -s \
  "$GATEWAY/hearing-query-api/query/api/rest/hearing/hearings/92ff0722-c287-11e9-9cb5-2a2ae2dbcce4/ptph-
  detail" \
  -H "Accept: application/vnd.hearing.get-ptph-detail+json" \
  -H "CJSCPPUID: $USER_ID"
```

This is the query LPT-2405 and the court-calendar-facing listing endpoints are expected to call (or mirror).