

3.2.1.2 CTAM Schema and Source Mapping

- [JO \(eLinks\) Integration — CTAM Schema & Source Mapping](#)
 - 1. Design decisions
 - 1.1 Naming
 - 1.2 JOH lifecycle (/people, /leavers, /deleted)
 - 1.3 Deprecated source attributes — excluded
 - 1.4 Sync / refresh metadata — separate side table
 - 1.5 Foreign-key strategy
 - 1.6 Special case — authorisations_with_dates.jurisdiction_id
 - 1.7 Location data — constraints and warnings
 - 2. Table list
 - 3. Column mappings
 - 3.1 jo_people
 - 3.2 jo_appointments
 - 3.3 jo_judiciary_role_assignments
 - 3.4 jo_authorisations_with_dates
 - 3.5 jo_appointment_titles
 - 3.6 jo_base_locations
 - 3.7 jo_contract_types
 - 3.8 jo_genders
 - 3.9 jo_judiciary_roles (reference list)
 - 3.10 jo_jurisdictions
 - 3.11 jo_locations
 - 3.12 jo_location_types
 - 3.13 jo_tickets
 - 3.14 jo_ticket_categories
 - 3.15 jo_ticket_category_types
 - 3.16 jo_sync_status (CTAM-internal, no source mapping)
 - 4. Refresh strategy (informational)
 - 5. Data warnings
 - 6. Open questions

JO (eLinks) Integration — CTAM Schema & Source Mapping

This document specifies the **CTAM tables** that replicate the **eLinks (Judicial Office)** dataset, and the **column-level mapping** from the source API to CTAM.

1. Source: eLinks (a.k.a. JHR — Judicial HR) REST API, Data Dictionary v2.0 (2025-07-02).
2. JO References: [eLinks Data Model](#), [eLinks Data Dictionary](#)
3. ER diagram: See [3.2.1.1 CTAM JO Schema](#)

1. Design decisions

1.1 Naming

1. Every replicated table uses the jo_ prefix.
2. Table names follow the source's endpoint/entity names, with **one disambiguation**:
 - a. The source has both a transactional judiciary_roles[] array (nested in /people) and a reference endpoint /reference_data/judiciary_roles. CTAM splits these as:
 - i. jo_judiciary_role_assignments — the transactional assignment of a judiciary role to a person.
 - ii. jo_judiciary_roles — the reference list of role names.
3. Column names follow the source's snake_case attribute names verbatim, except where a source attribute is documented as a deprecated alias (see §1.3).

1.2 JOH lifecycle (/people, /leavers, /deleted)

The source exposes three endpoints that all describe the **same underlying person** (judicial_office_holders in JHR), filtered by lifecycle state. CTAM models this as a **single jo_people table** keyed by personal_code (the only stable, never-reused identifier) with a status discriminator:

Endpoint that fed the row	jo_people.status	Rule on receipt (per source “Actions to be taken”)
/people (Current Office Holder)	active	Upsert by personal_code; full attributes populated.

/leavers (Leaver)	leaver	Upsert by personal_code; set left_on; null out PII where applicable (title, names, email, work_phone, gender, disability, etc.) — keep only personal_code, status, left_on. <i>The data to be removed needs investigation. Assume nothing is being deleted apart from the status update.</i>
/deleted (Deleted)	deleted	Upsert by personal_code; set deleted_on; null out everything except personal_code, status, deleted_on. The source instruction is to delete the account; CTAM will be soft-deleting the rows for reporting purposes. <i>Only soft delete</i>

Once a row is deleted it never becomes anything else (personal_code is not reused).

1.3 Deprecated source attributes — excluded

The following are present in the source dictionary but flagged DEPRECATED, so they are **not** replicated into CTAM:

Excluded	Use instead
per_id (integer alias of personal_code)	personal_code
sex	gender + gender_id
The old flat authorisations[] entity	jo_authorisations_with_dates

1.4 Sync / refresh metadata — separate side table

Refresh status is **not** stored on functional tables. A single jo_sync_status table keyed by source endpoint tracks the cursor for incremental refresh. Source-provided created_at/updated_at timestamps **are** kept on tables that expose them.

1.5 Foreign-key strategy

- Reference table PKs use the source integer id (= JHR integration_id), which the source guarantees stable across JHR releases and across Staging/Production.
- Transactional table PKs use the source-assigned id (appointment_id, judiciary_role_id, authorisation_id) — also guaranteed unique by JHR.
- jo_people.personal_code is a VARCHAR (it can contain alphanumerics like "A3447").
- Denormalised name columns (e.g. jo_appointments.role_name, jo_appointments.contract_type) are **preserved as the source provides them** so CTAM consumers can read without joining. The integer FK column is the authoritative link.

1.6 Special case — authorisations_with_dates.jurisdiction_id

The source documents an edge case: when an authorisation's jurisdiction == "Courts", the source returns the **ticket-category id** in the jurisdiction_id attribute (not a real jurisdiction id). CTAM faithfully replicates this — jo_authorisations_with_dates.jurisdiction_id is FK to jo_jurisdictions **unless** jurisdiction = 'Courts', in which case it is FK to jo_ticket_categories. The same quirk applies to the string jurisdiction column (it carries the ticket category name when source jurisdiction is Courts). This is the source's behaviour, not a CTAM transformation.

1.7 Location data — constraints and warnings

Location data in jo_appointments has several important constraints documented by the source:

- Belongs to the Appointment, not the JOH** — a JOH with multiple Appointments may indirectly have multiple locations. Location describes the contractual context of the Appointment, not where the JOH is physically working.
- Set at appointment creation, not updated** — location is captured when the Appointment is created and is not subsequently maintained. It may not reflect the JOH's current work location.
- Cross-type location IDs are unrelated** — location IDs for identically-named geographic areas across different entity types are entirely separate records with different IDs. For example, the “South East” region for Coroners (CORONERS_REGION) has a different id from “South East” for LJAs (MAGS_REGION). Do not compare or join location data across entity types using IDs.
- Tribunals chamber is not directly surfaced** — for Tribunal appointments, TRIBS_CHAMBER (level 2 of the hierarchy) has no dedicated attribute. To retrieve it: follow jo_appointments.base_location_id jo_base_locations.parent_id jo_locations.id. That jo_locations row is the chamber.

2. Table list

#	CTAM table	Category	Source endpoint / path
1	jo_people	Transactional	/people, /leavers, /deleted (merged)
2	jo_appointments	Transactional	/people appointments[]

3	jo_judiciary_role_assignments	Transactional	/people judiciary_roles[]
4	jo_authorisations_with_dates	Transactional	/people authorisations_with_dates[]
5	jo_appointment_titles	Reference	/reference_data/appointment_titles
6	jo_base_locations	Reference	/reference_data/base_locations
7	jo_contract_types	Reference	/reference_data/contract_types
8	jo_genders	Reference	/reference_data/genders
9	jo_judiciary_roles	Reference	/reference_data/judiciary_roles
10	jo_jurisdictions	Reference	/reference_data/jurisdictions
11	jo_locations	Reference	/reference_data/locations
12	jo_location_types	Reference	/reference_data/location_types
13	jo_tickets	Reference	/reference_data/tickets
14	jo_ticket_categories	Reference	/reference_data/ticket_categories
15	jo_ticket_category_types	Reference	/reference_data/ticket_category_types
16	jo_sync_status	CTAM-internal	(none — populated by sync job)

3. Column mappings

For every mapping table below:

	Column	Purpose
1	CTAM column	Column name in the CTAM database.
2	Type	Proposed CTAM column type (Postgres-flavoured; adjust to CTAM's chosen DBMS)
3	PK / FK	Primary key / foreign key designation
4	Source attribute	Attribute name in the source API response (or the JHR table.column where the dictionary makes it explicit)
5	Description / Notes / example	Transformation, nullability, deprecation, example value

3.1 jo_people

Replicated from /people, /leavers, /deleted. One row per physical JOH, keyed by personal_code. Lifecycle is encoded in status.

CTAM column	Type	Source attribute (per state)	Description / Notes / example
personal_code	VARCHAR (32)	personal_code (all 3 endpoints)	The only guaranteed-unique, never-reused identifier. "49728416", "A3447".
status	VARCHAR (16)	<i>derived</i>	'active' when sourced from /people, 'leaver' from /leavers, 'deleted' from /deleted.
ad_object_id	VARCHAR (64)	id (Master:eJ Active Directory Object Id)	eJ AD object id. Active/Leaver only. Not a unique key — eJ may reassign it. Null for deleted. Needed in CTAM ?
title	VARCHAR (64)	title (JHR:judicial_office_holders.judicial_title .civil_title_id)	Active only. "His Honour Judge", "Mrs". <i>How does this account for multiple roles that a JOH may be performing where each needs to be attributed separately</i>
known_as	VARCHAR (128)	known_as (JHR:judicial_office_holders.known_as)	Active only. Nickname/short/middle name; otherwise first name.
surname	VARCHAR (128)	surname (JHR:judicial_office_holders.last_name)	Active only.
fullname	VARCHAR (256)	fullname (JHR:calculated)	Active only. Includes postnominals.
initials	VARCHAR (16)	initials (JHR:calculated)	Active only.
post_nominals	VARCHAR (64)	post_nominals (JHR:judicial_office_holders.post_nominals)	Active only. e.g. "JP OBE".

email	VARCHAR (256)	email (Master:eJ JHR:ejudiciary_email_address)	Active only. Not unique — eJ may change/reuse.
email_personal	VARCHAR (256)	email_personal (JHR:personal_email_address)	Active only. May be null.
gender	VARCHAR (32)	gender (JHR:equal_opportunities_records.gender_id)	Active only. Denormalised name. - Need to keep only one of the these 2
gender_id	INT	gender_id (JHR:equal_opportunities_records.gender_id)	Active only - Need to keep only one of the these 2 FK jo_genders.id
work_phone	VARCHAR (32)	work_phone (JHR:contact_methods.value)	Active only. Picked from work phone/mobile in order.
disability	BOOLEAN	disability (JHR:diversity_records.disability_answer_id)	Active only.
retirement_date	DATE	retirement_date (JHR:judicial_office_holders.compulsory_retirement_date)	Active only. Compulsory retirement date.
leaving_on	DATE	leaving_on (JHR:judicial_office_holders.leaving_on_date)	Active only. Auto-set to latest appointment.end_date.
left_on	DATE	left_on (/leavers only)	Leaver only. Date the JOH left.
deleted_on	DATE	deleted_on (/deleted only)	Deleted only.

3.2 jo_appointments

Replicated from /people_appointments[]. Each appointment describes an instance of the person being appointed to a role at a location, under a contract type.

CTAM column	Type	Source attribute	Description / Notes / example
appointment_id	INT	appointment_id (JHR:appointment.id)	PK Source-assigned, unique. 145094.
personal_code	VARCHAR (32)	(parent in /people array)	FK jo_people.personal_code Link to parent JOH.
role_name	VARCHAR (128)	role_name (JHR:appointment_histories.appointment_title_id)	Denormalised role display name. "Circuit Judge".
role_name_id	INT	role_name_id (JHR:appointment_histories.appointment_title_id)	FK jo_appointment_titles.id Stable FK.
type	VARCHAR (32)	type (JHR:appointment_histories.location_id)	Static text from source. One of: 1. "Tribunals", 2. "Advisory Committee", 3. "LJA", 4. "Courts", 5. "Mags Area Committee", 6. "Mags Area Sub Committee", 7. "Mags Court", 8. "Coroners".
court_name	VARCHAR (128)	court_name (JHR:appointment_histories.location_id)	Mapping depends on type — see Section 1.7 Location data on this page
court_type	VARCHAR (128)	court_type (JHR:appointment_histories.location_id)	As above.
circuit	VARCHAR (128)	circuit (JHR:appointment_histories.location_id)	Courts only (= COURTS_REGION, e.g. "North East"). NULL for all other types.
bench	VARCHAR (128)	bench (JHR:appointment_histories.location_id)	LJA (= MAGS_AC_LJA) and Mags Court (= MAGS_AC_COURT_NAME) only. NULL for all other types.
advisory_committee_area	VARCHAR (128)	advisory_committee_area (JHR:appointment_histories.location_id)	LJA (= MAGS_AC) and Mags Court (= MAGS_AC) only. NULL for all other types.

location	VARCHAR (128)	location (JHR:appointment_histories.location_id)	Geographic area. For all non-Tribunal types this is the top-level region (e.g. "North East"). For Tribunals , this is TRIBS_LOCATION (the specific venue name, not a broad region).
base_location	VARCHAR (256)	base_location (JHR: appointment_histories.location_id)	Denormalised name of the leaf location. "Reading Magistrates Court". For Tribunals , the source concatenates Chamber and Location: "Social Entitlement Chamber - North East"
base_location_id	INT	base_location_id (JHR: appointment_histories.location_id)	FK jo_base_locations.id Lowest level of the location hierarchy.
is_principal	BOOLEAN	is_principal (JHR:appointmnet.primary)	Exactly one principal Appointment per Current Office Holder. <i>What does this mean ? and what implications does it have from availability perspective.</i>
start_date	DATE	start_date (JHR:appointment_histories.start_date)	
end_date	DATE	end_date (JHR:appointment_histories.end_date)	May be future-dated unless include_previous_appointments=true requested.
contract_type	VARCHAR (64)	contract_type (JHR: appointment_histories.contract_type_id)	Denormalised. "Fee-paid", "Salaried".
contract_type_id	INT	contract_type_id (JHR: appointment_histories.contract_type_id)	FK jo_contract_types.id

3.3 jo_judiciary_role_assignments

Replicated from /people_judiciary_roles[]. Records a JOH having been designated with a named judiciary role (applied to the person, not to an appointment).

CTAM column	Type	Source attribute	Description / Notes / example
judiciary_role_id	INT	judiciary_role_id (JHR)	PK Unique id of the assignment. 145094.
personal_code	VARCHAR(32)	(parent in /people array)	FK jo_people.personal_code
name	VARCHAR(128)	name (JHR)	Denormalised role name. "Bench Chair".
judiciary_role_name_id	INT	judiciary_role_name_id (JHR)	FK jo_judiciary_roles.id FK to the reference role list.
start_date	DATE	start_date (JHR)	
end_date	DATE	end_date (JHR)	

3.4 jo_authorisations_with_dates

Replicated from /people_authorisations_with_dates[]. The detailed view of every ticket the person has been authorised on (current and historic).

CTAM column	Type	Source attribute	Description / Notes / example
authorisation_id	INT	authorisation_id (JHR)	PK Unique. 135337.
personal_code	VARCHAR (32)	(parent in /people array)	FK jo_people.personal_code
appointment_id	INT	appointment_id (JHR)	FK jo_appointments.appointment_id Nullable. Source guarantees population after August 2025; older rows may be null.
jurisdiction	VARCHAR (64)	jurisdiction (JHR)	If the Jurisdiction is "Courts", the ticket category name is returned in this attribute instead (in other words, "Civil", "Family" or "Tribunals")

jurisdiction_id	INT	jurisdiction_id (JHR)	FK (conditional) FK jo_jurisdictions.id. When jurisdiction = 'Courts' FK jo_ticket_categories.id (this is the source's documented behaviour, not a CTAM transformation) Can CTAM create a separate column so ticket_category_id column gets mapped to the correct table from FK perspective, where jurisdiction = 'Courts'. Any side effect of deviation here?
ticket_category_id	INT	jurisdiction_id (JHR)	Can CTAM create a separate column so ticket_category_id column gets mapped to the correct table from FK perspective, where jurisdiction = 'Courts'. Any side effect of deviation here? FK jo_ticket_categories.id
ticket	VARCHAR(256)	ticket (JHR)	Denormalised ticket name. "03 - Disability Living Allowance".
ticket_id	INT	ticket_id (JHR)	FK jo_tickets.id
start_date	DATE	start_date (JHR)	
end_date	DATE	end_date (JHR)	

3.5 jo_appointment_titles

Reference list of appointment role names. Referenced by jo_appointments.role_name_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK Stable across JHR releases and StagingProduction.
name	VARCHAR(128)	name	"Magistrate", "Deputy District Judge - Fee-paid".
start_date	DATE	start_date	Selectable-from date; null = unconstrained.
end_date	DATE	end_date	Selectable-to date; null = unconstrained.
created_at	TIMESTAMP	created_at	Source row creation.
updated_at	TIMESTAMP	updated_at	Source row update.

3.6 jo_base_locations

Reference list of locations to which an appointment can be attached. Referenced by jo_appointments.base_location_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(256)	name	"Manchester Civil Justice Centre". Denormalised in jo_appointments.base_location EXCEPT for Tribunals.
type_id	INT	type_id	FK jo_location_types.id
parent_id	INT	parent_id	FK jo_locations.id Parent in the location hierarchy.
jurisdiction_id	INT	jurisdiction_id	FK jo_jurisdictions.id (hard-coded) Hard-coded enum: 1 Courts, 2 Tribunals, 3 Magistrates, 4 Coroners.
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

Tribunals chamber traversal — For Tribunal appointments, jo_appointments.base_location_id points to a TRIBS_LOCATION (leaf node). TRIBS_CHAMBER (one level up) is not surfaced as a standalone appointment attribute; retrieve it by following jo_base_locations.parent_id jo_locations.id. That jo_locations row is the chamber.

3.7 jo_contract_types

Reference list of appointment contract types. Referenced by jo_appointments.contract_type_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(64)	name	"Salaried", "Fee-paid", "Voluntary", "SPTW-50%".
salaried	BOOLEAN	salaried	Whether this contract type is salaried.
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.8 jo_genders

Reference list of gender values. Referenced by jo_people.gender_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(32)	name	"Male", "Female", "Other", "Prefer not to say".
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.9 jo_judiciary_roles (reference list)

Reference list of judiciary role names. Referenced by jo_judiciary_role_assignments.judiciary_role_name_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(128)	name	"International Committee Member", "Sentencing Council", "Appraisal Judge".
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.10 jo_jurisdictions

Reference list of jurisdictions. Referenced by ticket-related and location-related tables.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(64)	name	"Courts", "Tribunals", "Magistrates", "Coroners", "Skills". <i>What do the "Skills" refer to ?</i>
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	

updated_at	TIMESTAMP	updated_at	
------------	-----------	------------	--

3.11 jo_locations

*Reference list of **all** locations (the whole hierarchy). jo_base_locations is a subset of this (locations an appointment can attach to).*

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR: integration_id)	PK
name	VARCHAR(256)	name	"Manchester Civil Justice Centre", "Wiltshire LJA", "Other Tribunal", "National".
type_id	INT	type_id	FK jo_location_types.id
parent_id	INT	parent_id	FK jo_locations.id (self) Self-referencing hierarchy.
jurisdiction_id	INT	jurisdiction_id	FK jo_jurisdictions.id (hard-coded) Hard-coded enum: 1 Courts, 2 Tribunals, 3 Magistrates, 4 Coroners.
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.12 jo_location_types

Reference list of location-hierarchy types. Referenced by jo_locations.type_id and jo_base_locations.type_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(64)	name	"Court", "Area or Parent AC", "Chamber".
jurisdiction_id	INT	jurisdiction_id	FK jo_jurisdictions.id (hard-coded)
integration_code	VARCHAR(64)	integration_code	"MAGS_AREA_OR_PARENT_AC", "COURTS_COURT_NAME".
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.13 jo_tickets

Reference list of ticket (authorisation competency) names. Referenced by jo_authorisations_with_dates.ticket_id.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(256)	name	The display name of this reference data item. "Welsh Language", "Chancery", "Attempted Murder".
ticket_category_id	INT	ticket_category_id	FK jo_ticket_categories.id Indicates the category that this ticket falls into
start_date	DATE	start_date	
end_date	DATE	end_date	

created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.14 jo_ticket_categories

Reference list of ticket categories (hierarchy). Referenced by `jo_tickets.ticket_category_id` and by `jo_authorisations_with_dates.jurisdiction_id` when `jurisdiction = 'Courts'`.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR:integration_id)	PK
name	VARCHAR(256)	name	The display name of this reference data item. "Environment", "Direct and Indirect Taxation", "Appeals in Crown Court".
type_id	INT	type_id	FK jo_ticket_category_types.id Courts / Tribs etc.
jurisdiction_id	INT	jurisdiction_id	FK jo_jurisdictions.id (hard-coded) The jurisdiction that this ticket category falls into. 1 (Courts), 2 (Tribunals), 3 (Magistrates), 4 (Coroners)
parent_category_id	INT	parent_category_id	FK jo_ticket_categories.id (self) What does this represent. What is the basis on which the ticket categories are divided ?
start_date	DATE	start_date	
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.15 jo_ticket_category_types

Reference list of ticket-category types. Referenced by `jo_ticket_categories.type_id`.

CTAM column	Type	Source attribute	Description / Notes / example
id	INT	id (JHR: integration_id)	PK
name	VARCHAR (64)	name	The display name of this reference data item. "Court Type", "Skills Category", "Tribunal Name".
jurisdiction_id	INT	jurisdiction_id	FK jo_jurisdictions.id (hard-coded) The jurisdiction that this ticket category falls into. 1 (Courts), 2 (Tribunals), 3 (Magistrates), 4 (Coroners)
integration_code	VARCHAR (64)	integration_code	The text code that identifies the type of location, received from JHR. "COURTS_COURT_TYPE", "SKILLS_CATEGORY", "TRIBS_NAME".
start_date	DATE	start_date	The date from which which reference data item becomes available for selection. If null, the item is available for selection without limitation regarding its start.
end_date	DATE	end_date	
created_at	TIMESTAMP	created_at	
updated_at	TIMESTAMP	updated_at	

3.16 jo_sync_status (CTAM-internal, no source mapping)

One row per source endpoint, maintained by the CTAM ingestion job. Holds the cursor used for incremental refresh and the outcome of the last run.

CTAM column	Type	Description / Notes
source_endpoint	VARCHAR(128)	PK e.g. /people, /leavers, /deleted, /reference_data/{ref_data_type}
last_synced_at	TIMESTAMP	When the last sync run started.
last_successful_sync_at	TIMESTAMP	When the last successful sync completed.
last_status	VARCHAR(16)	success failed in_progress.
last_error_message	TEXT	Null when last run succeeded.
records_processed	INT	Count from the last run.
last_since_param	DATE	Cursor value sent on next call as updated_since / left_since / deleted_since.

4. Refresh strategy (informational)

- **Transactional** endpoints (/people, /leavers, /deleted) accept updated_since / left_since / deleted_since and are **paginated** (per_page < 200, page). Use jo_sync_status.last_since_param to drive incremental pulls.
- **Reference** endpoints are not paginated and have no since parameter — pull the whole list each refresh; replace-by-id is simplest.
- On receipt of a /leavers record: set jo_people.status='leaver', populate left_on, null out PII columns as per analysis.
- On receipt of a /deleted record: set jo_people.status='deleted', populate deleted_on, null out PII columns as per analysis.
- **personal_code is the only safe matching key** — never match on id (AD object id) or email, both of which the source warns can change or be reused.

5. Data warnings

The following warnings describe known limitations of the eLinks source data and API that affect freshness, completeness, and reliability of data in CTAM. These are characteristics of the source — not defects in the sync implementation — and must be understood by anyone building on or consuming CTAM data.

#	Warning	Affected fields	CTAM's behaviour
W1	Location fields are frozen at appointment creation and never updated by eLinks	jo_appointments: type, court_name, court_type, circuit, bench, advisory_committee_area, location, base_location, base_location_id	Replicate faithfully but treat as appointment-creation snapshot only. CTAM must not use these fields to infer where a JOH is currently working. Expose sync timestamp so consumers know the as-at date. <i>CTAM will need to build the ability for the RSU/Court users so it reflects the location changes as applicable to JOH.</i>
W2	Long-dormant leavers may be silently absent from the /leavers feed	jo_people.status	Treat status = 'active' as "active according to last eLinks sync", not a definitive guarantee. <i>As a compensating control, CTAM should flag appointments whose end_date has passed but whose owner is still active, surfacing them for manual review. Court/RSU users who work closely with JOH will have first hand knowledge, so this is not necessarily a concern from user's perspective. TBC.</i>
W3	email changes over time and can be reused	jo_people.email	Treat as a display/contact field only — never as a lookup or join key. Direct all consumers to use personal_code as the only stable identity. Staleness within a sync window is expected and accepted.
W4	ad_object_id changes over time and can be reused	jo_people.ad_object_id	Same as W3. Treat as informational only. Never use as a join key or identity anchor. personal_code is the only safe key.
W5	is_principal can flip between sync cycles as appointments are created or expire	jo_appointments.is_principal	Treat is_principal = true as accurate as-at the last sync timestamp only. Consumers must not cache or independently persist this flag outside of CTAM's own data.
W6	Reference data has no incremental sync mechanism — no updated_since parameter exists on any /reference_data/* endpoint	All denormalised name columns (e.g. role_name, contract_type, base_location)	Sync all reference endpoints in full on every sync cycle. Always run the reference data sync before processing transactional data in that cycle so FKs and denormalised names are never out of step.
W7	appointment_id is null on authorisation records created before August 2025	jo_authorisations_with_dates.appointment_id	Accept and store nulls. All queries joining jo_authorisations_with_dates to jo_appointments via this field must use a LEFT JOIN. This is a permanent historical gap — no remediation is possible.

W8	email_personal is sparsely populated — 3,724+ active JOHs had no value as of the source document date (Oct 2024)	jo_people.email_personal	Accept and store nulls. Treat as optional/best-effort data. Downstream consumers must not assume population. No remediation is possible; coverage depends on JOHs supplying the data to JHR.
----	--	--------------------------	--

6. Open questions

	Date added / Date updated	Description	Status	Comments
1	18 Jun 2026	Is there a master list of regions and circuits at JO level ? The JI system relies on circuits and regions as the basis of doing filtering for the JOH. How can JO data help establish these lists at a jurisdiction level ? Or is this something that needs to be managed at CTAM level ?	Closed	Yes, the location hierarchy has this information, but it needs to be reviewed in detail
2	18 Jun 2026	Authorisations current - This list coming from JO seems to be date related. As CTAM needs to be able to do forecasting in future and is not just concerned about the current list of authorisations, does it make sense to replicate this dataset coming via API ? Current thinking is that having the dates based authorisation is sufficient for CTAM to drive its logic	Closed	Only use the authorisations with dates.
3	18 Jun 2026	jo_authorisations_with_dates.jurisdiction_id When jurisdiction = 'Courts' FK jo_ticket_categories.id (this is the source's documented behaviour, not a CTAM transformation) Current thinking is that CTAM will create a separate column so ticket_category_id column gets mapped to the correct table from FK perspective, where jurisdiction = 'Courts'. Any side effect of deviation here? This will avoid the conditional FK within CTAM boundary.	Closed	Yes, map those data points to separate fields, and have the logic in the ingestion layer to be able to populate the fields conditionally
4	18 Jun 2026	jo_ticket_categories.parent_category_id What does this represent. What is the basis on which the ticket categories are divided ?	Closed	This is business defined categories. Need to check the ref data to understand their significance
5	18 Jun 2026	jo_people.ad_object_id - Do we need to replicate this ?	Closed	Yes, this can be useful for SSO purposes if using eJudiciary
6	18 Jun 2026	jo_people.title Active only. "His Honour Judge", "Mrs". How does this account for multiple roles that a JOH may be performing where each needs to be attributed separately	Closed	This is currently held at person level. Will need to incorporate this in CTAM, if needed.
7	18 Jun 2026	jo_people.gender , jo_people.gender_id Is this data duplicated purely for denormalisation reasons, or is there a legacy reason where date is present in one field and not in another for some rows	Closed	Only use gender_id. No need to replicate the denormalised data
8	18 Jun 2026	jo_appointments.is_principal What does this mean ? and what implications does it have from availability perspective.	Closed	This implies the main appointment that the JOH holds - it can change. Need to replicate this and discuss its implications from JO perspective.
9	18 Jun 2026	Authorisations_With_Dates belong to a Current Office Holder (through the parentage of the Current Office Holder.authorisations_with_dates[] array), but may be optionally associated with an Appointment, through the Authorisations_With_Dates.appointment_id attribute. Isn't ticket always associated with an appointment that a JOH carries e.g. if someone is a DDJ and a Recorder, the ticket would be associated with the appointment (DDJ) that the JOH holds. If it is not associated with an appointment, how do we know which role /appointment does this ticket belong to ?	Open	Need to review the data to understand this better.
10	18 Jun 2026	Why do some reference data have start and end dates attached to them ? What is it's significance.	Closed	This is applicable, if the location is closing down at a certain date. That is reflected in this data.
11	18 Jun 2026	jo_jurisdictions.name "Courts", "Tribunals", "Magistrates", "Coroners", "Skills". What do the "Skills" refer to ?	Open	Skills are relevant for Wales. Need to explore the data to understand this better.
12	18 Jun 2026	jo_ticket_category_types.integration_code The text code that identifies the type of location, received from JHR. "COURTS_COURT_TYPE", "SKILLS_CATEGORY", "TRIBS_NAME". How is it related to ticket category types?	Closed	Not relevant for clients. This is internal to eLinks.
13	18 Jun 2026	jo_people - What is the difference between retirement_date and leaving_on ? How is the data handled when a judge is sitting in retirement? This concept exists in current JI, wondering if it is captured at the JO data level ?	Closed	Sitting in retirement - comes in as a new appointment to a JOH. It can get attached to an existing Personnel number or a new one due to manual errors. Need to look into the deletions to understand its impact on CTAM

