

Locations

- [Population](#)
- [Data Constraints](#)
- [Data Flow](#)
- [Location Reference Data](#)
- [Id Consistency](#)
- [Mapping](#)
 - [Advisory Committees \(ACs\)](#)
 - [Coroners](#)
 - [Courts](#)
 - [Local Justice Area \(LJA\)](#)
 - [Mags Area Committee](#)
 - [Mags Area Sub Committee](#)
 - [Mags Court](#)
 - [Tribunals](#)

Locations are stored as attributes of Appointments in Judicial Office data. They are collected at the point of setting up an Appointment specifically for the purposes of the Judicial Office, and the following should be noted regarding their use:

1. They relate specifically to the contract between the Judicial Office and the JOH;
2. They are not updated after that point in time;
3. They do not necessarily have to relate to where the JOH is working;
4. They do not necessarily have to indicate the locality of the JOH;
5. They do not necessarily have to relate to where a JOH is anticipated to be from a tax or expense perspective;
6. Location belongs to an Appointment, not to a JOH; therefore, the JOH can have multiple locations indirectly associated with them.



WARNING

Based on the points above, significant care should be taken about the use of location data for purposes other than their collection by the Judicial Office.

Population

Location data is supplied and updated by the following:

JOH Type	Initial Population	Update
Courts	JO Pre-Appointments	JO Pre-Appointments
Tribunals	JO Pre-Appointments	JO Pre-Appointments
Magistrates	Applicant Tracking System (ATS)	Magistrates HR
Coroners	Coroners Team	Coroners Team

The population sources have agreed the locations reference data with the Judicial Office and may direct addition, change or retirement of location reference data.

Data Constraints

Location data is derived from the location associated with an Appointment. Location has the following data constraints:

- it is a foreign key to reference data; all location data is derived from this foreign key;
- the reference data is hierarchical with parent-child relationships; these relationships define all correlated data;
- the foreign key is densely-populated but not mandatory;
- TO DO Check against eLinks Swagger documentation; missing locations seem to be against Advisory Committees or some Tribs
- the data master for location is Appointment in Judicial HR (JHR);
- since a JOH can have multiple Appointments, they may indirectly have multiple locations.

Data Flow

Regardless of the population source, the source of truth for location data is Judicial HR (JHR). The following processes exist:

- Manual maintenance of the location reference data by the JOHR team in JHR;
- Automated import of Appointments and their associated location data from the population source;
- Manual maintenance of the Appointments and their associated location data by the JOHR team in JHR.

JOHs and their Appointments are synchronised one-way from JHR eLinks through the JHR API. eLinks connects periodically to the JHR API, and applies all changes (including those affecting locations) to its own database, although it should be noted that leavers data which has not changed in a long period of time may not be present in eLinks.

Location Reference Data

Location reference data is exposed as follows:

- Locations to which Appointments can be attached (i.e. locations without children) are available through the `reference_data/base_locations` endpoint in eLinks;
- All of the locations (i.e. the whole hierarchy) are available through the `reference_data/locations` endpoint in eLinks.

Each location item in the reference data endpoints has the following attributes:

- `id`
- `name`
- `type_id`
- `parent_id`
- `jurisdiction_id`
- `start_date`
- `end_date`
- `created_at`
- `updated_at`

The `parent_id` attribute determines the hierarchy; the `parent_id` of a location joins to the `id` of its parent. Where the `parent_id` is null, the location has no parent. Each mapping type (see Mapping below) has a consistent number of levels in its hierarchy, although the number of levels may differ between types. In other words, Courts always have three levels, and Advisory Committees always have four.

Id Consistency

CIPHR was the predecessor to Judicial HR, and had a different approach to location reference data, in that it did not maintain a true hierarchy with a separate record for each level of in the hierarchy. As a result, parent items in the hierarchy in CIPHR did not have their own Id.

The lowest level of the hierarchy for all location types except Tribunals have retained ownership of the Id from CIPHR, as this is the level which is attached to the Appointment as `base_location_id`.

In CIPHR for Tribunals, the chamber was attached to the Appointment as `base_location_id`, and the region was held in an entirely unrelated text field called `location`. In Judicial HR the hierarchy was refactored for Tribunals to include the location data on the bottom level of the hierarchy, and `base_location_id` was attached to the new bottom level (location). Therefore, for Tribunals, the chamber record (parent of the lowest level of the hierarchy) has retained the same id it previously had in CIPHR, but:

- `Appointment.base_location_id` is attached to the new location id;
- The chamber can be determined by finding the parent of the record attached to `Appointment.base_location_id` in the reference data endpoint, and the chamber's id is consistent between CIPHR and JHR.

Mapping

The data mappings differ depending on the type of entity being mapped. There are a total of 6 types:

- Advisory Committees (ACs)
- Coroners
- Courts
- Local Justice Areas (LJAs)
- Mags Court
- Tribunals

All types are identified (or distinguished) by the type code of the lowest item in their hierarchy.

It should be noted that the `location` attribute in eLinks will always be mapped to the geographic area, regardless of which entity type is being mapped.

**WARNING**

Locations or Regions for different entity types are entirely unrelated to each other. In other words, the South East location belonging to Coroners is a different item (with a different Id) from the South East location belonging to LJA. There is no implication that the regions are in any way harmonised.

Advisory Committees (ACs)

Advisory Committees are distinguished by the lowest item type code `MAGS_AREA_AC`. They have a 3-level hierarchy as follows:

Level	Contents
-------	----------

1	Region (MAGS_REGION)
^	
2	Area or Parent AC (MAGS_AREA_OR_PARENT_AC)
^	
3	AC (MAGS_AREA_AC)

Advisory Committees are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Advisory Committee		
court_name	Advisory Committee	Northumbria Recruitment AC	MAGS_AREA_AC	3
court_type	Parent	Northumbria AC	MAGS_AREA_OR_PARENT_AC	2
circuit	NULL			
bench	NULL			
advisory_committee_area	NULL			
location	Region	North East	MAGS_REGION	1
base_location	Advisory Committee	Northumbria Recruitment AC	MAGS_AREA_AC	3
base_location_id	Id	1422	Id of MAGS_AREA_AC	3

Coroners

Coroners are distinguished by the lowest item type code CORONERS_AREA. They have a 3-level hierarchy as follows:

Level	Contents
1	Region (CORONERS_REGION)
^	
2	Local Authority (CORONERS_LOCAL_AUTH)
^	
3	Area (CORONERS_AREA)

Coroners are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Coroners		
court_name	Area	East Riding and Hull	CORONERS_AREA	3
court_type	Local Authority	Hull City County	CORONERS_LOCAL_AUTH	2
circuit	NULL			
bench	NULL			
advisory_committee_area	NULL			
location	Region	Yorkshire and the Humber	CORONERS_REGION	1
base_location	Area	East Riding and Hull	CORONERS_AREA	3
base_location_id	Id	1229	Id of CORONERS_AREA	3

Courts

Courts are distinguished by the lowest item type code COURTS_COURT_NAME. They have a two-level hierarchy as follows:

Level	Contents
-------	----------

1	Region (COURTS_REGION)
^	
2	Court (COURTS_COURT_NAME)

Courts are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Courts		
court_name	Court Name	Morpeth County Court	COURTS_COURT_NAME	2
court_type	NULL			
circuit	Region	North East	COURTS_REGION	1
bench	NULL			
advisory_committee_area	NULL			
location	Region	North East	COURTS_REGION	1
base_location	Court	Morpeth County Court	COURTS_COURT_NAME	2
base_location_id	Id	940	Id of COURTS_COURT_NAME	2

Local Justice Area (LJA)

Local Justice Areas (LJAs) are distinguished by the lowest item type code MAGS_AC_LJA. They have a 3-level hierarchy as follows:

Level	Contents
1	Region (MAGS_REGION)
^	
2	Advisory Committee (MAGS_AC)
^	
3	Local Justice Area (MAGS_AC_LJA)

LJAs are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	LJA		
court_name	Local Justice Area	Surrey LJA	MAGS_AC_LJA	3
court_type	Advisory Committee	Surrey and Sussex AC	MAGS_AC	2
circuit	NULL			
bench	Local Justice Area	Surrey LJA	MAGS_AC_LJA	3
advisory_committee_area	Advisory Committee	Surrey and Sussex AC	MAGS_AC	2
location	Region	South East	MAGS_REGION	1
base_location	Local Justice Area	Surrey LJA	MAGS_AC_LJA	3
base_location_id	Id	1375	Id of MAGS_AC_LJA	3

Mags Area Committee

Magistrates Area Committees are distinguished by the lowest item type code MAGS_AREA_COMMITTEE, joining with the Advisory Committee hierarchy at the MAGS_AREA_OR_PARENT_AC level. They have a 3-level hierarchy as follows:

Level	Contents
1	Region (MAGS_REGION)
^	

2	Advisory Committee (MAGS_AREA_OR_PARENT_AC)
^	
3	Mags Area Committee (MAGS_AREA_COMMITTEE)

Magistrates Area Committees are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Mags Area Committee		
court_name	Mags Area Committee	Greater Manchester Committee	MAGS_AREA_COMMITTEE	3
court_type	Parent	Greater Manchester	MAGS_AREA_OR_PARENT_AC	2
circuit	NULL			
bench	NULL			
advisory_committee_area	NULL			
location	Region	Greater Manchester	MAGS_REGION	1
base_location	Mags Area Committee	Greater Manchester Committee	MAGS_AREA_COMMITTEE	3
base_location_id	Id	1910	Id of MAGS_AREA_COMMITTEE	3

Mags Area Sub Committee

Magistrates Area Sub Committees are distinguished by the lowest item type code MAGS_AREA_SUBCOMMITTEE, joining with the Advisory Committee hierarchy at the MAGS_AREA_OR_PARENT_AC level. They have a 3-level hierarchy as follows:

Level	Contents
1	Region (MAGS_REGION)
^	
2	Advisory Committee (MAGS_AREA_OR_PARENT_AC)
^	
3	Mags Area Committee (MAGS_AREA_SUBCOMMITTEE)

Magistrates Area Sub Committees are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Mags Area Sub Committee		
court_name	Mags Area Sub Committee	South East Essex Sub Committee	MAGS_AREA_SUBCOMMITTEE	3
court_type	Parent	Essex	MAGS_AREA_OR_PARENT_AC	2
circuit	NULL			
bench	NULL			
advisory_committee_area	NULL			
location	Region	Essex	MAGS_REGION	1
base_location	Mags Area Sub Committee	South East Essex Sub Committee	MAGS_AREA_SUBCOMMITTEE	3
base_location_id	Id	541	Id of MAGS_AREA_SUBCOMMITTEE	3

Mags Court

Magistrates Courts are distinguished by the lowest item type code MAGS_AC_COURT_NAME. They have a 3-level hierarchy as follows:

Level	Contents
1	Region (MAGS_REGION)
^	

2	Advisory Committee (MAGS_AC)
^	
3	Mags Court Name (MAGS_AC_COURT_NAME)

Magistrates Courts are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Mags Court		
court_name	Mags Court Name	Family Proceedings Court	MAGS_AC_COURT_NAME	3
court_type	Advisory Committee	London AC	MAGS_AC	2
circuit	NULL			
bench	Mags Court Name	Family Proceedings Court	MAGS_AC_COURT_NAME	3
advisory_committee_area	Advisory Committee	London AC	MAGS_AC	2
location	Region	London	MAGS_REGION	1
base_location	Mags Court Name	Family Proceedings Court	MAGS_AC_COURT_NAME	3
base_location_id	Id	1434	Id of MAGS_AC_COURT_NAME	3

Tribunals

Tribunals are distinguished by the lowest item type code TRIBS_LOCATION. They have a 3-level hierarchy as follows:

Level	Contents
1	Tier (TRIBS_TIER)
^	
2	Chamber (TRIBS_CHAMBER)
^	
3	Location (TRIBS_LOCATION)



WARNING

In addition to the warning above, tribunals locations are related only to their parent. In other words, the South East location belonging to the Social Entitlement Chamber is a different item (with a different id) from the South East location belonging to the Employment Tribunal (England & Wales) chamber. There is no implication that the locations are in any way harmonised.

In order that the data can be clearly attributed, base_location for Tribunals concatenates the chamber with the location, which also serves the purpose of displaying the chamber, not displayed in any other attribute on the /people (Appointments) endpoint. Tribunals are mapped in eLinks as follows:

eLinks attribute	Content	Data Example	JHR Mapping Item	JHR Mapping Level
type	Static Text	Tribunals		
court_name	Location	North East	TRIBS_LOCATION	3
court_type	Tier	First Tier Tribunal	TRIBS_TIER	1
circuit	NULL			
bench	NULL			
advisory_committee_area	NULL			
location	Location	North East	TRIBS_LOCATION	3
base_location	Concatenated Chamber, ' - ' and Location	Social Entitlement Chamber - North East	TRIBS_CHAMBER - TRIBS_LOCATION	2, 3
base_location_id	Id	1784	Id of TRIBS_LOCATION	3