

Laboratory 1

GUI (Graphical User Interface) in Java

Name: Mohammed Ziyad Alsharif

Student ID: 446818145

Activity 1 – Question 2

Write a Java program which creates two frames, each containing one button. When you execute the program only one JFrame will appear, and when you click on its button it will disappear and the other JFrame will appear. If you click on the button of the second frame, it will make it disappear and let the first frame appear. And so on.

Java Code

Activity1.java

```
import javax.swing.JButton;
import javax.swing.JFrame;
import java.awt.GridBagLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;

class MyFrame1 extends JFrame implements ActionListener {

    private JButton clickButton;
    private MyFrame2 frame2;

    public MyFrame1() {
        setTitle("MyFrame 1");
        setSize(320, 240);
        setLocationRelativeTo(null);
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);

        setLayout(new GridBagLayout());

        clickButton = new JButton("click");
        clickButton.addActionListener(this);
        add(clickButton);
    }

    public void setFrame2(MyFrame2 frame2) {
        this.frame2 = frame2;
    }

    @Override
    public void actionPerformed(ActionEvent e) {
        this.setVisible(false);
        frame2.setVisible(true);
    }
}

class MyFrame2 extends JFrame implements ActionListener {

    private JButton clickButton;
    private MyFrame1 frame1;

    public MyFrame2() {
        setTitle("MyFrame 2");
        setSize(320, 240);
        setLocationRelativeTo(null);
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);

        setLayout(new GridBagLayout());

        clickButton = new JButton("click");
        clickButton.addActionListener(this);
        add(clickButton);
    }

    public void setFrame1(MyFrame1 frame1) {
        this.frame1 = frame1;
    }
}
```

```
        @Override
        public void actionPerformed(ActionEvent e) {
            this.setVisible(false);
            frame1.setVisible(true);
        }
    }


    public class Activity1 {
        public static void main(String[] args) {
            MyFrame1 frame1 = new MyFrame1();
            MyFrame2 frame2 = new MyFrame2();

            frame1.setFrame2(frame2);
            frame2.setFrame1(frame1);

            frame1.setVisible(true);
        }
    }
}
```

Output Screenshot

MyFrame 1 visible when the program starts



MyFrame 2 visible after clicking the button on MyFrame 1

click

Activity 2 – Question 1

Using the FlowLayout, write the program that creates the Distance Converter interface. On the click of button **Convert!**, the integer value in the text field should be converted to kilometers and displayed in the text area below, in a new line. (1 mile = 1.60934 kilometers)

Java Code

DistanceConverterFlow.java

```
import javax.swing.JButton;
import javax.swing.JFrame;
import javax.swing.JLabel;
import javax.swing.JScrollPane;
import javax.swing.JTextArea;
import javax.swing.JTextField;
import java.awt.FlowLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import java.math.BigDecimal;

public class DistanceConverterFlow extends JFrame implements ActionListener {

    private JLabel milesLabel;
    private JTextField milesField;
    private JButton convertButton;
    private JTextArea resultArea;

    private static final BigDecimal MILES_TO_KM = new BigDecimal("1.60934");

    public DistanceConverterFlow() {
        setTitle("Distance Converter");
        setSize(400, 300);
        setLocationRelativeTo(null);
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);

        setLayout(new FlowLayout());

        milesLabel = new JLabel("Distance in miles:");
        milesField = new JTextField(8);
        convertButton = new JButton("Convert!");
        convertButton.addActionListener(this);

        resultArea = new JTextArea(8, 24);
        resultArea.setEditable(false);
        JScrollPane scrollPane = new JScrollPane(resultArea);

        add(milesLabel);
        add(milesField);
        add(convertButton);
        add(scrollPane);
    }

    @Override
    public void actionPerformed(ActionEvent e) {
        try {
            int miles = Integer.parseInt(milesField.getText().trim());
            BigDecimal km = new BigDecimal(miles).multiply(MILES_TO_KM);
            String kmText = km.stripTrailingZeros().toPlainString();
            resultArea.append(miles + " miles = " + kmText + " km\n");
        } catch (NumberFormatException ex) {
            resultArea.append("Please enter a valid integer.\n");
        }
    }

    public static void main(String[] args) {
        DistanceConverterFlow frame = new DistanceConverterFlow();
        frame.setVisible(true);
    }
}
```

```
}  
}
```

Output Screenshot

Input: 10 | Output: 10 miles = 16.0934 km

The screenshot shows a web interface for converting miles to kilometers. It features a label "Distance in miles:" followed by a text input field containing the number "10". To the right of the input field is a blue button with the text "Convert!". Below these elements is a large rectangular text area that displays the result: "10 miles = 16.0934 km".

Activity 2 – Question 2

Using a combination of two layout managers (BorderLayout and FlowLayout), modify the previous program to obtain the same interface. Place the label, text field and button in a FlowLayout panel positioned in the NORTH of a BorderLayout, and place the text area in the CENTER. On the click of button **Convert!**, the integer value in the text field should be converted to kilometers and displayed in the text area below, in a new line.

Java Code

DistanceConverterBorderFlow.java

```
import javax.swing.JButton;
import javax.swing.JFrame;
import javax.swing.JLabel;
import javax.swing.JPanel;
import javax.swing.JScrollPane;
import javax.swing.JTextArea;
import javax.swing.JTextField;
import java.awt.BorderLayout;
import java.awt.FlowLayout;
import java.awt.event.ActionEvent;
import java.awt.event.ActionListener;
import java.math.BigDecimal;

public class DistanceConverterBorderFlow extends JFrame implements ActionListener {

    private JLabel milesLabel;
    private JTextField milesField;
    private JButton convertButton;
    private JTextArea resultArea;

    private static final BigDecimal MILES_TO_KM = new BigDecimal("1.60934");

    public DistanceConverterBorderFlow() {
        setTitle("Distance Converter");
        setSize(400, 300);
        setLocationRelativeTo(null);
        setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);

        setLayout(new BorderLayout());

        JPanel northPanel = new JPanel(new FlowLayout());
        milesLabel = new JLabel("Distance in miles:");
        milesField = new JTextField(8);
        convertButton = new JButton("Convert!");
        convertButton.addActionListener(this);

        northPanel.add(milesLabel);
        northPanel.add(milesField);
        northPanel.add(convertButton);

        resultArea = new JTextArea();
        resultArea.setEditable(false);
        JScrollPane scrollPane = new JScrollPane(resultArea);

        add(northPanel, BorderLayout.NORTH);
        add(scrollPane, BorderLayout.CENTER);
    }

    @Override
    public void actionPerformed(ActionEvent e) {
        try {
            int miles = Integer.parseInt(milesField.getText().trim());
            BigDecimal km = new BigDecimal(miles).multiply(MILES_TO_KM);
            String kmText = km.stripTrailingZeros().toPlainString();
            resultArea.append(miles + " miles = " + kmText + " km\n");
        } catch (NumberFormatException ex) {
            resultArea.append("Invalid input\n");
        }
    }
}
```

```
        } catch (NumberFormatException ex) {
            resultArea.append("Please enter a valid integer.\n");
        }
    }

    public static void main(String[] args) {
        DistanceConverterBorderFlow frame = new DistanceConverterBorderFlow();
        frame.setVisible(true);
    }
}
```

Output Screenshot

Input: 10 | Output: 10 miles = 16.0934 km



Distance in miles:

10 miles = 16.0934 km