

# Step-by-Step Guide to Using RANSAC in OpenCV using Python

Last Updated : 28 Jun, 2024

---

**RANSAC (Random Sample Consensus)** is an iterative method to estimate the parameters of a mathematical model from a set of observed data that contains outliers. In computer vision, it's often used for tasks like estimating the fundamental matrix, homography, or any fitting problem with noisy data.

In Python, OpenCV provides built-in support for RANSAC. Below, I'll show you how to use RANSAC with OpenCV to estimate a homography matrix from point correspondences between two images.

## Step-by-Step Guide to Using RANSAC in OpenCV

### Table of Content

- [Step-by-Step Guide to Using RANSAC in OpenCV](#)
  - [Step 1 - Install OpenCV.](#)
  - [Step 2 - Import the required necessary libraries.](#)
  - [Step 3 - Load Data - a set of points, an image pair, or data relevant to the problem.](#)
  - [Step 4 - Detect Key points and Descriptors.](#)
  - [Step 5 - Match Descriptors.](#)
  - [Step 6 - Apply RANSAC to Find Homography.](#)
- [Implementation of RANSAC in OpenCV](#)
- [Conclusion](#)

Here's a detailed step-by-step guide on how to apply RANSAC in Python using OpenCV, specifically for estimating a homography matrix between two images.

## Step 1 - Install OpenCV.

```
pip install opencv-python
```



## Step 2 - Import the required necessary libraries.

```
import cv2  
import numpy as np
```



## Step 3 - Load Data - a set of points, an image pair, or data relevant to the problem.

```
# Example: Load two images
```

