

Qt Quickstart

Mathias M. Vege

November 20, 2018

Abstract

A short guide to getting started with Qt Creator.

Contents

1	Installing Qt	2
1.1	Mac	3
1.1.1	Prerequisite	3
1.1.2	Installing Qt	3
1.2	Ubuntu	3
1.2.1	Prerequisite	3
1.2.2	Installing Qt	3
1.3	Windows	3
1.3.1	Prerequisite	3
1.3.2	Installing Qt	3
2	Creating your first project	4
3	Project settings	8
3.1	Build settings	8
3.2	Changing build folder	9
3.3	Run settings	10
3.4	Command line arguments	10
4	Expanding your project	11
4.1	The .pro-file	11
4.2	Adding files and classes	11
4.2.1	New header files	12
4.2.2	New Classes	13
4.3	Adding existing files	14
5	Guides to external libraries for Qt	15
5.1	Armadillo	15
5.1.1	Installation	15
5.1.2	Including Armadillo in Qt Creator	15
5.1.3	Troubleshooting	16
5.2	OpenMP	16

5.3	MPI	16
6	Profiling your code	16
6.1	Installing Valgrind	16
6.1.1	Mac	16
6.1.2	Ubuntu	16
6.2	Installing K/QCachegrind	17
6.2.1	Mac	17
6.2.2	Ubuntu	17
6.3	Running Valgrind memory check(memcheck)	17
6.3.1	Qt Creator	17
6.3.2	Terminal	17
6.4	Profiling with Valgrind(Callgrind)	17
6.4.1	Qt Creator	17
6.4.2	Terminal	18
7	Optimizing your code	18
8	Parallelization	19
8.1	MPI	19
8.1.1	Mac	19
8.1.2	Ubuntu	19
8.1.3	Setting up MPI for QtCreator	19
8.2	OpenMP	21
8.2.1	Mac	21
8.2.2	Ubuntu	21
8.3	Troubleshooting	21
8.3.1	Orte Communications	21
8.3.2	Failed to start program	22

1 Installing Qt

In order to get Qt Creator up and running as an IDE, there are a few requirements. The following is needed,

- **Qt.** The Qt core package containing the core functionality and libraries used by Qt Creator. Contains the kits needed to compile and build projects, as well as libraries for building e.g. [Android and iPhone apps](#).
- **Qt Creator.** The IDE used for programming.
- **A C++compiler.** Needed in order to compile C++files in Qt Creator. The specific compiler needed depend on the OS.

NOTE: it is possible to update your Qt platform after installing it through the Qt Maintenance tool in case you are missing any of the Qt utilities, such as a proper Qt version.

1.1 Mac

1.1.1 Prerequisite

- brew. See <https://brew.sh/> for a guide to installing it.
- Xcode. Download from app-store. Through Xcode you should get a compiler for C++.

1.1.2 Installing Qt

Go to <https://www.qt.io/download>, and follow the instructions. Make sure to select a Qt version under the tab *Qt*, typically you select the newest version Qt.11.1(as of November 20, 2018). For me that is *macOS*. Qt Creator should be automatically selected under *Tools*.

1.2 Ubuntu

1.2.1 Prerequisite

Make sure you have a proper compiler. To install the essential tools for C++, type

```
$ sudo apt install build-essential
```

in the terminal. See [this page](#) for details on how to install a gcc or g++ compiler.

1.2.2 Installing Qt

There are two options for installing Qt on Ubuntu/Linux.

- Go to <https://www.qt.io/download>, and follow the instructions. Make sure to select a Qt version under the tab *Qt*, typically you select the newest version Qt.11.1(as of November 20, 2018). Qt Creator should be automatically selected under *Tools*.
- Simply type

```
$ sudo apt-get install qtcreator  
$ sudo apt-get install qt5-default
```

and you should have everything you need.

1.3 Windows

1.3.1 Prerequisite


Make sure you got a C++-compiler. For a quick and easy install, look up the [MinGW 64 bit compiler](#).

1.3.2 Installing Qt


Go to <https://www.qt.io/download>, and follow the instructions. Make sure to select a Qt version under the tab *Qt*, typically you select the newest version Qt.11.1(as of November 20, 2018). For me that is *macOS*, but that may differ on Windows. Qt Creator should be automatically selected under *Tools*.

2 Creating your first project


When starting up Qt Creator for the first time, this should be your starting screen. Start by clicking *New Project*.




You now choose a template. Select *Non-Qt Project* in the sidebar to the left, then select *Plain C++ Application* and click next.




Location. Then you give a name to your project and select its location.




Build System. Default is *qmake*, and is what we recommend.




Kit Selection. Select the newest kit available. May appear as *Desktop*(on Ubuntu), *Desktop Qt 5.11.1 clang 64bit*(on Mac) or similar. **Note:** if no kits are available, look back into the *Installing Qt* section¹.



Summary. Everything should now be set up and ready to go, and you can begin programming.



If you are missing a compiler, you might get a lot of errors under the *Issues* panel. Go back to *Installing Qt* section¹ for how to install a compiler for your operating system.



3 Project settings

3.1 Build settings

A plethora of important settings can be accessed from the *Build Settings* panel found in the side bar of Qt Creator.




Figure 1: Build settings panel.

3.2 Changing build folder

By default, Qt Creator will create a build folder located one folder above the project folder.

```
\home\<user>\programming\my_project
\home\<user>\programming\build-my_first_project-
  Desktop_Qt_5_11_1_clang_64bit2-Release
\home\<user>\programming\build-my_first_project-
  Desktop_Qt_5_11_1_clang_64bit2-Profiling
\home\<user>\programming\build-my_first_project-
  Desktop_Qt_5_11_1_clang_64bit2-Debug
```

It will typically make on folder for each of the **Release**, **Debug** and **Profiling** builds. If you want to change this go to the settings folder as listed in the figure above 1. This can be changed under the *General* section, by selecting a *build directory* depending on what build you are currently set to,




Figure 2: Build selecting found in the lower left corner.

3.3 Run settings

If we now click the *Run Settings* as seen on the *Build Settings* panel, we get the following screen up,





Figure 3: Run settings panel found at under the build settings panel¹.

3.4 Command line arguments

If you want to add command line arguments to your program, there are two ways of doing it. One is to run the program from the terminal in a regular fashion,

```
$ ./my_first_project arg1 arg2 arg3
```

Or, you can add the arguments under *Run* section in the *Command line arguments*,



You can also turn of the *Run in terminal* mode by unchecking the box slightly below the *Command line arguments* input.

```
$ ./my_first_project arg1 arg2 arg3
```

4 Expanding your project

4.1 The .pro-file

The `.pro` contains the settings for QMake, which is the compiling tool used by Qt (instead something like cmake). Your `.pro` file will look like this at the beginning of your project,

```
TEMPLATE = app
CONFIG += console c++11
CONFIG -= app_bundle
CONFIG -= qt

SOURCES += \
    main.cpp
```

From the `.pro` file you can specify what C++ version you are going to use (C++11 should be the default), what optimizations to utilize and what external libraries we are to use.


4.2 Adding files and classes

When adding new files to your project, either

- press `CMD+N`.
- click *New File* under *File*


- right click at the folder you wish to create a new file in the *Projects* tab and select *Add New....*

If you do either of the of the first two you should get up a panel similar to the one you got when starting a new folder. Instead of looking under the *Projects* templates, go beneath that to *Files and Classes* and select *C++*. Then select the type of file you are going to choose,




4.2.1 New header files

If you are going to create a header, select that and give it a name and location in the next panel. The summary screen will then look something like this,



4.2.2 New Classes

If you are setting up a class, select that and give it a name.



The files you are including will then be added to the `.pro` file automatically, and will now look something like,

```
TEMPLATE = app
CONFIG += console c++11
CONFIG -= app_bundle
CONFIG -= qt

SOURCES += \
    main.cpp \
    firstclass.cpp

HEADERS += \
    firstclass.h \
    firstheader.h
```

4.3 Adding existing files

Say we now want to add a files `"lib.h"` and its functions `"lib.cpp"` to our project. After taking note of their location, you simply add

```
<path_to_lib.h>/lib.h
```

under `HEADERS`, and

```
<path_to_lib.cpp>/lib.cpp
```

under `SOURCES` in the `.pro` file. Then you include the file by writing `#include "lib.h"` in the file you need it in. ¹

¹Go [here](#) for an explanation for why we use `"lib.h"` and not `<lib.h>`.

5 Guides to external libraries for Qt

After introducing the `.pro` file, we can look at how libraries is including. In the `.pro` this is done with primarily two commands:

```
LIBS += -L/<path_to_library> -l<library_name>
INCLUDEPATH += <path_to_search_for_headers_in>
```

5.1 Armadillo

5.1.1 Installation

- **Windows.** Look at [this guide](#) for how to install Armadillo on Windows.
- **Mac.** Install Armadillo by simply typing,

```
$ brew install armadillo
```

in the terminal.

- **Ubuntu.** To install Armadillo on Ubuntu, use

```
$ sudo apt-get install libarmadillo-dev
```

5.1.2 Including Armadillo in Qt Creator

- **Mac.** To include Armadillo on Mac in Qt Creator, you have to add following to your `.pro` file. This is assuming Brew linked Armadillo correctly and installed all dependencies.

```
INCLUDEPATH += /usr/local/include
LIBS += -L/usr/local/lib -llapack -lblas -larmadillo
```

The path was used here is the path provided by Brew when typing

```
brew info armadillo
```

After adding the path go to *Build* at the top, and select *Run qmake*.

- **Ubuntu.** After installing the required libraries, simply include

```
LIBS += -llapack -lblas -larmadillo
```

in your `.pro` file.

- **Windows.** See post on Piazza or go to the bottom of the same document listed in under the installation of Armadillo.

To include Armadillo in your C++ program, go to your `.pro` file and add the following,

An example of a full `.pro` file on Mac would be

```
TEMPLATE = app
CONFIG += console c++11
CONFIG -= app_bundle
CONFIG -= qt
```

```
SOURCES += \
```

```

main.cpp

INCLUDEPATH += /usr/local/include
LIBS += -L/usr/local/lib
LIBS += -llapack -lblas -larmadillo

```

5.1.3 Troubleshooting

- **Mac.** If you run into an issue where you get `Image not found` at run time, try to reinstall `arpack` and `Armadillo` with `brew`.

5.2 OpenMP

OpenMP is a method of parallelizing code.

5.3 MPI

6 Profiling your code

Two profiling methods will be presented in this section,

- *Memory profiling.* Will check if any memory is lost. I.e. you forget to de-allocate any memory.
- *Function profiling.* Will check the time spent in each function.

Methods for profiling code can be found at Qt Wiki for [Profiling and Memory Checking Tools](#). Here, we will present Valgrind as the choice of profiler.

To view output of the Valgrind profiler(in case you do not use Qt Creator), use KCacheGrind(or QCacheGrind for Mac users) which can be found [here](#).

6.1 Installing Valgrind

6.1.1 Mac

Install Valgrind with `brew`,

```
$ brew install valgrind
```

If you use MacOS High Sierra(10.13), you might get an error on the form of,

```
valgrind: mmap-FIXED(0x7fff5f400000, 8388608) failed in UME (load_unixthread1)
with error 22 (Invalid argument).
```

The fix is to uninstall Valgrind and reinstall with the `--HEAD`.

```
$ brew uninstall valgrind
$ brew install valgrind --HEAD
```

6.1.2 Ubuntu

Simple use

```
$ sudo apt-get install valgrind
```

and you should have it.

6.2 Installing K/QCachegrind

6.2.1 Mac

```
$ brew install kcachegrind
```

6.2.2 Ubuntu


```
$ sudo apt-get install kcachegrind
```

6.3 Running Valgrind memory check(memcheck)

6.3.1 Qt Creator

In Qt Creator, first compile your program in debug mode. Then select Analyze -> Valgrind Memory Analyzer with GDB. If the drop-down panel is something else than Debugger click it and select memcheck. If it does not start, click Run.

The output will then on the shape of



6.3.2 Terminal

If you want to run in terminal, you might want to have your program compiled in debug mode(not required though), and type following

```
$ valgrind --leak-check=full ./my_executable
```

The argument `--leak-check=full` prompts Valgrind to output a detailed overview of the locations of where it detected memory leaks.

Mac users: Valgrind may display many leaks which are related to the OS, and thus can be discarded.

6.4 Profiling with Valgrind(Callgrind)

6.4.1 Qt Creator

If Qt Creator, you select Analyze -> Valgrind Function Profiler. Qt Creator should now be profiling your code for you. Your result should look something like this:

The screenshot shows a C++ IDE with a file named `main.cpp`. The code includes `<iostream>`, `<random>`, `<cmath>`, and `<thread>`. It defines several functions: `randomNumberOperations`, `fillArraysWithRandomNumbers`, `fillArray`, `addArrays`, `cubeArray`, `double cuber`, and `addNumber`. The `main` function calls `randomNumberOperations` with `array_size` set to `pow(10,4)`. A warning "use of old-style cast" is shown for this line. The callgrind window displays a call stack with the following data:

Function	Location	Called	Self Cost: Ir	Incl. Cost: Ir
<code>_dyld_start</code>	<code>/usr/lib/dyld</code>	0	93	18 835 881
<code>main</code>	<code>/Users/hans...</code>	1	17	10 636 190
<code>randomNum...</code>	<code>/Users/hans...</code>	1	93	10 606 811
<code>std::_1::mer...</code>	<code>/Users/hans...</code>	40010	40 025	9 556 028
<code>dyldbootstr...</code>	<code>/usr/lib/dyld</code>	1	11 113	8 127 275
<code>dyld::main(...</code>	<code>/usr/lib/dyld</code>	1	1 667	8 099 220
<code>fillArray(dou...</code>	<code>/Users/hans...</code>	2	320 026	6 239 330
<code>operator ne...</code>	<code>/usr/lib/libc+...</code>	20003	40 006	5 929 718
<code>operator ne...</code>	<code>/usr/lib/libc+...</code>	20003	320 048	5 889 712
<code>__cxaatv1:...</code>	<code>/usr/lib/libc+...</code>	20017	20 047	5 794 522
<code>malloc</code>	<code>/usr/lib/syste...</code>	20019	320 368	5 526 614

6.4.2 Terminal

To run a Callgrind in terminal, use

```
$ valgrind --tool=callgrind ./my_executable
```

This produces an output on the format of `callgrind.out.<pid>`. The last numbers is just the Process identifier. To view this file (depending on OS), use, *Mac*:

```
$ qcachegrind callgrind.out.<pid>
```

Ubuntu:

```
$ kcachegrind callgrind.out.<pid>
```

7 Optimizing your code

By including `-march-native` you allow for processor specific compilation.

`-O3` you will allow get vectorization enabled, together with the optimizations from `-O2`, `-O1`, `-Ofast`.

With `-fopt-info` you will see what compiler optimizations is performed.

8 Parallelization

There are two main roads to parallelize your code: either through *MPI* or through *OpenMP*.

8.1 MPI

8.1.1 Mac

To parallelize with MPI, make sure you have OpenMPI installed,

```
$ brew install open-mpi
```

8.1.2 Ubuntu

To install MPI, simply type,

```
$ sudo apt install mpich
```

8.1.3 Setting up MPI for QtCreator

The first thing you need to do is to include MPI in the `.pro`-file as given [here](#),

```
# MPI Settings
QMAKE_CXX = mpicxx
QMAKE_CXX_RELEASE = $$QMAKE_CXX
QMAKE_CXX_DEBUG = $$QMAKE_CXX
QMAKE_LINK = $$QMAKE_CXX
QMAKE_CC = mpicc


QMAKE_CFLAGS += $$system(mpicc --showme:compile)
QMAKE_LFLAGS += $$system(mpicxx --showme:link)
QMAKE_CXXFLAGS += $$system(mpicxx --showme:compile) -DMPICH_IGNORE_CXX_SEEK
QMAKE_CXXFLAGS_RELEASE += $$system(mpicxx --showme:compile) -
    DMPICH_IGNORE_CXX_SEEK
```

After the QMake incantations has been invoked, it is time to set the correct parameters for Qt Creator. Go to your *build*-panel. There, if you are on Mac you will need to add the following line under the *Build Environment* section and in `PATH`,


```
/usr/local/bin
```



After that is done, you can move on to the run settings. There, you will need to add a new *Run configuration*. Click *Add* and select *Custom Executable*. By doing which `mpirun` in the terminal, you can type in the following,



To use this custom executable, select the newly created *mpi* from the *Run Selection Menu* as seen in following figure,



8.2 OpenMP

8.2.1 Mac

To parallelize with OpenMP on Mac², ensure you have `libomp`, by using Brew.

```
$ brew install 1stlisting
```

Then, to compile in terminal, write

```
$ g++ -Xpreprocessor -fopenmp -o <your-program>.o <your-program>.cpp -lomp
```

8.2.2 Ubuntu

To install OpenMP on Ubuntu, simply type

```
$ apt-get install libomp-dev
```

8.3 Troubleshooting

8.3.1 Orte Communications

Simple set the `tmp` path in Run Settings to `tmp` as seen in following figure,

²Discussion around how to make OpenMP run on Mac is covered in [this](#) stackoverflow post

Run Environment

Use **Build Environment** and Set **TMPDIR** to **/tmp**

Base environment for this run configuration: **Build Environment**

Variable	Value
Apple_PubSub_Socket_Render	/private/tmp/com.apple.launchd.Qyn0uto0aw/Render
HOME	/Users/hansmathiasmamenvege
LOGNAME	hansmathiasmamenvege
PATH	/Users/hansmathiasmamenvege/Qt/5.11.1/clang_64/bin:/usr/bin:/bin:/usr/sbin:...
QTDIR	/Users/hansmathiasmamenvege/Qt/5.11.1/clang_64
SECURITYSESSIONID	186a8
SHELL	/bin/zsh
SSH_AUTH_SOCK	/private/tmp/com.apple.launchd.E6fFd9LIDu/Listeners
TMPDIR	/tmp
USER	hansmathiasmamenvege
XPC_FLAGS	0x0
XPC_SERVICE_NAME	org.qt-project.qtcreator.9900
_CF_USER_TEXT_ENCODING	0x1F5:0x0:0x0

Edit
Add
Reset
Unset
Batch Edit...

8.3.2 Failed to start program

If you get the following error message,

```
15:51:07: Starting /usr/local/bin/mpirun...
15:51:07: Failed to start program. Path or permissions wrong?
15:51:07: /usr/local/bin/mpirun exited with code -1
15:51:07: The process failed to start. Either the invoked program "/usr/local/
        bin/mpirun" is missing, or you may have insufficient permissions to invoke
        the program.
```

you probable