

Improving Data Monitoring In UVM

Tips & Recommendations

Yogish Sekhar
Dialog Semiconductors

May 22, 2014
Reading, United Kingdom

Agenda

Review Of Current UVM Test Bench Structure

- Environment Architecture
- Limitations Of Current Analysis Ports / Port Macro's


Improvements & Dynamic Connections

TLM & UVM

Review of Current UVM Testbench Structure


Current UVM TB Structure

- Block Level



Current UVM TB Structure

- Cluster Level



Current UVM TB Structure


Characteristics

- Inherently Structural
- Quasi Static Connections
- Each Level Of Hierarchy
Need To Support Data
Transport

```
function void agent::connect_phase(uvm_phase phase);  
    super.connect_phase(phase);  
    `uvm_info(name, "Inside agent::connect()", UVM_LOW);  
  
    if (driver != null && sequencer != null) begin  
        // connect the driver with the sequencer  
        driver.seq_item_port.connect (sequencer.seq_item_export);  
    end  
    monitor.analysis_port.connect (monitor_ap);  
endfunction : connect_phase
```

Current UVM TB Structure

Connect Phase - Environments



```
function void block_env::connect_phase(uvm_phase phase);
  super.connect_phase(phase);
  `uvm_info(name, "Inside block_env::connect()", UVM_LOW);
  agent_1.monitor_ap.connect (block_checker.agent_1_ap);
  agent_2.monitor_ap.connect (block_checker.agent_2_ap);
  agent_1.monitor_ap.connect (this.agent_1_ap);
  agent_2.monitor_ap.connect (this.agent_2_ap);
endfunction : connect_phase
```

Current Connection Model

Subscriber Implementation

- 4 Stage Process
 - Stage 1
 - Provide an Implementation
 - Use one of the many ``*_imp_decl(<suffix>`` macro
 - Customize the template class

```
`uvm_analysis_imp_decl(ahb_trans)
```

```
uvm_analysis_imp_ahb_trans
#(type T=<transaction_type>,
  type IMP=<destination_type>)
```


```
typedef
uvm_analysis_imp_ahb_trans
#(ahb_transaction_c,
  snug2014_block_checker)
AHB_TRANS_AP;
```



Current Connection Model

Subscriber

- 4 Stage Process
 - Stage 2
 - Instance the customized class
 - Provide it with reference handle of the subscriber



```
class snug2014_block_checker
    extends uvm_scoreboard;
    .....
    AHB_TRANS_AP      ahb_trans_ap;
    .....
    function void build_phase(uvm_phase phase);
        ahb_trans_ap = new("ahb_ap", this);
    endfunction : build_phase
endclass
```

Current Connection Model

Subscriber

- 4 Stage Process
 - Stage 3
 - Ensure 'write_<suffix>(T trans)' is implemented in the subscriber
 - Stage 4
 - Connect to a data source through a sequence of hierarchical port/export connections



```
class snug2014_block_checker
    extends uvm_scoreboard;
    .....
    AHB_TRANS_AP      ahb_trans_ap;
    .....
    function void write_ahb_trans
        (ahb_transaction_c trans);
    endfunction
    .....
endclass
```

Current Connection Model

Subscriber

Limitations

- Need for template class customisation
 - This process can be defined inside the macro itself
- Name of the method in subscriber
- Using of connect_phase() through the hierarchy



```
class snug2014_block_checker
    extends uvm_scoreboard;
    .....
    AHB_TRANS_AP      ahb_trans_ap;
    .....
    function void write_ahb_trans
        (ahb_transaction_c trans);
    endfunction
    .....
endclass
```

Improvements For Establishing Dynamic Connections

Elements For Active Connection

- To Create Active Connection
 - Data Source
 - Monitor
 - Transaction Type
 - Derived from `uvm_sequence_item`
 - Destination Type
 - Type of the subscriber
 - Destination Method
 - Function in the subscriber capable of processing transaction provided by the monitor

UVM Monitor Base Class

```
virtual class uvm_monitor extends uvm_component;
    function new (string name, uvm_component parent);
        super.new(name, parent);
    endfunction

    const static string type_name = "uvm_monitor";

    virtual function string get_type_name ();
        return type_name;
    endfunction
endclass
```

- It's Just a wrapper on 'uvm_component'
- Specific Monitor Implementations
 - Customize the output transaction
 - Always associated with an interface

UVM Monitor Base Class

- Template the base monitor class
- Provides some common elements
 - Default analysis port
 - Broadcast method

```
virtual class dvm_monitor #(type T = uvm_sequence_item) extends uvm_monitor;  
    T mon_trans;  
  
    // Declare a default analysis port in the monitor  
    uvm_analysis_port#(T) default_ap;  
  
    // registration bit for callbacks  
    static local bit m_register_cb;  
  
    `uvm_component_param_utils(dvm_monitor #(T))  
    extern function new (string name, uvm_component parent);  
    extern function void notify(T trans);  
endclass : dvm_monitor
```

Improved Analysis Macro

```
`uvm_analysis_imp_decl(ahb_trans)
```

```
`dvm_analysis_imp_decl(ANALYSIS_OBJ_TYPE, MONITOR_NAME, TRANS_TYPE, RCV_TYPE, RCV_FUNC)
```

Parameter	Usage
ANALYSIS_OBJ_TYPE	Unique name to identify the customised analysis object class type
MONITOR_NAME	Name string to uniquely identify the monitor component Can contain wild characters to identify hierarchical components
TRANS_TYPE	Data transaction class type used by the monitor
RCV_TYPE	Class type of the receiver
RCV_FUNC	User defined method available in the in the subscriber that processes a transaction of type <code>`TRANS_TYPE'</code>

Improved Analysis Macro

- ``auto_connect()`
 - Hierarchical ``connect_phase()` redundant
 - Connections
 - Established by subscribers that need the information
 - Can be established any time after ``build_phase()`
 - No hierarchical components is involved in data transport
 - UVM component registry to find the necessary data sources

Improved Analysis Macro

Block Level UVM Environment

```
class snug2014_checker_1 extends uvm_component;
  // Create the classes needed for analysis objects
  `dvm_analysis_imp_decl(
    CK1_AP_MON_1, "*.snug2014_block_env_1.*.agent_1_monitor",
    snug2014_agent_1_transaction, snug2014_checker_1, func_agent_1)

  // Declare the Analysis Objects that are to be used
  CK1_AP_MON_1 ap_mon_1;
  .....


  // User Defined Callback functions for Analysis
  extern function void func_agent_1 (snug2014_agent_1_transaction trans);
endclass : snug2014_checker_1
```

Example Testbench

Block Level UVM Environment

```
function void snug2014_checker_1::<connect | post_elab | run>_phase(uvm_phase phase);  
    // Call auto_connect in order to connect up the monitor and the checker  
    ap_mon_1.auto_connect();  
    ap_mon_2.auto_connect();  
endfunction : connect_phase
```

Register With Monitor




Data Transfer

Example Testbench

Block Level UVM Environment

```
function void snug2014_checker_1::<connect | post_elab | run>_phase(uvm_phase phase);
    // Call auto_connect in order to connect up the monitor and the checker
    ap_mon_1.auto_connect();
    ap_mon_2.auto_connect();
endfunction : connect_phase
```



Example Testbench – Simulation - 1

```
UVM_INFO @ 0ns : [checker_1] : Inside snug2014_checker_1::connect_phase()
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_1]: CK1_AP_MON_1::auto_connect()
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_1]:
    Finding Monitor: *.SNUG2014_BLOCK_ENV_1.*.AGENT_1_MONITOR
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_1]:
    Connected      : uvm_test_top.snug2014_block_env_1.agent_1.agent_1_monitor
    To              : uvm_test_top.snug2014_block_env_1.snug2014_checker_1
    Transaction     : snug2014_agent_1_transaction
    Function Call: func_agent_1
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_2]: CK1_AP_MON_2::auto_connect()
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_2]:
    Finding Monitor: *.SNUG2014_BLOCK_ENV_1.*.AGENT_2_MONITOR
UVM_INFO @ 0ns : [ANALYSIS_PORT_AGENT_2]:
    Connected      : uvm_test_top.snug2014_block_env_1.agent_2.agent_2_monitor
    To              : uvm_test_top.snug2014_block_env_1.snug2014_checker_1
    Transaction     : snug2014_agent_2_transaction
    Function Call: func_agent_2
UVM_INFO @ 0ns : [snug2014_env_1] :
    Inside snug2014_block_env_1::connect_phase() - Nothing Done Here
```

```
UVM_INFO @ 100ns : [agent_1_monitor] :
    Something Interesting Seen Here - Build Transaction
UVM_INFO @ 100ns : [agent_1_monitor] : dvm_monitor::notify() - Called
UVM_INFO @ 100ns : [checker_1] : Inside snug2014_checker_1::func_agent_1()

UVM_INFO @ 200ns : [agent_2_monitor] :
    Something Interesting Seen Here - Build Transaction
UVM_INFO @ 200ns : [agent_2_monitor] : dvm_monitor::notify() - Called
UVM_INFO @ 200ns : [checker_1] : Inside snug2014_checker_1::func_agent_2()
```

Example Testbench – Simulation 2

```

UVM_INFO @ 0ns : [checker_soc] : Inside snug2014_soc_checker::connect_phase()
UVM_INFO @ 0ns : [SOC_CHK_CL_ANALYSIS_CONN_OBJ_4] : CK_SOC_C1_AP_MON_4::auto_connect()
UVM_INFO @ 0ns : [SOC_CHK_CL_ANALYSIS_CONN_OBJ_4] :
Finding Monitor: *.SNUG2014_CLUSTER_ENV.*.AGENT_4_MONITOR
UVM_INFO @ 0ns : [SOC_CHK_CL_ANALYSIS_CONN_OBJ_4] :
Connected      : uvm_test_top.snug2014_soc_env.snug2014_cluster_env
                  .snug2014_block_env_2.agent_4.agent_4_monitor
To              : uvm_test_top.snug2014_soc_env.checker_soc
Transaction     : snug2014_agent_4_transaction
Function        : cluster_func_agent_4
UVM_INFO @ 0ns : [SOC_CHK_BLK_ANALYSIS_CONN_OBJ_4]: CK_SOC_AP_MON_4::auto_connect()
UVM_INFO @ 0ns : [SOC_CHK_BLK_ANALYSIS_CONN_OBJ_4]:
Finding Monitor: *.SNUG2014_BLOCK_ENV_3.*.AGENT_4_MONITOR
UVM_INFO @ 0ns : [SOC_CHK_BLK_ANALYSIS_CONN_OBJ_4]:
Connected      : uvm_test_top.snug2014_soc_env.snug2014_block_env_3
                  .agent_4.agent_4_monitor
To              : uvm_test_top.snug2014_soc_env.checker_soc
Transaction     : snug2014_agent_4_transaction
Function        : block_func_agent_4
UVM_INFO @ 0ns : [snug2014_block_env_2] :
Inside snug2014_block_env_2::connect_phase() - Nothing Done Here
UVM_INFO @ 0ns : [snug2014_cluster_env] :
Inside snug2014_cluster_env::connect_phase() - Nothing Done Here
UVM_INFO @ 0ns : [snug2014_soc_env] :
Inside snug2014_soc_env::connect_phase() - Nothing Done Here
  
```

Current Vs Proposed

```
`uvm_analysis_imp_decl(ahb_trans)
```



```
uvm_analysis_imp_ahb_trans
#(type T=<transaction_type>,
  type IMP=<destination_type>)
```



```
typedef uvm_analysis_imp_ahb_trans
#(ahb_transaction_c,
  snug2014_block_checker)
AHB_TRANS_AP;
```



```
class snug2014_block_checker
  extends uvm_scoreboard;
  .....
  AHB_TRANS_AP      ahb_trans_ap;
  .....
endclass
```



```
class snug2014_block_checker
  extends uvm_scoreboard;
  .....
  function void write_ahb_trans
    (ahb_transaction_c trans);
endclass
```



```
ahb_trans_ap = new("AP");

// Use of Hierarchical
connections
```

```
`dvm_analysis_imp_decl(
CK_SOC_C1_AP_MON_2,
"*.snug2014_cluster_env.*.agent_2_monitor",
snug2014_agent_2_transaction,
snug2014_soc_checker,
cluster_func_agent_2)
```



```
class snug2014_soc_checker
  extends uvm_scoreboard;
  .....
  CK_SOC_C1_AP_MON_2      ck_soc_c1_ap_mon_2;
  .....
endclass
```



```
class snug2014_soc_checker
  extends uvm_scoreboard;
  .....
  function void cluster_func_agent_2
    (snug2014_agent_2_transaction trans);
  .....
endclass
```



```
ck_soc_c1_ap_mon_2 = new( "AP", this);
ck_soc_c1_ap_mon_2.auto_connect()
```

TLM & UVM

TLM & UVM

- TLM 2.0
 - Standardized Approach
 - Creating Models & Transaction Level Simulations
 - Enables Model Exchange
 - Provides Common Ground For Interfacing
- UVM Implementation - Analysis Ports
 - Based On OSCI Standard & SystemC Implementation
 - SystemC Analysis Ports
 - Not derived from 'sc_port'
 - Connections in SystemC analysis ports can be established even in the 'run_phase'
 - UVM Restrictive In The Way Analysis Ports Can Be Bound Or Connected

TLM & UVM

Impacts

- Performance Impact When Executing SOC Level Hardware-Software Co-Simulations
- Increased Memory Footprint
- Inability To Selectively Enable Block Level Environments After SOC Initialisation
- Re-Initialisation Of SOC In Every Testcase If Enabling Of Block Level Checkers At Runtime By Use Of Plusargs

Solution

- Make Analysis Ports Independent Of 'uvm_port_base'
 - Create A New Base Class Specifically For Analysis Ports
 - Bring In UVM Implementation Closer To SystemC Implementation

Conclusion

- Advantages
 - Reduction In Code To Support Data Movement
 - Establishes 1-1 Connection between Monitors and Checkers
 - Eliminating connect_phase() in hierarchical components
 - Subscribers Processing Transactions Responsible For Connections
 - Library Ensures Transaction Type Checking At Compile Time
 - Simplification In Connection Model
 - Allows Callbacks To Be Used Just As Analysis Ports
 - Allows Feedback To Active Sequences Needing Information From Monitors. Eg. Interrupt Monitoring
 - Use Of Wild Character Based Search String
 - Simplifies Debug As All Information Regarding Establishing Data Connection Available At A Single Location

Conclusion

- Limitations
 - Monitors Only Broadcast
 - Effectively Limited To A Push Model For Data Transmission
 - Monitor Search Path Strings Should Be Uniqifiable
 - Identify A Single Data Source

The background of the slide features a stylized globe with circuit board patterns overlaid on it. The globe is rendered in shades of blue and white, with circuit traces in green and yellow. The text 'Thank You' is centered over the globe.

Thank You