Lock_DiagEnbCnd

Software and calibration documentation (detailed) [COMP]

RB internal

I [Lock_DiagEnbCnd]

1 Function Definition

1.1 Purpose

Input the purpose of developing this function

1.2 Introduction

Lock Diag Enable Condition

2 Function Description

2.1 Behavior in normal mode

Figure 1   Lock_DiagEnbCnd [Lock_DiagEnbCnd]

Figure 2 Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_10ms_sys [Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_10ms_sys]

Figure 3 Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_10ms_sys_Chart [Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_10ms_sys_-Chart]



Figure 4 Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_Init [Lock_DiagEnbCnd_Lock_DiagEnbCnd_Runnable_Init]

BOSCH

Table 1   Data Types for port interfaces [PortInterfaceDataTypes]

Port	AccessMode	Interface	DE	Datatype
BattU_bVoltEnbPinDiag	ExplicitReceive	BattU_bVoltEnbPinDiag	Val	boolean
gCAN_u8UMM_UsageMo-deSt	ExplicitReceive	gCAN_u8UMM_UsageMo-deSt	Val	uint8
gPRM_u8VehicleTypeCfg	ExplicitReceive	gPRM_u8VehicleTypeCfg	Val	uint8
gLock_u8DiagEnbCnd	ExplicitSend	gLock_u8DiagEnbCnd	Val	uint8