

 Source Data From:
 PCB_Quadcopter.PrjPCB

 Project:
 PCB_Quadcopter.PrjPCB

 Variant:
 None

Creation Date: 10/21/2015 11:00:35 PM
Print Date: 42298 42298.95885

Footprint	Comment	LibRef	Designator	Description	Quantity
PIN1	ANT	ANT	ANT1	Anten	
C Tantalum	1uF	C Tantalum S.A	C1, C2	Midget Conformal Coated Solid Tantalum	2
S.A				Chip Capacitor: 1.5uF, 20% Tolerance, 15 WVDC @ +85°C, Surge = 20V	
C-0805	0.1uF	Cap Ceramic	C1, C3	Capacitor (Semiconductor SIM Model)	- 2
C-0805	10nF	Cap Ceramic	C2	Capacitor (Semiconductor SIM Model)	1
C-0805	2.2nF	Cap Ceramic	C4	Capacitor (Semiconductor SIM Model)	1
C-0603	100nF	Cap Ceramic	C8, C9	Capacitor (Semiconductor SIM Model)	2
C-0805 C-0805	20pF 2.2uF	Cap Ceramic	C10, C11 C11, C12	Capacitor (Semiconductor SIM Model) Capacitor (Semiconductor SIM Model)	1 2
C-0805	100nF	Cap Ceramic	C13, C14, C16, C17, C18, C19, C20, C21,		10
			C22, C23		
C-0805	1uF	Cap Ceramic	C15	Capacitor (Semiconductor SIM Model)	1
C Tantalum	10uF	C Tantalum S.A	C19, C20	Midget Conformal Coated Solid Tantalum	2
S.A				Chip Capacitor: 1.5uF, 20% Tolerance, 15	
C-0805	104	Cap Ceramic	C21, C22, C32	WVDC @ +85°C, Surge = 20V Capacitor (Semiconductor SIM Model)	
C-0603	22pF	Cap Ceramic	C24, C25	Capacitor (Semiconductor SIM Model)	2
C-0402	33nF	Cap Ceramic	C26	Capacitor (Semiconductor SIM Model)	1
C-0402	2.2nF	Cap Ceramic	C27	Capacitor (Semiconductor SIM Model)	1
C-0402	4.7pF	Cap Ceramic	C28	Capacitor (Semiconductor SIM Model)	1
C-0402 C-0402	1.5pF 1pF	Cap Ceramic Cap Ceramic	C29 C30	Capacitor (Semiconductor SIM Model) Capacitor (Semiconductor SIM Model)	
C-0805	33pF	Cap Ceramic	C31	Capacitor (Semiconductor SIM Model)	
C-0603	.22uF	Cap Ceramic	C33	Capacitor (Semiconductor SIM Model)	1
C-0603	4.7uF	Cap Ceramic	C34	Capacitor (Semiconductor SIM Model)	1
C-0603	.1uF	Cap Ceramic	C35	Capacitor (Semiconductor SIM Model)	1
1N4007 SMD	1N4007 MPU6050	1N4007	D1	1 Amp General Purpose Rectifier	1
QFN-24_N LPCC-16	HMC5883L	MPU6050 HMC5883L	IMU1 IMU2	-	
CDRH127	fcm1608-0603	Inductor	L1	Inductor	
12.3x12.3x8					
mm	1	l			
I-0402	2.7nH	Inductor	L2	Inductor	1
I-0402 I-0402	3.9nH 8.2nH	Inductor Inductor	L3 L3	Inductor	
I-0402 LED-0805	8.2nH ORANGE	Inductor LED	LD3	Inductor Typical INFRARED GaAs LED	
LED-0805	GREEN	LED	LD4	Typical INFRARED GaAs LED	
LED-0805	RED	LED	LD5	Typical INFRARED GaAs LED	1
LED-0805	BLUE	LED	LD6	Typical INFRARED GaAs LED	1
LQFP100_V		STM32F407VGT	MCU	ARM Cortex-M4 32b MCU+FPU, 210DMIP,	1
	6	6		1024 kB Flash, 192+4 kB RAM, Camera, 82 l/Os, 100-pin LQFP, -40 to +85°C, Tray	
				82 POS, 100-pill EQFP, -40 to 465 C, 11ay	
HDR1X2	Header 2	Header 2	P1	Header, 2-Pin	1
HDR1X3	PWM	Header 3	P2, P3, P4, P5	Header, 3-Pin	4
HDR1X6	Input_Rx	Header 6	P6	Header, 6-Pin	1
HDR1X4 R-0805	UART 10k	Header 4 RES	P7 R1, R2, R13, R16	Header, 4-Pin Rectangular Thick Film Chip Resistor, 10	1
rt-0000	IUK	RES	KI, K2, KI3, KI0	Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0603	4.7k	RES	R3, R4	Rectangular Thick Film Chip Resistor, 10	2
				Ohm to 1M Ohm Range, 0.1% and 0.5%	
R-0805	510	RES	DE D44 D47	Tolerance, 1/8W	
K-0805	510	RES	R5, R14, R17	Rectangular Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0805	680	RES	R6, R7, R8	Rectangular Thick Film Chip Resistor, 10	3
				Ohm to 1M Ohm Range, 0.1% and 0.5%	
R-0805	100k	DE0	R9	Tolerance, 1/8W	
K-0805	100K	RES	R9	Rectangular Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 0.1% and 0.5%	1
				Tolerance, 1/8W	
R-0805	100	RES	R10	Rectangular Thick Film Chip Resistor, 10	1
				Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0805	330	RES	R11	Rectangular Thick Film Chip Resistor, 10 Ohm to 1M Ohm Range, 0.1% and 0.5%	
	1	l		Tolerance, 1/8W	
R-0805	220k	RES	R12	Rectangular Thick Film Chip Resistor, 10	1
	1	l		Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0805	220	RES	R15	Rectangular Thick Film Chip Resistor, 10	1
	1	l		Ohm to 1M Ohm Range, 0.1% and 0.5% Tolerance, 1/8W	
R-0805	47	RES	R18	Rectangular Thick Film Chip Resistor, 10	
		l		Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0805	4.7k	RES	R19, R20	Rectangular Thick Film Chip Resistor, 10	2
				Ohm to 1M Ohm Range, 0.1% and 0.5% Tolerance, 1/8W	
R-0402	1M	RES	R21	Rectangular Thick Film Chip Resistor, 10	
110102		1120	12.	Ohm to 1M Ohm Range, 0.1% and 0.5%	
				Tolerance, 1/8W	
R-0603	22K	RES	R27	Rectangular Thick Film Chip Resistor, 10	1
				Ohm to 1M Ohm Range, 0.1% and 0.5%	
SB	SB	SB	SR1 SR2 SR3 SR4 SDE SDE	Tolerance, 1/8W	
SB3	SB3	SB3	SB1, SB2, SB3, SB4, SB5, SB6 SB7	1	
DPST-4	BUTTON B1	BUTTOND	SW	BUTTON	
DPST-4	BUTTON B2	BUTTOND	SW	BUTTON	
QFN-20	nRF24L01	nRF24L01	U3		1
SOT223_N	LM1117MPX-3.3	LM1117MPX-3.3	U4	800mA Low-Dropout Linear Regulator, 4-	1
XTAL	8Mhz	XTAL	X1	pin SOT-223 Crystal Oscillator	1
XTAL	16Mhz	XTAL	Y1	Crystal Oscillator Crystal Oscillator	
					94
Approved		Notes			
	_	_			