



Palindromic Linked List


Given the head of a singly linked list, determine if it's a palindrome.

Example 1:



Output: True

Example 2:




Output: False

Intuition


A linked list would be palindromic if its values read the same forward and backward. A naive way to check this would be to store all the values of the linked list in an array, allowing us to freely traverse these values forward and backward to confirm if it's palindromic. However, this takes linear space. Instead, it would be better if we had a way to traverse the linked list in reverse order to confirm if it's a palindrome. Is there a way to go about this?

Going off the above definition, we know that if a linked list is a palindrome, reversing it would result in the same sequence of values.



This means we could create a copy of the linked list, reverse it, and compare its values with the original linked list. However, this would still take up linear space. Can we adjust this idea to avoid creating a

with the reverse of the second half (if there are an odd number of elements, we can just include the middle node in both halves) to check if the linked list is a palindrome:




Before we can perform this comparison, we need to:

1. Find the middle of the linked list to get the head of the second half.
2. Reverse the second half of the linked list from this middle node.

Notice that step 2 involves modifying the input. In this problem, let's assume this is acceptable.


However, **it's always good to check with the interviewer if changing the input is allowed before moving forward with the solution.**

Now, let's see how these two steps can be applied. Start by obtaining the middle node (`mid`) of the linked list.



To learn how to get to the middle of a linked list, read the explanation in the *Linked List Midpoint* problem in the *Fast and Slow Pointers* chapter.


Then, reverse the second half of the linked list starting at `mid`. The last node of the original linked list becomes the head of the second half. This second head is used to traverse the newly reversed second half.



To learn how to reverse a linked list in $O(n)$ time, read the explanation in the *Reverse Linked List* problem in this chapter.

half to the corresponding node from the second half. If at any point the node values don't match, it indicates the linked list is not a palindrome.

We can use two pointers (**ptr1** and **ptr2**) to iterate through the first and the reversed second half of the linked list, respectively:



Implementation

Python

JavaScript

Java

```
from ds import ListNode

def palindromic_linked_list(head: ListNode) → bool:
    # Find the middle of the linked list and then reverse the second half of the
    mid = find_middle(head)
    second_head = reverse_list(mid)
    # Compare the first half and the reversed second half of the list
    ptr1, ptr2 = head, second_head
    res = True
    while ptr2:
        if ptr1.val ≠ ptr2.val:
            res = False
        ptr1, ptr2 = ptr1.next, ptr2.next
    return res

# From the 'Reverse Linked List' problem.
def reverse_list(head: ListNode) → ListNode:
    prevNode, currNode = None, head
    while currNode:
        nextNode = currNode.next
        currNode.next = prevNode
        prevNode = currNode
        currNode = nextNode
    return prevNode

# From the 'Linked List Midpoint' problem.
def find_middle(head: ListNode) → ListNode:
    slow = fast = head
```

```
return slow
```

Complexity Analysis

Time complexity: The time complexity of `palindromic_linked_list` is $O(n)$, where n denotes the length of the linked list. This is because it involves iterating through the linked list three times: once to find the middle node, once to reverse the second half, and once more to compare the two halves.

Space complexity: The space complexity is $O(1)$.

Interview Tip

Tip: Confirm if it's acceptable to modify the linked list. In our solution, we reversed the second half of the linked list which dismantled the input's initial structure. Why does this matter? Oftentimes, the input data structure should not be modified, particularly if it's shared or accessed concurrently. As such, it's important to confirm with your interviewer whether input modification is acceptable and to briefly address the implications of this.

☐ Mark as Complete[Teach on ByteByteGo](#)[Be an Affiliate](#)[Become a Contributor](#)hi@bytebytego.com[Report a Bug](#)[Our Team](#)[Newsletter](#)[Privacy Policy](#)



Do Not Sell or Share My Personal Information

YouTube

Visual Dev Guides

Find Jobs

Prepare for Coding Interviews