



Pair Sum - Unsorted

Given an array of integers, return the indexes of **any two numbers that add up to a target**. The order of the indexes in the result doesn't matter. If no pair is found, return an empty array.

Example:

```
Input: nums = [-1, 3, 4, 2], target = 3  
Output: [0, 2]
```

Explanation: `nums[0] + nums[2] = -1 + 4 = 3`

Constraints:

- The same index cannot be used twice in the result.

Intuition

A brute force approach is to iterate through every possible pair in the array to see if their sum is equal to the target. This is the same as the brute force solution described in the *Pair Sum - Sorted* problem, which has a time complexity of $O(n^2)$, where n is the length of the array. We could also sort the array and then perform the two-pointer algorithm used in *Pair Sum - Sorted*, which would take $O(n\log(n))$ time due to sorting. Let's see if we can find an even faster solution.

Complement

We're asked to find a pair (x, y) such that $x + y == \text{target}$. In this equation, there are two unknowns: x and y . An important observation is that if we know one of these numbers, we can easily calculate what the other number should be.


For each number x in `nums`, we need to find another number y such that $x + y = \text{target}$, or in other words, $y = \text{target} - x$. We can call this number the complement of x .

Keep in mind, we need to return the indexes of the pair of numbers, not the pair itself. So, we'll need a way to find a number's complement as well as its index.

One way we could do this is to loop through the array to find each number's complement and corresponding index. But this takes $O(n^2)$ time since we'd need to do a linear traversal to search for

Hash map

A hash map works great because we can store and look up values in $O(1)$ time. Each number and its index can be stored in the hash map as key-value pairs:



This allows us to retrieve the index of any number's complement efficiently. Notice that duplicate numbers don't need to be considered here since only one valid pair needs to be found.

The most intuitive way to incorporate a hash map is to:

1. In the first pass, populate the hash map with each number and its corresponding index.
2. In the second pass, scan through the array to check if each number's complement exists in the hash map. If it does, we can return the indexes of that number and its complement.

Below is the code snippet for this two-pass approach:

Python

JavaScript

Java

```
from typing import List


def pair_sum_unsorted_two_pass(nums: List[int], target: int) → List[int]:
    num_map = {}
    # First pass: Populate the hash map with each number and its index.
    for i, num in enumerate(nums):
        num_map[num] = i
    # Second pass: Check for each number's complement in the hash map.
    for i, num in enumerate(nums):
        complement = target - num
        if complement in num_map and num_map[complement] ≠ i:
            return [i, num_map[complement]]
    return []
```

This algorithm requires two passes. Is it possible to do this in only one? A one-pass solution implies that we would need to populate the hash map while searching for complements. Is this possible?

Consider the example below:


$[-1, 3, 4, 2], \text{ target} = 3$

0 1 2 3




- hashmap doesn't contain -1's complement (4)
- add (-1, 0) to hashmap

Next, let's look at index 1. Its complement (0) does not exist in the hash map. So, just add 3 and its index to the hash map:




- hashmap doesn't contain 3's complement (0)
- add (3, 1) to hashmap

At index 2, we notice 4's complement (-1) exists in the hash map. This means we found a pair that sums to the target:



- hashmap contains 4's complement (-1)

Now, we can return the indexes of the two values. Fetch the index of 4 from the input array and the index of its complement from the hash map:



Implementation

Python

JavaScript

Java

```
from typing import List

def pair_sum_unsorted(nums: List[int], target: int) → List[int]:
    hashmap = {}
    for i, x in enumerate(nums):
        if target - x in hashmap:
            return [hashmap[target - x], i]
```



Complexity Analysis

Time complexity: The time complexity of `pair_sum_unsorted` is $O(n)$ because we iterate through each element in the `nums` array once and perform constant-time hash map operations during each iteration.

Space complexity: The space complexity is $O(n)$ since the hash map can grow up to n in size.

Interview Tip

Tip: Iterate through solutions.

Don't always jump straight to the most optimal or clever solution, as this won't give the interviewer much insight into your problem-solving process. Consider multiple approaches, starting with the more straightforward ones, and gradually refine them. This way, you demonstrate your thought process and how you arrive at a more optimal solution.

☐ Mark as Complete

[Teach on ByteByteGo](#)

[Be an Affiliate](#)

[Become a Contributor](#)

hi@bytebytego.com

[Report a Bug](#)

[Our Team](#)

[Newsletter](#)

[Privacy Policy](#)

[Terms of Service](#)



YouTube

Visual Dev Guides

Find Jobs

Prepare for Coding Interviews

Copyright ©2022-2026 ByteByteGo Inc.